

Xerox® ColorQube® 9300 Series Color Multifunction Printer

The ColorQube 9302/9303 Color Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



System Specifications	ColorQube 9302	ColorQube 9303
Speed Color	High Resolution / Photo Mode: 35 ppm Enhanced Mode (Default): 45 ppm Standard Mode ¹ : 60 ppm Fast Color Mode ¹ : 70 ppm	High Resolution / Photo Mode: 38 ppm Enhanced Mode (Default): 55 ppm Standard Mode ¹ : 70 ppm Fast Color Mode ¹ : 85 ppm
Black and white	High Resolution / Photo Mode: 36 ppm High Speed Mode: 55 ppm Standard Mode ¹ : 70 ppm Fast Color Mode ¹ : 95 ppm	High Resolution / Photo Mode: 38 ppm High Speed Mode: 60 ppm Standard Mode ¹ : 70 ppm Fast Color Mode ¹ : 95 ppm
Flexible Print Speeds Color / Black-and-white	From 35-70 / 36-95 ppm	From 38-85 / 38-95 ppm
Monthly Duty Cycle ²	Up to 225,000 pages	Up to 300,000 pages
Recommended Average Monthly Print Volume ³	15,000 to 75,000 pages	
Hard Drive / Processor / Memory	Minimum 160 GB / 1.5 GHz Dual-core / 1 GB system plus 1 GB page memory	
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 Direct Print, Optional Wi-Fi Adapter	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning	
Copy and Print		
Copy and Print Resolution	Up to 600 x 600 dpi	
First-print-out Time	As fast as 7.2 seconds color	
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®)	
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring, Color By Words	
Mobile Printing	Apple® AirPrint™, Xerox® PrintBack, Xerox® Mobile Print (Optional), Xerox® Mobile Print Cloud (Optional), Mopria™ certified	
Scan		
Standard Features	Destinations: Scan to Mailbox, Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearized PDF / PDF/A	
Optional Features	Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, other solutions available through various Xerox Business Innovation Partners	
Fax		
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement	
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax),	
Security		
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, Hard Drive Image Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions	
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)	
Accounting		
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement	
Optional Features	Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Business Innovation Partners	

Xerox® ColorQube® 9302/9303

Device Specifications				
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan			
Accessories				
Optional	High Capacity Feeder HCF Letter / A4 SEF Kit HCF Tabloid / A3 Kit Offset Catch Tray Office Finisher High Volume Finisher (HVF) High Volume Finisher with Booklet Maker Z Fold / C Fold Unit with HVF with Booklet Maker Post Process Inserter with HVF and HVF with Booklet Maker Convenience Stapler Smart Card Enablement Kit Xerox Secure Access Unified ID System® Walk up Fax (One- or Two-line options, includes LAN Fax) Xerox® USB Wireless Adapter McAfee Integrity Control Enablement Kit			
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Device, this is an interface to third party access control devices, such as coin machines and card readers.			
Electrical Requirements				
North America	Voltage : 110-127 VAC, -10% / +6% (99-135 VAC) Frequency: 60 Hz, + / - 3, 15 A			
Europe	Voltage : 220-240 VAC, -10% / +6% (198-254 VAC) Frequency: 50 Hz, + / - 3, 10 A			
Power Consumption				
Printing (Max)	120V: 1800 watts (15A) 230V: 2300 watts (10A)			
Printing (Average)	610 watts			
Standby Mode	338 watts			
Low Power Mode	221 watts			
Auto Off / Sleep Mode	91 watts			
Warm-up (Ready to Mark)	From Low Power: As fast as 47 sec. (Dependent on the number of services registered) From Sleep: As fast as 3 min 30 sec. (Dependent on the number of services registered) The Intelligent Ready power management feature learns the unique print usage patterns of an office so the device will be in ready mode when needed and automatically go into lower power modes when not needed. This feature maximizes energy efficiency and results in pages being generated in as fast as 7.2 seconds			
Operating Environment				
Required Temperature Range	50° to 90° F (10° to 32° C)			
Required Relative Humidity	5% to 85%			
Sound	Run Continuous	Impulse	Standby	
Sound Power Levels	7.8 B(A)	8.6 B(A)	5.5 B(A)	
Sound Pressure Levels	63 dB(A)	71 dB(A)	40 dB(A)	
Dimensions and Weight	Width	Depth	Height	Weight
IOT with Offset Catch Tray (OCT)	55 in. / 1,398 mm	28.4 in. / 722 mm	45.5 in. / 1,156 mm	501 lbs. / 227 kg
IOT with Office Finisher	65 in. / 1,651 mm	28.4 in. / 722 mm	45.5 in. / 1,156 mm	562.2 lbs. / 255 kg
IOT with High Volume Finisher	81.7 in. / 2,075 mm	28.4 in. / 722 mm	45.5 in. / 1,156 mm	687 lbs. / 311.5 kg
IOT with High Volume Finisher with Booklet Maker, Post Process Inserter and Z-Fold / C-Fold Unit	96.2 in. / 2,443 mm	28.4 in. / 722 mm	45.5 in. / 1,156 mm	813 lbs. / 368.8 kg
IOT with OCT and High Capacity Feeder	63.6 in. / 1,607 mm	28.4 in. / 722 mm	45.5 in. / 1,156 mm	567 lbs. / 257 kg

Certifications	
	FCC Class A Compliant (U.S.); DOC Class A Compliant (Canada) CB Certified (IEC 60950/EN 60950) 2004/108/EC 2006/95/EC 99/5/EC Full System Common Criteria (ISO 15408) certification ENERGY STAR® EPEAT (United States) ECOLOGO® Citrix® Certified Cerner MEDITECH To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .
Paper Handling	
Duplex Automatic Document Feeder	
Capacity ^a	100 sheets
Speed	84 images per minute (ipm) black-and-white, 60 ipm color
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. SEF or 5.5 x 8.5 in. to 8.5 x 11 in. LEF (A5 / 148 x 210 mm to A3 / 297 x 420 mm SEF or A5 / 148 x 210 mm to A4 / 210 x 297 mm) LEF
Weights	13 lb. bond to 43 lb. bond (50 to 160 gsm)
Bypass Tray	
Capacity ^a	100 sheets of 20 lb. bond (75 gsm)
Sizes	A5 / 8.5 x 5.5 in. / #10 Envelope SEF to SRA3 / 12 x 18 in. SEF
Weights	16 lb. bond to 80 lb. cover (60 to 220 gsm)
Types	Plain Heavy weight Extra heavy weight Labels Transparencies (paper backed not supported) Envelopes Punched paper Recycled
Three Front Loading Paper Trays – Paper Trays 1, 2 and 3	
Capacity ^a	Trays 1-2: 550 sheets of 20 lb. bond (75 gsm) each tray Tray 3: 2,100 sheets of 20 lb. bond (75 gsm)
Sizes	Trays 1-2: 5.5 x 8.5 in. SEF to 11 x 17 in. SEF (A5 / 148 x 210 mm to A3 / 297 x 420 mm) Tray 3: 8.5 x 11 in. LEF (A4 / 210 x 297 mm)
Weights	16 lb. bond to 57 lb. bond / 80 lb. cover (60 to 220 gsm)
Types	Plain Labels (Trays 1-2 only) Punched paper (Trays 1-2 only)
High Capacity Feeder (Optional)	
Capacity ^a	Up to 4,000 sheets of 20 lb. bond (75 gsm)
Sizes	8.5 x 11 in. (A4 / 210 x 297 mm) LEF Optional 8.5 x 11 in. / 8.5 x 14 in. Short Edge Kit – 8.5 x 14 in. (A4 / 210 x 297 mm) SEF with 2,000 sheet capacity Optional 11 x 17 in. Short Edge Kit – 11 x 17 in. (A3 / 297 x 420 mm) SEF with 2,000 sheet capacity
Weights	16 lb. bond to 57 lb. bond / 80 lb. cover (60 to 220 gsm)
Total Capacity	
Standard Capacity ^a	3,300 sheets
Device Total Capacity ^a	7,300 sheets
Paper Output / Finishing	
Offset Catch Tray (OCT) (Optional)	
Capacity ^a	500 sheets of 20 lb. bond (75 gsm)
Office Finisher (Optional)	
Capacity ^a	Top Tray – 250 sheets Stacking Tray – 2,000 sheets
Sizes	5.5 x 8.5 in. (A5 / 148 x 210 mm) to 11 x 17 in. (A3 / 297 x 420 mm)
Weights	16 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm)

Stapling⁴	50 sheets Single and dual
Hole Punch (Optional) North America: Europe:	3-hole punch, 2-hole Legal punch 2-hole punch, 4-hole punch, 4-hole "Swedish" punch
High Volume Finisher (Optional)	
Capacity⁴	Top Tray – 250 sheets Stacking Tray – 3,000 sheets
Sizes	5.5 x 8.5 in. (A5 / 148 x 210 mm) to 11 x 17 in. (A3 / 297 x 420 mm)
Weights	13 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm)
Stapling⁴	100 sheets Front single (landscape), rear single (portrait), dual staples, multiple staples
Hole Punch (Optional) North America: Europe:	3-hole punch, 2-hole Legal punch 2-hole punch, 4-hole punch and 4-hole "Swedish" punch
High Volume Finisher with Booklet Maker (Optional)	
Capacity⁴	Top Tray – 250 sheets Stacking Tray – 3,000 sheets (2,000 sheets with Z-Fold / C-Fold)
Sizes	5.5 x 8.5 in. (A5 / 148 x 210 mm) to 11 x 17 in. (A3 / 297 x 420 mm)
Weights	16 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm)
Stapling⁴	100 sheets Front single (landscape), rear single (portrait), dual staples, multiple staples
Hole Punch (Optional) North America: Europe:	3-hole punch, 2-hole Legal punch 2-hole punch, 4-hole punch and 4-hole "Swedish" punch
Booklet Maker Capacity⁴	Tray stop up: 25 booklets (1-15 sheets per booklet) Tray stop down: Unlimited
Sizes	Letter – 8.5 x 11 in. (A4 / 210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3 / 297 x 420 mm)
Weights	16 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm)
Stapling⁴	Saddle-stitch (2-15 sheets / 8-60 page booklet)
Folding	V-folding (1-5 sheets / unstapled)
Z-Fold / C-Fold Unit with HVF with Booklet Maker (Optional)	
Capacity⁴	50 sheets or unlimited capacity with tray stop in the down position
Sizes	Letter – 8.5 x 11 in. (A4 / 210 x 297 mm)
Weights	16 lb. to 32 lb. bond (60 to 120 gsm)
Post Process Inserter (Optional with HVF and HVF with Booklet Maker)	
Capacity⁴	250 sheets Tray stop down: unlimited
Sizes	Letter – 8.5 x 11 in. (A4 / 210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3 / 297 x 420 mm)
Weights	16 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm)
Convenience Stapler (Optional)	
Capacity⁴	50 sheets 5,000 staples Requires a separate outlet
Copy	
First-copy-out Time (Letter / A4-size, from Platen to Center Tray)	As fast as 8.2 seconds color
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max.)	Up to 600 x 600 dpi
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)

Copy Features	<p>Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services (i.e. Color Copy) Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Transparencies</p>
Accessibility	<p>Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com</p>
Print	
Print Resolution	<p>Fast Color: 225 x 450 dpi Standard: 300 x 500 dpi Enhanced / High Speed: 450 x 567 dpi High Resolution: 600 x 600 dpi</p>
Print Features	<p>Application Defaults Banner Sheet Enable / Disable Bi-directional Status Custom Color Options (Color By Words) Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High)) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute LAN Fax (requires optional Fax Kit) Sample Set Saved Job (color jobs can be printed as monochrome) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)</p>
Print from USB	<p>Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS, PCL Color jobs can be printed as monochrome</p>
Operating Systems	<p>Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86 Ubuntu® 13.10 x64 openSUSE® 13.1 x64</p>

Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Print Solutions	
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer, Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
Unified Address Book for Fax, Internet Fax, Email and Scan to...	
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of fax numbers, emails, etc.
Scan	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)
Input Speed	Scan at up to 60 ipm color scanning, up to 84 ipm black-and-white – 8.5 x 11 in. / A4 LEF
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)
Maximum Scan Area	11 x 17 in. / A3
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS
File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearized PDF / PDF/A
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input
Scan Features	Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10)

Scan to Email (Standard)	
Scan Features	<ul style="list-style-type: none"> • Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options • Scan to Email S/MIME Encryption • Email signing (requires Smart Card option) • Auto send to self
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)
Scan to... (Standard)	
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)
Network Scanning – Software Solutions	
Xerox® Scan to PC Desktop® Professional (Optional)	<p>A desktop offering that provides advanced document imaging, archiving, editing and organization tools:</p> <ul style="list-style-type: none"> • PaperPort Professional image viewing and file management software <ul style="list-style-type: none"> – Complete PDF functionality – Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop / client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® ColorQube to individual desktops. Also includes email inbox polling capability
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.
Xerox® ConnectKey® Share to Cloud (Optional)	ConnectKey Share to Cloud provides organizations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs™, Salesforce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.
Xerox® ConnectKey® for DocuShare® (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).
Security	
Features	<ul style="list-style-type: none"> • Expanded Authentication <ul style="list-style-type: none"> – Network authentication to access device and / or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP – Xerox Secure Access Unified ID System® – Local Authentication (internal database) – Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET • Secure Data <ul style="list-style-type: none"> – Digitally signed PDF (when using Smart Card authentication) – Encrypted Scan to Email – Encrypted Password Protected PDF (Email and Network Scan Templates only) – Secure Print (up to 10 digit PIN or Network Authentication) – Immediate Image Overwrite – On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk – FIPS 140-2 256 bit Hard Disk Encryption • Expanded Authorization <ul style="list-style-type: none"> – SA access based on network credentials – Authorization per user per service – User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver • Secure Network Access <ul style="list-style-type: none"> • IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec integration, Device Security – McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) • Common Criteria Certification ISO 15408
Xerox Secure Access Unified ID System® (Optional)	<p>Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee / student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralized print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job.</p> <p>For more information, go to www.office.xerox.com/software-solutions</p>
Fax	
Network Server Fax Features	
Compatibility	ITU (CCITT) group 3 Various Xerox Business Innovation Partner Solutions
Maximum Scan Area	11 x 17 in. / A3
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print

Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Directory Access	Utilizes the Unified Address Book
Send / Receive	Multi-page TIFF, Image only PDF
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features (Optional (Customer-installable) – 1 and 2 lines)	
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilizing T38 (optional)
Compression / Speed	MH/G3, MMR/SG3
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report
Directory Access	Utilizes the Unified Address Book Group fax available
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals
Auto Resend	Up to 5 attempts
Device Management	
Management Support	SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. • CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®
Novell NDPS/NEPS	Server gateway application: centralized management tool.

Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions
CentreWare Internet Services – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts Remote Control Panel
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, RRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.
Accounting	
Xerox® Standard Accounting (Standard)	
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)
Features	<ul style="list-style-type: none"> • Administrator can manage the feature via the Web User Interface or device control panel in tools • Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file
Accounting Options – Network Accounting – Third Party Enablement	
	<ul style="list-style-type: none"> • Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party Networking Account • Interface with third party accounting terminal for accounting user interface

Xerox® ColorQube® 9302/9303

Supplies		
Cartridge-free Solid Ink Sticks⁵	4 sticks Black (Sold)	108R00832
	4 sticks Cyan (Sold)	108R00829
	4 sticks Magenta (Sold)	108R00830
	4 sticks Yellow (Sold)	108R00831
	4 sticks Black (Metered)	108R00836
	4 sticks Cyan (Metered)	108R00833
	4 sticks Magenta (Metered)	108R00834
	4 sticks Yellow (Metered)	108R00835
Staple Cartridge Staple Refills	Office Finisher	008R12964 008R12941
50 sheet Cartridge Staple Refills	High Volume Finisher	008R12919 008R12920
100 sheet Cartridge Staple Refills	High Volume Finisher	008R12912 008R12898
Staple Refills	Booklet Maker (for HVF)	008R12897
Staple Refills	Convenience Stapler	008R12941
Xerox® Smart Kit®		
Cleaning Unit		108R00989

¹ Standard and Fast Color speeds are available for printing in PostScript only. Copy settings are limited to High Resolution / Photo and Enhanced Mode speeds.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Expected regular monthly throughput.

⁴ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 24711. Yield will vary based on image, area coverage and print mode.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.
For more information, visit www.xerox.com/about-xerox/recycling.

For more information, call **1-800-ASK-XEROX** or visit us at www.xerox.com/office

