



# Xerox® VersaLink® B600 Printer

VersaLink B600 Printers are built on Xerox® ConnectKey® Technology. For more information, go to [www.connectkey.com](http://www.connectkey.com).

System Specifications		B600/DN
<b>One-sided Speed</b> A4 / 210 x 297 mm		Up to 55.5 ppm black and white
<b>Two-sided Speed</b> A4 / 210 x 297 mm		Up to 49.3 ppm black and white
<b>Monthly Duty Cycle<sup>1</sup></b>		Up to 250,000 pages / month
<b>Recommended Average Monthly Print Volume<sup>2</sup></b>		Up to 20,000 pages
<b>Hard Drive</b>		Optional 320 GB HDD
<b>Processor</b>		1.05 GHz ARM Dual Core
<b>Memory</b>		2 GB
<b>Connectivity</b>		Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
<b>Controller Features</b>		Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support (accessed from the user interface and print driver)
<b>User Interface Languages</b>		English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian
Device Specifications		
Electrical Requirements		
<b>Europe and Other Geographies</b>		Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 % Hz, 8 A
Power Consumption		
<b>Continuous Print<sup>3</sup></b>		900 watts or less
<b>Ready (Standby)<sup>3</sup></b>		72 watts or less
<b>Energy Saver (Sleep Mode)<sup>3</sup></b>		0.9 watts or less
<b>Power Off Mode<sup>3</sup></b>		0.3 watts or less
Operating Environment		
<b>Required Temperature Range (Storage)</b>		0° to 35° C
<b>Required Temperature Range (Operating)</b>		10 to 32° C
<b>Required Relative Humidity</b>		15 % to 85 %

## Xerox® VersaLink® B600 Printer

<b>Sound Power Levels</b> Running Standby	70 dB(a) or less 42 dB(a) or less			
<b>Sound Pressure Levels</b> Running Standby	56.8 dB(a) or less 27.1 dB(a) or less			
<b>Boot Time (from Off to UI Ready)</b>	Less than 79 seconds			
<b>Warm-up Time (from Sleep to UI Ready)</b>	Less than 47 seconds			
<b>Dimensions and Weight (Unpackaged)</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
B600/DN	427.4 mm	465.5 mm	443.4 mm	22.3 kg
B600/DN with 1 Additional Tray	427.4 mm	465.5 mm	566.4 mm	28.9 kg
B600/DN with High Capacity Feeder	427.4 mm	465.5 mm	902.4 mm	42 kg
B600/DN with High Capacity Feeder and Finisher	427.4 mm	465.5 mm	1150.4 mm	48.8 kg
B600/DN with High Capacity Feeder and Mailbox	427.4 mm	465.5 mm	1150.4 mm	47.3 kg
550-sheet Tray	420 mm	464.5 mm	123 mm	6.6 kg
2,000-sheet High Capacity Feeder (includes Caster Base)	724.2 mm	772.1 mm	459 mm	19.7 kg
Stand (includes Caster Base)	724.2 mm	772.1 mm	336 mm	16.6 kg
Caster Base	724.2 mm	772.1 mm	90 mm	8.5 kg
Mailbox	450.8 mm	477.6 mm	248.0 mm	5.3 kg
Finisher	450.8 mm	411.0 mm	248.0 mm	6.8 kg
<b>Dimensions and Weight (Packaged)</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
B600/DN	580 mm	634 mm	607 mm	28 kg
550-sheet Tray	535 mm	584 mm	248 mm	8.5 kg
2,000-sheet High Capacity Feeder (includes Caster Base)	568 mm	663 mm	711 mm	38 kg
Stand (includes Caster Base)	584 mm	629 mm	597 mm	28 kg
Caster Base	585 mm	619 mm	330 mm	18 kg
Mailbox	573 mm	518 mm	386 mm	7.8 kg
Finisher	573 mm	398 mm	386 mm	8.8 kg
Wireless Network Adapter (Wi-Fi Kit)	188 mm	136 mm	55 mm	0.1 kg
Hard Drive	116 mm	46 mm	178 mm	0.18 kg
<b>Certifications</b>				
To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .				

# Xerox® VersaLink® B600 Printer

Print	
<b>First-print-out Time</b>	As fast as 6.3 seconds
<b>Print Resolution</b>	Up to 1200 x 1200 dpi
<b>Page Description Languages</b>	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™
<b>Maximum Print Area</b>	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper
<b>Print Features</b>	Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to new paper size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default – DN configuration) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings
<b>Print from USB</b>	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A
<b>Operating Systems</b>	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP®  Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a>
<b>Fonts</b>	PostScript fonts: 136 PCL fonts: 83
<b>Xerox® Mobile Express Driver®</b>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favourite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.

# Xerox® VersaLink® B600 Printer

<b>Xerox® Pull Print Driver</b>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>
<b>Mobile Solutions and Mobile Device Apps</b>	
<b>Apple® AirPrint®</b>	<p>Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.</p>
<b>Google Cloud Print™</b>	<p>Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.</p>
<b>@PrintByXerox</b>	<p>@PrintByXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.</p>
<b>Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)</b>	<p>The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.</p>
<b>Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service</b>	<p>Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.</p>
<b>Security</b>	
<b>Security Features</b>	<ul style="list-style-type: none"> <li>Access Controls</li> <li>AES 256-bit Encryption</li> <li>Audit Log</li> <li>Certificate Path Validation</li> <li>Certificate Revocation List (CRL)/Status Protocol (OCSP)</li> <li>Detection of external programme falsification (XCP Plug-in)</li> <li>Cisco® Identity Services Engine (ISE) Integration</li> <li>Domain Filtering</li> <li>FIPS 140-2</li> <li>Firmware Verification</li> <li>Immediate Disk Overwrite*</li> <li>IP Address Filtering</li> <li>IPsec</li> <li>Network Authentication</li> <li>Port Filtering</li> <li>Pre-installed Self-Signed Certificates</li> <li>Role Based Permissions</li> <li>Secure Print</li> <li>Security Certificate Management</li> <li>Smart Card Enablement (CAC/PIV/.NET)</li> <li>SNMPv3</li> <li>Status Protocol (OCSP)</li> <li>TLS/SSL</li> </ul> <p>*Requires HDD/Productivity Kit</p>

# Xerox® VersaLink® B600 Printer

Accounting	
<b>Xerox® Standard Accounting / Network Accounting (Standard)</b>	
<b>Tracking</b>	Print usage
<b>Accounting</b>	<p>Xerox® Standard Accounting Tool            Up to 1,000 User Accounts without SSD            Up to 9,999 User Accounts with SSD            Up to 500 General accounts</p> <p>Network Accounting (Job Based Accounting)            Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD            Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD            Up to 14,000 accounting records (transactions)</p>
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server.
<b>Accounting Options – Network Accounting (Allows central server to manage all accounting)</b>	
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of print usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>
Paper Handling	
<b>Bypass Tray</b>	
<b>Capacity<sup>4</sup></b>	150 sheets
<b>Sizes</b>	Custom sizes: 76 x 127 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	60 to 220 gsm 60 to 176 gsm
<b>Media Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Labels Lightweight Card Stock Card Stock Letterhead Custom 1 - 5
<b>Tray 1</b>	
<b>Capacity<sup>4</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 76.2 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	60 to 220 gsm 60 to 176 gsm
<b>Media Types</b>	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Card Stock Card Stock Letterhead Custom 1 - 5

## Xerox® VersaLink® B600 Printer

Up to 4 Additional Trays (Optional)	
<b>Capacity<sup>4</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 76.2 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	60 to 220 gsm 60 to 176 gsm
<b>Media Types</b>	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Card Stock Card Stock Letterhead Custom 1 - 5
High Capacity Feeder (Optional - Can be combined with up to 1 Additional Tray)	
<b>Capacity<sup>4</sup></b>	2000 sheets
<b>Sizes</b>	Standard sizes: A4 SEF
<b>Weights</b> One-sided: Two-sided:	60 to 176 gsm 60 to 176 gsm
<b>Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Lightweight Card Stock Letterhead Custom 1 - 5
Total Paper Capacity <sup>4</sup>	
<b>Standard Paper Capacity</b>	700 sheets
<b>Maximum Paper Capacity</b>	3,250 sheets
Paper Output	
Output Tray	
<b>Capacity<sup>4</sup></b>	500 sheets with tray full sensor (without Finisher or Mailbox)
<b>Automatic Two-sided Printing</b>	Standard
Finisher (Optional)	
<b>Capacity<sup>4</sup></b>	500-sheet tray, 50-sheet stapling
Mailbox (Optional)	
<b>Capacity<sup>4</sup></b>	Four 100-sheet bins

# Xerox® VersaLink® B600 Printer

Device Management	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint® Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
Xerox® CentreWare® Web	
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
Embedded Web Server – Integrated Device Web Page	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Billing / Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management—view and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, PDF, XPS, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
Remote Services	
<b>Automated Meter Reading (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automated Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.
<b>MaintenanceAssistant</b>	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster with increased uptime.
What Comes in the Box	
	VersaLink B600 Printer Standard Capacity Print Cartridge –Black: 10,300 print capacity <sup>5</sup> Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord

# Xerox® VersaLink® B600 Printer

Supplies and Accessories	Quantity	Part Number
<b>Supplies</b>		
<b>Extra-High Capacity Toner Cartridge</b>	Black: 46,700 standard pages <sup>5</sup>	106R03944
<b>High Capacity Toner Cartridge</b>	Black: 25,900 standard pages <sup>5</sup>	106R03942
<b>Standard Capacity Toner Cartridge</b>	Black: 10,300 standard pages <sup>5</sup>	106R03940
<b>Drum Cartridge</b>	Black: 60,000 pages <sup>6</sup>	101R00582
<b>Accessories / Options</b>		
<b>2,000-sheet High Capacity Feeder (includes Caster Base)</b>		097S04948
<b>550-sheet Tray</b>		097S04949
<b>Finisher (500 sheets, 50-sheet stapler)</b>		097S04952
<b>4-Bin Mailbox (100 sheets per bin)</b>		097S04953
<b>Caster Base</b>		097S04954
<b>Stand (includes Caster Base)</b>		097S04994
<b>Wireless Network Adapter (Wi-Fi Kit)</b>		497K16750
<b>Productivity Kit with 320 GB HDD</b>		497K18360

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

<sup>4</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>6</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <http://www.office.xerox.com/latest/SUPGL-01.pdf>.

[www.xerox.com](http://www.xerox.com)

Configurations vary by geography.

