

Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

VersaLink® B7000 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.co.uk.

Convenience
Stapler (includes
Work Surface)



Office Finisher LX or Office
Finisher (not shown) with
optional Booklet Maker



High Capacity
Feeder



Integrated Office Finisher Type A or
Integrated Office Finisher (not pictured)



Single Tray Module

Single Tray
with Stand



Three Tray
Module



High-Capacity
Tandem Tray



| SYSTEM SPECIFICATIONS | VERSALINK® B7025 | VERSALINK® B7030 | VERSALINK® B7035 |
|--|--|--|--|
| One-sided Speed¹ A4/210 x 297 mm 216 x 356 mm A3/297 x 420 mm | Up to 25 ppm (pages per minute) long-edge feed (LEF) Up to 16 ppm Up to 14 ppm | Up to 30 ppm LEF Up to 20 ppm Up to 17 ppm | Up to 35 ppm LEF Up to 22 ppm Up to 19 ppm |
| Two-sided Speed¹ A4/210 x 297 mm 216 x 356 mm A3/297 x 420 mm | Up to 19 ppm LEF Up to 10 ppm Up to 9 ppm | Up to 23 ppm LEF Up to 12 ppm Up to 11 ppm | Up to 26 ppm LEF Up to 14 ppm Up to 13 ppm |
| Monthly Duty Cycle² | Up to 107,000 pages/month ¹ | Up to 129,000 pages/month ¹ | Up to 153,000 pages/month ¹ |
| Recommended Average Monthly Print Volume³ | Up to 13,000 pages | Up to 15,000 pages | Up to 17,000 pages |
| Hard Drive | 320 GB HDD (Optional on Desktop model) | | |
| Processor | 1.05 GHz Dual-Core | | |
| Memory | 2 GB | | |
| Connectivity | Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair | | |

Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

| | | | | |
|--|---|--------------|---------------|---------------|
| Controller Features | Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support | | | |
| User Interface Languages | English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian | | | |
| DEVICE SPECIFICATIONS | | | | |
| ELECTRICAL REQUIREMENTS | | | | |
| North America | Voltage: 110-127 V -10%/+6% Frequency: 50/60 Hz +/-3%, 12A | | | |
| Europe and Other Geographies | Voltage: 220-240 V +/- 10% Frequency: 50 Hz +/-3%, 8A | | | |
| POWER CONSUMPTION | | | | |
| Printing⁴ | 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh; 35 ppm = 1.7 kWh | | | |
| Standby Mode⁴ | 110V: 83 watts or less; For 220V: 86 watts or less | | | |
| Sleep Mode⁴ | 0.81 Watts or less | | | |
| OPERATING ENVIRONMENT | | | | |
| Required Temperature Range (Storage) | 0 to 35 °C | | | |
| Required Temperature Range (Operating) | 10 to 32 °C | | | |
| Required Relative Humidity | 10% to 85% | | | |
| Sound Power Levels | Printing: 6.75 B(A) or less • 25 ppm = 6.54 B(A); 30 ppm = 6.70 B(A); 35 ppm = 6.75 B(A) Standby: 4.10 B(A) or less • 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A); 35 ppm = 4.10 B(A) Full System (including Finisher and HCF) Printing: 25 ppm = 7.22 B(A); 30 ppm = 7.37 B(A); 35 ppm = 7.46 B(A) Standby: 25 ppm = 6.54 B(A); 30 ppm = 6.70 B(A); 35 ppm = 6.75 B(A) | | | |
| Sound Pressure Levels | Printing: 50.0 dB(A) • 25 ppm = 49.4 dB(A); 30 ppm = 49.7 dB(A); 35 ppm = 50.0 dB(A) Standby: 16.4 dB(A) • 25 ppm = 16.4 dB(A); 30 ppm = 16.4 dB(A); 35 ppm = 16.0 dB(A) Full System (including Finisher and HCF) Printing: 25 ppm = 53.4 dB(A); 30 ppm = 53.6 dB(A); 35 ppm = 54.0 dB(A) Standby: 25 ppm = 16.0 dB(A); 30 ppm = 16.0 dB(A); 35 ppm = 15.7 dB(A) | | | |
| Boot Time (from Off to UI Ready) | As fast as 98 seconds | | | |
| Warm-up Time (from Sleep to UI Ready) | As fast as 12 seconds | | | |
| DIMENSIONS AND WEIGHT (UNPACKAGED) | WIDTH | DEPTH | HEIGHT | WEIGHT |
| Base Unit | 590 mm | 670.8 mm | 767.9 mm | 51.3 kg |
| Base Unit with Single Tray with Stand Module | 615.7 mm | 670.8 mm | 1118.6 mm | 75.8 kg |
| Base Unit with High Capacity Tandem Tray Unit | 615.7 mm | 670.8 mm | 1118.6 mm | 87.2 kg |

Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

| | | | | |
|---|--|-------------------------|-------------------------|----------|
| Base Unit with Three Tray Module and Office Finisher (with Booklet Maker) | 1148.6 mm | 678.6 mm | 1118.6 mm | 124.2 kg |
| Base Unit with Three Tray Module and Office Finisher LX (with Booklet Maker) | 1194.0 mm | 681.8 mm | 1118.6 mm | 113.0 kg |
| CERTIFICATIONS | | | | |
| To view the latest list of certifications, go to www.xerox.com/OfficeCertifications . | | | | |
| PRINT | VERSALINK® B7025 | VERSALINK® B7030 | VERSALINK® B7035 | |
| First-Print-Out Time | As fast as 10.4 seconds | As fast as 9.1 seconds | As fast as 9.1 seconds | |
| Print Resolution | Up to 1200 x 1200 dpi | | | |
| Page Description Languages | PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™ (Optional) | | | |
| Maximum Print Area | 4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper | | | |
| Print Features | <ul style="list-style-type: none"> Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) LAN Fax (requires Fax Kit) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Earth Smart Driver Settings | | | |
| Print from USB | <ul style="list-style-type: none"> Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A | | | |

Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

| | | | |
|------------------------------------|--|---|---|
| Operating Systems | <p>Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 Mac OS® version 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com/en-gb.</p> | | |
| Fonts | <p>PostScript fonts: 136 PCL fonts: 83</p> | | |
| Xerox® Global Print Driver® | <p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end users, reducing the number of support calls and simplifying print services management.</p> | | |
| Xerox® Pull Print Driver | <p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p> | | |
| COPY | VERSALINK® B7025 | VERSALINK® B7030 | VERSALINK® B7035 |
| Document Scanner | 110-sheet Single Pass Duplex Automatic Document Feeder (DADF) | | |
| Document Scanner Size | <p>Platen: Up to 332.0 x 437 mm DADF: Up to 297 x 431.8 mm</p> | | |
| Simplex Copy Speed | <p>Up to 25 cpm (copies per minute) 216 x 279 mm Up to 25 cpm A4 (210 x 297 mm)</p> | <p>Up to 30 cpm (copies per minute) 216 x 279 mm Up to 30 cpm A4 (210 x 297 mm)</p> | <p>Up to 35 cpm (copies per minute) 216 x 279 mm Up to 35 cpm A4 (210 x 297 mm)</p> |
| Duplex Copy Speed | <p>Up to 20 cpm (copies per minute) 216 x 279 mm Up to 20 cpm A4 (210 x 297 mm)</p> | <p>Up to 20 cpm (copies per minute) 216 x 279 mm Up to 20 cpm A4 (210 x 297 mm)</p> | <p>Up to 20 cpm (copies per minute) 216 x 279 mm Up to 20 cpm A4 (210 x 297 mm)</p> |
| First-Copy-Out Time | As fast as 6.8 seconds | As fast as 5.4 seconds | As fast as 5.4 seconds |
| Sides (input: output) | 1:1, 1:2, 2:2 and 2:1 | | |
| Quantity | 1 to 999 | | |
| Resolution (max.) | Up to 600 x 600 dpi | | |
| Reduction/Enlargement | Variable zoom from 25 % to 400 % in 1 % increments | | |
| Concurrency | Concurrent scanning and printing | | |

| | |
|---|---|
| Copy Features | Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)* Automatic Background Suppression Book Copying with Centre Erase Booklet Copying* Collation Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Image Shift Lighten/Darken N-up Reduce/Enlarge 25% to 400% Original Orientation Original Size Original Type Page Layout Sample Copy Saturation Sharpness *Requires HDD/Productivity Kit |
| SCAN | |
| Capability | Black-and-white and colour scanning |
| Concurrency | Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs |
| Simplex Input Speed | Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – 55 ipm A4 (210 x 297 mm) |
| Duplex Input Speed | Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – 26 ipm A4 (210 x 297 mm) |
| Resolution | Optical – 600 x 600 dpi |
| Bit Depth | 24-bit colour/8-bit greyscale |
| Maximum Scan Area | Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm |
| Network Filing Protocols | FTP SMTP SMB sFTP |
| File Formats | JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearised PDF (set via embedded web server) and PDF/A |
| Scan Driver Compatibility (Network Only) | WIA TWAIN |

| | |
|---|---|
| Supported Scan Destinations | Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB) |
| NETWORK SCANNING – SOFTWARE SOLUTIONS | |
| Xerox® ConnectKey® Apps (Found at the Xerox App Gallery) | Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the Xerox® ConnectKey® Technology-enabled multifunction printer. |
| PSTN ONE-LINE OR THREE-LINE FAX (OPTIONAL) | |
| Fax⁵ | |
| Fax Speed | 33.6 Kbps |
| Resolution | Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi |
| Compression | MH, MR, MMR, JBIG |
| Fax Features | Walk-up Fax, includes LAN Fax, Direct Fax, Server Fax Enablement, Fax Forward to Email, Fax dialling via Unified Address Book (up to 2,000 contacts) |
| FAX OVER IP (OPTIONAL) | |
| Compliance | T.38 compliant IP/SIP |
| Resolution | Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi |
| Compression | MH, MR, MMR, JBIG |
| Fax Features | Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialling via Unified Address Book (up to 2,000 contacts) |
| MOBILE SOLUTIONS AND MOBILE DEVICE APPS | |
| Apple® AirPrint® | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network. |
| Mopria® Print Service | ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria®-supported (Android) smart phone, tablet and other mobile devices instantly and easily. |
| Xerox® @PrintByXerox App | @PrintByXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or multifunction printer using a single email address with no IT intervention. No training is needed. End users simply send attachments to the email address, and release them at the multifunction printer panel. |
| Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store) | The Xerox® Print Service plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store. |
| Xerox® Workplace Mobile App (download from the Xerox App Gallery) | The Xerox® Workplace Mobile App gives you the personal contactless connection you need with your multifunction printer (MFP), allowing you to save time on daily tasks and get work done safely. You can scan, print, copy or release jobs using your mobile smartphone as a remote control, without having to touch your MFP user panel. It takes the guesswork out of quickly and securely connecting your iOS and Android devices to your Xerox® Multifunction Printer. Download the app for free. Use it with Xerox® Workplace Solutions to access advanced features. |
| Xerox® Workplace Suite and Xerox® Workplace Cloud | Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution. |

| SECURITY | |
|--|--|
| Security Features | Access Controls AES 256-bit encryption Audit log Certificate path validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL *Requires HDD/Productivity Kit |
| ACCOUNTING | |
| XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD) | |
| Tracking | Copy, Print, Fax, Scan and Email usage |
| Accounting | Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job-Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions) |
| Features | Administrator can manage the feature via the Embedded Web Server. |
| ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING) | |
| | <ul style="list-style-type: none"> Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.co.uk Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third-party server, enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account |

| PAPER HANDLING | |
|---|--|
| DOCUMENT FEEDER | |
| Capacity⁶ | Duplex Automatic Document Feeder (DADF): 110 sheets |
| Sizes One-sided: Two-Sided | Custom sizes: 125 x 85 mm to 297 x 431.8 mm 125 x 110 mm to 297 x 431.8 mm |
| Weights One-sided: Two-Sided | 38 to 128 gsm 50 to 128 gsm |
| BYPASS TRAY | |
| Capacity⁶ | 100 sheets |
| Sizes | Custom sizes: 88.9 x 98.4 mm to 297 x 431.8 mm |
| Weights One-sided: Two-Sided | 60 to 216 gsm 60 to 169 gsm |
| Types | Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Card Stock Pre-Printed Recycled |
| TRAY 1 | |
| Capacity⁶ | 520 sheets |
| Sizes | Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm |
| Weights One-sided: Two-Sided | 60 to 256 gsm 60 to 169 gsm |
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Card Stock Heavyweight Cardstock Pre-Printed Recycled |

| SINGLE TRAY MODULE (OPTIONAL – BASE MODEL ONLY) | |
|--|--|
| Capacity⁶ | 520 sheets |
| Sizes | Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm |
| Weights One-sided: Two-Sided | 60 to 256 gsm 60 to 169 gsm |
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Card Stock Heavyweight Cardstock Pre-Printed Recycled |
| SINGLE TRAY MODULE WITH STAND (OPTIONAL) | |
| Capacity⁶ | 520 sheets |
| Sizes | Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm |
| Weights One-sided: Two-Sided | 60 to 256 gsm 60 to 169 gsm |
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Card Stock Heavyweight Cardstock Pre-Printed Recycled |
| THREE TRAY MODULE (OPTIONAL) | |
| Capacity⁶ | Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets |
| Sizes | Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm |
| Weights One-sided: Two-Sided | 60 to 256 gsm 60 to 169 gsm |

| | |
|--|--|
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Card Stock Heavyweight Cardstock Pre-Printed Recycled |
| HIGH CAPACITY TANDEM TRAY MODULE (OPTIONAL) | |
| Capacity⁶ | Tray 2: 520 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets |
| Sizes | Tray 2: Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm Tray 3: Standard Sizes: A4 or B5 Tray 4: Standard Sizes: A4 or B5 |
| Weights One-sided: Two-Sided | 60 to 256 gsm 60 to 169 gsm |
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Card Stock Heavyweight Cardstock Pre-Printed Recycled |
| ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL) | |
| Capacity⁶ | Up to 60 envelopes |
| Sizes | No. 10 Commercial, Monarch, DL, C5 Custom sizes: 98 x 148 mm to 162 x 241 mm |
| Weights | 75 to 90 gsm |
| HIGH CAPACITY FEEDER (OPTIONAL) | |
| Capacity⁶ | 2,000 sheets |
| Sizes | Standard Sizes: A4 or B5 |
| Weights One-sided: Two-Sided | 60 to 216 gsm 60 to 169 gsm |

| | |
|---|--|
| TOTAL CAPACITY | |
| Base Unit Capacity ⁶ | 620 sheets |
| Single Tray Module Capacity ⁶ | 1,140 sheets |
| Single Tray Module with Stand Capacity ⁶ | 1,140 sheets |
| Three Tray Module Capacity ⁶ | 2,180 sheets |
| High-Capacity Tandem Tray Capacity ⁶ | 3,140 sheets |
| FINISHING | |
| OUTPUT TRAYS (OPTIONAL ON DESKTOP MODEL) | |
| Dual Catch Trays ⁶ | 250 sheets each; Lower tray offsets |
| INTEGRATED OFFICE FINISHER TYPE A AND INTEGRATED OFFICE FINISHER (OPTIONAL) | |
| Stacking Tray | 500 sheets of 80 gsm – A4 or 250 sheets of 80 gsm – A3 |
| Sizes | 89 x 98 mm to 297 x 432 mm |
| Weights | Integrated Office Finisher Type A: 60 to 220 gsm Integrated Office Finisher: 60 to 256 gsm |
| Stapling | Dual Auto Stapling (Single for Type A): 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers) |
| OFFICE FINISHERS (OPTIONAL) | |
| Capacity ⁶ | Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (A4) (dual stapling only with optional booklet maker) |
| Sizes: Office Finisher LX Office Finisher | 210 x 182 mm to 297 x 432 mm 148.0 x 297.0 mm to 148.0 to 432.0 mm |
| Weights | Office Finisher LX: 60 to 220 gsm Office Finisher: 60 to 256 gsm |
| Multiposition Stapling | 50 sheets of 24 lb bond/90 gsm |
| Hole Punch (Optional) North America: Europe: | Office Finisher LX up to 200 gsm/Office Finisher up to 220 gsm 2-3 Hole Punch 2-4 Hole Punch |
| BOOKLET MAKER FOR OFFICE FINISHERS (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL) | |
| Capacity ⁶ | 40 booklets (2-15 sheets per booklet – 80 gsm or less) |
| Sizes | Letter – A4 SEF Legal – B4 SEF Ledger – A3 SEF |
| Saddle-stitch Stapling | 2-15 sheets/8-60 page booklet Office Finisher LX: 60 to 90 gsm Office Finisher: 64 to 220 gsm |
| Score/Crease | 1-15 sheets/unstapled/64-105 gsm |
| CONVENIENCE STAPLER (OPTIONAL – INCLUDES WORK SURFACE) | |
| Capacity ⁶ | 50-sheet stapling 5,000 staples Requires a separate outlet |
| DEVICE MANAGEMENT | |
| Network Protocols | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP Most protocols not in use can be disabled |

| | | |
|---|--|--------------------|
| Administrative Protocols | DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS | |
| REMOTE CONTROL PANEL | | |
| | <ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorised users can control the device remotely from a web page on any device • Remote user experience is identical to performing tasks directly at the device | |
| XEROX® CENTREWARE® WEB | | |
| | <ul style="list-style-type: none"> • A web-based server application for network administrators that permits web-browser-based device management from any workstation, whether running Windows, UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management | |
| XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE | | |
| Device Status | <ul style="list-style-type: none"> • Tray Status/Contents • Consumables Status • Billing/Usage • Quick Links • Online Support | |
| Print Queue Viewing | Job print queue management – view and delete | |
| Job Submission | Print-ready files (PS (with optional PostScript option), PCL, PDF, XPS, JPEG) | |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device | |
| Browsers | Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™ | |
| REMOTE SERVICES | | |
| Automatic Meter Readings (AMR) | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. | |
| Automatic Supplies Replenishment (ASR) | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory. | |
| SUPPLIES AND ACCESSORIES | | |
| | QUANTITY | PART NUMBER |
| SUPPLIES | | |
| Standard Capacity Print Cartridges⁷ | 15,500 standard pages | 106R03393 |
| High Capacity Print Cartridges⁷ | 31,000 standard pages | 106R03394 |
| Worldwide Metered Print Cartridge⁸ | 30,000 standard pages | 106R03392 |
| Black Drum Cartridge⁹ | 80,000 pages | 113R00779 |
| Office Finishers Booklet Maker Cartridge (8 cartridges per carton) | 16,000 staples | 008R12897 |
| Staple Refills for Finishers (3 cartridges per carton) | 15,000 staples | 008R12941 |
| Staple Cartridge for Finishers (1 cartridge per carton) | 5,000 staples | 008R12964 |

Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

| ACCESSORIES/OPTIONS | PART NUMBER |
|---|--|
| Single Tray Module (does not include Stand – for Base Model only) | 097S04910 |
| Single Tray with Stand Module | 097S04907 |
| Three Tray Module | 097S04908 |
| High-Capacity Tandem Tray Module | 097S04909 |
| Envelope Tray (This Replaces Tray 1) | 497K17720 |
| Center Output Tray (Dual Catch Tray) | 497K17800 |
| HDD (320 GB Hard Drive) | 497K17740 |
| Integrated Office Finisher (Type A) | 097S04911 |
| Integrated Office Finisher | 097S04847 |
| Office Finisher LX | 097S04848 |
| Office Finisher | 097S05019 |
| Booklet Maker for Office Finisher LX | 497K03852 |
| Booklet Maker for Office Finisher | 497K20590 |
| 2/3 Hole Punch for Office Finisher LX (available in Western Hemisphere) | 497K03860 |
| 2/3 Hole Punch for Office Finisher (available in Western Hemisphere) | 497K20600 |
| 2/4 Hole Punch for Office Finisher LX (available in Eastern Hemisphere) | 497K03870 |
| 2/4 Hole Punch for Office Finisher (available in Eastern Hemisphere) | 497K20610 |
| 1 Line Fax Kit (PSTN Fax) | 497K17750 |
| 3 Line Fax Kit (PSTN Fax) | 497K17760 |
| Wireless Network Adapter Kit | 497K16750 |
| Internal Card Reader/RFID Kit | 497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere) |
| PostScript Kit | 497K17810 |
| Fax Over IP Kit | 497K17820 |

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

⁵ Requires analogue phone line.

⁶ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks

⁷ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁸ Assumptions: Toner cartridge yield is based on 5% area coverage on A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

⁹ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed.

For more information, visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme.

For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.

Configurations vary by geography.