

Xerox® VersaLink® B610 Printer



VersaLink® B610 Printers are built on Xerox® ConnectKey® Technology.
For more information, go to www.ConnectKey.com.

SYSTEM SPECIFICATIONS	VERSALINK® B610
One-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 65 ppm black-and-white Up to 63 ppm black-and-white Up to 54 ppm black-and-white
Two-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 58.5 ppm black-and-white Up to 56 ppm black-and-white Up to 30.1 ppm black-and-white
Monthly Duty Cycle²	Up to 300,000 pages/month
Recommended Average Monthly Print Volume³	Up to 30,000 pages
Hard Drive	Optional 320 GB HDD
Processor	1.05 GHz ARM Dual Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 % Hz, 12 A			
Europe and Other Geographies	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 % Hz, 8 A			
POWER CONSUMPTION				
Continuous Print⁴	Maximum: 900 watts or less			
Ready (Standby)⁴	72 watts or less			
Energy Saver (Sleep Mode)⁴	0.79 watts or less			
Power Off Mode⁴	220-240 VAC: 0.3 watts or less 110-127 VAC: 0.2 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° to 95° F/0° to 35° C			
Required Temperature Range (Operating)	50 to 90° F/10 to 32° C			
Required Relative Humidity	15% to 85%			
Sound Power Levels Running Standby	70 dB(a) or less 42 dB(a) or less			
Sound Pressure Levels Running Standby	56.8 dB(a) or less 27.1 dB(a) or less			
Boot Time (from Off to UI Ready)	Less than 79 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 47 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	16.8 in./427.4 mm	18.3 in./465.5 mm	17.5 in./443.4 mm	49.2 lb./22.3 kg
Base Unit with Additional 550-sheet Tray	16.8 in./427.4 mm	18.3 in./465.5 mm	22.3 in./566.4 mm	63.8 lb./28.9 kg
Base Unit with High Capacity Feeder	16.8 in./427.4 mm	18.3 in./465.5 mm	35.5 in./902.4 mm	92.5 lb./42 kg
Base Unit with High Capacity Feeder and Finisher	16.8 in./427.4 mm	18.3 in./465.5 mm	45.3 in./1150.4 mm	107.5 lb./48.8 kg
Base Unit with High Capacity Feeder and Mailbox	16.8 in./427.4 mm	18.3 in./465.5 mm	45.3 in./1150.4 mm	104.2 lb./47.3 kg
550-sheet Tray	16.5 in./420 mm	10.4 in./464.5 mm	4.8 in./123 mm	14.6 lb./6.6 kg
High Capacity Feeder (includes Caster Base)	28.5 in./724.2 mm	30.4 in./772.1 mm	18 in./459 mm	43.3 lb./19.7 kg
Cabinet (includes Caster Base)	28.5 in./724.2 mm	30.4 in./772.1 mm	13.2 in./336 mm	37 lb./16.6 kg
Caster Base	28.5 in./724.2 mm	30.4 in./772.1 mm	3.5 in./90 mm	18.7 lb./8.5 kg
Mailbox	17.7 in./450.8 mm	18.8 in./477.6 mm	9.8 in./248.0 mm	11.7 lb./5.3 kg

Xerox® VersaLink® B610 Printer

Finisher	17.7 in./450.8 mm	16.2 in./411.0 mm	9.8 in./248.0 mm	15 lb./6.8 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	22.8 in/580 mm	25 in/634 mm	23.9 in/607 mm	61.6 lb./28 kg
550-sheet Tray	21 in/535 mm	23 in/584 mm	9.8 in/248 mm	18.7 lb./8.5 kg
High Capacity Feeder (includes Caster Base)	22.4 in/568 mm	26.1 in/663 mm	28 in/711 mm	79.4 lb./38 kg
Cabinet (includes Caster Base)	23 in/584 mm	24.8 in/629 mm	23.5 in/597 mm	57.3 lb./28 kg
Caster Base	23 in/585 mm	24.4 in/619 mm	13 in/330 mm	39.7 lb./18 kg
Mailbox	22.6 in/573 mm	20.4 in/518 mm	15.2 in/386 mm	16.3 lb./7.8 kg
Finisher	22.6 in/573 mm	15.7 in/398 mm	15.2 in/386 mm	18.6 lb./8.8 kg
Wireless Network Adapter (Wi-Fi Kit)	7.4 in/188 mm	5.4 in/136 mm	2.2 in/55 mm	1.05 lb./0.1 kg
Hard Drive	4.5 in/116 mm	1.8 in/46 mm	7 in/178 mm	0.4 lb./0.18 kg
CERTIFICATIONS				
To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .				
PRINT				
First-Print-Out Time	As fast as 3.7 seconds			
Print Resolution	Up to 1200 x 1200 dpi			
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
Maximum Print Area	4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper			

<p>Print Features</p>	<p>Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing Watermark (predefined and custom) Earth Smart Driver Settings</p>
<p>Print from USB</p>	<p>Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</p>
<p>Operating Systems</p>	<p>Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com</p>
<p>Fonts</p>	<p>PostScript fonts: 136 PCL fonts: 83</p>
<p>Xerox® Global Print Driver®</p>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<p>Xerox® Pull Print Driver</p>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>

SOFTWARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.
MOBILE SOLUTIONS AND MOBILE DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox® @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.
SECURITY	
Security Features	<ul style="list-style-type: none"> Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM) <p>*Requires HDD/Productivity Kit</p>

ACCOUNTING	
XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)	
Tracking	Print usage
Accounting	<p>Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts</p> <p>Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)</p>
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of print usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party NetworkingAccount Interface with third party accounting terminal for accounting user interface
PAPER HANDLING	
BYPASS TRAY	
Capacity⁵	150 sheets
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in./76 x 127 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
Media Types	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
TRAY 1	
Capacity⁵	550 sheets
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76.2 x 190 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm

Media Types	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
UP TO 4 ADDITIONAL TRAYS	
Capacity⁵	550 sheets
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76.2 x 190 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
Media Types	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
HIGH CAPACITY FEEDER (CAN BE COMBINED WITH UP TO 1 ADDITIONAL TRAY)	
Capacity⁵	2,000 sheets
Sizes	Standard sizes: A4 SEF, Letter SEF
Weights One-sided: Two-sided:	16 lb. bond to 65 lb. cover/60 to 176 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
Types	Plain Paper Bond Punched Pre-Printed Recycled Lightweight Cardstock Letterhead Custom 1 - 5
TOTAL PAPER CAPACITY⁵	
Base Unit	700 sheets
Base Unit with Additional 550-sheet Tray	1,250 sheets
Base Unit with High Capacity Feeder	2,700 sheets
Base Unit with High Capacity Feeder and Finisher	2,700 sheets
Base Unit with High Capacity Feeder and Mailbox	2,700 sheets
Maximum Paper Capacity	3,250 sheets

PAPER OUTPUT	
OUTPUT TRAY	
Capacity⁵	500 sheets with tray full sensor (without Finisher or Mailbox)
Automatic Two-sided Printing	Standard
FINISHER	
Capacity⁵	500-sheet tray, 50-sheet stapling
MAILBOX	
Capacity⁵	Four 100-sheet bins
DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint® Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
REMOTE CONTROL PANEL	
	<ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorized users can control the device remotely from a web page on any PC • Remote user experience is identical to performing tasks directly at the device
XEROX® CENTREWARE® WEB	
	<ul style="list-style-type: none"> • A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul style="list-style-type: none"> • Tray Status/Contents • Consumables Status • Billing/Usage • Quick Links • Online Support
Print Queue Viewing	Job print queue management — view and delete
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.

WHAT COMES IN THE BOX		
	VersaLink® B600 Printer Standard Capacity Print Cartridge –Black: 10,300 print capacity ⁶ Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Extra-High Capacity Toner Cartridge	Black: 46,700 standard pages ⁶	106R03944
High Capacity Toner Cartridge	Black: 25,900 standard pages ⁶	106R03942
Standard Capacity Toner Cartridge	Black: 10,300 standard pages ⁶	106R03940
Drum Cartridge	Black: 60,000 pages ⁷	101R00582
ACCESSORIES/OPTIONS		
2,000-sheet High Capacity Feeder (includes Caster Base)		097S04948
550-sheet Tray		097S04949
Finisher (500 sheets, 50-sheet stapler)		097S04952
4-Bin Mailbox (100 sheets per bin)		097S04953
Caster Base		097S04954
Stand (includes stabilizers)		097S04994
Wireless Connectivity Kit		497K16750
Productivity Kit with 320 GB HDD		497K18360

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.