

## Xerox<sup>®</sup> VersaLink<sup>®</sup> C400 Color Printer

VersaLink® C400 Color Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK® C400	
One-sided Speed <sup>1</sup> 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 36 ppm color and black-and-white Up to 35 ppm color and black-and-white Up to 30 ppm color and black-and-white	
Two-sided Speed <sup>1</sup> 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 24 ppm color and black-and-white Up to 23 ppm color and black-and-white Up to 21 ppm color and black-and-white	
Monthly Duty Cycle <sup>2</sup>	Up to 85,000 pages/month	
Recommended Average Monthly Print Volume <sup>3</sup>	Up to 8,500 pages	
Processor	1.05GHz ARM Dual-Core	
Memory	2 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian	

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 VAC+/- 10 % Frequency: 50/60 Hz+/- 3Hz, 10 A			
Europe and Other Geographies	Voltage: 220-240 VAC+/- 10 % Frequency: 50/60 Hz+/- 3Hz, 6 A			
POWER CONSUMPTION				
Continuous Printing <sup>4</sup>	705 watts or less			
Ready/Standby Mode <sup>4</sup>	76 watts or less			
Energy Saver/Sleep Mode <sup>4</sup>	4 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° F to 95° F/0° C to 35° C			
Required Temperature Range (Operating)	50° F to 90° F/10° C to 32° C			
Required Relative Humidity	10% to 85%			
Sound Power Levels Operating Standby	6.88 B(A) or less 5.0 B(A) or less			
Sound Pressure Levels Operating Standby	53.1 dB(A) or less 29.2 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 60 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 6 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersαLink® C400	19.3 in./491 mm	19.2 in./488 mm	15.7 in./399 mm	57 lb./26 kg
550-sheet Paper Tray	16.8 in./427 mm	19.1 in./485 mm	5.4 in./138 mm	8.6 lb./3.9 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C400	24.7 in./627 mm	25.1 in./638 mm	20.7 in./526 mm	67.13 lb./30.45 kg
550-sheet Paper Tray	23.2 in./590 mm	21.4 in./544 mm	9.5 in./241 mm	11.7 lb./5.3 kg
SYSTEM CERTIFICATION/REGUL				
Certifications	To view the latest list o	of certifications, go to www.x	xerox.com/OfficeCertificat	ions.
PRINT				
First-Print-Out Time	As fast as 9.3 seconds	color/8.2 seconds black-and	l-white	
Print Resolution	Up to 600 x 600 x 8 dp	oi (enhanced)		
Page Description Languages	PCL <sup>®</sup> 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe <sup>®</sup> PostScript <sup>®</sup> 3 <sup>™</sup>			
Maximum Print Area	4 mm from edge of paper			

Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printting Watermark (predefined and custom) Xerox® Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A	
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP®  Note: For information about supported versions for the above operating systems, please visit our Drivers &	
Fonts	Downloads page and specify your device at <a href="https://www.support.xerox.com">www.support.xerox.com</a> .  PostScript fonts: 136 PCL fonts: 83	
Xerox <sup>®</sup> Globαl Print Driver <sup>®</sup>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	

E DEVICE APPS	
Print email, photos and important office documents directly from an Apple iPhone <sup>®</sup> or iPad <sup>®</sup> with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.	
@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.	
The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	
The Xerox® Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox® Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly.	
Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.	
Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.	
Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Cisco® Identity Services Engine (ISE) Integration Detection of External Program Falsification (XCP Plug-in) Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3	

ACCOUNTING			
XEROX® STANDARD AC	COUNTING TOOL/NETWORK ACCOUNTING (STANDARD)		
Tracking	Print usage		
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts		
	Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)		
Features	Administrator can manage the feature via the Embedded Web Server.		
ACCOUNTING OPTION	S – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)		
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>		
PAPER HANDLING			
BYPASS TRAY			
Capacity <sup>5</sup>	150 sheets		
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in./76.2 x 127 mm to 216 x 356 mm		
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 60 lb. cover/60 to 163 gsm		
Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Labels Envelopes Custom		
TRAY 1			
Capacity <sup>5</sup>	550 sheets		
Sizes	Custom sizes: 5.8 x 8.3 in. to 8.5 x 14 in./148 x 210 mm to 216 x 356 mm		
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 60 lb. cover/60 to 163 gsm		

Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Custom	
OPTIONAL TRAY 2		
Capacity <sup>5</sup>	550 sheets	
Sizes	Custom Sizes: 5.8 x 8.3 in. to 8.5 x 14 in./148 x 210 mm to 216 x 356 mm	
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 60 lb. cover/60 to 163 gsm	
Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Custom	
TOTAL CAPACITY		
Standard Device Capacity <sup>5</sup>	700 sheets	
Total Device Capacity <sup>5</sup>	1,250 sheets	
PAPER OUTPUT		
Output Capacity <sup>5</sup>	250 sheets	
Automatic Two-sided Printing	Standard	

DEVICE MANAGEMENT		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS	
REMOTE CONTROL PANEL		
	<ul> <li>Enables faster, more convenient technical support and user training</li> <li>IT administrators and other authorized users can control the device remotely from a web page on any device</li> <li>Remote user experience is identical to performing tasks directly at the device</li> </ul>	
XEROX® CENTREWARE® WEB SO	OFTWARE	
	<ul> <li>A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>	
XEROX® EMBEDDED WEB SERVE	R – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul> <li>Tray Status/Contents</li> <li>Consumables Status</li> <li>Billing/Usage</li> <li>Quick Links</li> <li>Online Support</li> </ul>	
Print Queue Viewing	Job print queue management — view and delete	
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	
REMOTE SERVICES		
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	

## Xerox® VersaLink® C400 Color Printer

WHAT'S IN THE BOX			
	VersaLink C400 Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 2,000 print capacity <sup>6</sup> , Black: 3,000 print capacity <sup>6</sup> Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord  QUANTITY  PART NUMBER		
SUPPLIES AND ACCESSORIES			
SUPPLIES			
Standard Capacity Toner Cartridges	Cyan: 2,500 standard pages <sup>6</sup> Magenta: 2,500 standard pages <sup>6</sup> Yellow: 2,500 standard pages <sup>6</sup> Black: 2,500 standard pages <sup>6</sup>	106R03510 106R03511 106R03509 106R03508	
High Capacity Toner Cartridges	Cyan: 4,800 standard pages <sup>6</sup> Magenta: 4,800 standard pages <sup>6</sup> Yellow: 4,800 standard pages <sup>6</sup> Black: 5,000 standard pages <sup>6</sup>	106R03522 106R03523 106R03521 106R03520	
Extra-High Capacity Toner Cartridges	Cyan: 8,000 standard pages <sup>6</sup> Magenta: 8,000 standard pages <sup>6</sup> Yellow: 8,000 standard pages <sup>6</sup> Black: 10,500 standard pages <sup>6</sup>	106R03534 106R03535 106R03533 106R03532	
ROUTINE MAINTENANCE ITEM	S		
Imaging Unit (includes 4 imaging units)	Cyan: 60,000 standard pages <sup>7</sup> Magenta: 60,000 standard pages <sup>7</sup> Yellow: 60,000 standard pages <sup>7</sup> Black: 60,000 standard pages <sup>7</sup>		
Waste Cartridge	30,000 pages <sup>7</sup>	108R01124	
ACCESSORIES			
550-sheet Paper Tray		097S04400	
Productivity Kit with 320 GB HDD		097S04914	
Stand		497K13660	
Wireless Network Adapter		497K16750	

<sup>&</sup>lt;sup>1</sup>Declared print speed in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



Declared print speed in accordance with ISO/IEC. 24/34.

\*\*Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

\*\*Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

\*\*Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

\*\*Popper capacities are based on 20 Ib/75 gsm stock; capacities will vary with different weight stocks.

\*\*Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf.