

Xerox® VersaLink® C405 Color Multifunction Printer

VersaLink® C405 Color Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK® C405
One-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 36 ppm color and black-and-white Up to 35 ppm color and black-and-white Up to 30 ppm color and black-and-white
Two-sided Speed 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 24 ppm color and black-and-white Up to 23 ppm color and black-and-white Up to 21 ppm color and black-and-white
Monthly Duty Cycle²	Up to 85,000 pages/month
Recommended Average Monthly Print Volume³	Up to 8,500 pages
Processor	1.05 GHz ARM Dual-Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 VAC+/- 10% Frequency: 50/60 Hz+/- 3Hz, 10 A			
Europe and Other Geographies	Voltage: 220-240 VAC+/- 10% Frequency: 50/60 Hz+/- 3Hz, 6 A			
POWER CONSUMPTION				
Continuous Printing ⁴	750 watts or less			
Ready/Standby Mode ⁴	82 watts or less			
Energy Saver/Sleep Mode ⁴	4 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° F to 95° F/0° C to 35° C			
Required Temperature Range (Operating)	50° F to 90° F/10° C to 32° C			
Required Relative Humidity	10% to 85%			
Sound Power Levels Operating Standby	6.88 B(A) or less 5.0 B(A) or less			
Sound Pressure Levels Operating Standby	52.3 dB(A) or less 28.7 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 60 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 6 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C405	17 in./432 mm	21.3 in./540 mm	23.6 in./599 mm	72 lb./33 kg
550-sheet Paper Tray	16.8 in./427 mm	19.1 in./485 mm	5.4 in./138 mm	8.6 lb./3.9 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C405	23.7 in./602 mm	26.3 in./669 mm	30.0 in./761 mm	86 lb./39 kg
550-sheet Paper Tray	23.2 in./590 mm	21.4 in./544 mm	9.5 in./241 mm	11.7 lb./5.3 kg
SYSTEM CERTIFICATION/REGULATORY COMPLIANCE				
Certifications	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .			
PRINT				
First-Print-Out Time	As fast as 9.8 seconds color/8.7 seconds black-and-white			
Print Resolution	Up to 600 x 600 x 8 dpi (enhanced)			
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
Maximum Print Area	4 mm from edge of paper			

Xerox® VersaLink® C405 Color Multifunction Printer

<p>Print Features</p>	<p>Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) LAN Fax (requires Fax Kit) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Earth Smart Driver Settings</p>
<p>Print from USB</p>	<p>Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</p>
<p>Operating Systems</p>	<p>Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-LUX® Oracle® Solaris SUSE® SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.</p>
<p>Fonts</p>	<p>PostScript fonts: 136 PCL fonts: 83</p>
<p>Xerox® Global Print Driver®</p>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<p>Xerox® Pull Print Driver</p>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>

Xerox® VersaLink® C405 Color Multifunction Printer

COPY	
Document Scanner	50-sheet Single-Pass Duplex Automatic Document Feeder (DADF)
Document Scanner Size	Platen: Up to 8.5 x 11.7 in./A4 DADF: Up to 8.5 x 14 in./216 x 356 mm
Simplex Copy Speed	Up to 36 cpm (copies per minute) 8.5 x 11 in. Up to 35 cpm A4/210 x 297 mm
Duplex Copy Speed	Up to 24 cpm (copies per minute) 8.5 x 11 in. Up to 23 cpm A4/210 x 297 mm
First-Copy-Out Time	As fast as 10.6 seconds color/8.8 seconds black-and-white
Sides (input: output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution (max.)	Up to 600 x 600 dpi
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Concurrent scanning and printing
Copy Features	<p>Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping) including font format, color and style options*</p> <p>Auto-color Sensing</p> <p>Automatic Background Suppression</p> <p>Book Copying with Center Erase</p> <p>Booklet Copying*</p> <p>Collation</p> <p>Color Balance</p> <p>Color Effects</p> <p>Darkness Control</p> <p>Edge Erase</p> <p>Front Cover</p> <p>ID Card Copy</p> <p>Image Enhancement</p> <p>Image Shift</p> <p>Lighten/Darken</p> <p>N-up</p> <p>Original Orientation</p> <p>Original Size</p> <p>Original Type</p> <p>Page Layout</p> <p>Sample Copy</p> <p>Saturation</p> <p>Sharpness</p> <p>Reduce/Enlarge 25% to 400%</p> <p>*Requires HDD/Productivity Kit</p>

Xerox® VersaLink® C405 Color Multifunction Printer

SCAN	
Capability	Black-and-white and color scanning
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
Simplex Input Speed	Black-and-white: Scan up to 40 ipm – 8.5 x 11 in./38 ipm A4/210 x 297 mm Color: Scan up to 21 ipm – 8.5 x 11 in./20 ipm A4/210 x 297 mm
Duplex Input Speed	Black-and-white: Scan up to 52 ipm – 8.5 x 11 in./50 ipm A4/210 x 297 mm Color: Scan up to 27 ipm – 8.5 x 11 in./26 ipm A4/210 x 297 mm
Resolution	Optical – 600 x 600 dpi
Bit Depth	24-bit color/8-bit grayscale
Maximum Scan Area	Platen: Up to 8.5 x 11.7 in./A4/210 x 297 mm Document Feeder: Up to 8.5 x 14 in./216 x 356 mm
Network Filing Protocols	FTP SMTP SMB sFTP
File Formats	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A
Scan Driver Compatibility	WIA TWAIN
Supported Scan Destinations	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)
NETWORK SCANNING – SOFTWARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.
FAX	
FAX⁵	
Fax Speed	33.6 Kbps
Memory	4 MB
Resolution	Standard 200x100 dpi, Fine 200x200 dpi, Super Fine 300x300, 400x400, 600x600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, LAN Fax, Direct Fax, Server Fax Enablement, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)
MOBILE SOLUTIONS AND MOBILE DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.

Xerox® VersaLink® C405 Color Multifunction Printer

Xerox® @printbyXerox App	<p>@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.</p>
Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)	<p>The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.</p>
Xerox® Mobile Link App (Free at Google Play™ Store and Apple® App Store)	<p>The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® Multifunction Printer.</p>
Xerox® Workplace Suite and Xerox® Workplace Cloud	<p>Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.</p>

SECURITY

Security Features	<ul style="list-style-type: none"> Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Secure Scanning via SFTP Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM) <p>*Requires HDD/Productivity Kit</p>
--------------------------	---

Xerox® VersaLink® C405 Color Multifunction Printer

ACCOUNTING	
XEROX® STANDARD ACCOUNTING TOOL/NETWORK ACCOUNTING (STANDARD)	
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	<p>Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts</p> <p>Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)</p>
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account
PAPER HANDLING	
DOCUMENT FEEDER	
Capacity⁶	Single-Pass Duplex Automatic Document Feeder (DADF): 50 sheets
Sizes	Custom Sizes: 5.5 x 5.5 in. to 8.5 x 14 in./139.7 x 139.7 mm to 216 x 356 mm
Weights One-sided: Two-sided:	13 lb. bond to 45 lb. cover/50 to 125 gsm 16 lb. bond to 45 lb. cover/60 to 125 gsm
BYPASS TRAY	
Capacity⁶	150 sheets
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in./76.2 x 127 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 60 lb. cover/60 to 163 gsm
Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Labels Envelopes Custom

Xerox® VersaLink® C405 Color Multifunction Printer

TRAY 1	
Capacity⁶	550 sheets
Sizes	Custom sizes: 5.8 x 8.3 in. to 8.5 x 14 in./148 x 210 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220gsm 16 lb. bond to 60 lb. cover/60 to 163gsm
Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Custom
OPTIONAL TRAY 2	
Capacity⁶	550 sheets
Sizes	Custom sizes: 5.8 x 8.3 in. to 8.5 x 14 in./148 x 210 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220gsm 16 lb. bond to 60 lb. cover/60 to 163gsm
Types	Plain Lightweight Cardstock Cardstock Hole Punched Recycled Pre-Printed Letterhead Bond Lightweight Glossy Cardstock Glossy Cardstock Custom
TOTAL CAPACITY	
Standard Device Capacity⁶	700 sheets
Total Device Capacity⁶	1,250 sheets
PAPER OUTPUT	
Output Capacity⁶	250 sheets
Automatic Two-sided Printing	Standard
DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS

Xerox® VersaLink® C405 Color Multifunction Printer

REMOTE CONTROL PANEL	
	<ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorized users can control the device remotely from a web page on any device • Remote user experience is identical to performing tasks directly at the device
XEROX® CENTREWARE® WEB SOFTWARE	
	<ul style="list-style-type: none"> • A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul style="list-style-type: none"> • Tray Status/Contents • Consumables Status • Billing/Usage • Quick Links • Online Support
Print Queue Viewing	Job print queue management — view and delete
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
WHAT'S IN THE BOX	
	VersaLink® C405 Color Multifunction Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 2,000 print capacity ⁷ , Black: 3,000 print capacity ⁷ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord Fax Cord

Xerox® VersaLink® C405 Color Multifunction Printer

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Toner Cartridges	Cyan: 2,500 standard pages ⁷	106R03510
	Magenta: 2,500 standard pages ⁷	106R03511
	Yellow: 2,500 standard pages ⁷	106R03509
	Black: 2,500 standard pages ⁷	106R03508
High Capacity Toner Cartridges	Cyan: 4,800 standard pages ⁷	106R03522
	Magenta: 4,800 standard pages ⁷	106R03523
	Yellow: 4,800 standard pages ⁷	106R03521
	Black: 5,000 standard pages ⁷	106R03520
Extra-High Capacity Toner Cartridges	Cyan: 8,000 standard pages ⁷	106R03534
	Magenta: 8,000 standard pages ⁷	106R03535
	Yellow: 8,000 standard pages ⁷	106R03533
	Black: 10,500 standard pages ⁷	106R03532
ROUTINE MAINTENANCE ITEMS		
Imaging Unit (includes 4 imaging units)	Cyan: 60,000 standard pages ⁸	108R01121
	Magenta: 60,000 standard pages ⁸	
	Yellow: 60,000 standard pages ⁸	
	Black: 60,000 standard pages ⁸	
Waste Cartridge	30,000 standard pages ⁸	108R01124
ACCESSORIES		
550-sheet Paper Tray		097S04400
Productivity Kit with 320 GB HDD		097S04914
Stand		497K13660
Wireless Network Adapter		497K16750

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Requires analog phone line.

⁶ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁷ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁸ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.