

Xerox[®] VersaLink[®] C600 Colour Printer

VersaLink C600 Colour Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.

System Specifications	VersaLink 600/N	VersaLink 600/DN
One-sided Speed A4 / 210 x 297 mm	Up to 53 ppm colour and black and white	
Two-sided Speed A4 / 210 x 297 mm	NA	Up to 50 ppm colour and black and white
Monthly Duty Cycle ¹	Up to 120,000 pages / month ¹	
Recommended Average Monthly Print Volume ²	Up to 15,000 pages	
Hard Drive	Optional 320 GB HDD	
Processor	1.05 GHz	
Memory	2 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support (accessed from the user interface and print driver)	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian	
Device Specifications		
Electrical Requirements		
Europe and Other Geographies	Voltage: 220-240V +/- 10 % Frequency: 50/60 Hz +/-3 % , 8A	
Power Consumption		
Continuous Printing ⁴	800 watts or less	
Ready / Standby Mode ⁴	85 watts or less	
Energy Saver / Sleep Mode ⁴	0.7 watts or less	
Operating Environment		
Required Temperature Range (Storage)	0° to 35° C	
Required Temperature Range (Operating)	10° to 32° C	
Required Relative Humidity	15% to 85%	
Sound Power Levels Operating Standby	7.27 B(A) or less 4.84 B(A) or less	
Sound Pressure Levels Operating Standby	57.4 dB(A) or less, 33.5 dB(A) or less	
Boot Time (from Off to UI Ready)	As fast as 52 seconds	

Warm-up Time (from Sleep to UI Ready)	As fast as 11 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
VersaLink C600/N	427.4 mm	465.5 mm	443.4 mm	29.4 kg
VersaLink C600/DN	427.4 mm	465.5 mm	443.4 mm	29.4 kg
550-sheet Paper Tray	420 mm	464.5 mm	123 mm	6.6 kg
High Capacity Feeder	724.2 mm	772.1 mm	459 mm	19.7 kg
Stand (includes Caster Base)	724.2 mm	772.1 mm	336 mm	16.6 kg
Caster Base	724.2 mm	772.1 mm	90 mm	8.5 kg
Mailbox	450.8 mm	477.6 mm	248.0 mm	5.3 kg
Finisher	450.8 mm	411.0 mm	248.0 mm	6.8 kg
Dimensions and Weight (Packaged)	Width	Depth	Height	Weight
VersaLink C600/N	580 mm	634 mm	607 mm	35 kg
VersaLink C600/DN	580 mm	634 mm	607 mm	35 kg
550-sheet Paper Tray	535 mm	584 mm	248 mm	8.5 kg
High Capacity Feeder	568 mm	663 mm	711 mm	38 kg
Stand (includes Caster Base)	584 mm	629 mm	597 mm	28 kg
Caster Base	585 mm	619 mm	330 mm	18 kg
Mailbox	573 mm	518 mm	386 mm	7.8 kg
Finisher	573 mm	398 mm	386 mm	8.8 kg
Certifications				
	To view the latest list of	certifications, go to www.	xerox.com/OfficeCertific	ations.
Print	rint			
First-print-out Time	As fast as 8 seconds colour and black and white			
Print Resolution	Up to 1200 x 2400 dpi			
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
Maximum Print Area	4 mm from edge of paper			

Print Features	Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status	
	Booklet Layout Colour Adjustments (lightness, contrast, saturation, colour balance) Colour Correction	
	Draft Mode	
	Fit to new paper size	
	Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface)	
	N-up Page Layout (up to 16 pages per sheet)	
	Paper Selection by Attribute Personal Print	
	Print Around Enable / Disable	
	Print from USB Run Black	
	Sample Set	
	Saved Job	
	Scaling Secure Print	
	Skip Blank Pages	
	Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings	
	Stored Jobs Deletion	
	Two-sided Printing (as default – DN configuration)	
	Watermark (predefined and custom) Xerox® Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port	
	Supports direct printing from computer via Type B USB port	
	Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A	
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix®	
	Redhαt® Enterprise Linux® Fedora Core IBM® AIX®	
	HP-UX®	
	Oracle® Solaris SUSE®	
	SAP®	
	Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com .	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	

Mobile Solutions and Mobile Dev	vice Apps
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other webconnected device.
@PrintByXerox	@PrintByXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.
Software Solutions	
Xerox [®] ConnectKey [®] Apps (Found at the Xerox [®] App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled device.
Security	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external programme falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL *Requires HDD/Productivity Kit

Accounting		
Xerox® Standard Accounting / Network Accounting (Standard)		
Tracking	Print usage	
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)	
Features	• Administrator can manage the feature via the Embedded Web Server.	
Accounting Options – N	etwork Accounting (Allows central server to manage all accounting)	
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account 	
Paper Handling		
Bypass Tray		
Capacity ³	150 sheets	
Sizes	Custom sizes: 76 x 127 mm to 216 x 356 mm	
Weights	60 to 220 gsm	
Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Cardstock Pre-Printed Recycled	
Tray 1		
Capacity ³	550 sheets	
Sizes	Custom sizes: 76 x 190 mm to 216 x 356 mm	
Weights	60 to 220 gsm	
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled	

Up to Four Additional Trays			
Capacity ³	550 sheets		
Sizes	Custom sizes: 76 x 190 mm to 216 x 356 mm		
Weights	60 to 220 gsm		
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled		
High Capacity Feeder (Optional – only one additional 550-sheet Tray can be added to High Capacity Feeder)			
Capacity ³	2,000 sheets		
Sizes	A4		
Weights	60 to 176 gsm		
Types	Bond Plain Paper Hole Punched Letterhead Lightweight Cardstock Pre-Printed Recycled		
Total Capacity			
Standard Device Capacity ³	700 sheets		
Total Device Capacity ³	3,250 sheets		
Paper Output / Finishing	VersaLink 600/N	VersaLink 600/DN	
Capacity ³	Up to 500 sheets		
Automatic Two-sided Printing	NA	Standard	
Finisher (Optional)	Finisher (Optional)		
Capacity ³	500-sheet tray, 50-sheet stapling		
Mailbox (Optional)			
Capacity ³	Four 100-sheet bins		

Device Management	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™ Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
Xerox® CentreWare® Web Softw	vare
	 A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
Xerox [®] Embedded Web Server -	· Integrated Device Web Page
Device Status	 Tray status/contents Consumables status Billing/Usage Quick Links Online Support
Print Queue Viewing	Job print queue management—view and delete
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
Remote Services	
Automated Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automated Supplies Replenishment (ASR)	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster with increased uptime.
What's In The Box	
	VersaLink C600 Colour Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 6,000 print capacity ⁵ , Black: 10,000 print capacity ⁵ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord

Supplies and Accessories	Quantity	Part Number	
Supplies			
Standard Capacity Print Cartridges	Black: 6,000 standard pages ⁵ Cyan: 6,000 standard pages ⁵ Magenta: 6,000 standard pages ⁵ Yellow: 6,000 standard pages ⁵	106R03899 106R03896 106R03897 106R03898	
High Capacity Print Cartridges	Black: 12,200 standard pages ⁵ Cyan: 10,100 standard pages ⁵ Magenta: 10,100 standard pages ⁵ Yellow: 10,100 standard pages ⁵	106R03907 106R03904 106R03905 106R03906	
Extra High Capacity Print Cartridges	Black: 16,900 standard pages ⁶ Cyan: 16,800 standard pages ⁶ Magenta: 16,800 standard pages ⁶ Yellow: 16,800 standard pages ⁶	106R03923 106R03920 106R03921 106R03922	
Routine Maintenance Items			
Drum Cartridges	Cyan: 40,000 pages ⁶ Magenta: 40,000 pages ⁶ Yellow: 40,000 pages ⁶ Black: 40,000 pages ⁶	108R01485 108R01486 108R01487 108R01488	
Waste Cartridge	30,000 pages ⁶	108R01416	
Accessories			
550-sheet Feeder		097S04949	
2,000-sheet High Capacity Feede	er (includes Stand/Caster Base)	097S04948	
Stand (includes Caster Base)		097S04994	
Caster Base		097S04954	
Finisher (500 sheets, 50-sheet stapler)		097S04952	
4-Bin Mailbox (100 sheets per bin)		097S04953	
Productivity Kit with 320 GB HDD		497K18360	
Wireless Network Adapter (Wi-Fi Kit)		497K16750	
External Card Reader		497K18380	

www.xerox.com

Configurations vary by geography.



¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
2 Expected regular monthly throughput.
3 Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.
4 Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.
5 Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.
6 Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.