



# Xerox<sup>®</sup> VersaLink<sup>®</sup> C605 Colour Multifunction Printer

VersaLink C605 Colour Multifunction Printers are built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to [www.connectkey.com](http://www.connectkey.com).

System Specifications		VersaLink 605/X
<b>One-sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 55 ppm colour and black and white Up to 53 ppm colour and black and white Up to 45 ppm colour and black and white	
<b>Two-sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 52 ppm colour and black and white Up to 50 ppm colour and black and white Up to 26 ppm colour and black and white	
<b>Monthly Duty Cycle<sup>1</sup></b>	Up to 120,000 pages / month <sup>1</sup>	
<b>Recommended Average Monthly Print Volume<sup>2</sup></b>	Up to 15,000 pages	
<b>Hard Drive</b>	320 GB HDD	
<b>Processor</b>	1.05 GHz	
<b>Memory</b>	4 GB	
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
<b>Controller Features</b>	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform <sup>®</sup> , Xerox App Gallery, Xerox <sup>®</sup> Standard Accounting, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support (accessed from the user interface and print driver)	
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian	
Device Specifications		
Electrical Requirements		
<b>North America</b>	Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A	
<b>Europe and Other Geographies</b>	Voltage: 220-240V +/- 10% Frequency: 50/60 Hz +/-3%, 8A	
Power Consumption		
<b>Continuous Printing<sup>4</sup></b>	820 watts or less	
<b>Ready (Standby) Mode<sup>4</sup></b>	90 watts or less	
<b>Energy Saver (Sleep) Mode<sup>4</sup></b>	0.9 watts or less	
Operating Environment		
<b>Required Temperature Range (Storage)</b>	32° to 95° F (0° to 35° C)	
<b>Required Temperature Range (Operating)</b>	50° to 90° F (10° to 32° C)	
<b>Required Relative Humidity</b>	15% to 85%	
<b>Sound Power Levels</b> Operating Standby	7.27 B(A) or less 4.84 B(A) or less	

## Xerox® VersaLink® C605 Colour Multifunction Printer

<b>Sound Pressure Levels</b> Operating Standby	57.4 dB(A) or less 33.5 dB(A) or less			
<b>Boot Time (from Off to UI Ready)</b>	As fast as 65 seconds			
<b>Warm-up Time (from Sleep to UI Ready)</b>	As fast as 11 seconds			
<b>Dimensions and Weight (Unpackaged)</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
VersaLink C605/X	18.5 in. / 470 mm	19.8 in. / 503 mm	25.4 in. / 643.7 mm	79.6 lb. / 36.1 kg
VersaLink C605/XL	19.2 in. / 487.5 mm	19.8 in. / 503 mm	33.2 in. / 843.7 mm	79.6 lb. / 36.1 kg
550-sheet Paper Tray	16.5 in. / 420 mm	18.3 in. / 464.5 mm	4.8 in. / 123 mm	4.1 lb. / 6.6 kg
High Capacity Feeder	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	18.1 in. / 459 mm	43.4 lb. / 19.7 kg
Cabinet	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	13.2 in. / 336 mm	37 lb. / 16.6 kg
Stand / Caster Base	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	3.5 in. / 90 mm	18.7 lb. / 8.5 kg
Mailbox	17.7 in. / 450.8 mm	18.8 in. / 477.6 mm	9.8 in. / 248 mm	11.7 lb. / 5.3 kg
Finisher	17.7 in. / 450.8 mm	16.2 in. / 411.0 mm	9.8 in. / 248 mm	15 lb. / 6.8 kg
<b>Dimensions and Weight (Packaged)</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
VersaLink C605/X	23.4 in. / 594 mm	25.8 in. / 655 mm	31.1 in. / 789 mm	97 lb. / 44 kg
VersaLink C605/XL	24 in. / 610 mm	26.4 in. / 670 mm	43.7 in. / 1110 mm	97 lb. / 44 kg
550-sheet Paper Tray	21.1 in. / 535 mm	23 in. / 584 mm	9.8 in. / 248 mm	18.7 lb. / 8.5 kg
High Capacity Feeder	22.4 in. / 568 mm	26.1 in. / 663 mm	28 in. / 711 mm	83.8 lb. / 38 kg
Cabinet	23 in. / 584 mm	24.8 in. / 629 mm	23.5 in. / 597 mm	57.3 lb. / 28 kg
Stand / Caster Base	23 in. / 585 mm	24.4 in. / 619 mm	13 in. / 330 mm	39.7 lb. / 18 kg
Mailbox	22.6 in. / 573 mm	20.4 in. / 518 mm	15.2 in. / 386 mm	16.3 lb. / 7.8 kg
Finisher	22.6 in. / 573 mm	15.7 in. / 398 mm	15.2 in. / 386 mm	18.6 lb. / 8.8 kg
<b>Certifications</b>				
	To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .			
<b>Print</b>				
<b>First-print-out Time</b>	As fast as 10 seconds colour and black and white			
<b>Print Resolution</b>	Up to 1200 x 2400 dpi			
<b>Page Description Languages</b>	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
<b>Maximum Print Area</b>	4 mm from edge of paper			

## Xerox® VersaLink® C605 Colour Multifunction Printer

<b>Print Features</b>	<ul style="list-style-type: none"> <li>Application Defaults</li> <li>Banner Pages Enable / Disable</li> <li>Bi-directional Real-time Status</li> <li>Booklet Layout</li> <li>Draft Mode</li> <li>Fit to new paper size</li> <li>Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)</li> <li>Job Monitoring (Client or Local User Interface)</li> <li>LAN Fax (requires Fax Kit)</li> <li>N-up Page Layout (up to 16 pages per sheet)</li> <li>Paper Selection by Attribute</li> <li>Personal Print</li> <li>Print Around Enable / Disable</li> <li>Print from USB</li> <li>Sample Set</li> <li>Saved Job</li> <li>Scaling</li> <li>Secure Print</li> <li>Skip Blank Pages</li> <li>Special Pages (exception page programming: covers, inserts, exceptions pages)</li> <li>Store and Recall Driver Settings</li> <li>Stored Jobs Deletion</li> <li>Two-sided Printing (as default)</li> <li>Watermark (predefined and custom)</li> <li>Xerox® Earth Smart Driver Settings</li> </ul>
<b>Print from USB</b>	<ul style="list-style-type: none"> <li>Allows walk-up printing from Type A USB port</li> <li>Supports direct printing from computer via Type B USB port</li> <li>Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</li> </ul>
<b>Operating Systems</b>	<ul style="list-style-type: none"> <li>Windows® 7, 8, 8.1, 10</li> <li>Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016</li> <li>macOS® 10.11, 10.12, 10.13</li> <li>Citrix®</li> <li>Redhat® Enterprise Linux®</li> <li>Fedora Core</li> <li>IBM® AIX®</li> <li>HP-UX®</li> <li>Oracle® Solaris</li> <li>SUSE®</li> <li>SAP®</li> </ul> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers &amp; Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a>.</p>
<b>Fonts</b>	<ul style="list-style-type: none"> <li>PostScript fonts: 136</li> <li>PCL fonts: 83</li> </ul>
<b>Xerox® Mobile Express Driver®</b>	<p>Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p>
<b>Xerox® Global Print Driver®</b>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<b>Xerox® Pull Print Driver</b>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>

# Xerox® VersaLink® C605 Colour Multifunction Printer

Copy	
<b>Document Scanner</b>	100-sheet Single-Pass Duplex Automatic Document Feeder (DADF)
<b>Maximum Scan Area</b>	Platen: Up to 8.5 x 14 in. / 216 x 356 mm DADF: Up to 8.5 x 14 in. / 216 x 356 mm
<b>Simplex Copy Speed</b>	Up to 55 cpm (copies per minute) 8.5 x 11 in. Up to 53 cpm A4 / 210 x 297 mm
<b>Duplex Copy Speed</b>	Up to 50 cpm (copies per minute) 8.5 x 11 in. Up to 47 cpm A4 (210 x 297 mm)
<b>First-copy-out Time</b>	As fast as 7 seconds colour / 5 seconds black and white
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 999
<b>Resolution (max.)</b>	Up to 600 x 400 dpi
<b>Reduction / Enlargement</b>	Variable zoom from 25 % to 400 % in 1 % increments
<b>Concurrency</b>	Concurrent scanning and printing
<b>Copy Features</b>	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)* Auto-color Sensing Automatic Background Suppression Book Copying with Centre Erase Booklet Copying* Collation Color Balance Color Effects Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Lighten/Darken N-up Reduce / Enlarge 25 % to 400 % Image Shift Original Orientation Original Size Original Type Page Layout Sample Copy Saturation Sharpness  *Requires HDD/Productivity Kit
Scan	
<b>Capability</b>	Black and white and colour scanning
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Simplex Input Speed</b>	Black-and-white: Scan up to 49 ipm 8.5 x 11 in. / 46 ipm A4 Color: Scan up to 47 ipm 8.5 x 11 in. / 46 ipm A4
<b>Duplex Input Speed</b>	Black-and-white: Scan up to 75 ipm 8.5 x 11 in. / 71 ipm A4 Color: Scan up to 55 ipm 8.5 x 11 in. / 52 ipm A4
<b>Resolution</b>	Optical – 600 x 600 dpi
<b>Bit Depth</b>	24-bit colour / 8-bit grayscale
<b>Maximum Scan Area</b>	Platen: Up to 8.5 x 14 in. / 216 x 356 mm Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm
<b>Network Filing Protocols</b>	FTP SMTP SMB

## Xerox® VersaLink® C605 Colour Multifunction Printer

<b>File Formats</b>	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearised PDF (set via embedded web server) and PDF/A
<b>Scan Driver Compatibility (Network Only)</b>	WIA TWAIN
<b>Supported Scan Destinations</b>	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)
<b>Network Scanning – Software Solutions</b>	
<b>Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled device.
<b>Fax</b>	
<b>Fax<sup>5</sup></b>	
<b>Fax Speed</b>	33.6 Kbps
<b>Memory</b>	4 MB
<b>Resolution</b>	Standard 200x100 dpi, Fine 200x200 dpi, Super Fine 300x300, 400x400, 600x600 dpi
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Fax Features</b>	Walk-up Fax, LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)
<b>Mobile Solutions and Mobile Device Apps</b>	
<b>Apple® AirPrint®</b>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
<b>Google Cloud Print™</b>	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.
<b>@PrintByXerox</b>	@PrintByXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
<b>Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)</b>	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
<b>Xerox® Mobile Link App (Free at Google Play™ Store and Apple® App Store)</b>	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.
<b>Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service</b>	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.

Security	
<b>Security Features</b>	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 TLS/SSL  *Requires HDD/Productivity Kit
Accounting	
Xerox® Standard Accounting / Network Accounting (Standard)	
<b>Tracking</b>	Copy, Print, Fax, Scan and Email usage
<b>Accounting</b>	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General accounts  Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)
<b>Features</b>	<ul style="list-style-type: none"> <li>Administrator can manage the feature via the Embedded Web Server.</li> </ul>
Accounting Options – Network Accounting (Allows central server to manage all accounting)	
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>
Paper Handling	
Document Feeder	
<b>Capacity<sup>3</sup></b>	Single-Pass Duplex Automatic Document Feeder (DADF): 100 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 140 x 140 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 32 lb. bond / 60 to 128 gsm 16 lb. bond to 32 lb. bond / 60 to 128 gsm

# Xerox® VersaLink® C605 Colour Multifunction Printer

Bypass Tray	
<b>Capacity<sup>3</sup></b>	150 sheets
<b>Sizes</b>	Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm
<b>Media Types</b>	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Cardstock Pre-Printed Recycled
Tray 1	
<b>Capacity<sup>3</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm
<b>Media Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled Envelope
Up to Four Additional Trays (Optional)	
<b>Capacity<sup>3</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm
<b>Media Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled
High Capacity Feeder (Optional – only one additional 550-sheet Tray can be added to High Capacity Feeder)	
<b>Capacity<sup>3</sup></b>	2,000 sheets
<b>Sizes</b>	Letter/A4
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 65 lb. cover / 60 to 176 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm

## Xerox® VersaLink® C605 Colour Multifunction Printer

<b>Media Types</b>	Bond Plain Paper Hole Punched Letterhead Lightweight Cardstock Pre-Printed Recycled
<b>Total Capacity</b>	
<b>Standard Device Capacity<sup>3</sup></b>	700 sheets
<b>Maximum Device Capacity<sup>3</sup></b>	3,250 sheets
<b>Paper Output / Finishing</b>	
<b>Capacity<sup>3</sup></b>	Up to 400 sheets
<b>Automatic Two-sided Printing</b>	Standard
<b>Finisher (Optional)</b>	
<b>Capacity<sup>3</sup></b>	500-sheet tray, 50-sheet stapling
<b>Mailbox (Optional)</b>	
<b>Capacity<sup>3</sup></b>	Four 100-sheet bins
<b>Device Management</b>	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™ FTP Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
<b>Xerox® CentreWare® Web Software</b>	
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
<b>Xerox® Embedded Web Server – Integrated Device Web Page</b>	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management—view and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, PDF, XPS, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
<b>Remote Services</b>	
<b>Xerox® Meter Assistant® Service</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Xerox® Supplies Assistant® Service</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.



# Xerox® VersaLink® C605 Colour Multifunction Printer

<b>MaintenanceAssistant</b>	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	
<b>What's In The Box</b>		
	VersaLink C605 Colour Multifunction Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 6,000 print capacity <sup>6</sup> , Black: 10,000 print capacity <sup>6</sup> Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord Fax cord	
<b>Supplies and Accessories</b>	<b>Quantity</b>	<b>Part Number</b>
<b>Supplies</b>		
<b>Standard Capacity Print Cartridges</b>	Black: 6,000 standard pages <sup>6</sup> Cyan: 6,000 standard pages <sup>6</sup> Magenta: 6,000 standard pages <sup>6</sup> Yellow: 6,000 standard pages <sup>6</sup>	106R03911 106R03908 106R03909 106R03910
<b>High Capacity Print Cartridges</b>	Black: 12,200 standard pages <sup>6</sup> Cyan: 10,100 standard pages <sup>6</sup> Magenta: 10,100 standard pages <sup>6</sup> Yellow: 10,100 standard pages <sup>6</sup>	106R03915 106R03912 106R03913 106R03914
<b>Extra High Capacity Print Cartridges</b>	Black: 16,900 standard pages <sup>6</sup> Cyan: 16,800 standard pages <sup>6</sup> Magenta: 16,800 standard pages <sup>6</sup> Yellow: 16,800 standard pages <sup>6</sup>	106R03939 106R03936 106R03937 106R03938
<b>Routine Maintenance Items</b>		
<b>Drum Cartridges</b>	Cyan: 40,000 pages <sup>7</sup> Magenta: 40,000 pages <sup>7</sup> Yellow: 40,000 pages <sup>7</sup> Black: 40,000 pages <sup>7</sup>	108R01485 108R01486 108R01487 108R01488
<b>Waste Cartridge</b>	30,000 pages <sup>7</sup>	108R01416
<b>Accessories</b>		
<b>550-sheet Feeder</b>		097S04949
<b>2,000-sheet High Capacity Feeder (includes Stand/Caster Base)</b>		097S04948
<b>Cabinet (includes Stand/Caster Base)</b>		097S04955
<b>Stand/Caster Base</b>		097S04954
<b>Finisher (500 sheets, 50-sheet stapler)</b>		097S04952
<b>4-Bin Mailbox (100 sheets per bin)</b>		097S04953
<b>Wireless Network Adapter (Wi-Fi Kit)</b>		497K16750

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

<sup>5</sup> Requires analog phone line.

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <http://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme.

For more information, visit [www.xerox.com/about-xerox/recycling](http://www.xerox.com/about-xerox/recycling).

For more information, visit us at [www.xerox.com/office](http://www.xerox.com/office)

Configurations vary by geography.

