

Xerox® VersaLink® C8000W Colour Printer



The VersaLink® C8000W Colour Printer is built on Xerox® ConnectKey® Technology. For more information, go to <https://www.xerox.co.uk/en-gb/office/printers/versalink-c8000w>

SYSTEM SPECIFICATIONS	VERSALINK® C8000W/DT
One-Sided Speed ¹ 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in./SRA3/320 x 450 mm	Up to 45 ppm (pages per minute) long edge feed (LEF) Up to 32 ppm Up to 26 ppm Up to 22 ppm
Two-Sided Speed ¹ 8.5 x 11 in./A4 8.5 x 11 in./A4 SEF 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm/ 12 x 18 in./SRA3/320 x 450 mm	Up to 45 ppm LEF Up to 32 ppm Up to 17 ppm Up to 15 ppm
Monthly Duty Cycle ²	Up to 205,000 pages per month
Recommended Average Monthly Print Volume ³	Up to 20,000 pages per month
Hard Drive	320 GB HDD (Optional)
Processor	1.6 GHz Dual-Core
Memory	4 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role-Based Permissions, Convenience Authentication Enabled
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan

Xerox® VersaLink® C8000W Colour Printer

DEVICE SPECIFICATIONS

ELECTRICAL REQUIREMENTS

North America	Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A
Europe and Other Geographies	Voltage: 220-240V +/- 10% Frequency: 50/60 Hz +/-3%, 10A

POWER CONSUMPTION

Printing ⁴	For 110V: 2.30 kWh for 220V: 2.32 kWh
Standby Mode ⁴	110V: 75.3 Watts or less 220V: 73.8 Watts or less
Sleep Mode ⁴	110V: 0.48 watts or less 220V: 0.53 watts or less

OPERATING ENVIRONMENT

Required Temperature Range (Storage)	Below 48° C, and in compliance with MN2-810.13
Required Temperature Range (Operating)	10° to 28° C (50° to 83° F) Must be 28° C or below if humidity is at 85%
Required Relative Humidity	15% to 85% Must be 62.5% or below at 32° C
Sound Power Levels	Printing: 6.63 B(A) or less Standby: 3.24 B(A) or less Full System (including finisher) Printing: 7.56 B(A) Standby: 3.36 B(A)
Sound Pressure Levels	Printing: 56.8 dB or less Standby: 15.4 dB or less Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB
Boot Time (From Off to UI-Ready)	Less than 60 seconds
Warm-up Time (From Sleep to UI-Ready)	Less than 10 seconds (without HDD) Less than 16 seconds (with HDD)

DIMENSIONS AND WEIGHT (UNPACKAGED)

	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C8000W/DT	24.4 in./620 mm	28.5 in./723 mm	31.9 in./809.3 mm	178 lb/80.8 kg
Two-Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	60.0 lb/27.2 kg
Tandem Tray Module	26.3 in./668.5 mm	28.5 in./723 mm	10.3 in./261.2 mm	74.5 lb/33.8 kg
High-Capacity Feeder	15.3 in./389 mm	23.7 in./602.9 mm	15.0 in./380.01 mm	63.9 lb/29.0 kg
Office Finisher	19.7 in./501 mm	25.7 in./653 mm	38.7 in./983 mm	55.1 lb/25 kg
Booklet Maker Option for Office Finisher	11.75 in./298.5 mm	26.4 in./673 mm	42.5 in./1080 mm	22.0 lb/10 kg
BR Booklet Maker Finisher	30.28 in./769.2 mm	28.5 in./723 mm	41.5 in./1055.1 mm	134.3 lb/60.9 kg

Xerox® VersaLink® C8000W Colour Printer

DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C8000W/DT	32.8 in./833 mm	28.2 in./717 mm	33.4 in./852 mm	209.4 lb/95 kg
High-Capacity Feeder	20.7 in./526 mm	29.8 in./756 mm	19.3 in./491 mm	74.3 lb/33.7 kg
Two-Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	72.7 lb/33 kg
Tandem Tray Module	32.7 in./830 mm	33.5 in./850 mm	15.75 in./400 mm	86 lb/39 kg
Office Finisher	31.1 in./790 mm	38.9 in./990 mm	21.8 in./555 mm	77.1 lb/35 kg
Booklet Maker Option for Office Finisher	19.4 in./495 mm	30 in./761 mm	16.9 in./430 mm	31 lb/14 kg
BR Booklet Maker Finisher	30 in./764 mm	30.5 in./774 mm	47.4 in./1203 mm	169.7 lb/77 kg
Horizontal Transport for BR Booklet Maker Finisher	21 in./533 mm	23.1 in./589 mm	12.6 in./319 mm	14.3 lb/6.5 kg

CERTIFICATIONS

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.

PRINT

First-Print-Out Time	As fast as 15 seconds colour As fast as 14 seconds monochrome
Print Resolution	Up to 1200 x 2400 dpi
Page Description Languages	Adobe® PostScript® 3™
Colour Management	Xerox Colour Management for 12 different media colours
Maximum Print Area	4 mm from lead edge of the paper, 2 mm from side and trail edges of the paper
Print Features	<ul style="list-style-type: none"> Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on the first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings
Operating Systems	<ul style="list-style-type: none"> Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019 macOS® 10.14, 10.15, 11 <p>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.</p>

Xerox® VersaLink® C8000W Colour Printer

Fonts	PostScript fonts: 136
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox Devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management.
SECURITY	
Security Features	<p>Access Controls AES 256-bit Encryption Audit Log Certificate path validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure print Security Certificate Management SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)</p> <p>*Requires HDD/Productivity Kit</p>
ACCOUNTING	
XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)	
Tracking	Print usage
Accounting	<p>Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts</p> <p>Network Accounting (Job-Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)</p>
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device print usage Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.co.uk Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at the control panel and pass to third-party Networking Account

Xerox® VersaLink® C8000W Colour Printer

PAPER HANDLING			
BYPASS TRAY			
Capacity ⁵	100 sheets		
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 482.6 mm Banners: 3.5 x 3.9 in. to 12.6 x 52 in./88.9 x 98.4 mm to 320 x 1320.8 mm		
Weights	Simplex and Duplex: 18 lb bond to 110 lb cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Envelopes Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Pre-Printed Postcards Recycled
TRAY 1 AND 2			
Capacity ⁵	520 sheets each		
Sizes	Tray 1: 3.9 x 5.8 in. to 11.7 x 17 in./100 x 148 mm to 297 x 431.8 mm Tray 2: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
Weights	Simplex and Duplex: 18 lb bond to 110 lb cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-printed Recycled
TWO-TRAY MODULE			
Capacity ⁵	1,040 sheets		
Sizes	Custom sizes: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm		
Weights	Simplex and Duplex: 18 lb bond to 110 lb cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled

Xerox® VersaLink® C8000W Colour Printer

TANDEM TRAY MODULE																
Capacity ⁵	2,000 sheets															
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5															
Weights	Simplex and Duplex: 18 lb bond to 110 lb cover/64 to 300 gsm															
Types	<table border="0"> <tr> <td>Bond</td> <td>Hole Punched</td> <td>Lightweight Cardstock</td> </tr> <tr> <td>Plain Paper</td> <td>Labels</td> <td>Lightweight Glossy Cardstock</td> </tr> <tr> <td>Cardstock</td> <td>Heavyweight Cardstock</td> <td>Pre-Printed</td> </tr> <tr> <td>Custom</td> <td>Heavyweight Glossy Cardstock</td> <td>Recycled</td> </tr> <tr> <td>Glossy Cardstock</td> <td>Letterhead</td> <td></td> </tr> </table>	Bond	Hole Punched	Lightweight Cardstock	Plain Paper	Labels	Lightweight Glossy Cardstock	Cardstock	Heavyweight Cardstock	Pre-Printed	Custom	Heavyweight Glossy Cardstock	Recycled	Glossy Cardstock	Letterhead	
Bond	Hole Punched	Lightweight Cardstock														
Plain Paper	Labels	Lightweight Glossy Cardstock														
Cardstock	Heavyweight Cardstock	Pre-Printed														
Custom	Heavyweight Glossy Cardstock	Recycled														
Glossy Cardstock	Letterhead															
HIGH-CAPACITY FEEDER																
Capacity ⁵	2,000 sheets															
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5															
Weights	18 lb bond to 95 lb cover/64 to 216 gsm															
Types	<table border="0"> <tr> <td>Bond</td> <td>Glossy Cardstock</td> <td>Lightweight Glossy Cardstock</td> </tr> <tr> <td>Plain Paper</td> <td>Hole Punched</td> <td>Recycled</td> </tr> <tr> <td>Cardstock</td> <td>Letterhead</td> <td></td> </tr> <tr> <td>Custom</td> <td>Lightweight Cardstock</td> <td></td> </tr> </table>	Bond	Glossy Cardstock	Lightweight Glossy Cardstock	Plain Paper	Hole Punched	Recycled	Cardstock	Letterhead		Custom	Lightweight Cardstock				
Bond	Glossy Cardstock	Lightweight Glossy Cardstock														
Plain Paper	Hole Punched	Recycled														
Cardstock	Letterhead															
Custom	Lightweight Cardstock															
ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL)																
Capacity ⁵	Up to 50 envelopes															
Sizes	No. 10 commercial, Monarch, DL, C4, C5, C6 Custom sizes: 3.5 x 3.85 in. to 9.5 x 13.1 in./90 x 98 mm to 241 x 332 mm															
TOTAL CAPACITY																
VersaLink® C8000/DT/W	1,140 sheets															
Maximum Capacity ⁵	5,140 sheets															
FINISHING																
OUTPUT TRAYS																
Dual Offset Catch Tray (Standard when finishers are not attached)	500 sheets (without centre tray) 2 x 250 sheets (with centre tray when offset is off) 2 x 125 sheets (with centre tray when offset is on)															
OFFICE FINISHER (OPTIONAL)																
Capacity ⁵	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single-stapled or 750 sheets dual-stapled (8.5 x 11 in./A4) Offset available for collated sets of standard size paper (8.5 x 11 in./A4 to 11 x 17 in./A3)															
Sizes	11.7 x 17 in./297 x 432 mm minimum for stapling 210 x 148 mm															
Weights	18 lb bond/60 to 256 gsm															
Multi-position Stapling	50 sheets of 24 lb bond/90 gsm															
Hole Punch (Optional) North America: Europe and Other Geographies:	Up to 65 lb cover (220 gsm uncoated) 2/3-hole punch 2/4-hole punch															
BOOKLET MAKER FOR OFFICE FINISHER (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)																
Capacity ⁵	40 booklets (2 to 15 sheets per booklet – 20 lb/80 gsm or less)															
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF															

Xerox® VersaLink® C8000W Colour Printer

Saddle-stitch Stapling	2 to 15 sheets/8-60-page booklet 18 lb bond to 24 lb bond/60 to 90 gsm (up to 220 gsm can be used for cover only)
Score/Crease	1 to 15 sheets/unstapled/60 to 105 gsm only
OPTIONAL BR BOOKLET MAKER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)	
Capacity ⁵	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3
Sizes	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
Weights	16 lb bond to 110 lb cover/60 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America Europe	2/3-hole punch 2/4-hole punch 4 hole 'Swedish' punch (optional)
Booklet maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported
DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
REMOTE CONTROL PANEL	
	<ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorised users can control the device remotely from a web page on any device • Remote user experience is identical to performing tasks directly at the device
XEROX® CENTREWARE® WEB	
	<ul style="list-style-type: none"> • A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running on Windows or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul style="list-style-type: none"> • Tray status/Contents • Consumables Status • Billing/Usage • Quick Links • Online Support
Print Queue Viewing	Job print queue management, view and delete
Device Administration	Allows simple, remote installation setting of configuration options and management of the device

Xerox® VersaLink® C8000W Colour Printer

Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	
REMOTE SERVICES		
Xerox® Automated Meter Reads (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
WHAT'S IN THE BOX		
	<ul style="list-style-type: none"> • VersaLink® C8000W/DT Colour Printer • Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 8,000 print capacity⁶, White: 5,000 print capacity) • Drum Cartridge – One of each (Cyan, Magenta, Yellow and White: 240,000 print capacity)⁷ • Quick User Guide • Install Guide • VersaLink C8000W Starter and Sample Media Kit • Software and Documentation CD (with Drivers, Warranty Statement and Safety Regulatory Recycle Disposal Guide) • Power Cord 	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Toner Cartridges	Cyan: 7,600 standard pages ⁶ Magenta: 7,600 standard pages ⁶ Yellow: 7,600 standard pages ⁶ White: 5,000 standard pages ⁸	106R04034 106R04035 106R04036 106R04646
High-Capacity Toner Cartridges	Cyan: 16,500 standard pages ⁶ Magenta: 16,500 standard pages ⁶ Yellow: 16,500 standard pages ⁶	106R04046 106R04047 106R04048
Drum Cartridge	Cyan: 190,000 standard pages ⁷ Magenta: 190,000 standard pages ⁷ Yellow: 190,000 standard pages ⁷ White: 190,000 standard pages ⁹	101R00602
Waste Cartridge	Up to 47,000 standard pages ¹⁰	108R01504
IBT Cleaner	160,000 standard pages ⁷	104R00256
Transfer Roller	200,000 standard pages ⁷	116R00015
Office Finisher Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897
Staple Refills for Office Finisher (3 refills per container)	15,000 staples (5,000 each refill)	008R12941
Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R12964
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R13177

Xerox® VersaLink® C8000W Colour Printer

ACCESSORIES/OPTIONS	
Two-Tray Module	097S04969
Tandem Tray Module	097S04970
High-Capacity Feeder	097S04845
Envelope Tray (Replaces Tray 1)	497K17880
Office Finisher	097S05019
2/3 Hole Punch for Office Finisher (available in Eastern Hemisphere)	497K20600
2/4 Hole Punch for Office Finisher (available in Western Hemisphere)	497K20610
Booklet Maker for Office Finisher	497K20590
BR Booklet Maker Finisher with 2/3 Hole Punch (requires Horizontal Transport Kit)	097S04981
BR Booklet Maker Finisher with 2/4 Hole Punch (requires Horizontal Transport Kit)	097S04982
Horizontal Transport Kit for BR Finisher	497K17440
320 GB HDD	097S04971
Wireless Network Adapter Kit	497K16750
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)
Bianco Digitale SW Kit	497N07139

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information, visit: <http://www.office.xerox.com/latest/SUPGL-01.pdf>.

⁸ Using 5% coverage.

⁹ Up to 240,000 standard pages running white pages only.

¹⁰ Max yield running 100% white pages with 5% coverage. expected yield 30.4K running 50% WCMY, 40%W, 10%CMY pages.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.

Configurations vary by geography.