

# Xerox® VersaLink® C9000 Colour Printer



The VersaLink® C9000 Colour Printer is built on Xerox® ConnectKey® Technology. For more information, go to [www.ConnectKey.com](http://www.ConnectKey.com).

System Specifications	VersaLink® C9000DT
<b>One-Sided Speed</b> 8.5 x 11 in. / A4 8.5 x 11 in. / A4 SEF 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm / 12 x 18 in / SRA3 / 320 x 450 mm	Up to 55 ppm (pages per minute) long edge feed (LEF) Up to 40 ppm Up to 32 ppm Up to 27 ppm
<b>Two-Sided Speed</b> 8.5 x 11 in. / A4 8.5 x 11 in. / A4 SEF 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm / 12 x 18 in / SRA3 / 320 x 450 mm	Up to 55 ppm LEF Up to 40 ppm Up to 21 ppm Up to 19 ppm
<b>Monthly Duty Cycle<sup>1</sup></b>	Up to 270,000 pages / month
<b>Recommended Average Monthly Print Volume<sup>2</sup></b>	Up to 30,000 pages per month
<b>Hard Drive</b>	320 GB HDD
<b>Processor</b>	1.6 GHz Dual-Core
<b>Memory</b>	4 GB
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
<b>Controller Features</b>	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting Tool, Role Based Permissions, Convenience Authentication Enabled
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan

# Xerox® VersaLink® C9000 Colour Printer

Device Specifications				
<b>Electrical Requirements</b>				
<b>North America</b>	Voltage: 110-127V +/-10 % Frequency: 50/60 Hz +/-3 %, 12A			
<b>Europe and Other Geographies</b>	Voltage: 220-240V +/- 10 % Frequency: 50/60 Hz +/-3 %, 10A			
<b>Power Consumption</b>				
<b>Printing<sup>3</sup></b>	For 110V: 2.85 kWh For 220V: 2.82 kWh			
<b>Standby Mode<sup>3</sup></b>	110V: 75.3 Watts or less 220V: 73.8 Watts or less			
<b>Sleep Mode<sup>3</sup></b>	110V: 0.48 watts or less 220V: 0.53 watts or less			
<b>Operating Environment</b>				
<b>Required Temperature Range (Storage)</b>	Below 48° C, and in compliance with MN2-810.13			
<b>Required Temperature Range (Operating)</b>	50° to 83° F (10° to 28° C) Must be 28° C or below if humidity is at 85 %			
<b>Required Relative Humidity</b>	15 % to 85 % Must be 62.5 % or below at 32° C			
<b>Sound Power Levels</b>	Printing: 6.83 B(A) or less Standby: 3.24 B(A) or less  <b>Full System (including finisher)</b> Printing: 7.64 B(A) Standby: 3.38 B(A)			
<b>Sound Pressure Levels</b>	Printing: 58.2 dB or less Standby: 15.1 dB or less  <b>Full System (including finisher)</b> Printing: 58.1 dB Standby: 15.3 dB			
<b>Boot Time (from Off to UI Ready)</b>	Less than 60 seconds			
<b>Warm-up Time (from Sleep to UI Ready)</b>	Less than 16 seconds			
<b>Dimensions and Weight (Unpackaged)</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
VersaLink® C9000/DT	24.4 in. / 620 mm	28.5 in. / 723 mm	31.9 in. / 809.3 mm	178 lb. / 80.8 kg
Two Tray Module	26.3 in. / 668.5 mm	28.5 in. / 723 mm	10.3 in. / 261.2 mm	60.0 lb. / 27.2 kg
Tandem Tray Module	26.3 in. / 668.5 mm	28.5 in. / 723 mm	10.3 in. / 261.2 mm	74.5 lb. / 33.8 kg
High Capacity Feeder	15.3 in. / 389 mm	23.7 in. / 602.9 mm	15.0 in. / 380.01 mm	63.9 lb. / 29.0 kg
Office Finisher	22 in. / 559.8 mm	21.7 in. / 552 mm	39.8 in. / 1012 mm	61.7 lb. / 28.0 Kg
Booklet Maker (Office Finisher)	11.75 in. / 298.5 mm	23.5 in. / 597 mm	42.5 in. / 1080 mm	20.3 lb. / 9.2 Kg
BR Booklet Maker Finisher	30.28 in. / 769.2 mm	28.5 in. / 723 mm	41.5 in. / 1055.1 mm	134.3 lb. / 60.9 Kg
<b>Dimensions and Weight (Packaged)</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
VersaLink® C9000/DT	32.8 in. / 833 mm	28.2 in. / 717 mm	33.4 in. / 852 mm	209.4 lb. / 95 kg
High Capacity Feeder	20.7 in. / 526 mm	29.8 in. / 756 mm	19.3 in. / 491 mm	74.3 lb. / 33.7 kg
Two Tray Module	32.7 in. / 830 mm	33.5 in. / 850 mm	15.75 in. / 400 mm	72.7 lb. / 33 kg

## Xerox® VersaLink® C9000 Colour Printer

Tandem Tray Module	32.7 in. / 830 mm	33.5 in. / 850 mm	15.75 in. / 400 mm	86 lb. / 39 kg
Office Finisher	27.2 in. / 690 mm	40.2 in. / 1021 mm	25.7 in. / 654 mm	82 lb. / 37 kg
Booklet Maker Finisher	20 in. / 507 mm	30 in. / 761 mm	17.2 in. / 437 mm	31 lb. / 14 kg
BR Booklet Maker Finisher	30 in. / 764 mm	30.5 in. / 774 mm	47.4 in. / 1203 mm	169.7 lb. / 77 kg
Horizontal Transport for BR Booklet Maker Finisher	21 in. / 533 mm	23.1 in. / 589 mm	12.6 in. / 319 mm	14.3 lb. / 6.5 kg
<b>Certifications</b>				
To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .				
<b>Print</b>				
<b>First-print-out Time</b>	As fast as 10.5 seconds colour			
	As fast as 10 seconds black			
<b>Print Resolution</b>	Up to 1200 x 2400 dpi			
<b>Page Description Languages</b>	Adobe® PostScript® 3™ PCL® 5c, 6 PDF XPS TIFF JPEG HP-GL			
<b>Colour Management</b>	Embedded spot colour table with the ability to swap out PANTONE® approved colour table, Custom spot colour editor, optional Xerox® Precise Colour Management System software			
<b>Maximum Print Area</b>	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper			
<b>Print Features</b>	<ul style="list-style-type: none"> <li>Application Defaults</li> <li>Banner Pages Enable / Disable</li> <li>Bi-directional Real-time Status</li> <li>Booklet Layout</li> <li>Colour Adjustments (lightness, contrast, saturation, colour balance)</li> <li>Colour Correction</li> <li>Draft Mode</li> <li>Finishing (requires finishing)</li> <li>Fit to new paper size</li> <li>Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)</li> <li>Job Monitoring (Client or Local User Interface)</li> <li>N-up Page Layout (up to 16 pages per sheet)</li> <li>Paper Selection by Attribute</li> <li>Personal Print</li> <li>Print Around Enable / Disable</li> <li>Print from USB</li> <li>Run Black</li> <li>Sample Set</li> <li>Saved Job</li> <li>Scaling</li> <li>Secure Print</li> <li>Skip Blank Pages</li> <li>Special Pages (exception page programming: covers, inserts, exceptions pages)</li> <li>Store and Recall Driver Settings</li> <li>Stored Jobs Deletion</li> <li>Two-sided Printing (as default)</li> <li>Watermark (predefined and custom)</li> <li>Xerox® Earth Smart Driver Settings</li> </ul>			
<b>Print from USB</b>	<ul style="list-style-type: none"> <li>Allows walk-up printing from Type A USB port</li> <li>Supports direct printing from computer via Type B USB port</li> <li>Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</li> </ul>			

## Xerox® VersaLink® C9000 Colour Printer

<b>Operating Systems</b>	<p>Windows® 7, 8, 8.1, 10          Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019          macOS® 10.11, 10.12, 10.13          Citrix®          Redhat® Enterprise Linux®          Fedora Core          IBM® AIX®          HP-UX®          Oracle® Solaris          SUSE®          SAP®          UNIX®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers &amp; Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a>.</p>
<b>Fonts</b>	<p>PostScript fonts: 136          PCL fonts: 83</p>
<b>Xerox® Mobile Express Driver®</b>	<p>Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p>
<b>Xerox® Global Print Driver®</b>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<b>Xerox® Pull Print Driver</b>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>
<b>Mobile Solutions and Mobile Device Apps</b>	
<b>Apple® AirPrint®</b>	<p>Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.</p>
<b>Google Cloud Print™</b>	<p>Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.</p>
<b>Mopria® Certified</b>	<p>ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android™) smartphone, tablet and other mobile devices instantly and easily.</p>
<b>@PrintByXerox</b>	<p>@PrintByXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.</p>
<b>Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)</b>	<p>The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.</p>
<b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>	<p>Xerox® Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience and security—for any brand printer, anywhere. Xerox® Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow.</p> <ul style="list-style-type: none"> <li>• Xerox® Workplace Suite: On site, your server</li> <li>• Xerox® Workplace Cloud: Simple setup, cloud administration</li> </ul> <p>To learn more about the Xerox® Workplace Suite and Xerox® Workplace Cloud, visit <a href="http://www.xerox.com/Mobility">www.xerox.com/Mobility</a>.</p>

# Xerox® VersaLink® C9000 Colour Printer

<b>Software Solutions</b>	
<b>Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, Serverless ConnectKey Apps to the device.
<b>Security</b>	
<b>Security Features</b>	<p>Access Controls            AES 256-bit Encryption            Audit Log            Certificate Path Validation            Certificate Revocation List (CRL)/Status Protocol (OCSP)            Detection of external programme falsification (XCP Plug-in)            Cisco® Identity Services Engine (ISE) Integration            Domain Filtering            FIPS 140-2            Firmware Verification            Immediate Disk Overwrite            IP Address Filtering            IPsec            Network Authentication            Port Filtering            Pre-installed Self-Signed Certificates            Role Based Permissions            Secure Print            Security Certificate Management            Smart Card Enablement (CAC/PIV/.NET)            SNMPv3            Status Protocol (OCSP)            TLS/SSL</p>
<b>Accounting</b>	
<b>Xerox® Standard Accounting / Network Accounting (Standard)</b>	
<b>Tracking</b>	Print usage
<b>Accounting</b>	<p><b>Xerox® Standard Accounting Tool</b>            Up to 9,999 User Accounts            Up to 500 General accounts</p> <p><b>Network Accounting (Job Based Accounting)</b>            Up to 60,000 User IDs; Up to 60,000 Account IDs            Up to 14,000 accounting records (transactions)</p>
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server.
<b>Accounting Options – Network Accounting (Allows central server to manage all accounting)</b>	
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device print usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>
<b>Paper Handling</b>	
<b>Bypass Tray</b>	
<b>Capacity<sup>4</sup></b>	100 sheets
<b>Sizes</b>	<p>Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 482.6 mm            Banners: 3.5 x 3.9 in. to 12.6 x 52 in./88.9 x 98.4 mm to 320 x 1320.8 mm</p>
<b>Weights</b>	<p>Simplex: 18 lb. bond to 130 lb. cover/64 to 350 gsm            Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm</p>

## Xerox® VersaLink® C9000 Colour Printer

<b>Types</b>	Bond Plain Paper Cardstock Custom Envelopes Extra Heavyweight Cardstock Extra Heavyweight Glossy Cardstock Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Postcards Recycled
<b>Tray 1 and 2</b>	
<b>Capacity<sup>4</sup></b>	520 sheets each
<b>Sizes</b>	Tray 1: 3.9 x 5.8 in. to 11.7 x 17 in./100 x 148 mm to 297 x 431.8 mm Tray 2: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm
<b>Weights</b>	18 lb. bond to 110 lb. cover/64 to 300 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
<b>Two Tray Module</b>	
<b>Capacity<sup>4</sup></b>	1,040 sheets
<b>Sizes</b>	Custom sizes: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm
<b>Weights</b>	18 lb. bond to 110 lb. cover/64 to 300 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
<b>Tandem Tray Module</b>	
<b>Capacity<sup>4</sup></b>	2,000 sheets
<b>Sizes</b>	8.5 x 11 in., 7.25 x 10.5 in./A4, B5
<b>Weights</b>	18 lb. bond to 110 lb. cover/64 to 300 gsm

## Xerox® VersaLink® C9000 Colour Printer

<b>Types</b>	Bond Plain Paper Cardstock Custom Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
<b>High Capacity Feeder</b>	
<b>Capacity<sup>4</sup></b>	2,000 sheets
<b>Sizes</b>	8.5 x 11 in., 7.25 x 10.5 in./A4, B5
<b>Weights</b>	18 lb. bond to 95 lb. cover/64 to 216 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Recycled
<b>Envelope Tray – Replaces Tray 1 (Optional)</b>	
<b>Capacity<sup>4</sup></b>	Up to 50 envelopes
<b>Sizes</b>	#10 commercial, Monarch, DL, C4, C5, C6 Custom sizes: 3.5 x 3.85 in. to 9.5 x 13.1 in./90 x 98 mm to 241 x 332 mm
<b>Total Capacity</b>	
<b>VersaLink® C9000/DT Capacity<sup>4</sup></b>	1,140 sheets
<b>Maximum Capacity<sup>4</sup></b>	5,140 sheets
<b>Finishing</b>	
<b>Output Trays</b>	
<b>Catch Tray</b>	500 sheets (without center tray) 2x 250 sheets (with center tray when offset is off) 2x 125 sheets (with center tray when offset is on)
<b>Office Finisher (Optional)</b>	
<b>Capacity<sup>4</sup></b>	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) (dual stapling only with optional booklet maker) Offset available for collated sets of standard size paper (8.5 x 11 in. / A4 to 11 x 17 in. / A3)
<b>Sizes</b>	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm
<b>Weights</b>	16 lb. bond to 80 lb. cover/60 to 220 gsm
<b>Multiposition Stapling</b>	50 sheets of 24 lb. bond/90 gsm

## Xerox® VersaLink® C9000 Colour Printer

<b>Hole Punch (Optional)</b> North America: Europe:	Up to 65 lb cover (200 gsm) 2/3 hole punch 2/4 hole punch
<b>Booklet Maker for Office Finisher (Score/Crease, Saddle-stitch Staple) (Optional)</b>	
<b>Capacity<sup>4</sup></b>	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)
<b>Sizes</b>	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF
<b>Saddle-stitch Stapling</b>	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm
<b>Score / Crease</b>	1-15 sheets / unstapled / 60-105 gsm only
<b>Optional BR Booklet Maker Finisher (Requires Horizontal Transport Kit)</b>	
<b>Capacity<sup>4</sup></b>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3
<b>Sizes</b>	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling
<b>Weights</b>	16 bond to 110 lb. cover/60 to 300 gsm (coated and uncoated)
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb. / 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
<b>Hole Punch</b> North America Europe	2/3 hole punch 2/4 hole punch 4 hole “Swedish” punch (optional)
<b>Booklet Maker</b>	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported
<b>Device Management</b>	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD, LDAP, Bonjour® / AirPrint™ Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNMP, MDNS
<b>Xerox® CentreWare® Web</b>	
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
<b>Xerox® Embedded Web Server – Integrated Device Web Page</b>	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management—view and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, PDF, XPS, JPEG, TXT, PRN, TIF)



## Xerox® VersaLink® C9000 Colour Printer

<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device	
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	
<b>Remote Services</b>		
<b>Xerox® MeterAssistant® Service</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
<b>Xerox® SuppliesAssistant® Service</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
<b>MaintenanceAssistant Service</b>	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	
<b>What's In The Box</b>		
	<ul style="list-style-type: none"> <li>• VersaLink® C9000 Colour Printer</li> <li>• Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 12,000 print capacity<sup>5</sup>, Black: 18,000 print capacity<sup>5</sup>)</li> <li>• Drum Cartridge – One of each (Cyan, Magenta, Yellow, and Black 190,000 print capacity)<sup>6</sup></li> <li>• Quick Use Guide</li> <li>• Install Guide</li> <li>• Software and Documentation CD (with Drivers, Warranty Statement and Safety Regulatory Recycle Disposal Guide)</li> <li>• Power Cord</li> </ul>	
<b>Supplies and Accessories</b>	<b>Quantity</b>	<b>Part Number</b>
<b>Supplies</b>		
<b>Standard Capacity Toner Cartridges</b>	Cyan: 12,300 standard pages <sup>5</sup> Magenta: 12,300 standard pages <sup>5</sup> Yellow: 12,300 standard pages <sup>5</sup> Black: 18,900 standard pages <sup>5</sup>	106R04070 106R04071 106R04072 106R04073
<b>High Capacity Toner Cartridges</b>	Cyan: 26,500 standard pages <sup>5</sup> Magenta: 26,500 standard pages <sup>5</sup> Yellow: 26,500 standard pages <sup>5</sup> Black: 31,400 standard pages <sup>5</sup>	106R04082 106R04083 106R04084 106R04085
<b>Drum Cartridge</b>	Cyan: 190,000 standard pages <sup>6</sup> Magenta: 190,000 standard pages <sup>6</sup> Yellow: 190,000 standard pages <sup>6</sup> Black: 190,000 standard pages <sup>6</sup>	101R00602
<b>Waste Cartridge</b>	47,000 standard pages <sup>6</sup>	108R01504
<b>IBT Cleaner</b>	160,000 standard pages <sup>6</sup>	104R00256
<b>Transfer Roller</b>	200,000 standard pages <sup>6</sup>	116R00015
<b>Tray 1-4 Feed Rollers</b>	300,000 standard pages <sup>6</sup>	109R00790
<b>Tray 5 (MPT) Feed Rollers</b>	100,000 standard pages <sup>6</sup>	116R00016
<b>Tray 6 Feed Rollers</b>	300,000 standard pages <sup>6</sup>	116R00017
<b>Office Finisher Booklet Maker Cartridge (8 cartridges per container)</b>	16,000 staples (2,000 each cartridge)	008R12897
<b>Staple Refills for Office Finisher (3 refills per container)</b>	15,000 staples (5,000 each refill)	008R12941

## Xerox® VersaLink® C9000 Colour Printer

<b>Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)</b>	5,000 staples (5,000 each cartridge)	008R12964
<b>Staple Cartridges for BR Booklet Maker (1 cartridge per carton)</b>	5,000 staples (5,000 each cartridge)	008R13177
<b>Accessories / Options</b>		
<b>Xerox® Precise Colour Management System Software</b>		097S04974
<b>Two Tray Module</b>		097S04969
<b>Tandem Tray Module</b>		097S04970
<b>High Capacity Feeder</b>		097S04845
<b>Envelope Tray (Replaces Tray 1)</b>		497K17880
<b>Office Finisher Gap Filler (required)</b>		097S04848 497K17370
<b>2/3 Hole Punch for Office Finisher</b>		497K03860
<b>2/4 Hole Punch for Office Finisher</b>		497K03870
<b>Booklet Maker for Office Finisher</b>		497K03852
<b>BR Booklet Maker Finisher with 2/3 Hole Punch</b>		097S04981
<b>BR Booklet Maker Finisher with 2/4 Hole Punch</b>		097S04982
<b>Horizontal Transport for BR Finisher (required with BR Booklet Maker Finisher)</b>		497K17440
<b>Swedish 4 Hole Punch for BR Finisher</b>		497K14370
<b>Wireless Network Adapter Kit</b>		497K16750
<b>Xerox Precise Colour Management System</b>		097S04974

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

<sup>4</sup> Paper capacities are based on 20 lb. 75 gsm stock; capacities will vary with different weight stocks.

<sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

<sup>6</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <http://www.office.xerox.com/Latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling programme. For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

For more information, visit us at [www.xerox.com/Office](http://www.xerox.com/Office).

Configurations vary by geography.