

Xerox[®] VersaLink[®] C9000 Colour Printer



The VersaLink[®] C9000 Colour Printer is built on Xerox[®] ConnectKey[®] Technology. For more information, go to www.connectkey.co.uk.

SYSTEM SPECIFICATIONS	VERSALINK [®] C9000DT
One-Sided Speed¹ A4 A4 SEF 216 x 356 mm A3/297 x 420 mm/ SRA3/320 x 450 mm	Up to 55 ppm (pages per minute) long edge feed (LEF) Up to 40 ppm Up to 32 ppm Up to 27 ppm
Two-Sided Speed¹ A4 A4 SEF 216 x 356 mm A3/297 x 420 mm/ SRA3/320 x 450 mm	Up to 55 ppm LEF Up to 40 ppm Up to 21 ppm Up to 19 ppm
Monthly Duty Cycle ²	Up to 270,000 pages/month
Recommended Average Monthly Print Volume ³	Up to 30,000 pages per month
Hard Drive	320 GB HDD
Processor	1.6 GHz Dual-Core
Memory	4 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform [®] , Xerox [®] App Gallery App, Xerox [®] Standard Accounting Tool, Role Based Permissions, Convenience Authentication Enabled
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 V +/-10% Frequency: 50/60 Hz +/-3%, 12 A			
Europe and Other Geographies	Voltage: 220-240 V +/-7 Frequency: 50/60 Hz +/			
POWER CONSUMPTION				
Printing ⁴	For 110 V: 2.85 kWh For 220 V: 2.82 kWh			
Standby Mode ⁴	110 V: 75.3 Watts or les 220 V: 73.8 Watts or les			
Sleep Mode ⁴	0.71 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	Below 48 °C, and in con	npliance with MN2-81	10.13	
Required Temperature Range (Operating)	10° to 28 °C Must be 28	10° to 28 °C Must be 28 °C or below if humidity is at 85 %		
Required Relative Humidity	15% to 85%; must be	62.5 % or below at 32	2 °C	
Sound Power Levels	Printing: 6.83 B(A) or less Standby: 3.24 B(A) or less Full System (including finisher) Printing: 7.64 B(A) Standby: 3.38 B(A)			
Sound Pressure Levels	Printing: 58.2 dB or less Standby: 15.1 dB or less Full System (including finisher) Printing: 58.1 dB Standby: 15.3 dB			
Boot Time (from Off to UI Ready)	Less than 60 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 16 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C9000/DT	620 mm	723 mm	809.3 mm	80.8 kg
Two Tray Module	668.5 mm	723 mm	261.2 mm	27.2 kg
Tandem Tray Module	668.5 mm	723 mm	261.2 mm	33.8 kg
High-Capacity Feeder	389 mm	602.9 mm	380.01 mm	29.0 kg
Office Finisher LX	559.8 mm	552 mm	1012 mm	28.0 kg
Office Finisher with Booklet Maker attached	1513 mm 723 mm 1076 mm 151.6 kg			
BR Booklet Maker Finisher	769.2 mm 723 mm 1055.1 mm 60.9 kg			

Xerox[®] VersaLink[®] C9000 Colour Printer

WIDTH	DEPTH	HEIGHT	WEIGHT
833 mm	717 mm	852 mm	95 kg
526 mm	756 mm	491 mm	33.7 kg
830 mm	850 mm	400 mm	33 kg
830 mm	850 mm	400 mm	39 kg
690 mm	1021 mm	654 mm	37 kg
507 mm	761 mm	437 mm	14 kg
764 mm	774 mm	1203 mm	77 kg
533 mm	589 mm	319 mm	6.5 kg
	833 mm 526 mm 830 mm 830 mm 690 mm 507 mm 764 mm	833 mm 717 mm 526 mm 756 mm 830 mm 850 mm 830 mm 850 mm 690 mm 1021 mm 507 mm 761 mm 764 mm 774 mm	833 mm 717 mm 852 mm 526 mm 756 mm 491 mm 830 mm 850 mm 400 mm 830 mm 850 mm 400 mm 690 mm 1021 mm 654 mm 507 mm 761 mm 437 mm 764 mm 774 mm 1203 mm

CERTIFICATIONS

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.

PRINT First-Print-Out Time As fast as 10.5 seconds colour As fast as 10 seconds black **Print Resolution** Up to 1200 x 2400 dpi Page Description Languages Adobe[®] PostScript[®] 3[™] PCL[®] 5c, 6 PDF XPS TIFF JPEG HP-GL Embedded spot colour table with the ability to swap out PANTONE® approved colour table, Custom spot colour editor, Xerox® Precise Colour Management System software **Colour Management** Maximum Print Area 4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper

Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Colour Adjustments (lightness, contrast, saturation, colour balance) Colour Correction Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Store dobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A
Operating Systems	Windows® 7, 8, 8.1, 10Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX®
Fonts	PostScript fonts: 136 PCL fonts: 83
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox [®] devices from a single driver. It provides a consistent, easy-to-use interface for end users, reducing the number of support calls and simplifying print services management.

Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
MOBILE SOLUTIONS AND MOBILE	DEVICE APPS
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone [®] or iPad [®] with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria certification ensures that you can print wirelessly from your Mopria supported (Android™) smartphone, tablet and other mobile devices instantly and easily.
Xerox [®] @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android [™] , Google [®] Chromebook [™] and more) to a Xerox [®] printer or multifunction printer using a single email address with no IT intervention. No training is needed. End users simply send attachments to the email address and release them at the panel on the multifunction printer.
Xerox® Print Services plug-in for Android™	The Xerox [®] Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.
Xerox® Workplace Suite and Xerox® Workplace Cloud	 Xerox[®] Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience and security – for any brand printer, anywhere. Xerox[®] Workplace Solutions offer flexible licence options to suit any size business with the ability to scale as you grow. Xerox[®] Workplace Suite: On-site, your server Xerox[®] Workplace Cloud: Simple set-up, cloud administration To learn more about the Xerox[®] Workplace Suite and Xerox[®] Workplace Cloud, visit www.xerox.co.uk/en-gb/office/software-solutions/xerox-workplace-cloud.
SOFTWARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery App)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the device.

SECURITY	
Security Features	Access Controls AES 256-bit encryption Audit log Certificate path validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate disk overwrite IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)
ACCOUNTING	
XEROX [®] STANDARD ACCOUNT	ING/NETWORK ACCOUNTING (STANDARD)
Tracking	Print usage
Accounting	Xerox® Standard Accounting Tool Up to 9,999 User Accounts Up to 500 General Accounts Network Accounting (Job-Based Accounting) Up to 60,000 User IDs; Up to 60,000 Account IDs Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS - NET	WORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)
	 Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device print usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.co.uk Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account
PAPER HANDLING	
BYPASS TRAY	
Capacity ⁵	100 sheets
Sizes	Custom sizes: 88.9 x 98.4 mm to 320 x 482.6 mm Banners: 88.9 x 98.4 mm to 320 x 1320.8 mm
Weights	Simplex: 64 to 350 gsm Duplex: 64 to 300 gsm

Xerox[®] VersaLink[®] C9000 Colour Printer

Types	Bond Plain Paper Cardstock Custom Envelopes Extra Heavyweight Cardstock Extra Heavyweight Glossy Cards	Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock tock Letterhead	Lightweight Card Stock Lightweight Glossy Cardstock Pre-Printed Postcards Recycled	
TRAY 1 AND 2				
Capacity ⁵	520 sheets each			
Sizes	Tray 1: 100 x 148 mm to 297 x 43 Tray 2: 100 x 148 mm to 320 x 45			
Weights	64 to 300 gsm			
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Card Stock Lightweight Glossy Cardstock Pre-Printed Recycled	
TWO TRAY MODULE				
Capacity ⁵	1,040 sheets	1,040 sheets		
Sizes	Custom sizes: 100 x 148 mm to 32	Custom sizes: 100 x 148 mm to 320 x 457.2 mm		
Weights	64 to 300 gsm	64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Card Stock Lightweight Glossy Cardstock Pre-Printed Recycled	
TANDEM TRAY MODULE				
Capacity ⁵	2,000 sheets			
Sizes	A4, B5	A4, B5		
Weights	64 to 300 gsm	64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Card Stock Lightweight Glossy Cardstock Pre-Printed Recycled	
HIGH-CAPACITY FEEDER	2			
Capacity ⁵	2,000 sheets			
Sizes	A4, B5			
Weights	64 to 216 gsm			
Types	Bond Plain Paper Cardstock Custom	Glossy Cardstock Hole Punched Letterhead Lightweight Card Stock	Lightweight Glossy Cardstock Recycled	

ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL)				
Capacity ⁵	Up to 50 envelopes			
Sizes	No. 10 commercial, Monarch, DL, C4, C5, C6 Custom sizes: 90 x 98 mm to 241 x 332 mm			
TOTAL CAPACITY				
VersaLink® C9000/DT Capacity5	1,140 sheets			
Maximum Capacity5	5,140 sheets			
FINISHING				
OUTPUT TRAYS				
Catch Tray	500 sheets (without centre tray) 2x 250 sheets (with centre tray when offset is off) 2x 125 sheets (with centre tray when offset is on)			
OFFICE FINISHERS (OPTIONAL)				
Capacity ⁵	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (A4) (dual stapling only with optional booklet maker) Offset available for collated sets of standard size paper (A4 to A3)			
Sizes				
Office Finisher LX:	210 x 182 mm to 297 x 432 mm			
Office Finisher:	148.0 to 297.0 mm x 148.0 to 432.0 mm			
Weights Office Finishr LX:	60 to 220 gsm			
Office Finisher	60 to 256 gsm			
Multiposition Stapling	50 sheets of 90 gsm			
Hole Punch (Optional) North America: Europe:	Office Finisher LX: up to 200 gsm/Office Finisher: up to 220 gsm 2/3 hole punch 2/4 hole punch			
BOOKLET MAKER FOR OFFICE FINISHERS (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)				
Capacity ⁵	40 booklets (2-15 sheets per booklet – 80 gsm or less)			
Sizes	Letter – A4 SEF Legal – B4 SEF Ledger – A3 SEF			
Saddle-stitch Stapling	2-15 sheets/8-60 page booklet 60 to 90 gsm			
Score/Crease	1-15 sheets/unstapled/60-105 gsm only			
OPTIONAL BR BOOKLET MAKER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)				
Capacity ⁵	Offsetting Top Tray: 500 sheets of A4 unstapled Stacking Stapling Tray: 1,500 sheets of A4/A3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3			
Sizes	A6 to A3 for stacking B5 to A3 for stapling			
Weights	60 to 300 gsm (coated and uncoated)			
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported			

Hole Punch North America Europe	2/3 hole punch 2/4 hole punch 4 hole "Swedish" punch (optional)	
Booklet maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported	
DEVICE MANAGEMENT		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	
REMOTE CONTROL PANEL		
	 Enables faster, more convenient technical support and user training IT administrators and other authorised users can control the device remotely from a web page on any PC Remote user experience is identical to performing tasks directly at the device 	
XEROX [®] CENTREWARE [®] WEB		
	 A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 	
XEROX [®] EMBEDDED WEB SERVER	– INTEGRATED DEVICE WEB PAGE	
Device Status	 Tray status/contents Consumables status Billing/Usage Quick Links Online Support 	
Print Queue Viewing	Job print queue management – view and delete	
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG, TXT, PRN, TIF)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	
REMOTE SERVICES		
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox [®] device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory.	

WHAT'S IN THE BOX			
	 VersaLink[®] C9000 Colour Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 12,000 print capacity⁶, Black: 18,000 print capacity)⁶ Drum Cartridge – One of each (Cyan, Magenta, Yellow and Black 190,000 print capacity)⁶ Quick Use Guide Install Guide Software and Documentation CD (with Drivers, Warranty Statement and Safety Regulatory Recycle Disposal Guide) Power Cord 		
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER	
SUPPLIES	·		
Standard Capacity Toner Cartridges	Cyan: 12,300 standard pages ⁵ Magenta: 12,300 standard pages ⁵ Yellow: 12,300 standard pages ⁵ Black: 18,900 standard pages ⁵	106R04066 106R04067 106R04068 106R04069	
High Capacity Toner Cartridges	Cyan: 26,500 standard pages ⁶ Magenta: 26,500 standard pages ⁶ Yellow: 26,500 standard pages ⁶ Black: 31,400 standard pages ⁶	106R04078 106R04079 106R04080 106R04081	
Drum Cartridge	Cyan: 190,000 standard pages ⁶ Magenta: 190,000 standard pages ⁶ Yellow: 190,000 standard pages ⁶ Black: 190,000 standard pages ⁶	101R00602	
Waste Cartridge	47,000 standard pages ⁷	108R01504	
IBT Cleaner	160,000 standard pages ⁷	104R00256	
Transfer Roller	200,000 standard pages ⁷	116R00015	
Office Finisher Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897	
Staple Refills for Office Finisher (3 refills per container)	15,000 staples (5,000 each refill)	008R12941	
Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R12964	
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R13177	
ACCESSORIES/OPTIONS			
Two Tray Module		097S04969	
Tandem Tray Module		097S04970	
High-Capacity Feeder		097S04845	
Envelope Tray (Replaces Tray 1)		497K17880	
Office Finisher LX (includes Gap Filler)		097S04848	
Office Finisher		097S05019	
2/3 Hole Punch for Office Finisher L	497K03860		
2/3 Hole Punch for Office Finisher (497K20600		
2/4 Hole Punch for Office Finisher L	497K03870		

2/4 Hole Punch for Office Finisher (available in Eastern Hemisphere)	497K20610
Booklet Maker for Office Finisher LX	497K03852
Booklet Maker for Office Finisher	497K20590
BR Booklet Maker Finisher with 2/3 Hole Punch (comes with Horizontal Transport)	497K21000
BR Booklet Maker Finisher with 2/4 Hole Punch	097504982
Swedish 4 Hole Punch for BR Finisher	497K14370
Wireless Network Adapter Kit	497K16750
Xerox Precise Colour Management System	097504974
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.
 ⁴ Power states defined per ENERGY STAR[®] Programme requirements for Imaging Equipment.
 ⁵ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/Latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox[®] Green World Alliance[®] collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.

Configurations vary by geography.

© 2021 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, ConnectKey®, Global Print Driver®, Green World Alliance®, VersaLink® and Xerox Extensible Interface Platform® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 04/21 TSK-1696 BR26419 VC9SS-01EK

