



WorkCentre 5225 shown with High-Capacity Tandem Tray and Integrated Office Finisher



WorkCentre 5230 shown with High-Capacity Tandem Tray and Office Finisher LX with Booklet Maker

	Tandem Tray and Integrated Office Finisher	Tandem Tray and Office Finisher LX with Bookiet Maker	
	WorkCentre® 5225 / WorkCentre® 5225A	WorkCentre® 5230 / WorkCentre® 5230A	
Output Speed – Printing and copying	Up to 25 ppm (pages per minute) 8.5 x 11 in. (A4/210 x 297 mm) LEF	Up to 30 ppm 8.5 x 11 in. (A4/210 x 297 mm) LEF	
Black and White	Up to 16 ppm 8.5 x 14 in. (216 x 356 mm)	Up to 19 ppm 8.5 x 14 in. (216 x 356 mm)	
	Up to 14 ppm 11 x 17 in. (A3/297 x 420 mm	Up to 16 ppm 11 x 17 in. (A3/297 x 420 mm)	
First-Image-Out Time (FCOT) - Letter-size, from Platen to Offset Catch Tray	As fast as a	4.3 seconds	
	Print Spec	cifications	
System Memory	256 MB		
System Disk	40 GB		
Network Printing – Network Controller Processor	333 MHz		
Printer Languages (auto sensing/switching)	PCL [®] 5e PCL [®] 6 HP-GL2 Adobe [®] Postscript [®] 3 [™] (optional)		
Network Printing – Resolution	600 x 600 dpi, 1200 x 1200 dpi		
Network Printing – Printing Features Features	600 x 600 dpi, 1200 x 1200 dpi Secure print Delay print (specific time) Sample set Booklet creation Cover selection Paper selection by attribute N-up Watermark Fit to new paper size Transparency separators Banner sheet enable/disable Output tray selection Drage quality (High Speed, High Resolution) Draft mode Store and recall driver settings Reduce/enlarge Mirror image Save to Mailbox Finishing options Bi-Directional		

Driver Settings	 Application specific saved settings – uses the registry of the application to print per preferences set on client PC. Works at server for applications hosted on a server. Driver only feature. Driver Pre-Configuration – enables drivers to be configured to an administrator-defined standard before being pushed out. Driver only feature. 			
Print Protocols and Networks Physical	100 Base-TX/10 BaseT USB 2.0 printer port Wireless Ethernet (IEEE 802.11b/g) via third-party adapters			
Operating Systems	Microsoft® Windows® XP® 32-bit, XP 64-bit, Windows Server 2003 32-bit, Windows Server 2003 64-bit, Windows Server 2008 32-bit, Windows Server 2008 64-bit, Windows Vista 32-bit, Windows Vista 64-bit, Windows 7 32-bit, Windows 7 64-bit Mac OS® X 10.3–10.5 (PS mandatory) AIX 5Iv5.3 HP UX 11.0, 11i v2 Solaris 8, 9, 10 Linux® FedoraCore 1, 5 RedHat Enterprise Linux 4 SUSE 10.x			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, IPv6 Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway), TCP/IP AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI (All protocols not in use can be disabled)			
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP [®] v2, HTTP, RARP, DHCP Autonet, SSL			
Fonts	Postscript 3: 136 Type 1 fonts, 2 PCL: 81 scalable fonts, line printe			
Print Drivers	Environment Windows XP Windows Vista (32-bit and 64-bit) (Microsoft certified) Windows Server 2003, 2008 (32-bit and 64-bit) Widows 7 (32-bit and 64-bit)	PCL 5e Bidirectional with user- selectable interface (standard ² and enhanced ¹)	PostScript (requires optional kit) Bidirectional with user-selectable interface (standard ² and enhanced ¹)	
	Macintosh® System OS X 10.3–10.5 ³	N/A	Enhanced PPD file	
	UNIX	N/A	Bidirectional with user-selectable interface (standard ² and enhanced ¹)	
Print Submission Tools	Command prompt LPR/UNIX tool for print submission Xerox TIFF submission tool supports TIFF and PDF: Supported in Windows 2000/XP/Vista/Windows Server 2003 Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation) Contents Bridge tool supports TIFF/PDF/XPS			
Device Management Management Support	SNMP Version 1, SNMP Version 2c and Version 3 trap over TCP/IP and IP MIB contains the following standards: RFC 1213, RFC 1514, RFC 1759 and XCMI ver. 3.0			
Xerox CentreWare® Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 			
IP Filter	Allows administrator to control print access to device via IP address			
Xerox CentreWare® for Unicenter TNG®	Provides added identification t Unicenter TNG Business Proce	 Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk 		
Xerox CentreWare® for Tivoli® NetView®	 Provides full integration with event management and the choice to integrate with problem management and davanced help Desk Provides for the identification of Xerox Phaser printers and WorkCentre multifunction printers in the general discovery performed by Tivoli NetView Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC) 			

³ Support for Intel and PPC chipsets.

² Standard: Driver based on Microsoft tree structure user interface (includes Xerox features and functionality).

	WorkConstra® 5225 / WorkConstra® 5220 WorkConstra® 52254 / WorkConstra® 52204		
	Scan Specifications		
Browsers	Windows® XP, Vista, 7: Netscape Navigator®, Firefox® Microsoft® Internet Explorer Macintosh® OS X: Netscape Navigator® 6.x, Apple® Safari™, Firefox® Linux: Netscape® 6.x		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Job Submission	Print-ready files (PS, PCL, TIFF, PDF, XPS) Output feature selection		
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete		
CentreWare® Internet Services – Integrated Device Web Page Device Status	Web server embedded on SMart Network Controller™ Tray status/contents Consumables status 		
Supplies Assistant	Device Direct or via proxy		
SMart eSolutions Meter Assistant	Device Direct or via proxy		
Xerox Barcode Pro PS (Optional) Purchase via Type House 800-445-3668	Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.		
Xerox SAP R/3 Intelligent Barcode Utility (Optional) Purchase via Type House 800-445-3668	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on SMart network controller • Tray status/contents • Consumables status		
Xerox Device Types for SAP R/3 Environment	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): • Simplex or duplex printing • Finishing—single or dual stapling • Tray pull location from any tray • Print security via PIN ID capability at the WorkCentre		
Xerox CentreWare® for HP® OpenView®	 Provides for the identification of Xerox Phaser printers and WorkCentre multifunction printers in the general discovery performed by HP OpenView Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via color-coded icons Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView 		

	WorkCentre® 5225 / WorkCentre® 5230	WorkCentre® 5225A / WorkCentre® 5230A	
Scanning			
(Optional)			
Capability	Black and white (optional)	Color Scanning, Grayscale, Black and white	
Concurrency	Scan while the system is printing copy or network print jobs, or wh	ile it is transferring scan to network or fax jobs	
Input Speed	Scan at 54.8 ipm monochrome 8.5 x 11 in. (216 x 279 mm/A4)	Scan at 54.8 ipm monochrome / 45 ipm color 8.5 x 11 in.	
	long edge feed 200 dpi	(216 x 279 mm/A4) long edge feed 200 dpi	
Resolution	600 x 600 dpi	600 x 600 dpi	
	400 x 400 dpi	400 x 400 dpi	
	300 x 300 dpi	300 x 300 dpi	
	200 x 200 dpi	200 x 200 dpi	
	Bit depth: 1 bit (monochrome)	Bit depth: 1 bit (monochrome), 8 bit (grayscale), 24 bit (color)	
Maximum Scan Area	11.7 x 17 in. / 297 x 432 mm		
Network Protocol	FTP via TCP/IP		
	Microsoft SMB via TCP/IP		

File Formats	TIFF PDF XPS Format	JPEG TIFF PDF XPS Text Searchable PDF (optional)	
Compression method	MH (photo), MMR (text, text/photo), JBIG2 (PDF)	MH (photo), MMR (text, text/photo), JBIG2 (PDF), MRC Compression (optional)	
Document Management Fields	One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard Only for Network Scan through templates		
Scan Features	Bound originals Edge erase Reduction/enlargement Fit to size Scan presets Compression MR, MMR, JBIG2 (with PDF) Original type (photo and text, photo, text) Background Suppression MRC (available for color scanning 5225A / 5230A configurat	ons only)	
Supported Scan Destinations (Varies by scanning software options purchased.)	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (workflow, Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop [™] (Professional and SE editions) Scan to Windows XP client SMB or FTP Scan to Mailbox Scan to Home Scan to PC		
Scan to PC Desktop SE	 A desktop and server-based offering that provides document imaging, archiving, editing and organization tools ScanSoft PaperPort – image viewing and file management software ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. 		
Scan to PC Desktop Pro	 A desktop and server based offering that provides document imaging, archiving, editing and organization tools ScanSoft PaperPort Pro – image viewing and file management software ScanSoft OmniPage Pro (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an Email inbox polling capability. 		
Email (Included with Optional Scan to Email Kit or Network Scan kit, Standard on WorkCentre 5225A / 5230A) Capability	WorkCentre 5225 / 5230: Black and white WorkCentre 5225A / 5230A: Color, Grayscale, Black and W Direct document email from device Manual or directory Exchange/Notes/LDAP address searching "From" field auto-populated from LDAP (when authentication	1	
Network Protocol	SMTP, S/MIME, LDAP, LDAP with SSL, POP3		
Authentication	Device login with network user name and password Supports: Kerberos (UNIX/Windows 2003 Server), SMB, (Windows 2000/Windows 2003 Server) LDAP Domino		
Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)		
Scan to Mailbox (Included with Scan to Email Kit or Network Scan Kit) Capability	WorkCentre 5225 / 5230: Black and white WorkCentre 5225A / 5230A: Color, Grayscale, Black and W	hite	
Features	Images can be scanned, printed and faxed directly to the de the mailbox can then be printed, emailed, sent via fax, sent v	vice hard drive and stored in a mailbox. Scanned images that are stored in ia IFax, routed to a PC, an FTP or SMB server.	

	Fax Specifications		
Fax (Optional – One Line Option)	ITY (CCITT) group 3 quality/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi		
Speed / Modem(s)	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.		
Speed / Compression	MH/MMR, JBIG Super G3		
Fax Send Features	Fax from print driver (LAN Fax) Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan PSTN Fax (VOIP and DSL not supported) Phone number entry via keyboard or address book Secure Fax via FCODE		
Fax Receive Features	One- or two-sided printing Reduction at reception to fit available paper FCODE Secure Fax		
Fax Forwarding	When enabled with the scan and fax kit, faxes can be received into a mailbox. Using Job Flow Sheets, images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax		
Fax Reports	Activity report Dial directory Transmission confirmation Pending fax Mailbox		
Fax Receive Mailboxes	Up to 200 password-protected mailboxes		
Auto Dialing	Auto redial, Batch send		
Speed Dials	500 speed dials Up to 50 dial groups		
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Finisher output tray selection Secure print on/off		
Internet Fax (Optional – Requires Printer/ Copier configuration and Fax Kit) Capability	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients		
Maximum Scan Area	11.7 x 17 in. / 297 x 432 mm		
Address Directory Access	Downloaded address list (comma-separated file format)		
File Formats	TIFF-S, TIFF-F, TIFF-J		
Resolutions	600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (monochrome)		
Network Protocols	SMTP POP3		
Compliance	ITU-T T.37 compliant		

Network Fax Server	One- or two-sided scanning		
Integration	Phone number entry		
(Optional – requires Printer/	Add to send list (50 numbers maximum)		
Copier configuration and one	Delay send (specific time)		
of the scan options) Fax Send Features	Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo and text, photo, text)		
ax Server Vendors Multiple vendors, certified by the Xerox Alliance Partners Program For details, visit www.xerox.com			
	Copy Specifications		
Copying			
Document Scanner	Duplex Automatic Document Feeder with 75-sheet capacity (based on 20 lb. bond / 80 gsm paper)		
Sides (input:output)	1:1, 1:2, 2:2 and 2:1		
Quantity	1 to 999		
Resolution	600 x 600 dpi		
Concurrency	Concurrent scanning and printing		
Digital Imaging	Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness		
Reduction/Enlargement	Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable percentages		
Special Features	Auto paper selectAuto reduction/enlargement to fit selected paper sizeAuto registrationAuto tray switchingAuto tray switchingAuto matic job recoveryPoster modeWatermarkAnnotationBates StampCopy calibrationBooket creationMulti-up—2, 4 or 8 upTransparency dividersNegative imageMirror imageCover insertion (front only, front and back; blank or printed)Build Job (enables special programming for different pages in one document—can be used for inserts, different paper sourcesand mixing input from the document glass and the document feeder)Store and recall job programmingJob interruptBook copyingSample jobMixed-size originalsDirect ConvertionMixed-size originals		
Foreign Device Interface	ID Card Copy Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service		

Device Specifications			
Paper Handling – Duplex Automatic Document Feeder Capacity	75 shoets (kreed on 20 lk head (80 som anner)		
Speed	75 sheets (based on 20 lb bond/80 gsm paper) WorkCentre 5225 / 5230: 54.8 images per minute (ipm) black ar	nd white (Letter/A4 long edge feed (LEE))	
Speed	WorkCentre 52257 5250. 54.0 images per minute (pm) black and WorkCentre 5225A / 5230A: 54.8 ipm black and white / 45 ipm	color (Letter/A4 long edge feed (LEF))	
Sizes	5.5 x 8.3 in (140 x 210 mm) to 11.7 x 17 in. (297 x 432 mm) and	standard sizes of 5.5 x 8.5 in. to 11 x 17 in. (A5 to A3)	
Weights	16 to 32 lb. bond / 38 to 128 gsm		
Paper Handling – Bypass Tray Capacity ⁴	100 sheets		
Sizes	3.5 x 3.9 in. (A6/89 x 98.4 mm) to 11 x 17 in. (A3/297 x 420 mm)		
Weights	16 lb bond to 80 lb Cover / 60 to 215 gsm		
Types	Same as front-loading trays plus labels, envelopes and transparence	ies	
Paper Handling	Tray 1	Tray 2	
 Front-Loading Tray (Standard) Capacity⁴ 	500 sheets	500 sheets	
Sizes	5.5 x 8.5 in. (140 x 216 mm) to 11 x 17 in. (A3/297 x 420 mm)	5.5 x 7.3 in. (A5/140 x 182 mm) to 11 x 17 in. (A3/297 x 420 mm)	
Weights	16 lb. bond to 28 lb. bond / 60 to 105 gsm	16 lb. bond to 80 lb. Cover / 60 to 215 gsm	
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Punched Letterhead Pre-printed	Plain Paper Recycled Bond Custom Type 1 through 5 Punched Letterhead Pre-printed Heavyweight	
Paper Handling – Input Tray Options–Two Tray Module Tray 3 –Tray 4	500 sheets		
Sizes	User adjustable from 5.5 x 7.2 in. (A5/139.7 x 182 mm) to 11 x 17	' in. (A3/297 x 420 mm)	
Weights	16 lb bond to 80 lb Cover / 60 to 215 gsm		
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Punched Letterhead Pre-printed Heavyweight		
Total Capacity ⁴	2,100 sheets (includes Trays 1–4 and Bypass Tray)		
Paper Handling – Input Tray Options–High- Capacity Tandem Tray Tray 3	800 sheets		
Tray 4	1200 sheets		
Sizes	8.5 x 11 in., B5, A4		
Weights	16 lb bond to 80 lb Cover / 60 to 215 gsm		

Types	Plain Paper Recycled Bond Custom Type 1 through 5 Punched Letterhead Pre-printed Heavyweight
Total Capacity ⁴	3,100 sheets (includes Trays 1–4 and Bypass Tray)
Paper Handling – High-Capacity Feeder (HCF) (Compatible with Stand, Two Tray Module and High-Capacity Tandem Tray) Capacity	2,000 sheets of 20 lb. bond (75 gsm)
Sizes	8.5 x 11 in. LEF (A4 / 210 x 297 mm), 7.25 x 10.5 LEF (184 x 266.7 mm)
Weights	16 lb bond to 80 lb Cover / 60 to 215 gsm
Total Capacity ⁴	5,100 sheets with High Capacity Tandem Tray / 4,100 sheets with two tray module
Paper Handling – Input Tray Options–Envelope Tray (Replaces Tray 1) Capacity	Up to 65 Envelopes
Types	#10 commercial, Monarch, DL, C5, large US Postcard, A6
Output – Integrated Office Finisher Option Stacking Tray	500 sheets of 20 lb bond (80 gsm) 8.5 x 11 in./A4 or 250 sheets of 20 lb bond (80 gsm) 11 x 17 in./A3
Sizes	8 x 10 in. / B5 to 11 x 17 in. / A3
Weights	16 lb bond to 80 lb cover / 60 to 215 gsm
Stapling	Single Auto stapling (50 sheets – 90 gsm or less; 2 cover sheets – 215 gsm + 48 sheets – 90 gsm or less) Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Output – Office Finisher LX Option Stacking Tray	2,000 sheets unstapled or 1,000 sheets single staple or 750 sheets dual staple (24 lb. bond / 90 gsm)
Sizes	8 x 10 in. / B5 to 11 x 17 in. / A3
Weights	16 lb bond to 80 lb cover / 60 to 215 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum less than 90 gsm) Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Output – Optional Hole Punch for Office Finisher LX North America	3-hole punch 2-hole Legal punch
Europe	2-hole punch 4-hole punch
Output – Optional Booklet Maker for Office Finisher LX (Score/ Crease, Saddle-stitch Staple) Capacity	40 booklets (1-15 sheets per booklet – 80 gsm or less; 2-10 sheets per booklet – over 80 gsm)
Sizes	Letter – 8.5 x 11 in. (A4/210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3/297 x 420 mm)

Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 14 lb. bond to 24 lb. bond/50 – 90 gsm		
Score/Crease	1-15 sheets / unstapled		
Security Capability	Secure Print, Password Protected PDF, timed auto delete secure print, NDS Authentication over IP, Encrypted Scan to Email (with Scan option), LDAP/Kerberos/SMB, IPv6, 802.1x, IPSec, IP Filtering, Email over SSL, Image Overwrite, Data Encryption, Audit Log		
Secure Access and Authentication (optional)	Optional secure device login with network user name and password Supports: Kerberos (Windows 2000/UNIX/Windows Server 2003, 2008), SMB (Windows 2000/Windows Server 2003, 2008/Vista) LDAP		
Accounting Accounting with Third-Party Server Applications (optional)	Up-to-the-minute data on how the system is being used; comprehe	nsive usage tracking and reporting: print, scan, copy and fax	
Auditron	Controls and tracks copy, print, fax and scan usage, supports up to 5		
Accounting Control	Xerox Standard Accounting Job based accounting Third-party integration Supports Foreign Device Interface Active directory user profile – Controls copy and print usage		
Accounting Xerox Standard Accounting Tracking	Copy, Print, Fax and Scan usage		
Accounting	Up to 1,000 User accounts (User ID) Up to 500 General accounts (Client) Up to 750 Group accounts (Department)		
Features	Enable/disable via the web UI or the GUI in tools, admin can manage CSV file, user required to enter XSA ID into the print driver when sub		
	WorkCentre [®] 5225 / 5225A	WorkCentre [®] 5230 / 5230A	
Monthly Duty Cycle	Up to 75,000	Up to 100,000	
Basic Configurations	WorkCentre 5225 / 5230 Copier: Copy capability with Duplex Aut WorkCentre 5225 / 5230 Network Multifunction System: Copy Document Feeder WorkCentre 5225A / 5230A Network Multifunction System ⁵ : C Controller and Duplex Automatic Document Feeder	and Print capability with Network Controller and Duplex Automatic	
Accessories	Office Finisher LX Office Finisher LX Hole Punch Unit		

Electrical Requirements	220–240 V Nominal, 50/60 Hz, 10A 100-127 Vac, 50/60 Hz, 15A			
Power Consumption Running	< 605 watts			
Standby	< 95 watts			
Sleep Mode	< 3 watts			
Warm Up (from power off)	45 seconds (maximum)			
Low-Power Recovery	26 seconds (maximum)			
Required Temperature Range	50° to 82° F (10° to 28° C)			
Required Relative Humidity	15% to 85%			
Noise Emission	22 dB(A) standby 56 dB(A) running			
Heat Emission	2320 BTU/Hr running 380 BTU/Hr standby			
Dimensions and Weights	Width	Depth	Height	Weight
Base Unit with Two Tray Module	25.2 in. / 640 mm	25.7 in. / 654 mm	43.8 in. / 1,112 mm	214 lbs / 97 kg
Base Unit with Integrated Office Finisher	25.2 in. / 640 mm	25.7 in. / 654 mm	43.8 in. / 1,112 mm	239 lbs / 108.3 kg
Base Unit with Office Finisher LX and Booklet Maker	50.5 in. / 1,283 mm	26.7 in. / 677 mm	43.8 in. / 1,112 mm	253 lbs / 115 kg
Xerox Extensible Interface Platform (EIP)	Xerox Extensible Interface Platform (EIP) is an embedded software platform built with state of the art web technologies. This platform provides the means for software developers to quickly build solutions that are more intuitive and user-friendly for the office workers. Chief among the capabilities provided by EIP is the development of tailored applications with customized user interfaces, and cardbased authentication solutions supporting a personalized user experience.			
			4.03 and Express v 4.03, Omtool G 5 or higher and Xerox Secure Acces	
Certifications	FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada) 89/336/EEC (Europe) UL Listed (UL60950-1, First Edition) CB Certified (IEC 60950-1/EN 60950-1) 73/23/EEC (Europe) Windows Hardware Quality Labs Energy Star Qualified GOST NOM			
	Description		Order Number	
Supplies	Black (Metered)		106R01304	
Toner Cartridges	Black (Sold)		106R01306	
Staple Refills	Staple Refill (Both Finishers)		008R12941	
	Staple Cartridge (Both Finishers)		008R12964	
	Staple Cartridge (Booklet Maker)		008R12897	
Smart Kits	Smart Kit™ Drum Cartridge		101R00434	
	Long Life Drum Cartridge 101R00435			



© 2010 Xerox Corporation. All rights reserved. XEROX[®], XEROX and Design[®], WorkCentre[®], CentreWare[®] and Copier Assistant are trademarks of Xerox Corporation. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR[®] is a U.S. registered mark. As an ENERGY STAR[®] Partner, Xerox Corporation has determined that these products meet the ENERGY STAR[®] guidelines for energy efficiency. Postscript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. Product information and/or specifications are subject to change without notice. Updated 11/10 W30S5-01UG

