

Detailed Specifications



CopyCentre 232 shown with Duplex Automatic Document Handler, High Capacity Feeder and Offset Catch Tray



WorkCentre 238 shown with Duplex Automatic Document Handler, High Capacity Feeder and Basic Office Finisher



WorkCentre 245 shown with Duplex Automatic Document Handler, High Capacity Feeder and Office Finisher



WorkCentre Pro 255 shown with Duplex Automatic Document Handler, High Capacity Feeder, Professional Finisher and Convenience Stapler/Shelf

and Offset Catch Tra	y and Basic Office Finisher	and Office Finisher	Finisher and Convenience Stapler/Shelf
	CopyCentre/WorkCentre/WorkCentre Pro 232/238	CopyCentre/V	VorkCentre/WorkCentre Pro 245/255
OUTPUT SPEED – printing an	nd copying		
	Up to 32 and 38 ipm (images per minute) A4/210 x 297 mm	Up to 4	5 and 55 ipm (images per minute) A4/210 x 297 mm
_	Up to 25 ipm 216 x 356 mm		Up to 36 ipm 216 x 356 mm
	Up to 22 ipm A3/297 x 420 mm		Up to 31 ipm A3/297 x 420 mm
FIRST-COPY-OUT TIME (FCOT	FIRST-COPY-OUT TIME (FCOT) – A4 size, from platen to offset catch tray		
	As fast as 4.5 seconds		As fast as 3.3 seconds
	CopyCentre/WorkCentre/WorkCentre Pro Copy Specifications		
COPYING			
Document Scanner	Single Pass – Platen (available with CopyCentre and WorkCentre 232/238/245) or Duplex Automatic Document Handler (DADH) option. Scans sizes up to A3/297 x 420 mm Short Edge Feed		
Sides (input:output)	1:1, 1:2, 2:2 and 2:1		
Quantity	1 to 9,999		
Resolution	600 x 600 x 8 bit dpi input / 4800 x 600 dpi interpolated output		
Concurrency*	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)		
Copy Pre-Collation Memory (EPC)	128 MB — CopyCentre / WorkCentre (expandable to 512 MB) 384 MB — WorkCentre Pro (expandable to 512 MB)		



	CopyCentre/WorkCentre/WorkCentre Pro Copy Specifications		
COPYING (Continued)			
Basic Copy Features/Options	Features Collation Automatic 2-Sided/Duplex Auto Reduction and Enlargement to fit selected paper size Auto Paper Select Auto Tray Switching	Options Hole Punching Stapling Booklet Creation	
Imaging Copy Features	Image Quality		
Output Copy Features	Transparencies (including dividers – blank or printed) Booklet Creation Multi-up (up to six columns by six rows) Invert Image (negative or mirror image) Covers (Front only, Front and Back, Back only: Blank or Printed) Annotation and Bates Stamping Build Job (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Inserts and Tab copying Sample Set and Job Storage (Store and Recall job programming) Heavy weight paper (not rough stock)		
Other Copy/Device Features	Job Interrupt (Interrupt the current job) Help (Intuitive text and graphic descriptions) Internal Auditron (Copy) Languages (Select up to 20 languages for User Interface – US English, International English, International French, Italian, German, International Spanish, Dutch, Portuguese, Brazilian [Latin Portuguese], Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)		
Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments Six User-Programmable percentages (25%, 64%, 78%, 129%, 154% and 200%)		
Foreign Device Interface (FD (Optional)	I) Interface to third-party access control devices, coin machines, card r Supports a variety of vending solutions available through the Xerox Alliand		
USB Port	PC interface for upload/download of internal auditron data and Xerox Customer device administration/software upgrade	Copier Assistant™	

	CopyCentre/WorkCentre/WorkCentre Pro Copy Specifications
COPYING (Continued)	
Accessibility Option	Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features (English only).
PAPER HANDLING - Duples	x Automatic Document Handler (DADH) (optional with 232/238/245 CopyCentre/WorkCentre/WorkCentre Pro configurations)
Capacity*	75 sheets
Speed	232/238: Up to 38 ipm (images per minute), A4/210 x 297 mm long edge feed (LEF) 245/255: Up to 55 ipm (images per minute), A4/210 x 297 mm long edge feed (LEF)
Paper Sizes Sensed	A3/297 x 420 mm SEF A4/210 x 297 mm LEF or SEF A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF) Legal/216 x 356 mm SEF
Weights	50 to 120 gsm
PAPER HANDLING – Two F	Front Loading Paper Trays
Capacity*	550 sheets each
Sizes	User adjustable from A5/148 x 210 mm to A3/297 x 420 mm
Weights	60 to 200 gsm
Types	Letterhead Preprinted forms Plain Paper Hole-punched Heavyweight Recycled Tab Stock Bond Custom Settings (up to 7)



	CopyCentre/WorkCentre/WorkCentre Pro Copy Specifications
PAPER HANDLING – Bypass	s Tray
Capacity*	100 sheets
Sizes	User Adjustable from 105 x 148 mm to A3/297 x 420 mm
Weights	60 to 216 gsm
Types	Letterhead Preprinted forms Plain Paper Hole-punched Heavyweight Recycled Label Stock Transparencies Inserts/Tabs Bond Custom Settings (up to 7)
PAPER HANDLING – High C	apacity Feeder (HCF) (optional)
Capacity*	Two trays: 1,600 and 2,000 sheets each
Sizes	A4/210 x 297 mm LEF
Weights	60 to 200 gsm
PAPER HANDLING - Total C	apacity
Device Total Capacity*	4,800 sheets (with Bypass tray, front loading paper trays and High Capacity Feeder)
OUTPUT OPTION - Offset Ca	atch Tray (OCT) option
Capacity*	300 sheets
Sizes	A6/105 x 148 mm to A3/297 x 420 mm
Weights	60 to 216 gsm
OUTPUT OPTION - Basic Of	fice Finisher option (available for 232, 238 and 245 only)
Capacity*	Top Tray — 250 sheets Stacking Tray — 1,000 sheets

A6/105 x 148 mm to A3/297 x 420 mm

Single position (top left hand corner)

60 to 216 gsm

30 sheets

Sizes

Weights

Stapling*

	CopyCentre/WorkCentre/WorkCentre Pro Copy Specifications	
OUTPUT OPTION – Office Finisher option		
Capacity*	Top Tray — 250 sheets Stacking Tray — 2,000 sheets	
Sizes	A6/105 x 148 mm to A3/297 x 420 mm	
Weights	60 to 216 gsm	
Stapling*	50 sheets Single (any corner) and dual	
Hole Punch (Optional)	2-hole punch 4-hole punch 4-hole "Swedish" punch	
OUTPUT OPTION - Profess	ional Finisher option	
Capacity*	Top Tray – 250 sheets Stacking Tray – 1,500 sheets	
Sizes	A6/105 x 148 mm to A3/297 x 420 mm	
Weights	60 to 216 gsm	
Stapling*	50 sheets Single (any corner), multi-stapling (up to 4 staples)	
Hole Punch (Standard)	2-hole punch	
Hole Punch (Optional)	4-hole punch 4-hole "Swedish" punch	
Booklet Maker Capacity*	 Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited 	
Sizes	• A3/297 x 420 mm • A4/210 x 297 mm • Legal/216 x 356 mm	
Weights	• 60 to 216 gsm	
Stapling*	Saddle-stitch (2-15 sheets / 8-60 page booklet)	
Folding	V-folding (1-15 sheets / stapled OR 1-5 sheets / unstapled)	
OUTPUT OPTION - Conven	ience stapler option	

50 sheets

Capacity*

WorkCentre/WorkCentre Pro Print Specifications

NETWORK PRINTING - SMart Controller (Simultaneous rip, receive, programme ahead, queue processing and transmit)

Processor 1.4 GHz AMD Athlon dedicated

Memory (ESS) WorkCentre 128 MB (expandable to 256 MB)

WorkCentre Pro 256 MB

System Disk 80 GB Hard Drive shared

Printer Language (PDL) auto switching

WorkCentre

• PCL 6/PCL 5e

PostScript 3 emulation (optional)

- TIFF (6.0 Old JPEG and New JPEG)

- TIFF Fax Extended (TIFF - FX)

- PDF

 \bullet LCDS, SCS, XES and IPDS through third

party transforms

WorkCentre Pro

• PCL 6/PCL 5e

PostScript 3 emulation (standard)

• TIFF (6.0 Old JPEG and New JPEG)

• TIFF Fax Extended (TIFF - FX)

• PDF

LCDS, SCS, XES and IPDS through third party

transforms

NETWORK PRINTING - Resolution (printing via CentreWare software)

PostScript emulation: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey)

PCL: 600 x 600 dpi

Supports PCL and PS switching within job

NETWORK PRINTING - Printing Features

Bi-directional Print Drivers

Embedded web server for remote control/monitor/setup

Job monitoring at the device and at desktop

Advanced Features Include: Special font

Banner Sheet Rotate Image Offset

NETWORK PRINTING - Print Driver Options

Paper Output Job Type

• Secure, Sample, Delay

LAN Fax-with fax option

Save and Save & Print – WorkCentre Pro**

Paper Selection by attribute (including transparency separators)

Duplex (2-sided)

Finishing

Multiple Stapling positions

• Hole punch (if configured)

Booklet creation

• Fit to new paper size

• Saddle stitch (with Professional Finisher)

Output tray selections Store and recall driver setting

Special Pages Exception Page programming (covers, inserts/tabs, exception pages)

Continued

WorkCentre/WorkCentre Pro Print Specifications

NETWORK PRINTING – Printing Features (Continued)

Image Options

Light/Dark

Toner saver

Resolution options (600 x 600 and 1200 x 1200 dpi)

Reduction/Enlargement Margins (edge to edge printing) Invert Image (negative/mirror)

Layout/Watermark

N-up (16)/Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark options

PRINT PROTOCOLS AND NETWORKS

Physical

Ethernet 10/100BaseT, 10BaseT, 10Base2 (IEEE802.5), Token ring - via third party adapter, wireless Ethernet (IEEE802.11a/b/g) - via third party adapter

Operating Systems

WorkCentre

Microsoft Windows 98, Me, NT 4.0, 2000, XP,
 Windows Server 2003, Citrix, Novell NetWare 4.x, 5.x, 6

USB 2.0 / (IEEE1284) Parallel Port Kit (WorkCentre Pro option)

- Optional with PostScript:
 - Mac OS 8.x, 9.x, OS X, 10.3 and higher
 - Solaris 2.8, 2.9, 2.10
 - HPUX 11.0
 - IBM AIX 4.3.3
 - Linux Fedora Core 1 (Intel)
 - Linux Yellowdog 3.0

WorkCentre Pro

- Microsoft Windows 98, Me, NT 4.0, 2000, XP,
 Windows Server 2003, Citrix, Novell NetWare 4.x, 5.x, 6
- Mac OS 8.x, 9.x, OS X, 10.3 and higher
- Solaris 2.8, 2.9, 2.10
- HPUX 11.0
- IBM AIX 4.3.3
- Linux Fedora Core 1 (Intel)
- Linux Yellowdog 3.0

Network Protocols

WorkCentre

- TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP, NDPS *NEPS
- AppleTalk/EtherTalk, Bonjour (optional)

WorkCentre Pro

- TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP, NDPS®/NEPS
- AppleTalk/EtherTalk, Bonjour

Administration Protocols

DHCP, BOOTP, SNMP, WINS, DDNS, SLP v2, HTTP, RARP, DHCP Autonet

Security Protocols/Features

Protocols

- HTTPS
- IPSec
- 802.1x

Features

- IP filtering
- Unlimited Secure Print
- Audit log
- Image Overwrite (optional)
- LDAP Secure Authentication / Secure LDAP
- Data Encryption



WorkCentre/WorkCentre Pro Print Specifications

PRINT PROTOCOLS AND NETWORKS (Continued)

Fonts

PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (true type fonts)
PostScript 3: 136 PostScript standard fonts (true type fonts/send fonts as/substitution table)
Font Management Utility for downloading additional fonts (available for Windows and Mac)

Print Drivers	Environment	PCL6/5e	PostScript 3
	Windows 98/Me, NT 4.0, 2000/XP, Windows Server 2003, Windows Walk-up (PS), Microsoft Certified	Bi-directional features (Xerox custom graphical user interface) Job, Paper and Toner status Job status notification Just in time Bi-Di Auto population of IP address Delete jobs	Bi-directional features (Xerox custom graphical user interface) Job, Paper and Toner status Job status notification Just in time Bi-Di Auto population of IP address Delete jobs
Print Submission Tools	Macintosh System 8.x – 10.2	N/A	Generic PPD Bi-Directional via AppleTalk (9.x)
	Macintosh System 10.3 and higher	N/A	Bi-directional features (Xerox custom graphical user interface)
			 Job, Paper and Toner status Job status notification Just in time Bi-Di Auto population of IP address Delete jobs
	Environment Solaris 2.8, 2.9, 2.10; HPUX 11.0,	PCL	PostScript 3 Submission Tool with full feature set
	IBM AIX 4.3.3; Linux Fedora Core 1 (Intel); Linux YellowDog 3.0	Submission Tool only	(includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows 98/Me/NT 4.0/2000/XP, Windows Server 2003	Submission Tool for any TIFF or PDF file	N/A

	WorkCentre/WorkCentre Pro Print Specifications
DEVICE MANAGEMENT	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2
Xerox CentreWare Internet Services	Allows simple remote installation setting of configuration options and management of the device
Xerox CentreWare Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher
Novell NDPS/NEPS (gateway for WorkCentre Pro	Server gateway application: centralised management tool
Xerox CentreWare for Unicenter TNG	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre Pro under a Unicenter TNG Business Process View
Xerox CentreWare for Tivoli NetView	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction systems in the general discovery performed by Tivoli NetView
Xerox CentreWare for HP OpenView	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
Xerox Barcode Pro PS (optional) Purchase via www.font.net	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
Xerox Device Types for SAP R/3 Environment are available at www.xeroxofficesapsolutions.com	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre Pro printing functionality (PostScript and PCL): • One- to Two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • Number of copies – provide the ability to print multiple copies • Paper Type and colour – provide ability to select different paper types and paper colours, such as transparency, red, etc. • Print security via PIN ID capability at the WorkCentre Pro • Job Based Accounting (JBA) – Provides capability to add JBA UserIDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net
Xerox SAP R/3 Intelligent Barcode Utility (optional) Purchase via www.font.net	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.



	WorkCentre/WorkCentre Pro Print Specifications	
CENTREWARE INTERNET SE	ERVICES – Integrated device Web page	
Device Status	Web server embedded on SMart Controller • Tray status/contents • Consumables status • Alerts	
Job-Print Queue Viewing	Complete job print queue management – delete	
Job Submission	Print ready files PCL (WorkCentre) Print ready files PostScript, PCL TIFF, PDF (WorkCentre Pro) Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Scan Template Management	250 templates can be created Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning	
Browsers	Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x Safari 1.x Mozilla Firefox 1.x	
Support	Online support available via web page	
	WorkCentre/WorkCentre Pro Scan Specifications	
SCANNING		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs	
Input Speed	Scan at 38 ipm (232/238) or 55 ipm (245/255) – A4/210 x 297 mm LEF at all resolutions	
Resolutions DPI Options	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi	
Scan Presets	 Archival Record (Normal Quality - Smallest file size) – 100 x 100 For Sharing and Printing (Normal Quality - Small file size) – 200 x 200 For High Quality Printing (High Quality - Large file size) – 300 x 300 For OCR (High Quality - Large file size) – 300 x 300 Simple Scan (Normal Quality - Small file size) – 200 x 200 	
Quality/File Size	 Normal Quality (Small file size) Higher Quality (Large file size) Highest Quality (Largest file size) 	



	WorkCentre/WorkCentre Pro Scan Specifications
SCANNING (Continued)	
Maximum Scan Area	A3/297 x 420 mm
File Formats	TIFF 6.0 with G3 MH, G4 MMR, MRC or JPEG compression (single page or multiple pages) PDF (image only with G3 MH, G4 MMR, JPEG or JBIG2 compression) Linearised PDF**
SCAN TO EMAIL (Optional v	with WorkCentre / Standard with WorkCentre Pro)
Capability	Scan to e-mail (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients)
Network Protocol	SMTP MIME encoded
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options
NETWORK SCANNING (Star	ndard with WorkCentre Pro)
Capability	 Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services Scan to Home displays one template and populates with the user's directory path after authentication ** Scan to file Scan to network server / directory Scan to Mailbox** Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from www.xerox.com
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template - Metadata Fields consists of field name, display at the user interface or not, default value and other configurations Customised fields viewed on user interface Variable data entered using virtual keyboard at device

WorkCentre/WorkCentre Pro Scan Specifications

NETWORK SCANNING (Standard with WorkCentre Pro) (Continued)

Scan Template Management Share scan templates among WorkCentre Pro via device cloning

Scan template management (250 templates) with CentreWare Internet Services

Select confirmation sheet option

Scan Features

Build job for scan to file only (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size,

Scan mixed size originals, scan to edge.

NETWORK SCANNING SOFTWARE SOLUTIONS (WorkCentre Pro only)

FreeFlow Scan to PC **Desktop Workgroup Edition** SE V 8.0 (optional)

A desktop offering that provides document imaging, archiving, editing and organization tools

ScanSoft PaperPort SE 10 - image viewing and file management software

ScanSoft OmniPage SE 4.0 – offer desktop/client installation – OCR and file format conversion software

Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre Pro to individual desktops

FreeFlow Scan to PC **Desktop Workgroup Edition** Professional V 8.0 (optional)

A desktop offering that provides advanced document imaging, archiving, editing and organization tools.

ScanSoft PaperPort Professional 10 image viewing and file management software

- Complete PDF functionality
- Secure PDF workflow of all scanning applications

ScanSoft OmniPage Pro 15 Office (for desktop/client installation) Professional OCR software for digital archiving and document conversion

Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre Pro to individual desktops. Also includes an email inbox polling capability

FreeFlow SMARTsend (optional)

Server base document routing software that supports multiple scan-enabled multifunction systems

Enables transformation, distribution and routing of scanned documents

Workflow creation via Web browser-based task creation (destinations, devices, document attributes, workflow settings, workflow summary)

- Scan to File Destinations: email, Microsoft NetWare folder, network folder, FTP, Microsoft Exchange 2000 web folders, web URL, remote printers
- Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint, Hummingbird DNS, Open Text Livelink, Documentum, Interwoven Work Site Workflow initiation via device scanning user interface (template selection at device UI) Adding of Metadata information

FreeFlow SMARTsend Professional (optional)

Everything in Free Flow SMARTsend, plus:

- Workflow initiation via Paperware (Scan coversheets)
- Server-based Optical Character Recognition (OCR) File types including searchable PDF
- Searchable PDF
- Scan to Internet fax file destination
- TrueMatch patented search technology

	Co	pyCentre/WorkCentre/WorkCentre Pro Fax Specifications
FAX OPTIONS -Walk-up o	ption (One or Two Lines options)	
Compatibility	ITU (CCITT) Group 3	
Memory	32 MB (One Line) 256 MB (Two Line)	
Speed/Modem(s)	1 or 2 V.34 modems: 33,600bps	s. Less than 4 seconds per page transmission time, ISDN via third party adapter
Compression/Speed	MH/MR/MMR/G3/Super G3	
Fax Send Features	Quality/Resolution	
Fax Receive Features	One or two-sided printing Stapled or unstapled, hole punch Receive print mode -Manual (size Auto answer delay Secure receive Junk fax prevention	
Fax Reports	Activity Dial directory Group directory Options Pending Jobs	
Fax Mailboxes	Up to 100 password-protected Poll Remote mailboxes (up to 25	55) password-protected
Auto Dialing Features		o to 200 recipients per group (One-line option) o to 400 recipients per group (Two-line option) ory capacity)
Resolutions	200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi	200 x 400 dpi 400 x 400 dpi 400 x 600 dpi 600 x 600 dpi (Super fine)

CopyCentre/WorkCentre Pro Fax Specifications

FAX OPTIONS - LAN Fax with Walkup Fax (Optional with WorkCentre and WorkCentre Pro)

Driver based LAN fax for Windows and Macintosh users (PCL and PS drivers)

Recipient options (add recipient or add from phone book)

User personal phone book – up to 1,000 entries

Confirmation sheet

Send speed (14.4/33.6kbps or 4800bps)

Send time

Dialing options (prefix or credit card)

Cover sheet (add notes)

Preferences – Phonebook (personal or shared LDAP)

FAX OPTIONS – Internet Fax (Optional with W	VorkCentre Pro)
---	-----------------

FAX OPTIONS – Internet Fax	(Optional with WorkCentre Pro)	
Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients	
Maximum Scan Area	A3/297 x 420 mm	
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book	
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF	
Resolutions	600 x 600 dpi 200 x 100 dpi 400 x 400 dpi 100 x 100 dpi 300 x 300 dpi 72 x 72 dpi 200 x 200 dpi	
Network Protocols	SMTP POP3 (RFC 1939)	
Compliance	ITU-T T.37 complaint	
Features	Signature (system administrator configurable –16 lines each of 128 character max) Delivery Confirmation • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body	



	CopyCentre/WorkCentre/WorkCentre Pro Fax Specifications
FAX OPTIONS - Network Fa	ax Server Enablement (Optional with WorkCentre Pro)
Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration (via SMTP).
Maximum Scan Size	A3/297 x 420mm
Network Protocols	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
Fax Send Features	One- or two-sided scanning (up to A3/297 x 420 mm) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, seven levels of contrast, seven levels of sharpness)
Fax Print Features	One — or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Programme. For details visit www.xerox.com

	CopyCentre/WorkCentre/WorkCentre Pro Device Management Specifications
ACCOUNTING OPTION	NS – Internal Auditron
Tracking	Copy usage
Accounting	Up to 2,150 User accounts Up to 5,925 General accounts Up to 256 Group accounts
Features	Auditron report printout, ability to upload/download account and usage data via USB connection using Microsoft Windows based software
ACCOUNTING OPTION	NS – Xerox Standard Accounting (Standard with WorkCentre and WorkCentre Pro)
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,500 User accounts (User Id) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.
ACCOUNTING OPTION	NS – Network Accounting – 3rd Party Enablement (Optional with WorkCentre Pro)

ctwork Accounting - Stu Party Linabicinicit (Optional With Work Genue Pro)

Enhanced network accounting with up to the minute data on how the WorkCentre Pro system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Alliance Partner Programme. For details visit www.xerox.com

Security enhancements with the addition of HTTPS protocol support

WorkCentre Pro requests account authentication from third party server enabling larger databases of users and accounts

SECURITY - See supplemental Security brochure for details

Authentication Secure device login with network user name and password

Supports Kerberos (Windows 2000/UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003)

Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x)

PIN-based guest login

Features 802.1x**

HTTPS (SSL) SNMP V3 IPSec

Network Authentication

Device Access Password Protection

IP Filtering Audit Log

Encryption - for Store Print and Scan to Mailbox features on WorkCentre Pro**

Secure Print Fax Security

CopyCentre/WorkCentre/WorkCentre Pro Device Management Specifications

SECURITY - See supplemental Security brochure for details

Options

Disk Image Overwrite

• Immediate, On Demand and Scheduled

Xerox Secure Access**

- Enables convenient and secure access to the WorkCentre / WorkCentre Pro with a simple swipe of your existing employee or student identification card (supports HID, Mifare, Legic, Magnetic Strip)
- Allows 2 factor identification with entry of pin or password on the user interface of the WorkCentre / WorkCentre Pro
- Enables card based follow-you print, allowing users to retrieve print jobs at any device configured with Secure Access
- Single-Sign-On for all device features (copy, fax, scan, email) and pre-populates "to" and "from" fields for email and fax

Common Criteria Certified Software Level

Provides the exact certified software level that was certified by the National Information Assurance Partnership (NIAP).
 This software level does not include the items noted in this document with **

XEROX EXTENSIBLE INTERFACE PLATFORM™ (EIP)

Xerox EIP is a development platform that allows you, Xerox Alliance Partners and System Integrators to build unique applications that are presented at the WorkCentre Pro 232/238/245/255 user interface. The Xerox EIP is an open standard platform that utilises industry standard development tools enabling applications that are easily developed and customised to meet the needs of any business environment or personalised for each user. These applications will yield simpler user interactions and result in less time interacting with the multifunction system which drives increased worker productivity and systems that easily adapt to your business processes.

CopyCentre/WorkCentre/WorkCentre Pro Machine Specifications

MONTHLY DUTY CYCLE

232 – up to 125,000 pages 238 – up to 150,000 pages

245 - up to 175,000 pages

255 – up to 200,000 pages

BASIC CONFIGURATIONS*

CopyCentre and WorkCentre with Platen, Two Trays and Stand (232/238/245 option) CopyCentre, WorkCentre and WorkCentre Pro with DADH, Two Trays and Stand CopyCentre, WorkCentre and WorkCentre Pro with DADH and HCF

CopyCentre/WorkCentre/WorkCentre Pro Machine Specifications

ACCESSORY OPTIONS*

CopyCentre

Walkup Fax

- One line
- Two lines

Offset Catch Tray (OCT)

Basic Office Finisher (available with 232/238/245 only)

Office Finisher Professional Finisher Convenience Stapler

Hole Punch (with Office Finisher — see Output Options for details)

256 MB Pre Collation Memory (EPC) Foreign Interface Device (FDI) Xerox Copier Assistant (XCA)

Upgrade Kits to WorkCentre or WorkCentre Pro

WorkCentre – same as CopyCentre, plus:

Walkup Fax with LAN Fax

- One line
- Two lines

PostScript 3 emulation/MAC Ethertalk

Image Overwrite Security

Email with LDAP / Authentication and additional memory

SecureAccess

Common Criteria Certified Software Level

WorkCentre Pro – same as CopyCentre plus:

Walkup Fax with LAN Fax

- One line
- Two lines

Image Overwrite Security

USB 2.0 / (IEEE1284) Parallel Port Kit

FreeFlow Scan to PC Desktop SE and Professional

Internet Fax

Enablement for Fax/Scan/Accounting Xerox Alliance Partner solutions

SecureAccess

Common Criteria Certified Software Level

CopyCentre/WorkCentre/WorkCentre Pro Machine Specifications

ELECTRICAL REQUIREMENTS

220-240 Volt Nominal, 50 Hz, 10A

Note: Convenience Stapler requires separate 220V 1.2A circuit

POWER CONSUMPTION ¹	232/238 CopyCentre	232/238 WorkCentre/WorkCentre Pro	245/255 CopyCentre	245/255 WorkCentre/WorkCentre Pro
Running	≤ 1080 watts	≤ 1130 watts	≤ 1180 watts	≤ 1230 watts
Standby	≤ 220 watts	≤ 260 watts	≤ 240 watts	≤ 290 watts
Low Power Mode	≤ 90 watts	≤ 120 watts	≤ 100 watts	≤ 125 watts
Auto Off / Sleep mode	≤ 5 watts	≤ 9 watts	≤ 5 watts	≤ 9 watts
Warm up to Copy	≤ 28 seconds	≤ 28 seconds	≤ 28 seconds	≤ 28 seconds
Ready to Print	NA	≤ 130 seconds	NA	≤ 130 seconds
Low Power Recovery	≤ 20 seconds	≤ 20 seconds	≤ 20 seconds	≤ 20 seconds

ENVIRONMENTAL CONSIDERATIONS

Required Temperature Range 10° to 32° C

Required Relative Humidity 10% to 85%

DIMENSIONS AND WEIGHTS (CopyCentre)	Width	Depth	Height ³	Weight ²
Configuration With Offset Catch Tray (OCT)	955 mm	650 mm	1,460 mm	Platen/HCF/OCT 100 kg DADH/HCF/OCT 119 kg
With Basic Office Finisher (BOF)	1,214 mm	650 mm	1,460 mm	Platen/HCF/B0F 123 kg DADH/HCF/B0F 142 kg
With Office Finisher (OF)	1,214 mm	650 mm	1,460 mm	Platen/HCF/OF 128 kg DADH/HCF/OF 147 kg
With Professional Finisher (PF)	1,420 mm	650 mm	1,460 mm	Platen/HCF/PF 176 kg DADH/HCF/PF 195 kg
DIMENSIONS AND WEIGHTS (WorkCentre / WorkCentre Pro)	Width	Depth	Height ³	Weight ²
Configuration With Offset Catch Tray	1,240 mm	830 mm	1,460 mm	DADH/HCF/OCT 126 kg
Configuration With Offset Catch Tray With Basic Office Finisher	1,240 mm 1,499 mm	830 mm 830 mm	1,460 mm 1,460 mm	DADH/HCF/BOF 149 kg
			,	•

	CopyCentre/WorkCentre/WorkCentre Pro Machine Specifications			
SPACE REQUIREMENTS (Fixed)	Width	Depth	Height	
Configuration With Offset Catch Tray	2,955 mm	CopyCentre 2,650mm WorkCentre/ WorkCentre Pro 2,710mm	1,981 mm	
With Basic Office Finisher	3,214 mm	CopyCentre 2,650mm WorkCentre/ WorkCentre Pro 2,710mm	1,981 mm	
With Office Finisher	3,214 mm	CopyCentre 2,650mm WorkCentre/ WorkCentre Pro 2,710mm	1,981 mm	
With Professional Finisher	3,420 mm	CopyCentre 2,650mm WorkCentre/ WorkCentre Pro 2,710mm	1,981 mm	
SPACE REQUIREMENTS (Moveable)	Width	Depth	Height	
Configuration With OCT	1,955 mm	CopyCentre 1,650mm WorkCentre/ WorkCentre Pro 1,710mm	1,981 mm	
With Basic Office Finisher	2,214 mm	CopyCentre 1,650mm WorkCentre/ WorkCentre Pro 1,710mm	1,981 mm	
With Office Finisher	2,214 mm	CopyCentre 1,650mm WorkCentre/ WorkCentre Pro 1,710mm	1,981 mm	
With Professional Finisher	2,420 mm	CopyCentre 1,650mm WorkCentre/ WorkCentre Pro 1,710mm	1,981 mm	

CERTIFICATIONS

FCC Class A Compliant (US), DOC Class A Compliant (Canada) 89/336/EEC (Europe)
UL Listed (UL 1950, Third Edition)
CB Certified (IEC 60950/EN 60950)
73/23/EEC (Europe)
95/5/EEC (Europe)
Energy Star

SUPPLIES	Description	Order Number	No. per Box	Expected Yield
	Toner Cartridge	6R01046	2	30,000 at 6% area coverage
	Waste Toner Bottle (supplied with each toner cartridge box)		1	100,000
	Staple Cartridge / Pack (for Basic Office Finisher)	108R00682 / 108R00535	1 3	3,000 per cartridge 3,000 per cartridge (9,000 staples)
	Staple Cartridge (for Office Finisher)	108R00493	3	5,000 per cartridge (15,000 staples)
	Staple Cartridge (for Booklet maker saddle-stitch stapling)	8R12897	8 (4 x 2)	2,000 per cartridge (16,000 staples)
	Staple Cartridge (for Convenience Stapler) • Complete Cartridge • Refill Cartridge	8R12964 8R12941	1 3	5,000 per cartridge 5,000 per cartridge (15,000 staples)



	CopyCentre/WorkCentre/WorkCentre Pro Machine Specifications			
SMart Kits	Description	Order Number	No. per Box	Expected Yield
	Fuser Module (includes ozone filter)	109R00751	1	350,000
	Xerographic Module- Metered (232/238)	113R00608	1	200,000
	Xerographic Module - Metered (245/255)	113R00672	1	400,000
	Xerographic Module - Sold (232/238)	113R00607	1	200,000
	Xerographic Module - Sold (245/255)	113R00673	1	400,000
	Document Handler Feeder Rolls	113R00686	1	150,000 feeds

