

# WorkCentre™ 5325/5330/5335

## Multifunction Printer



**WorkCentre 5300 Series**  
shown with Stand



**WorkCentre 5300 Series**  
shown with High-Capacity Tandem  
Tray, High-Capacity Feeder and  
Integrated Office Finisher



**WorkCentre 5300 Series**  
shown with High-Capacity Tandem  
Tray and Office Finisher LX with  
Booklet Maker.

	WorkCentre 5325	WorkCentre 5330	WorkCentre 5335
<b>Configurations</b>			
	<b>Copy:</b> Black and white copying		
	<b>Copy/Print/Scan/Optional Fax:</b> Black and white copying, network black and white printing, colour scanning, black and white faxing		
<b>Speed</b>			
<b>Black and white</b>	Up to 25 ppm (pages per minute) A4/210 x 297 mm (8.5 x 11 in.) LEF	Up to 30 ppm A4/210 x 297 mm (8.5 x 11 in.) LEF	Up to 35 ppm A4/210 x 297 mm (8.5 x 11 in.) LEF
	Up to 16 ppm 216 x 356 mm (8.5 x 14 in.)	Up to 19 ppm 216 x 356 mm (8.5 x 14 in.)	Up to 20 ppm 216 x 356 mm (8.5 x 14 in.)
	Up to 14 ppm A3/297 x 420 mm (11 x 17 in.)	Up to 16 ppm A3/297 x 420 mm (11 x 17 in.)	Up to 17 ppm A3/297 x 420 mm (11 x 17 in.)
<b>First-Page-Out Time</b>			
<b>Copy</b>	WorkCentre 5325/5330: As fast as 4.2 seconds WorkCentre 5335: As fast as 4.0 seconds		
<b>Print</b>	As fast as 11.0 seconds		
<b>Paper Handling</b>			
<b>Duplex Automatic Document Feeder (Standard)</b>			
<b>Capacity<sup>1</sup></b>	110 sheets		
<b>Speed</b>	55 images per minute (Letter/A4 long edge feed (LEF))		
<b>Sizes</b>	A5 to A3 (5.5 x 8.5 in. to 11 x 17 in.) SEF Custom sizes: 85 x 125 mm to 297 x 432 mm (3.3 x 4.9 in. to 11.7 x 17 in.) (simplex); 110 x 125 mm to 297 x 432 mm (4.3 x 4.9 in. to 11.7 x 17 in.) (duplex)		
<b>Weights</b>	38 to 128 gsm (13 to 32 lb. bond) (simplex); 50 to 128 gsm (16 to 32 lb. bond) (duplex)		
<b>Bypass Tray (Standard)</b>			
<b>Capacity<sup>1</sup></b>	50 sheets		
<b>Sizes</b>	Custom sizes: 89 x 98 mm to 297 x 432 mm (3.5 x 3.9 in. to 11.7 x 17 in.)		

<sup>1</sup> Paper capacities are based on 75 gsm (20 lb. bond) stock; capacities will vary with different weight stocks.

<b>Weights</b>	60 to 215 gsm (16 lb. bond to 80 lb. cover)
<b>Types</b>	Same as front-loading trays plus envelopes, postcards and labels
<b>Stand Option</b>	
<b>Capacity<sup>1</sup></b>	Trays 1 and 2: 520 sheets each
<b>Sizes</b>	Custom sizes: 140 x 182 mm to 297 x 432 mm (5.5 x 7.2 in. to 11.7 x 17 in.)
<b>Weights</b>	Tray 1: 60 to 105 gsm (16 lb. to 28 lb. bond) Tray 2: 60 to 215 gsm (16 lb. bond to 80 lb. cover)
<b>Types</b>	Plain Paper Recycled Bond Custom Type 1 through 5 Heavyweight Extra Heavyweight Punched Letterhead Pre-printed
<b>Total Capacity</b>	1,090 sheets
<b>High-Capacity Tandem Tray Option</b>	
<b>Capacity<sup>1</sup></b>	Trays 1 and 2: 520 sheets each High-Capacity Tandem Tray: 2,000 sheets
<b>Sizes</b>	Trays 1 and 2: Custom sizes: 140 x 182 mm to 297 x 432 mm (5.5 x 7.2 in. to 11.7 x 17 in.) High-Capacity Tandem Tray: Standard selectable sizes: A4 and B5 (8.5 x 11 in. and 7.25 x 10.5 in.)
<b>Weights</b>	60 to 215 gsm (16 lb. bond to 80 lb. cover)
<b>Types</b>	Plain Paper Recycled Bond Custom Type 1 through 5 Heavyweight Extra Heavyweight Punched Letterhead Pre-printed
<b>Total Capacity</b>	3,090 sheets
<b>High Capacity Feeder (HCF) (Optional with High-Capacity Tandem Tray Module only)</b>	
<b>Capacity<sup>1</sup></b>	2000 sheets
<b>Sizes</b>	Standard Sizes: A4, B5 (7.25 x 10.5 in., 8.5 x 11 in. LEF)
<b>Weights</b>	60 to 215 gsm (16 lb. bond to 80 lb. cover)
<b>Envelope Tray (Optional – replaces Tray 1)</b>	
<b>Capacity<sup>1</sup></b>	Up to 60 envelopes
<b>Sizes</b>	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5 Custom sizes: 98 x 148 mm to 162 x 241 mm (3.9 x 5.8 in. to 6.4 x 9.5 in.)
<b>Weights</b>	75 to 90 gsm (20 lb. bond to 24 lb. bond)
<b>Output / Finishing</b>	
<b>Dual Catch Tray (Standard)</b>	
<b>Capacity<sup>1</sup></b>	Up to 250 sheets each, lower output offset
<b>Sizes</b>	89 x 98 mm to A3/297 x 420 mm (3.5 x 3.9 in. to 11 x 17 in.)
<b>Weights</b>	60 to 215 gsm (16 lb. bond to 80 lb. cover)

<sup>1</sup> Paper capacities are based on 75 gsm (20 lb. bond) stock; capacities will vary with different weight stocks.

Integrated Office Finisher (Optional)	
Stacking Tray <sup>1</sup>	<ul style="list-style-type: none"> <li>• 500 sheets of A4 (8.5 x 11 in.)</li> <li>• 250 sheets of A3 (11 x 17 in.)</li> </ul>
Sizes	89 x 98 mm to 297 x 432 mm (3.5 x 3.9 in. to 11.7 x 17 in.)
Weights	60 to 215 gsm (16 lb. bond to 80 lb. cover)
Stapling	Single Auto stapling: <ul style="list-style-type: none"> <li>• 50 sheets maximum: A4/B5/Letter-size sheets (less than 90 gsm)</li> <li>• 30 sheets maximum: A3/B4/Legal/Tabloid-size sheets (less than 90 gsm)</li> </ul>
Office Finisher LX (Optional)	
Stacking Tray	2,000 sheets unstapled or 1,000 sheets single staple or 750 sheets dual staple (90 gsm (24 lb. bond) A4 (letter))
Sizes	89 x 98 mm to 297 x 432 mm (3.5 x 3.9 in. to 11.7 x 17 in.)
Weights	60 to 215 gsm (16 lb. bond to 80 lb. cover)
Stapling	<ul style="list-style-type: none"> <li>• Single and dual</li> <li>• Auto stapling (50 sheets maximum less than 90 gsm)</li> <li>• A3, A4, B4 and B5 (Letter, Legal, Tabloid) sizes supported</li> </ul>
Hole Punch for Office Finisher LX (Optional)	
North America	<ul style="list-style-type: none"> <li>• 2/3-hole punch</li> </ul>
Europe	<ul style="list-style-type: none"> <li>• 2-hole punch</li> <li>• 4-hole punch</li> </ul>
Booklet Maker (Score/Crease, Saddle-stitch Staple) for Office Finisher LX (Optional)	
Capacity	40 booklets (1-15 sheets per booklet – 80 gsm or less; 2-10 sheets per booklet – over 80 gsm)
Sizes	A4/210 x 297 mm (Letter – 8.5 x 11 in.) 216 x 356 mm (Legal – 8.5 x 14 in.) A3/297 x 420 mm (Ledger – 11 x 17 in.)
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 55 to 90 gsm (16 lb. bond to 24 lb. bond)
Convenience Stapler (Optional)	
Capacity <sup>1</sup>	<ul style="list-style-type: none"> <li>• 50-sheet stapling</li> <li>• 5,000 staples</li> <li>• Requires a separate power outlet</li> </ul>
Copy Specifications	
Document Scanner	Duplex Automatic Document Feeder with 110-sheet capacity <sup>1</sup>
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scanning and printing
Digital Imaging	Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness

<sup>1</sup> Paper capacities are based on 75 gsm (20 lb. bond) stock; capacities will vary with different weight stocks.

<b>Reduction/Enlargement</b>	Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable percentages
<b>Copy Features</b>	Annotation Automatic booklet creation Automatic tray selection Automatic two-sided Auto reduction/enlargement to fit selected paper size Background Suppression Book copying Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Covers insertion (front only, front and back, back only, blank or printed) Delete Outside/Delete Inside Electronic pre-collation Form Overlay Hole Punch (requires Office Finisher LX and Hole Punch options) ID Card Copy Mixed-size originals Multi-position stapling (requires Office Finisher LX and Booklet Maker options) Multi-up – 2, 4 or 8 up Negative/mirror image Page Layout Poster mode Saddle-stitch booklets (requires Office Finisher LX and Booklet Maker options) Sample set Single position stapling (requires Integrated Office Finisher) Watermark
<b>Foreign Device Interface (Optional)</b>	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service
<b>Print Specifications</b>	
<b>System</b>	
<b>Memory</b>	Copier: 1 GB Copier/Printer/Scanner: 1 GB (2 GB with optional PostScript Kit)
<b>Hard Drive</b>	160 GB minimum
<b>Network Printing – Network Controller</b>	
<b>Processor</b>	667 MHz
<b>Supported Page Description Languages on the Device</b>	PCL® 5e PCL 6 HP-GL / HP-GL2 TIFF/PDF XPS® Adobe® Postscript® 3™ (optional)
<b>Supported Page Description Languages on the Driver</b>	PCL 6 Adobe® Postscript® 3™
<b>Network Printing – Resolution</b>	
	1200 x 1200 dpi

Network Printing – Printing Features			
<b>Features</b>	Automatic two-sided Banner Sheets Bi-directional status Booklet creation Cover selection Delay Print (specific time) Draft Mode Fit to new paper size Hole Punch (requires Office Finisher LX and Hole Punch option) Image Quality (High speed, high resolution) Mirror image N-up Output tray selection Paper selection by attribute Print from USB Reduce/enlarge Saddle-stitch booklet making (requires Office Finisher LX and Booklet Maker option) Sample Set Save to Device Folder Secure Print Store and recall driver settings Transparency separators		
<b>Connectivity</b>	10/100/1000Base-TX Ethernet High speed USB 2.0 direct print		
<b>Client Operating Systems</b>	Microsoft® Windows® XP SP3 (32- and 64-bit), Windows Server 2003 (32- and 64-bit), Windows Vista (32- and 64-bit), Windows Server 2008 (32- and 64-bit), Windows 7 (32- and 64-bit) Mac OS® 10.5 and above Netware: 5.11J / 5.12J AIX 5 v5.3 HP UX 11.0, 11i v2 Oracle® Solaris 9, 10 Linux® Fedora Core 12-14 Red Hat Enterprise Linux® 4		
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, IPv6 Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway), TCP/IP AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI (All protocols not in use can be disabled) WSD, IPP SMB (Windows network)		
<b>Administrative Protocols</b>	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL		
<b>Fonts</b>	Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 82 scalable fonts, line printer bitmap font		
<b>Printer Drivers</b>	<b>Operating System</b>	<b>PCL 6</b>	<b>PostScript</b>
<b>Print Drivers</b>	Windows® 2003/XP SP3 (32- and 64-bit) Windows Vista 32- and 64-bit Windows Server 2008 (32- and 64-bit) Windows 7 (32- and 64-bit) (Microsoft® certified)	Bidirectional with user-selectable interface (standard <sup>3</sup> and enhanced <sup>2</sup> )	Bi-directional with user-selectable interface (standard <sup>3</sup> and enhanced <sup>2</sup> )
	Macintosh® OS 10.5 and above	N/A	Bi-directional with user-selectable interface
	Linux (HP-UX 11.0, 11i, AIX 5 (Red Hat® Enterprise, Fedora Core 12-14))	N/A	Bi-directional with Xerox Custom Graphical User Interface

<b>Xerox Mobile Express Driver® (X-MED)</b>	<p>Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p> <ul style="list-style-type: none"> <li>• Printers are automatically discovered</li> <li>• Printer list can be managed based on location</li> <li>• Gives Bi-directional feedback device status, supplies, queue management</li> </ul>
<b>Xerox Global Print Driver® (X-GPD)</b>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> <ul style="list-style-type: none"> <li>• Printers are automatically discovered</li> <li>• Printer list can be managed based on location</li> <li>• Gives Bi-directional feedback device status, supplies, queue management</li> </ul>
<b>Print Submission Tools</b>	<ul style="list-style-type: none"> <li>• Command prompt LPR/UNIX tool for print submission</li> <li>• Contents Bridge tool supports TIFF/PDF/XPS and Office 2007 direct print</li> </ul>
<b>Device Management</b>	
<b>Management Support</b>	<ul style="list-style-type: none"> <li>• SNMP Version 1, SNMP Version 2c and Version 3 trap over TCP/IP and IP</li> <li>• MIB access (IETF-MIB II RFC 1213), Host Resources</li> <li>• MIB RFC 2790, Printer MIB RFC 1759 v. 2</li> </ul>
<b>IP Filter</b>	Allows administrator to control print access to device via IP address. Restricts access to device to/from network.
<b>Xerox CentreWare® Web</b>	<ul style="list-style-type: none"> <li>• CentreWare Web is an innovative office software package that installs, configures, manages, monitors, and reports on SNMP compliant networked printers and multifunction devices in the enterprise – regardless of manufacturer. Robust and easy to use, CentreWare Web allows System Administrators to manage diverse environments from a single location. Using their Web browsers, System Administrators perform multiple administrative functions including installing, configuring, and monitoring networked devices. Customers track usage within the account via the report features of CentreWare Web.</li> </ul>
<b>Xerox CentreWare® for HP® OpenView®</b>	Xerox CentreWare for HP OpenView will be extended to provide for the identification of this device in the general discovery performed by HP OpenView Network Node Manager. It provides the ability to see the current status of discovered Xerox printers/devices under a Xerox Printer Map and IP Map via colour-coded icons. In addition, CentreWare for HP OpenView provides traps and message updates to the OpenView alarm browser and provides the ability to launch CentreWare Internet Services for device management directly from HP OpenView.
<b>CentreWare for IBM Tivoli NetCool/OMNIBus</b>	Xerox CentreWare for IBM Tivoli OMNIBus is device management software that provides simple administration of Xerox products within the IBM Tivoli OMNIBus and Tivoli Network Manger network management toolsets.
<b>CentreWare for Unicenter</b>	Xerox CentreWare for Unicenter provides simple administration of Xerox products within the Unicenter network management tool. It is an easy to install enhancement that expands Unicenter management capability to Xerox networked products. Once successfully installed, you will be able to see all the discovered Xerox printers under one Unicenter Business Process View screen. In addition, CentreWare for Unicenter provides full integration with Event Management, and the choice to integrate with Problem Management and Advanced Help Desk.
<b>CentreWare Management Pack for Microsoft System Centre Operations Manager (SCOM)</b>	Xerox CentreWare Management Pack for System Centre Operations Manager (SCOM) provides the added identification of Xerox devices to the SCOM database. In addition, the Management Pack provides Xerox device management within the SCOM user interface. Once successfully installed, you will be able to see all the discovered Xerox printers under one Xerox device folder. Using the management pack, Alerts, Events, State, Tasks and Diagram views will be available for Operators and Administrators to manage Xerox devices. Alerts and events will be created for conditions that are relevant to the device’s ability to print.
<b>Xerox CentreWare® for Microsoft Management Console (MMC)</b>	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.
<b>Xerox Novell Distributed Print Services Solution (NDPS)</b>	<ul style="list-style-type: none"> <li>• Novell OES 2.0/1.0 – In this environment the Xerox solution includes a snap-in for iManager, a tool for driver installation, and facilities for installation across one or more OES Servers.</li> <li>• Novell NetWare (NetWare 6.5, 6.0, 5.x) – In this environment the Xerox solution includes a snap-in for iManager (NetWare 6.5 SP3 and newer), a printer control snap-in for NWAdmin, a print agent creation utility that allows for discovery of Xerox devices, a tool for driver installation, facilities for installation across one or more NetWare Servers, and integration of the Xerox NDPS Gateway.</li> </ul>

<sup>2</sup> Enhanced: Xerox custom graphical user interface

<sup>3</sup> Standard: Driver based on Microsoft tree structure user interface (includes Xerox features and functionality)

<b>Xerox Device Manager</b>	Xerox Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox Device Manager provides: <ul style="list-style-type: none"> <li>• Device monitoring and troubleshooting</li> <li>• Extensive reporting and discovery of new devices</li> <li>• Usage collection, chargeback and billing capabilities</li> </ul>
<b>Xerox Device Types for SAP R/3 Environment</b> <i>Information available at <a href="http://www.xeroxofficesap.com">www.xeroxofficesap.com</a></i>	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): <ul style="list-style-type: none"> <li>• Simplex or duplex printing</li> <li>• Finishing – single or dual stapling</li> <li>• Tray pull location from any tray</li> <li>• Print security via PIN ID capability at the WorkCentre</li> </ul>
<b>Xerox SAP R/3 Intelligent Barcode Utility (Optional)</b> <i>Information available at <a href="http://www.xeroxofficesap.com">www.xeroxofficesap.com</a></i>	<ul style="list-style-type: none"> <li>• Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Centre Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded the network controller</li> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>
<b>Xerox Barcode Pro PS</b> <i>Information available at <a href="http://www.xeroxofficesap.com">www.xeroxofficesap.com</a></i>	Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or main-frame) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
<b>Smart eSolutions</b>	
<b>MeterAssistant®</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. <ul style="list-style-type: none"> <li>• Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.</li> </ul>
<b>SuppliesAssistant®</b>	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory. <ul style="list-style-type: none"> <li>• Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.</li> </ul>
<b>CentreWare® Internet Services – Integrated Device Web Page</b>	
<b>Device Status</b>	Web server embedded on device controller <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>
<b>Print Queue Viewing</b>	Complete job print queue management – promote and delete
<b>Job Submission</b>	<ul style="list-style-type: none"> <li>• Print-ready files (PS, PCL, TIFF, PDF, XPS)</li> <li>• Output feature selection</li> </ul>
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Netscape Navigator® Mozilla Firefox® Microsoft® Internet Explorer Apple® Safari™
<b>Fax Specifications</b>	
<b>PSTN One-line or Three-line Fax (Optional)</b>	
<b>Resolution</b>	ITY (CCITT) group 3 quality/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi
<b>Speed</b>	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
<b>Compression</b>	G3 Auto Forced 4800 bps G4 Auto

<b>Fax Send Features</b>	<p>Fax from print driver (LAN Fax)                      Auto fax transmission reduction                      Page-by-page job status at the machine                      Fax from glass                      Delay start                      Automatic memory resend                      Automatic cover sheets                      Priority send                      Broadcast                      Booklet Scan                      PSTN Fax                      Phone number entry via keyboard or address book                      Secure Fax via FCODE                      Up to 50 group dials with up to 20 recipients per group</p>
<b>Fax Receive Features</b>	<ul style="list-style-type: none"> <li>• One- or two-sided printing</li> <li>• Reduction at reception to fit available paper</li> <li>• FCODE Secure Fax</li> </ul>
<b>Fax Forwarding</b>	<p>When enabled with the scan and fax kit, faxes can be received into a folder. Using Job Flow Sheets, images that are in the folder can be routed to an Email, an FTP or SMB location or a Fax</p>
<b>Fax Reports</b>	<p>Activity report                      Dial directory                      Transmission confirmation                      Pending fax                      Folder</p>
<b>Fax Receive Mailboxes</b>	<p>Up to 200 password-protected mailboxes</p>
<b>Auto Dialing</b>	<p>Auto redial, Batch send</p>
<b>Fax Print Features</b>	<p>One- or two-sided printing                      Quantity                      Staple on/off                      Collate on/off                      Finisher output tray selection                      Secure print on/off</p>
<b>Internet Fax (Requires Fax Kit)</b>	
<b>Capability</b>	<p>Direct document transmission to remote Internet Fax machines or email clients (SMTP)                      Reception and automatic printout of documents in black and white sent via email from remote Internet Fax machines or email clients</p>
<b>Maximum Scan Area</b>	<p>A3/297 x 432 mm (11 x 17 in.)</p>
<b>Address Directory Access</b>	<p>Downloaded address list (comma-separated value file format)</p>
<b>File Formats</b>	<p>TIFF-S, TIFF-F, TIFF-J</p>
<b>Resolutions</b>	<p>600 x 600 dpi                      400 x 400 dpi                      200 x 200 dpi                      200 x 100 dpi                      Bit Depth: 1 bit (monochrome)</p>
<b>Network Protocols</b>	<p>SMTP                      POP3</p>
<b>Compliance</b>	<p>ITU-T T.37 compliant</p>



Fax over IP (Optional with Copy/Print/Scan configuration)	
<b>Resolution</b>	T.38 compliant IP fax/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi
<b>Fax Send Features</b>	LAN Fax - Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan
<b>Fax Receive Features</b>	One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention
<b>Fax Forward</b>	Faxes can be received into a folder on the device hard drive. Images that are in the folder can be routed to a combination of Email addresses, FTP or SMB sites or locations, or Fax destinations
<b>Fax Reports</b>	Activity report Address Book Transmission confirmation Pending fax Folder List
<b>Fax Receive Folders</b>	Up to 200 password-protected folders
<b>Auto Dialing</b>	Auto redial, Batch send
Scan Specifications	
Scanning (Standard with Copy/Print/Scan configuration)	
<b>Capability</b>	Colour scanning, gray scale, black and white
<b>Concurrency</b>	Scan while the system is printing or while it is transferring Scan to Network or Fax jobs
<b>Input Speed</b>	Scan at 55 ipm Colour / Black and white (216 x 279 mm/A4 long edge feed)
<b>Resolution</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1-bit (monochrome), 8-bit (grayscale), 24-bit (colour)
<b>Maximum Scan Area</b>	A3/297 x 432 mm (11 x 17 in.)
<b>Network Protocol</b>	FTP via TCP/IP Microsoft® SMB via TCP/IP HTTP/Web DAV (scan template only)
<b>File Formats</b>	PDF Image Only PDF (Searchable) PDF (Linearised) PDF (A-1 Level A) TIFF v.6 JFIF JPEG XPS
<b>Compression Method</b>	MH (photo) MMR (text, text/photo) JBIG2 (PDF) MRC Compression (optional)

<b>Document Management Fields</b>	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard Only for Network Scan through templates
<b>Scan Features</b>	Bound originals Edge erase Reduction/enlargement Fit to size Scan presets Original type (photo and text, photo, text) Background Suppression
<b>Supported Scan Destinations</b>	Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to Application (workflow, Electronic Document Management System/Repositories) (optional) Scan to Microsoft® Exchange 2000 Web Folders (optional) Scan to client SMB or FTP Scan to Folder Scan to Home Scan to PC (network scanning) WSD Scan (Microsoft® Client OS)
<b>Scan to PC Desktop SE (Optional)</b>	<ul style="list-style-type: none"> <li>• A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools</li> <li>• Nuance PaperPort – image viewing and file management software</li> <li>• Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.</li> </ul>
<b>Scan to PC Desktop Pro (Optional)</b>	<ul style="list-style-type: none"> <li>• A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools</li> <li>• The PaperPort Personal Scanning Platform empowers office workers with the ability to customise, directly from the desktop, the scanning menus available to them on Xerox EIP enabled MFP devices.</li> <li>• Nuance PaperPort Pro – image viewing and file management software</li> <li>• Nuance OmniPage Pro (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox or through email WorkCentre to individual desktops. Also includes an Email inbox polling capability.</li> </ul>
<b>Scan to Email (Standard with Copier/Printer/Scanner configuration)</b>	
<b>Capability</b>	<ul style="list-style-type: none"> <li>• Colour scanning, gray scale, black and white</li> <li>• Direct document email from device</li> <li>• Manual or directory Exchange/Notes/LDAP address searching</li> <li>• “From” field auto-populated from LDAP (when authentication is used)</li> </ul>
<b>Network Protocol</b>	SMTP, S/MIME, LDAP, LDAP with SSL, POP3, SMTP with SSL
<b>Authentication</b>	Device login with network user name and password Single sign-on supports: Kerberos (UNIX/Windows 2003 Server), SMB, (Windows 2000/Windows 2003 Server), LDAP
<b>Directory Access</b>	Corporate address list via LDAP Downloaded address list (comma-separated file format)
<b>Scan to Folder (Standard with Copy/Print/Scan configuration)</b>	
<b>Capability</b>	Colour scanning, gray scale, black and white
<b>Features</b>	Images can be scanned, printed and faxed directly to the device hard drive and stored in a mailbox. Scanned images that are stored in the mailbox can then be printed, emailed, sent via fax, sent via IFax, routed to a PC, an FTP or SMB server.
<b>Thumbnail Preview (Optional)</b>	
	Images that are stored in the folder on the device hard drive can be viewed at the User Interface.

Device Specifications		
Security	WorkCentre 5325/5330/5335 Copier	WorkCentre 5325/5330/5335 Copier/Printer/Scanner
Capability	256-bit Hard Disk Encryption Image Overwrite	802.1X Annotation Audit Log Authentication with LDAP/Kerberos/SMB/CAC Email over SSL FIPS 140-2 encryption IPsec Image Overwrite LDAP over SSL Encrypted Scan to Email (S/MIME) SNMP v3.0 Secure Print Watermark Secure Web Page via SSL (HTTPS) SSL/TLS IP filtering PDF/XPS digital signatures Digital certificate management OCSP/CRL IPv6 256-bit Hard Disk Encryption Encrypted Password Protected PDF
Secure Access and Authentication (Optional)	Optional secure device login with network user name and password Remote Authentication: Kerberos (Windows Server 2003, Windows Server 2008, Windows 7, UNIX), SMB (Windows Server 2003, Windows Server 2008, Windows Vista, Windows 7) Local Authentication LDAP	
Accounting		
Auditron (Local Accounting)	Controls and tracks black and copy, print, fax and scan usage	
Accounting with Third-Party Server Applications (optional with Copier/Printer/Scanner)	Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax	
Accounting Control	Xerox Standard Accounting Job based accounting Supports Foreign Device Interface Active directory user profile – Controls copy and print usage and feature/pathway control Xerox Page Accountant (optional) Print Audit 5 (optional)	
Accounting – Xerox Standard Accounting (Copier/Printer/Scanner only)		
Tracking	Copy, Print, Fax and Scan usage	
Accounting	Up to 9,999 User accounts (User ID); Up to 9,999 Group accounts (Department)	
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.	
Monthly Duty Cycle		
	WorkCentre 5325: Up to 100,000 pages / month WorkCentre 5330: Up to 125,000 pages / month WorkCentre 5335: Up to 150,000 pages / month	

Xerox Extensible Interface Platform® (EIP)						
	Xerox EIP is a software platform inside the WorkCentre 5300 series that enables personalised solutions you can access right from the device touch screen. These applications can leverage your existing databases and meet your specific business challenges.					
Basic Configurations						
	<b>Copier:</b>		<b>Copier/Printer/Scanner:</b>			
	WorkCentre 5325/5330/5335 with Stand		WorkCentre 5325/5330/5335 with Stand			
	WorkCentre 5325/5330/5335 with High-Capacity Tandem Tray Module		WorkCentre 5325/5330/5335 with High-Capacity Tandem Tray Module			
Optional Accessories						
	Xerox Secure Access Unified ID System® One-line or Three-line PSTN fax with Internet Fax Fax over IP (T.38) Server Fax Enablement Kit Scan to PC Desktop® (Professional or SE edition) Integrated Office Finisher Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Foreign Device Interface Convenience Stapler Envelope Tray (replaces Tray 1) PostScript Kit (required for Mac printing) Thumbnail Preview Kit Searchable PDF Kit Network Accounting Enablement Kit Upgrade to Copier/Printer/Scanner					
Electrical						
<b>Input Voltage</b>	220–240 V Nominal, 50/60 Hz, 8A 110-127 V, 50/60 Hz, 12A					
<b>Warm Up</b>	40 seconds (maximum)					
<b>Low-Power Recovery</b>	12 seconds (maximum)					
<b>Required Temperature Range</b>	10° to 32° C (50 to 90° F)					
<b>Required Relative Humidity</b>	15 to 85 %					
Average Power Consumption	WorkCentre 5325		WorkCentre 5330		WorkCentre 5335	
	Copier	Copier/Printer/Scanner	Copier	Copier/Printer/Scanner	Copier	Copier/Printer/Scanner
<b>110–127 V</b>						
Running:	695 watts	699 watts	721 watts	692 watts	744 watts	730 watts
Standby:	111 watts	127 watts	112 watts	111 watts	115 watts	111 watts
Low Power Mode:	89 watts	89 watts	89 watts	89 watts	89 watts	89 watts
Sleep Mode:	1.1 watts	1.3 watts	1.1 watts	1.3 watts	1.1 watts	1.3 watts
<b>220–240 V</b>						
Running:	724 watts	706 watts	742 watts	720 watts	783 watts	757 watts
Standby:	115 watts	122 watts	111 watts	108 watts	115 watts	118 watts
Low Power Mode:	87 watts	87 watts	87 watts	87 watts	87 watts	87 watts
Sleep Mode:	1.6 watts	1.8 watts	1.6 watts	1.8 watts	1.6 watts	1.8 watts

Heat Emission						
<b>110–127 V</b> Running: Standby:	2,370 BTU/Hr 379 BTU/Hr	2,384 BTU/Hr 433 BTU/Hr	2,459 BTU/Hr 382 BTU/Hr	2,360 BTU/Hr 379 BTU/Hr	2,537 BTU/Hr 392 BTU/Hr	2,489 BTU/Hr 379 BTU/Hr
<b>220–240 V</b> Running: Standby:	2,469 BTU/Hr 392 BTU/Hr	2,407 BTU/Hr 416 BTU/Hr	2,530 BTU/Hr 379 BTU/Hr	2,455 BTU/Hr 368 BTU/Hr	2,670 BTU/Hr 392 BTU/Hr	2,581 BTU/Hr 402 BTU/Hr
Acoustic Noise Emission						
<b>Sound Power</b> Standby: Running:	3.82 (LwAd)b 6.46 (LwAd)b		3.82 (LwAd)b 6.56 (LwAd)b		3.82 (LwAd)b 6.65 (LwAd)b	
<b>Sound Pressure</b> Standby: Running:	20 (LmAp)dBA 47 (LmAp)dBA		20 (LmAp)dBA 48 (LmAp)dBA		20 (LmAp)dBA 50 (LmAp)dBA	
Dimensions and Weights	Width	Depth	Height	Weight		
<b>Base Unit with Bypass Tray Closed</b>	597 mm (23.5 in.)	637.5 mm (25.1 in.)	1,115 mm (43.9 in.)	100 kg (220 lb.)		
<b>Base Unit with Office Finisher LX</b>	1,239 mm (48.8 in.)	651 mm (25.6 in.)	1,115 mm (43.9 in.)	137.2 kg (301.9 lb.)		
<b>Base Unit with High Capacity Feeder</b>	932 mm (36.7 in.)	648 mm (25.5 in.)	1,115 mm (43.9 in.)	129 kg (283.8 lb.)		
Certifications						
	FCC Class A Compliant (U.S./Canada) ENERGY STAR® 89/336/EEC (Europe) TUV Listed CB Certified (IEC 60950-1/EN 60950-1) 2006/95/EC Windows Hardware Quality Labs Blue Angel (Europe) EcoLogo Certified Common Criteria (ISO 15408) - Pending GS Mark Environmental Choice NOM/GOST					
Supplies	Description	Order Number				
<b>Toner Cartridges</b>	Black - Sold	006R01160				
<b>Staple Refills</b>	Integrated Office Finisher	008R12941				
	Office Finisher LX	008R12941				
<b>Staple Cartridges</b>	Integrated Office Finisher	008R12964				
	Office Finisher LX	008R12964				
	Booklet Maker for Office Finisher LX	008R12897				
Smart Kits®	Description	Order Number				
	Smart Kit® Drum Cartridge	013R00591				

