

# Xerox<sup>®</sup> WorkCentre<sup>®</sup> 5945i/5955i Multifunction Printer

The WorkCentre 5945i/5955i Multifunction Printer is built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to **www.connectkey.com**.



Device Specifications				
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan, Arabic			
Accessories	1			
Optional	Envelope Tray Kit (replaces Tray 2) Office Finisher Office Finisher with Booklet Maker Hole Punch for Office Finisher Convenience Stapler (recommended use with optional Work Surface) Horizontal Transport Kit Smart Card Enablement Kit Walk up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit			
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Devi	ce, this is an interface to third party acc	ess control devices, such as coin mac	hines and card readers.
Electrical Requirements				
North America	Voltage : 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 15 A			
Europe	Voltage : 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 5 % , 10 A			
Power Consumption	WorkCentre 5945i		WorkCentre 5955i	
Running (Average) Base Unit with Offset Catch Tray: Base Unit with Office Finisher: Base Unit with Office Finisher with Booklet Maker:	1,150 watts 1,230 watts		1,250 watts 1,330 watts 1,330 watts	
Standby Mode Base Unit with Offset Catch Tray: Base Unit with Office Finisher: Base Unit with Office Finisher with Booklet Maker:	1,230 watts 45 watts 55 watts 55 watts		45 watts 55 watts 55 watts	
Sleep mode	3 watts			
Warm-up	Time from power off to when servic	es are displayed: As fast as 163 second	S	
Recovery from Low Power	As fast as 4 seconds			
Recovery from Sleep	As fast as 28 seconds			
Operating Environment				
Required Temperature Range	10° to 32° C / 50° to 90° F			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating 7.1 B(A), Standby: 5.0 B(A)			
Sound Pressure Levels	Operating: 56 dB(A), Standby: 35 dB(A)			
Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration with Internal Tray	850 mm / 33.5 in.	665 mm / 26.2 in.	1,150 mm / 45.3 in.	113 kg / 249 lbs.
With Office Finisher	1,470 mm / 57.9 in.	665 mm / 26.2 in.	1,150 mm / 45.3 in.	142.5 kg / 314.5 lbs.
With Office Finisher with Booklet Maker	1,530 mm / 60.2 in.	665 mm / 26.2 in.	1,150 mm / 45.3 in.	158.5 kg / 349.5 lbs.
Work Surface (does not add to overall width with Bypass Tray open)	285 mm / 11.2 in.	-	-	-

Certifications		
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) ENERGY STAR® GOST NOM Apple® AirPrint™ 1.4 Certification Mopria® Certified Wi-Fi Direct Certification Blue Angel ECOLOGO® CE Marked Common Criteria (IEEE 2600.2 standard) (undergoing evaluation) EPEAT (United States) Citrix® Certified WHQL	
	MEDITECH Cerner	
	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.	
Paper Handling		
Single-pass Automatic Document	Feeder	
Capacity <sup>3</sup>	200 sheets	
Speed (black and white and colour)	Up to 105 images per minute (ipm) (simplex) Up to 200 ipm (duplex) black and white, up to 160 ipm (duplex) colour	
Paper Sizes Sensed	125 x 138 mm to 297 x 432 mm / 4.9 x 5.4 in. to 11.7 x 17 in.	
Weights	50 gsm to 160 gsm / 13 lb. bond to 43 lb. bond	
Bypass Tray		
Capacity <sup>3</sup>	100 sheets	
Sizes	Custom sizes: A6 to A3 / 4.25 x 5.5 in. to 11 x 17 in.	
Weights	60 to 216 gsm / 16 lb. bond to 80 lb. cover	
Types	Bond         Carbonless         Card Stock         Envelopes         Hole punched         Index         Labels         Letterhead         Plain         Preprinted         Recycled	
Trays 1 and 2		
Capacity <sup>3</sup>	500 sheets each	
Sizes	Custom Sizes from A5 to A3 / 5.5 x 8.5 in. LEF to 11 x 17 in. SEF	
Weights	60 to 200 gsm / 16 lb. bond to 53 lb. bond	
Types	BondCard StockGlossyHole punchedIndexLabelsLetterheadLightweight Card StockPlainPreprintedRecycledTransparencies (Tray 2 only)	
High Capacity Tandem Tray		
Capacity <sup>3</sup>	Tray 3: 1,600 sheets Tray 4: 2,000 sheets	
Sizes	Standard Sizes: A4 / 8.5 x 11 in. LEF	
Weights	60 to 216 gsm / 16 lb. bond to 53 lb. bond	

Types	Bond Card Stock Glossy Hole punched Index Letterhead Lightweight Card Stock Plain Preprinted Recycled
Envelope Kit (Replaces Tray 2)	
Capacity <sup>3</sup>	Up to 50 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), DL, C5
Weights	75 to 90 gsm / 20 lb. bond to 24 lb. bond
Total Capacity	
Device Total Capacity <sup>3</sup>	4,700 sheets
Finishing	
Centre Offsetting Tray	
Capacity	Up to 400 sheets of 80 gsm / 20 lb. bond
Office Finisher (Optional)	
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Top Tray Sizes Stacking Tray Sizes	A6 to A3 / 4.25 x 5.85 in. to 11 x 17 in. A5 to A3 / 5.5 x 8.5 in. to 11 x 17 in.
Weights	60 to 216 gsm / 16 lb. bond to 58 lb. bond
Multiposition Stapling	50 sheets of 80 gsm / 20 lb. bond
<b>Hole Punch (Optional)</b> North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Office Finisher with Booklet Make	r (Optional)
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Top Tray Sizes Stacking Tray Sizes	A6 to A3 / 4.25 x 5.85 in. to 11 x 17 in. A5 to A3 / 5.5 x 8.5 in. to 11 x 17 in.
Weights	60 to 216 gsm / 16 lb. bond to 58 lb. bond
Multiposition Stapling	50 sheets of 80 gsm / 20 lb. bond
<b>Hole Punch (Optional)</b> North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Booklet Making Capacity <sup>3</sup>	40 booklets (2-15 sheets per booklet – 80 gsm / 20 lb. or less)
Booklet Making Sizes	A4 / 8.5 x 11 in. (SEF) B4 / 8.5 x 14 in. (SEF) A3 / 11 x 17 in. (SEF)
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 60 to 90 gsm / 16 lb. bond to 24 lb. bond
Folding (unstapled)	1-5 sheets / unstapled
Convenience Stapler (Optional – R	tecommended Use with Optional Work Surface)
Capacity <sup>3</sup>	50-sheet stapling 5,000 staples Requires a separate power outlet
Сору	
First-copy-out Time	As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max.)	Scan: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi, 256 shades of grey
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)

Copy Features	Annotation and Bates <sup>™</sup> stamping (with colour capability and font size adjustment) Author Reduction for Services Auto Reduction & Enlargement to fit selected paper size Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Transparencies	
	features. Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com.	
Print		
First-print-out Time	As fast as 7 seconds	
Print Resolution	Up to 1200 x 1200 dpi, 256 shades of grey	
Print Features	Application Defaults         Banner Sheet Enable / Disable         Bidirectional Real-time Status         Cover Selection         Delay Print (specific time)         User Permissions         Image Options (Toner Saver, Resolution (Standard, Enhanced, High)         Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)         LAN Fax (requires optional Fax Kit)         Layout / Watermark         N-up (up to 16 pages per sheet)         Booklet layout         Finishing         Fit to new paper size         Hold All Jobs         Page Selection by Attribute         Sample Set         Saved Job         Secure Print with Timed Deletion         Special Pages (exception page programming: covers, inserts, exception pages)         Store and Recall Driver Settings         Sustainability Features (Xerox* Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)         Two-sided Printing (as default)	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS <sup>4</sup> , PCL	
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 SP2 R2 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.8, 10.9, 10.10, 10.11 Linux® Redhat® Fedora® Core 20 x86 Ubuntu® 14.04 x64 openSUSE® 13.1 x64	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® / AirPrint™ IPv6 Secure FTP Most protocols not in use can be disabled	

Administrative Protocols	DHCP, SNMP, WINS, SLP <sup>®</sup> v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support)	
	PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox <sup>®</sup> and non-Xerox <sup>®</sup> devices in every new location. Plug into a new network, and Xerox <sup>®</sup> Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	
Print Solutions		
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.	
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printer using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from t Google Play <sup>™</sup> store.	
Xerox® Mobile Link App (Free at Google Play Store and Apple® App Store)	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.	
Unified Address Book		
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of all services supported	
Scan		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed	Scan at up to 160 ipm colour scanning and 200 ipm black and white scanning – A4 / 8.5 x 11 in. (LEF)	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)	
Maximum Scan Area	A3 / 11 x 17 in.	
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options	
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS	
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Linearised PDF / PDF/A	
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customised fields viewed on user interface for variable data input	
Scan Features	Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10)	
Scan to Email (Standard)		
Scan Features	<ul> <li>Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options</li> <li>Scan to Email S/MIME Encryption</li> <li>Email signing (requires Smart Card option)</li> <li>Auto send to self</li> </ul>	

Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilizes the Unified Address Book	
Scan to (Standard)		
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)	
Network Scanning – Software Solu	utions	
Xerox® Scan to PC Desktop® Professional (Optional)	<ul> <li>A desktop offering that provides advanced document imaging, archiving, editing and organisation tools:</li> <li>PaperPort Professional image viewing and file management software <ul> <li>Complete PDF functionality</li> <li>Secure PDF workflow of all scanning applications</li> </ul> </li> <li>OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion</li> <li>Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability</li> </ul>	
Xerox® ConnectKey® for DocuShare® (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).	
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer.	
Security		
Features	<ul> <li>Expanded Authentication         <ul> <li>Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008), NDS, LDAP authentication</li> <li>Local Authentication (internal database)</li> <li>Smart Card authentication - 144k CAC / PIV Card Support (2048 bit certificate key) / .NET</li> </ul> </li> <li>Secure Data         <ul> <li>Digitally signed PDF (when using Smart Card authentication)</li> <li>Encrypted / Password Protected PDF (Email and Network Scan Templates only)</li> <li>Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>Immediate Image Overwrite / Securely delete jobs using approved algorithms</li> <li>On Demand Image Overwrite / Securely delete jobs using approved algorithms</li> <li>On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>FIPS 140-2 256 bit Hard Disk Encryption</li> </ul> </li> <li>Expanded Authorisation         <ul> <li>SA access based on network credentials</li> <li>Authorisation per user per service</li> <li>User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver</li> </ul> </li> <li>Secure Network Access</li> <li>IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration (optional), Device Security             <ul> <li>McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional)</li> <li>Common Criteria Certification ISO 15408 (undergoing evaluation)</li> </ul> </li></ul>	
Xerox® PrintSafe Software	This authentication software integrates with trusted industry cards and readers and provides PIN access to nearly any printer in a customer's secured print environment. It works with both Xerox® devices and devices from other vendors. This software is open to work with a variety of industry standard secure readers and cards.	
Fax		
Network Server Fax Features		
Compatibility	ITY (CCITT) group 3 Various Xerox® Business Innovation Partner Solutions	
Maximum Scan Area	A3 / 11 x 17 in.	
Fax Send Features	One- or two-sided scanning (up to A3 / 11 x 17 in.) Add to send list (50 numbers maximum) Build Job, Favourites, Delay send (specific time) Original type (photo, text or photo and text)	
Fax Print Features	One- or two-sided printing, staple, Secure Print	
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi	
Internet Fax Features		
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients	
Address Directory Access	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)	
Network Protocols	SMTP (send), POP3 (receive)	

Walk-up Fax Features (Optional (Cu	ustomer-installable) – 1 and 2 lines)	
Compatibility	ITU (CCITT) Group 3	
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analogue terminal adapter utilising T38 (optional)	
Compression / Speed	MH/G3, MMR/SG3	
Resolution	Walkup Send:         Standard: 200 x 100 dpi         Fine: 200 x 200 dpi         Superfine: 600 x 600 dpi         Receive:         Accepts all sizes	
Fax Send Features	LAN Fax (fax from print driver) Auto fax transmission reduction Page-by-page job status at the machine Delay start, Build Job, Favourites Automatic memory resend Automatic cover sheets PSTN Fax Device Address Book (up to 1,000 contacts)	
Fax Receive Features	One- or two-sided printing Stapled or unstapled Receive print mode – Manual (size, margin, stock, header) / Auto Output tray selection Up to 200 password protected mailboxes Secure receive Receive timestamp Auto answer delay	
Fax Forward	Forward to Email or SMB Location Fax forward on receive only	
Fax Reports	Activity, Dial directory, Group directory, Transmission confirmation, Pending fax, Options report, On demand overwrite report, Mailbox report, Broadcast report	
Auto Dialing	Speed Dials: 5,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts (per country requirements) • 1 to 25 minute intervals • Batch send (up to memory capacity)	
Device Management		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2	
Xerox® CentreWare® Web	<ul> <li>A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:</li> <li>Works with any SNMP-managed printer from any manufacturer.</li> <li>Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher.</li> <li>CentreWare Integration available for Tivoli<sup>®</sup> NetView<sup>®</sup>, Unicentre TNG<sup>®</sup>, Microsoft Management Console (MMC), HP<sup>®</sup> OpenView<sup>®</sup></li> </ul>	
Novell NDPS/NEPS	Server gateway application: centralised management tool.	
Xerox® Device Manager	<ul> <li>Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:</li> <li>Device monitoring and troubleshooting</li> <li>Extensive reporting and discovery of new devices</li> <li>Usage collection, chargeback and billing capabilities</li> </ul>	
Xerox <sup>®</sup> Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions	
Xerox® SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions	
Xerox <sup>®</sup> Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard dis Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions	
CentreWare Internet Services – Int	egrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel	

Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS <sup>4</sup> , TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)			
Device Administration	Allows simple, remote installation setting of configuration options and ma	nagement of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12			
Support	Install print / scan drivers and online support available via web page			
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic			
Remote Print Services	-			
Automatic Meter Reading (AMR) (May not be available in all regions)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time- consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.			
Automatic Supplies Replenishment (ASR) (May not be available in all regions)	Automatically orders supplies for Xerox output devices based on actual us not be available in all countries).	age, eliminating the need to mo	anually manage supplies inventory (may	
Accounting				
Xerox® Standard Accounting (Star	ndard)			
Tracking	Copy, Print, Fax, Scan and Email usage			
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)			
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>			
Accounting Options – Network Ac	counting (Allows central server to manage all accounting)			
	<ul> <li>Enhanced network accounting with up to the minute data on how the sy</li> <li>Comprehensive management and enterprise scale tracking and reportin</li> <li>Numerous solutions are available through Xerox Business Innovation Par</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>WorkCentre requests account authentication from third party server ena</li> <li>Accept Authentication Login at control panel and pass to third party Net accounting user interface</li> </ul>	g of device usage of copy, print, tners. For details visit www.xero bling larger databases of users c	and accounts	
Supplies	Description	Quantity	Part Number	
Toner Cartridge	Includes 2 Toner Cartridges	88,000 pages <sup>5</sup> (44,000 pages each) <sup>5</sup>	006R01606	
	Office Finisher with Booklet Maker – saddle-stitch stapling	2,000 per cartridge (8,000 staples)	108R01158	
	Convenience Stapler – Complete Cartridge – Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12964 008R12941	
Smart Kits®				
Fuser Module	North America: Europe:	350,000 <sup>5</sup> 350,000 <sup>5</sup>	109R00847 109R00848	
Print Cartridge	Includes xerographic drums, developer module, including dual auger ring, toner despense, toner concentration sensor, development roll, trim bar and developer material	200,0005	013R00669	

<sup>2</sup> Expected regular monthly throughput

<sup>3</sup> Paper capacities are based on 75 gsm / 20 lb. stock; capacities will vary with different weight stocks.

<sup>4</sup> XPS option is required to print XPS files.

<sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area cover and print mode.

Return spent imaging supplies through the Xerox® Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office.



