Detailed Specifications



WorkCentre 7655 shown with Advanced Finisher and Convenience Stapler options



WorkCentre 7665 shown with Professional Finisher and Convenience Stapler options



WorkCentre 7675 shown with High Capacity Feeder and Light Production Finisher with Folder option

	WorkCentre® 7655	WorkCentre® 7665	WorkCentre® 7675	
OUTPUT SPEED – Printing and Copying				
Black and White	Up to 55 ipm (images per minute) A4/210 x 297 mm	Up to 65 ipm A4/210 x 297 mm	Up to 75 ipm A4/210 x 297 mm	
Colour	Up to 40 ipm A4/210 x 297 mm	Up to 50 ipm A4/210 x 297 mm	Up to 50 ipm A4/210 x 297 mm	
FIRST-IMAGE-OUT TIME -	A4 Size, from Platen to Centre Tray			
Black and White	As fast as 5.5 seconds	As fast as 5.5 seconds	As fast as 5.5 seconds	
Colour	As fast as 8.9 seconds	As fast as 8.9 seconds	As fast as 8.9 seconds	
	Copy Specifications			
COPYING				
Document Scanner	Duplex Automatic Document Handler (DADH) 250-sheet capacity			
Sides (input:output)	1-1, 1-2, 2-2, 2-1			
Quantity	1 to 9,999			
Resolution	Scan at 600 x 600 dpi, output at 2400 x 2400 dpi			
Concurrency	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)			
Copy Pre-collation Memory (EPC)	512 MB DRAM 20 GB Disk minimum			

•••••	Copy Specifications	
COPYING (Continued)		
Basic Copy Features & Options	Collation Automatic 2-sided/Duplex Auto Reduction & Enlargement to fit selected paper size Hole Punching Booklet Creation Stapling Large Job Interrupt Copy on Tabs support Auto Paper Select Authentication for Services (i.e. Colour Copy) Auto Tray Switching	
Imaging Copy Features	 Image Quality: Original Type Selection: Photo & Text, Photo, Text, Newspaper/Magazine, Inkjet Original, Maps. Image Options: Lighten/Darken, Sharpness, Saturation. Image Enhancement: Auto Background Suppression, Auto and Manual Contrast. Colour Effects: Off, Single Colour, Lively, Bright, Warm, Cool. Colour Balance: Normal, Basic Colour, Advanced Colour. Colour Shift: Superior Copy Image Quality Book Copying/Bound Copying Edge Erase (with Print to Edge option) Single Colour Repeat Image Mixed Size Original Image Shift (with Auto Centre option) Image Shift Preset: Support for 3 Preset Options Annotation and Bates™ stamping (with colour capability) 	
Output Copy Features	Transparencies (blank or printed) Dividers (blank) Booklet Creation Multi-up (up to 15 columns by 15 rows) Invert Image (negative or mirror image) Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Build Job: (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Inserts and Tab copying Sample Set and Job Storage (Store and recall job programming) Heavyweight paper (not rough stock)	
Features	Help (Intuitive text and graphic descriptions) Internal Auditron (Copy) Xerox Standard Accounting (Copy, Print, Scan, Fax) Languages: (Select up to 20 languages for user interface – US English, International English, International French, Italian, German, International Spanish, Dutch, Portuguese, Brazilian (Brazilian Portuguese), Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)	

•••••	Copy Specifications	
COPYING (Continued)		
Security	IP Filtering for TCP/IP network communications Enable Secure Workflows Audit Log: Provide export capability of log, includes Username of log on attempts SNMPv3 Support LUI job queue Confidentiality: Require a PIN to delete a Secure print job Image Security Overwrite Auto On-demand Image Overwrite Encryption of user jobs stored on hard disk	
Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments Size user-programmable percentages (100%, Auto%, 25%, 50%, 64%, 70%, 78%, 94%, 141%, 180%, 200%, 400%)	
Foreign Device Interface (FDI) (Optional)	Interface to 3rd party access control devices, coin machines, card readers Validates Metadata Accept Authentication Login at LUI and pass to 3rd party Networking Account Interface with 3rd party accounting terminal for accounting UI MIB Compliance — supports the Finishing MIB Support a variety of vending stations available through the Xerox Custom Application Service	
USB Port	PC Interface for upload/download of Internal Auditron data and Xerox Copier Assistant Customer device administration/software upgrade	
Accessibility Option	Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.	
PAPER HANDLING - Duplex	Automatic Document Handler	
Capacity	250 sheets	
Speed	80 images per minute black and white, 50 ipm colour	
Paper Sizes Sensed	A5/148 x 210 mm to A3/297 x 420 mm or A5/148 x 210 mm to A4/210 x 297 mm	
Weights	80 gsm to 105 gsm	

_		_			
	opv	Cn.	aciti	cat	inne
U	UUV	DILLO	-1711	wai	யாக

PAPER HANDLING - Four Front Loading Paper Trays - Paper Trays 1,2,3 & 4

Capacity

(trays 1 & 2) 500 sheets of 90 gsm each tray

(tray 3) 870 sheets of 90 gsm (tray 4) 1,140 sheets of 90 gsm

Sizes

(trays 1 & 2) A5/148 x 210 mm to A3/297 x 420 mm

(trays 3 & 4) A4/210 x 297 mm

Weights 64 gsm to 220 gsm

Types Plain

Bond

Heavyweight Extra Heavyweight

Glossy

Heavyweight Glossy

Labels

Transparencies

Custom

PAPER HANDLING - Bypass Tray

Capacity 250 sheets of 90 gsm

Sizes 101.6 x 152.4 mm SEF, SRA3 SEF, B5 SEF, A4 SEF & LEF, B4 SEF, A3 SEF

Weights 64 to 300 gsm

Types Plain

Bond

Heavyweight Extra Heavyweight

Glossy

Heavyweight Glossy

Labels Transparencies

Custom

PAPER HANDLING - High Capacity Feeder (HCF)

Capacity 2000 sheets of 90 gsm

210 x 297 mm / A4 LEF, 184 x 266.7 mm LEF Sizes

Weights 64 to 220 gsm

PAPER HANDLING - Total Capacity

Device Total Capacity 5,260 sheets

Copy Specifications

OUTPUT OPTION - Simple Catch Tray (SCT) Option

Capacity 500 sheets of 90 gsm

OUTPUT OPTION - Offsetting Catch Tray (OCT) Option

Capacity 500 sheets of 90 gsm

OUTPUT OPTION - Advanced Office Finisher

Capacity Top tray: 500 sheets

Lower tray: 3,000 sheets of 90 gsm, A4/210 x 297 mm

Sizes 101.6 x 152.4 mm to 304.8 x 482.6 mm

Weights 64 to 300 gsm

Stapling 50 sheets of 90 gsm

Hole Punch 2-4 Hole Punch

Swedish 4-Hole Punch (Optional)

OUTPUT OPTION - Professional Finisher (with Booklet Maker)

Capacity Top tray: 500 sheets

Lower tray: 1,500 sheets of 75 gsm, A4/210 x 297 mm

Sizes 101.6 x 152.4 mm to 304.8 x 482.6 mm

Weights 64 to 300 gsm

Stapling 50 sheets of 90 gsm

Hole Punch (Standard) 2-4 Hole Punch

Swedish 4-Hole Punch (Optional)

Booklet Maker Bi-folded booklets (5 sheets maximum)

Saddle-stitched and Centre folded booklets (15 sheets maximum)

OUTPUT OPTION - Convenience Stapler

Capacity 5,000 staples

Requires a separate outlet

OUTPUT OPTION - Light Production Finisher

Capacity Top tray: 500 sheets

Lower tray: 2,000 sheets of 80 gsm, A4/210 x 297 mm

Sizes 101.6 x 152.4 mm to 304.8 x 482.6 mm

Weights 64 to 300 gsm

Stapling Up to 100 sheets of 80 gsm

•••••	Print Specifications
OUTPUT OPTION - Light F	Production Finisher (Continued)
Hole Punch (Standard)	2-4 Hole Punch Swedish 4-Hole Punch (Optional)
Booklet Maker	Bi-folded booklets (5 sheets maximum) Saddle-stitched and Centre folded booklets (15 sheets maximum)
Post Process Interposer	200 sheet capacity
OUTPUT OPTION - Light F	Production Finisher with Folder
Capacity	Top tray: 500 sheets Lower tray: 2,000 sheets of 80 gsm, A4/210 x 297 mm
Sizes	101.6 x 152.4 mm to 304.8 x 482.6 mm
Weights	64 to 300 gsm
Stapling	Up to 100 sheets of 80 gsm
Hole Punch (Standard)	2-4 Hole Punch Swedish 4-Hole Punch (Optional)
Booklet Maker	Bi-folded booklets (5 sheets maximum) Saddle-stitched and Centre folded booklets (15 sheets maximum)
Post Process Interposer	200 sheet capacity
Folding	Single Sheet C- and Z-folding on 60 to 90 gsm, A4 / A3-sizes Folding Tray: Up to 40 sheets
NETWORK PRINTING - SM	Mart Controller (Simultaneous rip, receive, programme ahead, queue processing, and transmit)
Processor	1.8 GHz Athlon
Memory (ESS)	1 GB
System Disk	80 GB
Print Languages (PDL)	PCL 6 / PCL 5e emulation PostScript 3 emulation TIFF (6.0 Old JPEG and New JPEG) TIFF Fax Extended (TIFF - FX) PDF LCDS, SCS, XES and IPDS through 3rd-party transforms
NETWORK PRINTING - Re	esolution (printing via CentreWare® software)
	PostScript emulation: 600×600 dpi and 1200×1200 dpi (up to 256 shades of grey) PCL: 600×600 dpi Supports PCL and PS switching within job

Print Specifications

NETWORK PRINTING - Printing Features

Bi-directional Print Drivers provide device and job status Embedded Web server for remote control/monitor/setup

Job monitoring at the device and at desktop

Special font Banner Sheet Rotate Image Offset

Support PCL and PS switching

Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print)

Support for Print on Tabs / Page Segmentation

Linearized PDF

Save and restore print job settings

NETWORK PRINTING - Print Driver Options

Paper Output

Job Type

· Secure, Sample, Delay

Paper Selection by attribute (including transparency separators)

Duplex (2-sided) Finishing

· Multiple stapling positions

Hole punch Booklet creation Fit to new paper size

· Saddle stitch with Professional Finisher and Light Production Finishers

Output tray selections Store and recall driver setting

Special Pages

Exception page programming (covers, inserts/tabs, exception pages)

Image Options

Light/Dark

Toner saver

Resolution options (600 x 600 and 1200 x 1200 dpi)

Reduction/Enlargement

Margins (edge to edge printing)
Invert Image (negative/mirror)

Layout/Watermark

N-up (16) / Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark option

PRINT PROTOCOLS AND NETWORKS

Physical

Ethernet 10/100BaseT, 10BaseT, 10Base2 (IEEE802.5) (Token ring) – via adapter, wireless Ethernet

(IEEE802.11a/b/g) - via 3rd party adapter USB 2.0 / IEEE1284 Parallel Port Kit option

IPv6 support for printing

802.1x support

•••••		Print Specifica	ations
PRINT PROTOCOLS AND I	NETWORKS (Continued)		
Operating Systems	Microsoft Windows 2000 Mac OS 8.x, 9.x, OS X, 1 Solaris 2.8, 2.9, 2.10 HPUX 11.0, 11iv2 AIX 5I v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise	0.3 and higher	s Vista, Citrix, Novell NetWare 4.x, 5.x, 6
Network Protocols	TCP/IP, LPR/LPD, Raw II AppleTalk/EtherTalk, Bon	P (Port 9100), NetBIOS SMB, IPX/SP) jour	K, IPP, NDPS [®] /NEPS
Administration Protocols	DHCP, BOOTP, SNMP, W	INS, DDNS, SLP v2, HTTP, RARP, DH	CP Autonet
Security Protocols/Features	Protocols: HTTPS Presc Features: Presc Features: Presc Pre	eue on nage Overwrite	
Fonts		ine printer and bitmap format line prin cript standard fonts (TrueType fonts/se	,
Print Drivers	Environment	PCL XL/5C	PostScript 3

Environment	PCL XL/5C	PostScript 3
Windows 2000/XP, Windows Server 2003, Windows Vista, Windows Walk-up (PS), Microsoft Certified (32 bit and 64 bit)	Bi-directional enhanced (Xerox custom graphical user interface)	Bi-directional enhanced (Xerox custom graphical user interface)
Macintosh System 8.x - 10.2	N/A	Generic PPD Bi-directional via AppleTalk (9.x)
Macintosh System 10.3 and higher	N/A	Bidirectional enhanced (Xerox custom graphical user interface)
Environment	PCL	PostScript 3
Solaris 2.8, 2.9, 2.10 HPUX 11.0 AIX 5I v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise Linux 4	Submission Tool only	Submission Tool with full feature set (Includes administration, GUI/TTY print driver and software installation)
TIFF/PDF: Supported in Windows 2000/XP Windows Server 2003	Submission Tool for any TIFF or PDF file	N/A
	Windows 2000/XP, Windows Server 2003, Windows Vista, Windows Walk-up (PS), Microsoft Certified (32 bit and 64 bit) Macintosh System 8.x - 10.2 Macintosh System 10.3 and higher Environment Solaris 2.8, 2.9, 2.10 HPUX 11.0 AIX 5I v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise Linux 4 TIFF/PDF: Supported in Windows	Windows 2000/XP, Windows Server 2003, Windows Vista, Windows Walk-up (PS), Microsoft Certified (32 bit and 64 bit) Macintosh System 8.x - 10.2 Macintosh System 10.3 and higher N/A Environment PCL Solaris 2.8, 2.9, 2.10 HPUX 11.0 AIX 5I v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise Linux 4

•••••	Print Specifications
DEVICE MANAGEMENT	
	Font Management Utility for downloading additional fonts (available for Windows and Mac)
Software Installation and Upgrade	Network Controller Install Wizard Software Upgrade via Network
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2
E-Services	Automated Billing Meter Reads
Xerox CentreWare Internet Services	Allows simple remote installation setting of configuration options and management of the device.
Xerox CentreWare Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher
Novell NDPS/NEPS	Server gateway application: centralised management tool
Xerox CentreWare for Unicenter TNG	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View
Xerox CentreWare for Tivoli Netware	Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView
Xerox CentreWare for HP OpenView	Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
Xerox Barcode Pro PS (Optional) Purchase via www.font.net	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.

Print Specifications

DEVICE MANAGEMENT (Continued)

Xerox Device Types for SAP R/3 Environment Available at

www.xeroxofficesapsolutions.com

Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):

- · One- to two-sided printing
- · Finishing provides single or dual stapling
- Tray pull location from any tray
- # of copies provide the ability to print multiple copies
- Paper Type and colour provide ability to select different paper types and paper colours, such as transparency, red, etc.
- · Print security via PIN ID capability
- Job Based Accounting (JBA) Provides capability to add JBA UserIDs to SAP print jobs
- Printer banner sheet Provide the ability to enable/disable printer banner sheets
- Barcode printing Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net

Xerox SAP R/3 Intelligent Barcode Utility (Optional) Purchase via www.font.net Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string, and data compression.

CENTREWARE INTERNET SERVICES - Integrated Web Pages Provided by the Device

Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs.
SCANNING	
Support	Online support available via web page
Browsers (minimum versions)	Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x Safari 1.x Mozilla Firefox 1.x
Scan Template Management	Supports 250 scan templates Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Job Submission	Print ready files PS, PCL, TIFF, PDF Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)
Device Status	Web server embedded on SMart Controller:



•••••	Print Specifications
SCANNING (Continued)	
Input Speed	Scan at up to 50 ipm colour scanning, up to 80 ipm black and white – A4/210 x 297 mm at all resolutions
Resolutions (DPI Options)	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi
Scan Presets	Archival Record (Normal Quality - Smallest file size) For Sharing and Printing (Normal Quality - Small file size) For High Quality Printing (High Quality - Large file size) For OCR (High Quality - Large file size) Simple Scan (Normal Quality - Small file size)
Quality / File Size	Normal Quality (Small file size) Higher Quality (Large file size) Maximum Quality (Largest file size)
Maximum Scan Area	A3/297 x 420 mm
Authentication	Secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x / 5.x / 6.x) PIN-based guest login
File Formats	TIFF 6.0 with G3 MH, G4 MMR, or JPEG compression (single page or multiple pages) PDF (image only and searchable PDFs with G3 MH, G4 MMR, MRC, JPEG or JBIG2 compression) JIFF with JPEG compression Microsoft XML Paper Spec (XPS)
Scan Features	Mixed sized Original Support for Scan Export New scan to export compression formats: • MRC (multi-layer) • JBIG2 Simplify the scanning workflow User Interface (IQ, file size, Templates) Enhanced IQ Support for Barcode Readers and OCR Scan in Novell IP Build job for Scan to File Auto Detect Colour or Black and White Image data Auto Contrast support for Scan Export – Enable better colour and greyscale scanned Image Quality by correcting for different levels of black within a scanned image Scan to Searchable PDF, PDF/A and XPS Scan to Home Scan to Mailbox Store and reprint print jobs

	Print Specifications	
SCAN TO EMAIL - Option	al	
Capability	Scan to email (manual address entry), directory (Exchange/Notes/LDAP) address searching, internal address book or Public address book (up to 128 recipients)	
Network Protocol	SMTP MIME encoded	
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options	

NETWORK SCANNING - Optional

Capability

Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services:

- · Scan to file
- Scan to network server / directory
- Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from www.xerox.com
- · Scan to email
- Scan to Microsoft Exchange public folders
- · Scan to PC Desktop

Network Protocol

Novell (NCP via IPX/SPX)

FTP

Microsoft SMB via TCP / IP

HTTP / HTTPS

Document Management Fields (Metadata)

Features only available in Network Scan to File Templates:

Fields (Metadata)

- 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata Field consists of field name, display at the LUI or not, default value and other configurations
- · Customised fields viewed on user interface
- · Variable data entered using virtual keyboard at device

Scan Template Management

Share scan templates among WorkCentre via device cloning

Scan template management (250 templates) with CentreWare Internet Services

Select confirmation sheet option

Scan Features

Build job (for scan to file only) (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge

NETWORK SCANNING - Software Solutions

Supported Scan Scan to application (workflow, Electronic Document Management System / Repositories)

Destinations - scan Scan to Microsoft Exchange 2000 Web folders

template creation Scan to Web URL
(Varies by scanning Scan to remote printer

software options Scan to PC Desktop (SE and Professional editions)

purchased) Scan to Mailbox

•••••	Copy Specifications
NETWORK SCANNING - S	Software Solutions (Continued)
FreeFlow Scan to PC	A desktop offering that provides document imaging, archiving, editing and organisation tools:
Desktop SE (optional)	 ScanSoft PaperPort SE 10 – image viewing and file management software ScanSoft OmniPage SE 3.0 – offer desktop / client installation – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre to individual desktops
FreeFlow Scan to PC Desktop Professional (optional)	 A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: ScanSoft PaperPort Professional 10 image viewing and file management software: Complete PDF functionality Secure PDF workflow of all scanning applications ScanSoft OmniPage Pro 14 Office (for desktop / client installation) – Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an email inbox polling capability
FreeFlow SMARTsend (optional)	 Server based document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per server): Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary) Scan to File Destinations: email, Novell Netware folder, network folder, SMB folder, FTP, Microsoft Exchange 2000 Web folders, Web URL, remote printers

FreeFlow SMARTsend Professional (optional)

Everything in Free Flow SMARTsend, plus:

- Workflow initiation via Paperware (Scan coversheets)
- Server-based Optical Character Recognition (OCR)
- Adding of Metadata information
- Scan to Internet fax file destination

	Fax Specifications		
FAX OPTIONS - Walk Up Option (one or two lines options)			
Compatibility	ITU (CCITT) Group 3		
Memory	32 MB (One line) 256 MB (Two line)		
Speed / Modems	1 or 2 V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time.		
Compression / Speed	MH / MR / MMR / G3 / Super G3		

• Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint

• Workflow initiation via device scanning user interface (template selection at device UI)

Fax Specifications

FAX OPTIONS - Walk Up Option (one or two lines options) (Continued)

Fax Send Features

Quality / Resolution

Original type: Photo, Photo/Text, Text Only
 Server of Plates residual sizes on Payard (Payard)

• Fax – off Platen, mixed sizes or Bound / Book

Auto Send (Up to 5)
Audio line monitor

Transmission options (Report/Header) Reduce / Split large documents

Cover letter Delayed send

Build Job (up to 1,000 images)

Polling

Fax Receive Features

One- or two-sided printing

Stapled or unstapled, hole punch

Receive print mode - Manual (size, margin, stock, header) / Auto

Auto answer delay Secure receive Junk fax prevention

Fax Reports

Activity
Dial directory
Group directory
Options
Pending Jobs

Fax Mailboxes

Up to 200 password-protected

Poll Remote mailboxes (up to 255) password-protected

Auto Dialing Features

Speed Dials:

- 200 (One-line option)
- 1,000 (Two-line option)

Group Dials:

- Up to 100 groups with up to 200 recipients per group (One-line option)
- Up to 200 groups with up to 400 recipients per group (Two-line option)

Auto Redial:

- Up to 14 attempts
- · Up to 25 min intervals
- Batch Send (up to memory capacity)

_	•				
Fax	w	naci	tica	tın	ne

FAX OPTIONS - Walk Up Option (one or two lines options) (Continued)

Resolutions Send:

200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 600 x 600 dpi (Superfine)

Receive:

200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi (Superfine) 400 x 400 dpi (Superfine) 600 x 600 dpi (Superfine)

LAN Fax Send fax directly from print drivers

FAX OPTIONS - Internet Fax

Capability Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP)

Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail

clients

Maximum Scan Area A3/ 297 x 420 mm

Authentication Optional secure device login with network user name and password

Supports: Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003)

Novell over IP / IPX (Netware 4.x / 5.x / 6.x)

Optional PIN-based guest login

Address Directory Access Corporate address list via LDAPv3

Downloaded address list (comma-separated file format)

Internal LDAP or Public address book

File Formats TIFF-FX profiles S, F with G3 MH or JPEG compression

PDF (image only) with G3 MH, G4 MMR or JPEG compression

PDF and Multi TIFF

Resolutions 600 x 600 dpi

 $400 \times 400 \text{ dpi}$

300 x 300 dpi

200 x 200 dpi

200 x 100 dpi

100 x 100 dpi

72 x 72 dpi

Network Protocols SMTP

POP3 (RFC 1939)

•••••	Fax Specifications		
FAX OPTIONS - Internet	Fax (Continued)		
Compliance	ITU-T T.37 complaint 508 Compliant		
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation: • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body		
FAX OPTIONS - Network	Fax Server Enablement		
Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration.		
Maximum Scan Size	A3/ 297 x 420mm		
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP / IPX (Netware 4.x / 5.x / 6.x) Optional PIN-based guest login		
Network Protocols	Novell (NCP via IPX / SPX) or IP FTP Microsoft SMB via TCP / IP HTTP / HTTPS SMTP		
Fax Send Features	One- or two-sided scanning (up to A3/ 297 x 420 mm) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, five levels of contrast, five levels of sharpness)		
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)		
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Program. For details visit www.xerox.com		

	Fax Specifications			
ACCOUNTING OPTIONS - Internal Auditron				
Tracking	Copy usage			
Accounting	Up to 2,150 User accounts Up to 5,925 General accounts Up to 256 Group accounts			
Features	Auditron report printout, ability to upload/download account and usage data via direct connection using Microsoft Windows based software			
ACCOUNTING OPTI	ONS - Xerox Standard Accounting			
Tracking	Copy, Print, Fax and Scan usage to secure print			
Accounting	Up to 2,500 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)			
<i>Features</i>	Enable/disable via the Web UI or the device GUI in tools, admin can manage the feature remotely via the Web UI, Data can be exported via a CSV file, supports entering XSA ID into the print driver when submitting a print job.			

ACCOUNTING OPTIONS - Job Based Accounting - 3rd-Party enablement

Enhanced network accounting with up to the minute data on how the WorkCentre system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Alliance Partner solutions. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support WorkCentre requests account authentication from 3rd-party server enabling larger databases of users and accounts

Machine Specifications

MONTHLY DUTY CYCLE

WorkCentre 7655: up to 200,000 pages/month WorkCentre 7665: 300,000 pages/month WorkCentre 7675: 300,000 pages/month

Average Monthly Print

Volume*

15,000 to 50,000 pages per month

ELECTRICAL REQUIREMENTS

Voltage: 220-240 VAC +/- 10% (198-264 VAC) Frequency: 50/60 Hz +/- 3%, 10 A (220/240 V)

Power Consumption: 1.145 KVA maximum printing continuously

	Machine Specifications				
POWER CONSUMPTION					
Running	< 1104 watts/hour				
Standby	< 285 watts/hour	< 285 watts/hour			
Low Power Mode	< 218 watts/hour (De	< 218 watts/hour (Default time to Low Power = 15 minutes)			
Auto Off / Sleep mode	< 23.7 watts/hour (D	< 23.7 watts/hour (Default time to Sleep mode = 45 minutes)			
Warm-up Ready to Copy	< 28 seconds (Recov	< 28 seconds (Recovery from Sleep)			
Warm-up Ready to Print	< 130 seconds (Reco	< 130 seconds (Recovery from Sleep)			
Low Power Recovery	< 20 seconds				
ENVIRONMENTAL CONSIDERATIONS					
Required Temperature Range	10° to 28° C				
Required Relative Humidity	10% to 85%				
DIMENSIONS AND WEIGHT	width	depth	height	weight	
Configuration with SCT or OCT	1,574 mm	921 mm	1,460 mm	277.7 kg	
With Advanced Office Finisher	2,096 mm	921 mm	1,460 mm	351.7 kg	
With Professional Finisher (with Booklet Maker)	2,096 mm	921 mm	1,460 mm	379.4 kg	
With Light Production Finisher	2,286 mm	921 mm	1,460 mm	398.2 kg	
With Light Production Finisher with Folder	2,489 mm	921 mm	1,460 mm	455.9 kg	
CERTIFICATIONS					
	FCC Class A Compliant (US), DOC Class A Compliant (Canada) 89/336/EEC (Europe) UL Listed (UL 1950, Third Edition) CB Certified (IEC 60950/EN 60950) 73/23/EEC (Europe) 95/5/EEC (Europe) Energy Star				

Device Specifications

XEROX EXTENSIBLE INTERFACE PLATFORM (EIP)

Xerox Extensible Interface Platform (EIP) is an embedded software platform built with state of the art web technologies. This platform provides the means for software developers to quickly build solutions that are more intuitive and user-friendly for the office workers. Chief among the capabilities provided by EIP is the development of tailored applications with customised user interfaces, and card-based authentication solutions supporting a personalised user experience.

SUPPLIES	Description	Order Number
Toner Cartridges	Black	006R01223
	Cyan	006R01226
	Magenta	006R01225
	Yellow	006R01224
Waste Toner Bottle	Supplied with each toner cartridge box	008R12990
Staple Cartridge	For Office Finisher / Advanced Office Finisher	008R12964
Staple Cartridge	For Light Production Finisher	008R13029
Staple Cartridge	For Booklet maker saddle-stitch stapling	008R12925
Staple Cartridge	For Convenience Stapler	008R12964 008R12941
SMART KITS	Description	Order Number
Fuser Module	Includes ozone filter	008R12989













