

# WorkCentre® 7120/7125

## Color Multifunction Printer



**WorkCentre 7120/7125**  
shown with two trays and Stand



**WorkCentre 7120/7125**  
shown with four trays, Office Finisher LX with Booklet Maker, Work Surface and Convenience Stapler

	WorkCentre 7120/7125	WorkCentre 7125
<b>Output Speed – Printing and Copying</b>		
<b>Black and white</b>	Up to 20 ppm (pages per minute) 8.5 x 11 in. (A4/210 x 297 mm) LEF  Up to 13 ppm 8.5 x 14 in. (216 x 356 mm)  Up to 11 ppm 11 x 17 in. (A3/297 x 420 mm)	Up to 25 ppm (pages per minute) 8.5 x 11 in. (A4/210 x 297 mm) LEF  Up to 16 ppm 8.5 x 14 in. (216 x 356 mm)  Up to 14 ppm 11 x 17 in. (A3/297 x 420 mm)
<b>Color</b>	Up to 20 ppm 8.5 x 11 in. (A4/210 x 297 mm)  Up to 13 ppm 8.5 x 14 in. (216 x 356 mm)  Up to 11 ppm 11 x 17 in. (A3/297 x 420 mm)	Up to 25 ppm 8.5 x 11 in. (A4/210 x 297 mm)  Up to 16 ppm 8.5 x 14 in. (216 x 356 mm)  Up to 14 ppm 11 x 17 in. (A3/297 x 420 mm)
<b>First-Page-Out Time</b>		
<b>Copy – Black and white</b>	As fast as 6.5 seconds	
<b>Copy – Color</b>	As fast as 8.1 seconds	
<b>Paper Handling</b>		
<b>Paper Handling – Duplex Automatic Document Feeder</b>		
<b>Capacity</b>	110 sheets (based on 20 lb Bond/75 gsm paper)	
<b>Speed</b>	55 images per minute Color / Black and white (Letter/A4 long edge feed (LEF))	

<b>Sizes</b>	5.5 x 8.5 in. (A5) to 11 x 17 in. (A3) SEF Custom sizes: 3.3 x 4.9 in. (85 x 125 mm) to 11.7 x 17 in. (297 x 432 mm)
<b>Weights</b>	13 to 32 lb Bond / 38 to 128 gsm
<b>Paper Handling – Bypass Tray</b>	
<b>Capacity*</b>	50 sheets
<b>Sizes</b>	Custom sizes: 3.5 x 3.9 in. (89 x 98 mm) to 11.7 x 17 in. (297 x 432 mm)
<b>Weights</b>	16 lb Bond to 80 lb Cover / 60 to 216 gsm
<b>Types</b>	Same as front-loading trays plus envelopes, postcards, glossy media and labels
<b>Paper Handling – Trays 1 &amp; 2 (with Stand) or Trays 1 - 4</b>	
<b>Capacity*</b>	520 sheets each
<b>Sizes</b>	User adjustable from 5.5 x 8.5 in. (A5) to 11 x 17 in. (A3), Custom sizes: 5.5 x 7.2 in. (140 x 182 mm) to 11.7 x 17 in. (297 x 432 mm)
<b>Weights</b>	16 lb Bond to 140 lb Index / 60 to 256 gsm
<b>Types</b>	Plain Paper Recycled Bond Custom Type 1 through 5 Heavyweight Extra Heavyweight Punched Letterhead Pre-printed
<b>Total Capacity</b>	2 Trays with Stand: 1,090 sheets 4 Trays: 2,130 sheets
<b>Envelope Tray (Optional – replaces Tray 1)</b>	
<b>Capacity*</b>	Up to 60 envelopes
<b>Sizes</b>	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, Custom sizes: 3.9 x 5.8 in. (98 x 148 mm) to 6.4 x 9.5 in. (162 x 241 mm)
<b>Weights</b>	20 lb Bond to 24 lb Bond / 75 to 90 gsm
<b>Output – Standard</b>	
<b>Stacking Trays*</b>	Dual Catch Tray – up to 250 sheets each, lower tray offsets
<b>Sizes</b>	3.5 x 3.9 in. (89 x 98 mm) to 11 x 17 in. (A3/297 x 420 mm)
<b>Weights</b>	16 lb Bond to 140 lb Index / 60 to 256 gsm
<b>Output – Integrated Office Finisher Option</b>	
<b>Stacking Tray</b>	500 sheets of 20 lb Bond (75 gsm) 8.5 x 11 in./A4 or 250 sheets of 20 lb Bond (75 gsm) 11 x 17 in./A3
<b>Sizes</b>	3.5 x 3.9 in. (89 x 98 mm) to 11 x 17 in. (A3/297 x 420 mm)
<b>Weights</b>	16 lb Bond to 80 lb Cover / 60 to 220 gsm
<b>Stapling</b>	Single Auto stapling: 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or two sheets of 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or two sheets of 220 gsm covers)

\* Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Output – Office Finisher LX Option	
Stacking Tray	2,000 sheets unstapled or 1,000 sheets single staple or 750 sheets dual staple (24 lb Bond / 90 gsm Letter/A4)
Sizes	7.2 x 8.3 in. (182 x 210 mm) to 11 x 17 in. / A3
Weights	16 lb Bond to 80 lb Cover / 60 to 220 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum less than 90 gsm) Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Output – Optional Hole Punch for Office Finisher LX	
North America	3-hole punch 2-hole Legal punch
Europe	2-hole punch 4-hole punch
Output – Optional Booklet Maker (Score/Crease, Saddle-stitch Staple) for Office Finisher LX	
Capacity	40 booklets (1-15 sheets per booklet – 80 gsm or less; 2-10 sheets per booklet – over 80 gsm)
Sizes	Letter – 8.5 x 11 in. (A4/210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3/297 x 420 mm)
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 16 lb Bond to 24 lb Bond / 55 to 90 gsm
Score/Crease	1-15 sheets / unstapled
Copy Specifications	
Document Scanner	Duplex Automatic Document Feeder with 110-sheet capacity (based on 20 lb / 75 gsm paper)
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scan, print, fax
Digital Imaging	Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Color balance, color shift and saturation
Reduction/Enlargement	Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable percentages

<b>Special Features</b>	<p>Auto paper select          Auto reduction/enlargement to fit selected paper size          Auto tray switching          Automatic job recovery          Auto color selection          Area Designation          Poster mode          Watermark          Annotation          Single/Dual color          Booklet creation          Multi-up – 2, 4 or 8 up          Repeat Image          Negative image          Mirror image          Covers insertion (front only, front and back, back only, blank or printed)          Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder)          Job interrupt          Book copying          Sample job          Mixed-size originals          Hole Punch (requires Office Finisher LX)          Saddle-stitch booklets (requires Office Finisher LX)          Single position stapling (requires Integrated Office Finisher or Office Finisher LX)          Multi-position stapling (requires Office Finisher LX)          ID Card Copy</p>
<b>Foreign Device Interface</b>	<p>Interface to third-party access control devices, coin machines and card readers          Supports a variety of vending stations available through the Xerox Custom Application Service</p>
<b>Print Specifications</b>	
<b>First-Page-Out Time</b>	
<b>Print – Black and white</b>	As fast as 11 seconds
<b>Print – Color</b>	As fast as 13 seconds
<b>System</b>	
<b>Memory</b>	2 GB
<b>System Disk</b>	Minimum 80 GB
<b>Network Printing – Network Controller</b>	
<b>Processor</b>	667 MHz
<b>Printer Languages</b>	<p>Adobe® Postscript® 3™ (optional)          TIFF          PS-PDF: v1.6          PCL® 6          XPS®          HP-GL2 via direct submission</p>
<b>Network Printing – Resolution</b>	
	Print Engine: 600 x 600 x 4 dpi

Network Printing – Printing Features	
<b>Features</b>	Secure Print Delay Print (specific time) Sample Set Booklet creation Cover selection Inserts and exception pages Store File in Folder Paper selection by attribute N-up Saddle-stitch booklet making (requires Office Finisher LX) Hole Punch (requires Office Finisher LX) Watermark Fit to new paper size Banner Sheet enable/disable Output tray selection Image Quality Draft Mode Reduce/enlarge Mirror image Margins Bi-directional status Two sided printing Scaling LAN Fax (requires optional Fax Kit)
<b>Connectivity</b>	Ethernet 10/100BaseTX High speed USB 2.0 printer port Wireless Ethernet (IEEE 802.11b) via third-party adapters
<b>Operating Systems</b>	Microsoft® Windows® XP SP3 and above (32- and 64-bit), Windows Server 2003 (32- and 64-bit), Windows Vista (32- and 64-bit), Windows Server 2008 (32- and 64-bit), Windows 7 (32- and 64-bit) Mac OS® 10.4 and above AIX 5 v5.3 HP UX 11.0, 11i v2 Solaris 8, 9, 10 Linux® FedoraCore 1, 5 RedHat Enterprise Linux 4 SUSE 10/11
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6 Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI (All protocols not in use can be disabled)
<b>Administrative Protocols</b>	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL
<b>Fonts</b>	Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 82 scalable fonts, line printer bitmap font

Printer Drivers	Environment	PCL 6	PostScript
<b>Print Drivers</b>	Windows 2003/XP SP3 and above (32- and 64-bit) Windows Vista 32- and 64-bit Windows Server 2008 (32- and 64-bit) Windows 7 (32- and 64-bit) (Microsoft certified)	Bidirectional with user-selectable interface (standard** and enhanced*)	Bi-directional with user-selectable interface (standard** and enhanced*)
	Macintosh® OS 10.4	N/A	Generic PPD file
	Macintosh® OS 10.5 and above	N/A	Bi-directional with user-selectable interface
	UNIX	N/A	Bi-directional with Xerox Custom Graphical User Interface
<b>Xerox Mobile Express Driver® (X-MED)</b>	<p>Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p> <ul style="list-style-type: none"> <li>• Printers are automatically discovered</li> <li>• Printer list can be managed based on location</li> <li>• Gives Bi-directional feedback device status, supplies, queue management</li> </ul>		
<b>Xerox Global Print Driver® (X-GPD)</b>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> <ul style="list-style-type: none"> <li>• Printers are automatically discovered</li> <li>• Printer list can be managed based on location</li> <li>• Gives Bi-directional feedback device status, supplies, queue management</li> </ul>		
<b>Print Submission Tools</b>	<ul style="list-style-type: none"> <li>• Command prompt LPR/UNIX tool for print submission</li> <li>• Contents Bridge tool supports TIFF/PDF/XPS and Office 2007 direct print</li> </ul>		
<b>Device Management</b>			
<b>Management Support</b>	SNMP Version 1, SNMP Version 2c and Version 3 trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2		
<b>Xerox CentreWare® Web</b>	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		
<b>IP Filter</b>	Allows administrator to control print access to device via IP address. Restricts access to device to/from network.		
<b>Xerox CentreWare® for Unicenter TNG®</b>	<ul style="list-style-type: none"> <li>• Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View</li> <li>• Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk</li> </ul>		
<b>Xerox CentreWare® for Microsoft System Center Operations Manager (SCOM)</b>	<ul style="list-style-type: none"> <li>• Provides the identification of Xerox printers on the network and populates the SCOM database</li> <li>• Automatically changes the status and color in the printer icon to reflect the printer status in each view. Events and alerts are also available in the Operator console</li> <li>• Easily access embedded web server through the icon displayed in the Xerox agent</li> <li>• Manage Xerox devices on network by displaying all discovered printers in a folder in any available Operator console view</li> <li>• Provides full use of Management Packs, Administrator and Operator console to ease management process</li> <li>• Using SNMP trap-capable Xerox devices enables unsolicited device feedback for device events (for example, machine out of toner)</li> </ul>		

\* Enhanced: Xerox custom graphical user interface

\*\* Standard: Driver based on Microsoft tree structure user interface (includes Xerox features and functionality)

<b>Xerox CentreWare® for Microsoft Management Console (MMC)</b>	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.
<b>Xerox CentreWare® for HP® OpenView®</b>	<ul style="list-style-type: none"> <li>• Provides for the identification of Xerox WorkCentre multifunction printers in the general discovery performed by HP OpenView</li> <li>• Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via color-coded icons</li> <li>• Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView</li> </ul>
<b>Xerox Device Manager</b>	<p>Xerox Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox Device Manager provides:</p> <ul style="list-style-type: none"> <li>• Device monitoring and troubleshooting</li> <li>• Extensive reporting and discovery of new devices</li> <li>• Usage collection, chargeback, and billing capabilities</li> </ul>
<b>Xerox Device Types for SAP R/3 Environment</b> <i>Information available at <a href="http://www.xeroxofficesap.com">www.xeroxofficesap.com</a></i>	<p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> <li>• Simplex or duplex printing</li> <li>• Finishing – single or dual stapling</li> <li>• Tray pull location from any tray</li> <li>• Print security via PIN ID capability at the WorkCentre</li> </ul>
<b>Xerox SAP R/3 Intelligent Barcode Utility (Optional)</b> <i>Information available at <a href="http://www.xeroxofficesap.com">www.xeroxofficesap.com</a></i>	<p>Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded the network controller</p> <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>
<b>Xerox Barcode Pro PS</b> <i>Information available at <a href="http://www.xeroxofficesap.com">www.xeroxofficesap.com</a></i>	<p>Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.</p>
<b>Smart eSolutions®</b>	
<b>MeterAssistant®</b>	<p>Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.</p> <p>Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.</p>
<b>SuppliesAssistant®</b>	<p>Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.</p> <p>Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.</p>
<b>CentreWare® Internet Services – Integrated Device Web Page</b>	
<b>Device Status</b>	<p>Web server embedded on device controller</p> <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>
<b>Print Queue Viewing</b>	Complete job print queue management – promote and delete
<b>Job Submission</b>	<p>Print-ready files (PS, PCL, TIFF, PDF, XPS)</p> <p>Output feature selection</p>
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device

<b>Browsers</b>	Netscape Navigator®, Mozilla Firefox® Microsoft® Internet Explorer Apple® Safari™
<b>Fax Specifications</b>	
<b>Server Fax Enablement (Optional)</b>	
<b>Fax Send Features</b>	One-sided, two-sided, or two-sided rotate side 2 Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo, text, or photo and text)
<b>Fax Print Features</b>	One- or two-sided printing Quantity Staple on/off Collate on/off Finisher output tray selection Secure print on/off
<b>Fax Vendors</b>	Multiple vendors, certified by the Xerox Alliance Partner Program For details, visit <a href="http://www.xerox.com">www.xerox.com</a>
<b>PSTN Fax (Optional) – One or Three Line Fax Option</b>	
	ITY (CCITT) group 3 quality/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi
<b>Speed/Modem(s)</b>	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
<b>Speed/Compression</b>	MH/G3, MMR/G4, JBig Super G3
<b>Fax Send Features</b>	LAN Fax - Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan Up to 50 group dials with up to 20 recipients per group
<b>Fax Receive Features</b>	One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention Thumbnail Preview
<b>Fax Forward</b>	Faxes can be received into a folder on the device hard drive. Images that are in the folder can be routed to a combination of Email addresses, FTP or SMB sites or locations or Fax destinations
<b>Fax Reports</b>	Activity report Address Book Transmission confirmation Pending fax Folder List
<b>Fax Receive Mailboxes</b>	Up to 200 password-protected folders
<b>Auto Dialing</b>	Auto redial, Batch send



Internet Fax (Optional) – Standard with One or Three Line Fax Option	
<b>Capability</b>	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents in black and white sent via email from remote Internet Fax machines or email clients
<b>Maximum Scan Area</b>	11 x 17 in./A3
<b>Address Directory Access</b>	Downloaded address list (comma-separated value file format)
<b>File Formats</b>	TIFF-FX Profiles S with G3 MH, F with G4 MMR, or J with JBIG
<b>Resolutions</b>	600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (monochrome)
<b>Network Protocols</b>	SMTP POP3
<b>Compliance</b>	ITU-T T.37 compliant
Fax over IP (Optional)	
	T.38 compliant IP fax/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi
<b>Fax Send Features</b>	LAN Fax - Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan
<b>Fax Receive Features</b>	One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention Thumbnail Preview
<b>Fax Forward</b>	Faxes can be received into a folder on the device hard drive. Images that are in the folder can be routed to a combination of Email addresses, FTP or SMB sites or locations, or Fax destinations
<b>Fax Reports</b>	Activity report Address Book Transmission confirmation Pending fax Folder List
<b>Fax Receive Mailboxes</b>	Up to 200 password-protected folders
<b>Auto Dialing</b>	Auto redial, Batch send
Scan Specifications	
Scan to Email (Standard)	
<b>Capability</b>	Color scanning, Auto Color, Grayscale, Black and White Direct document email from device Manual or directory Exchange/Notes/LDAP address searching Signing and encryption Email over SSL Preview scan job

<b>Input Speed</b>	Scan at 55 ipm Color / Black and white (216 x 279 mm/A4 long edge feed)
<b>Resolution</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
<b>Network Protocol</b>	SMTP, S/MIME, POP3
<b>File Formats</b>	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF, PDF/A with MRC, JPEG, G3 MH, G4 MMR, MRC, JBIG 2 Huffman, JBIG Arithmetic Compression JPEG XPS Searchable PDF, PDF/A, XPS Password Protected PDF Encrypted PDF Linearized PDF
<b>Authentication</b>	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)
<b>Directory Access</b>	Corporate address list via LDAP Downloaded address list (comma-separated file format)
<b>Scan to Folder (Standard)</b>	
<b>Capability</b>	Color, Auto Color, Black and White
<b>Features</b>	Images can be scanned, printed and faxed directly to the device hard drive and stored in a folder. Scan or fax images that are stored in the folder can then be printed, emailed, sent via fax, sent via IFax, routed to a PC, an FTP or SMB site via Job Flow Sheets. Thumbnail Preview
<b>Network Scanning (Standard)</b>	
<b>Capability</b>	Color Scanning, Grayscale, Black and White, Auto Color
<b>Concurrency</b>	Scan while printing or while it is transferring scan to network or fax jobs
<b>Input Speed</b>	Scan at 55 ipm Color / Black and white (216 x 279 mm/A4 long edge feed)
<b>Resolution</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
<b>Maximum Scan Area</b>	11.7 x 17 in./297 x 432 mm
<b>Network Protocol</b>	FTP via TCP/IP Microsoft SMB via TCP/IP Netware, HTTP and HTTPS
<b>File Formats</b>	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF, PDF/A with MRC, JPEG, G3 MH, G4 MMR, MRC, JBIG 2 Huffman, JBIG Arithmetic Compression JPEG XPS Searchable PDF, PDF/A, XPS Password Protected PDF Encrypted PDF Linearized PDF

<b>Document Management Fields</b>	One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard
<b>Scan Features</b>	Mixed size originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job
<b>Supported Scan Destinations (Varies by scanning software options purchased.)</b>	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop® (Professional and SE editions) SMARTsend® ScanFlowStore® Scan to Windows XP client SMB or FTP Scan to Folder Scan to Home Scan to USB
<b>Scan to PC Desktop SE (Optional)</b>	<ul style="list-style-type: none"> <li>• A desktop and server-based offering that provides document imaging, archiving, editing and organization tools</li> <li>• Nuance PaperPort – image viewing and file management software</li> <li>• Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.</li> </ul>
<b>Scan to PC Desktop Pro (Optional)</b>	<ul style="list-style-type: none"> <li>• A desktop and server-based offering that provides document imaging, archiving, editing and organization tools</li> <li>• The PaperPort Personal Scanning Platform empowers office workers with the ability to customize, directly from the desktop, the scanning menus available to them on Xerox EIP enabled MFP devices.</li> <li>• Nuance PaperPort Pro – image viewing and file management software</li> <li>• Nuance OmniPage Pro (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox or through email WorkCentre to individual desktops. Also includes an Email inbox polling capability.</li> </ul>
<b>Common Access Card Enablement (optional)</b>	Common Access Card Enablement is a solution that increases security of government facilities and critical information through the use of smart identification cards. (Available only in U.S.)
<b>Thumbnail Preview (Standard)</b>	
	Images that are stored in the folder on the device hard drive can be viewed at the User Interface.

Device Specifications	
<b>Security</b>	
<b>Capability</b>	Secure Print, NDS Authentication over IP, LDAP/Kerberos/SMB, Password Protected PDF and Encrypted Scan to Email. Secure Web Page via SSL. FIPS 140-2 IPsec Audit Log SSL/TLS IP filtering 802.1X SMIME Watermark Annotation PDF/XPS signatures Digital certificate management OCSP/CRL Email over SSL Image Overwrite Encrypted Disk
<b>Secure Access and Authentication</b>	Optional secure device login with network user name and password Remote Authentication: Kerberos (Windows Server 2003, Windows Server 2008, Windows 7, UNIX), SMB (Windows Server 2003, Windows Server 2008, Windows Vista, Windows 7) Local Authentication LDAP
<b>Accounting</b>	
<b>Auditron (Local Accounting)</b>	Controls and tracks black and color copy, print, fax and scan usage
<b>Accounting with Third-Party Server Applications (optional)</b>	Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax
<b>Accounting Control</b>	Xerox Standard Accounting Job based accounting Third-party integration through Network Accounting Enablement Kit Supports Foreign Device Interface Active directory user profile – Controls color copy and print usage and feature/pathway control Xerox Page Accountant Print Audit 5
<b>Accounting – Xerox Standard Accounting</b>	
<b>Tracking</b>	Copy, Print, Fax and Scan usage
<b>Accounting</b>	Up to 2,500 User accounts (User ID); Up to 500 Group accounts (Department)
<b>Features</b>	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.
<b>Monthly Duty Cycle</b>	
	WorkCentre 7120: 50,000 pages / month WorkCentre 7125: 60,000 pages / month
<b>Basic Configurations</b>	
	Network Multifunction System with network controller – Copy, Print and Network Scan capability standard WorkCentre 7120/7125: 2 Tray with Stand Configuration WorkCentre 7120T/7125T: 4 Tray Configuration

Accessories				
	One-line PSTN fax with Internet Fax Three-line PSTN fax with Internet Fax Fax over IP (T.38) Server Fax Enablement Scan to PC Desktop® (Professional or SE edition) Media Print (Print from a media card) Scan to / Print from USB Integrated Office Finisher Office Finisher LX Booklet Maker (requires Office Finisher LX) Foreign Device Interface Convenience Stapler			
Electrical Requirements				
	220–240 V Nominal, 50/60 Hz, 10A 110-127 VAC, 50/60 Hz, 15A			
Power Consumption				
	WorkCentre 7120		WorkCentre 7125	
Running (avg)	220V: 578 watts; 120V: 613 watts		220V: 578 watts; 120V: 613 watts	
Standby	119 watts		119 watts	
Low-Power Mode	74 watts		78 watts	
Sleep Mode	3.08 watts		3.2 watts	
Warm Up	40 seconds (maximum)			
Low-Power Recovery	29 seconds (maximum)			
Required Temperature Range	50° to 90° F (10° to 32° C)			
Required Relative Humidity	15 % to 85 %			
	WorkCentre 7120		WorkCentre 7125	
Noise Emission	16 dB(A) standby 52 dB(A) running		16 dB(A) standby 52 dB(A) running	
Heat Emission	1734 BTU/Hr running 357 BTU/Hr standby		220V: 1957 BTU/Hr running 110V: 2090 BTU/Hr running 389 BTU/Hr standby	
Dimensions and Weights	Width	Depth	Height	Weight
Base Unit	23 in. / 585 mm	25.2 in. / 640 mm	44.6 in. / 1132 mm	251 lbs / 114 kg
Xerox Extensible Interface Platform® (EIP)				
	Xerox EIP is a software platform inside the WorkCentre 7120/7125 that enables personalized solutions you can access right from the device touch screen. These applications can leverage your existing databases and meet your specific business challenges.			

Certifications			
	FCC Class B Compliant (U.S./Canada) ENERGY STAR® 89/336/EEC (Europe) TUV Listed CB Certified (IEC 60950-1/EN 60950-1) 73/23/EEC (Europe) Windows Hardware Quality Labs Blue Angel (Europe) EcoLogo Certified Common Criteria (ISO 15408) Certification (pending)		
Supplies	Description	Order Number	
Toner Cartridges	Black Toner Cartridge - Metered	006R01453	
	Yellow Toner Cartridge - Metered	006R01454	
	Magenta Toner Cartridge - Metered	006R01455	
	Cyan Toner Cartridge - Metered	006R01456	
	Black Toner Cartridge - Sold	006R01457	
	Yellow Toner Cartridge - Sold	006R01458	
	Magenta Toner Cartridge - Sold	006R01459	
	Cyan Toner Cartridge - Sold	006R01460	
Staple Refills	Integrated Office Finisher	008R12941	
	Office Finisher LX	008R12941	
Staple Cartridges	Integrated Office Finisher	008R12964	
	Office Finisher LX	008R12964	
	Booklet Maker for Office Finisher LX	008R12897	
Smart Kits	Description	Order Number	
	Smart Kit® Drum Cartridge	Black Yellow Magenta Cyan	013R00657 013R00658 013R00659 013R00660
	Waste Toner Container		008R13089
	Smart Kit Fuser Module (220 V)		008R13088
	Smart Kit Fuser Module (110 V)		008R13087
	Second Bias Transfer Roll		008R13086
	Transfer Belt		001R00610

