

Xerox[®] WorkCentre[™] 7755/7765/7775 Multifunction System



WorkCentre 7755 shown with Advanced Finisher and Convenience Stapler options



WorkCentre 7765 shown with Professional Finisher and Convenience Stapler options



WorkCentre 7775 shown with High Capacity Feeder and Light Production Finisher

			J	
	Xerox WorkCentre 7755	Xerox WorkCentre 7765	Xerox WorkCentre 7775	
Output Speed – Printing a	Output Speed – Printing and Copying			
Colour	Up to 40 ipm A4/210 x 297 mm	Up to 50 ipm A4/210 x 297 mm	Up to 50 ipm A4/210 x 297 mm	
Black and white	Up to 55 ipm (images per minute) A4/210 x 297 mm	Up to 65 ipm A4/210 x 297 mm	Up to 75 ipm A4/210 x 297 mm	
First-Copy-Out Time – A4,	from Platen to Centre Tray			
Colour	As fast as 5.5 seconds	As fast as 5.5 seconds	As fast as 5.5 seconds	
Black and white	As fast as 8.9 seconds	As fast as 8.9 seconds	As fast as 8.9 seconds	
Copy Specifications				
Copying				
Document Scanner	Duplex Automatic Document Feede	r (DADF) 250-sheet capacity ¹		
Sides (input:output)	1-1, 1-2, 2-2, 2-1			
Quantity	1 to 9,999			
Resolution (max)	Scan at 600 x 600 dpi, output at 24	00 x 2400 dpi		
Concurrency	Unlimited programme-ahead consis	tent with configuration (Copy, Print, F	ax and Scan)	
Copy Pre-collation Memory (EPC)	1 GB DRAM, 80 GB Disk minimum			
Basic Copy Features & Options	Collation Automatic 2-sided/Duplex Auto Reduction & Enlargement to fi Hole Punching Booklet Creation Stapling Large Job Interrupt Copy on Tabs support Auto Paper Select Authentication for Services (i.e. Colo Auto Tray Switching			

Imaging Copy Features	 Image Quality: Original Type Selection: Photo & Text, Photo, Text, Newspaper/Magazine, Inkjet Original, Maps. Image Options: Lighten/Darken, Sharpness, Saturation. Image Enhancement: Auto Background Suppression, Auto and Manual Contrast. Colour Effects: Off, Single Colour, Lively, Bright, Warm, Cool. Colour Balance: Normal, Basic Colour, Advanced Colour. Colour Shift: Superior Copy Image Quality Book Copying/Bound Copying Edge Erase Single Colour Repeat Image Mixed Size Original Image Shift (with Auto Center option) Image Shift Preset: Support for 3 Preset Options Annotation and Bates[™] stamping (with colour capability)
Output Copy Features	Transparencies (blank or printed) Dividers (blank) Booklet Creation Multi-up (up to 15 columns by 15 rows) Invert Image (negative or mirror image) Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Build Job: (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Inserts and Tab copying Sample Set and Job Storage (Store and recall job programming) Heavyweight paper (not rough stock)
Features	Features Help (Intuitive text and graphic descriptions) Xerox Standard Accounting (Copy, Print, Scan, Fax) Languages: (Select up to 20 languages for user interface – International English, International French, Italian, German, International Spanish, Dutch, Portuguese, Brazilian (Brazilian Portuguese), Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)
Security	Enable Secure Workflows Audit Log: Provide export capability of log, includes Username of log on attempts Graphical User Interface (GUI) job queue Confidentiality: Require a PIN to delete a Secure print job Image Security Overwrite Auto On-demand Image Overwrite Encryption of user jobs stored on hard disk
Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments Size user-programmable percentages (100%, Auto%, 25%, 50%, 64%, 70%, 78%, 94%, 141%, 180%, 200%, 400%)
Foreign Device Interface (FDI) (Optional)	Interface to third party access control devices, coin machines, card readers Validates Metadata Accept Authentication Login at GUI and pass to 3rd party Networking Account Interface with 3rd party accounting terminal for accounting UI MIB Compliance – supports the Finishing MIB Support a variety of vending stations available through the Xerox Custom Application Service
USB Port ²	PC Interface for upload/download of Xerox Copier Assistant For Software Upgrade
Accessibility Option	Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.

Paper Handling – Duplex Automatic Document Feeder		
Capacity ¹	250 sheets	
Speed	80 images per minute black and white, 50 ipm colour	
Paper Sizes Sensed	A5/148 x 210 mm to A3/297 x 420 mm SEF or A5/148 x 210 mm to A4/210 x 297 mm LEF	
Weights	64 gsm to 300 gsm	
Paper Handling – Four From	nt Loading Paper Trays - Paper Trays 1, 2, 3 and 4	
Capacity ¹	Trays 1 & 2: 500 sheets each tray Trays 3: 870 sheets Trays 4: 1,140 sheets	
Sizes	Trays 1 & 2: A5/148 x 210 mm LEF to A3/297 x 420 mm SEF Trays 3 & 4: A4/210 x 297 mm LEF	
Weights	64 to 220 gsm	
Types	Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Custom	
Paper Handling – Bypass Ti	ray	
Capacity ¹	250 sheets	
· -		
Sizes	Custom sizes up to SRA3	
	Custom sizes up to SRA3 64 to 300 gsm	
Sizes		
Sizes Weights	64 to 300 gsm Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Pre-cut Tabs Custom	
Sizes Weights Types	64 to 300 gsm Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Pre-cut Tabs Custom	
Sizes Weights Types Paper Handling – High Cap	64 to 300 gsm Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Pre-cut Tabs Custom acity Feeder (HCF)	
Sizes Weights Types Paper Handling – High Cap Capacity ¹	64 to 300 gsm Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Pre-cut Tabs Custom acity Feeder (HCF) 2000 sheets	
Sizes Weights Types Paper Handling – High Cap Capacity ¹ Sizes	64 to 300 gsm Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Pre-cut Tabs Custom acity Feeder (HCF) 2000 sheets A4/210 x 297 mm LEF 64 to 220 gsm	
Sizes Weights Types Paper Handling – High Cap Capacity ¹ Sizes Weights	64 to 300 gsm Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Pre-cut Tabs Custom acity Feeder (HCF) 2000 sheets A4/210 x 297 mm LEF 64 to 220 gsm	
Sizes Weights Types Paper Handling – High Cap Capacity ¹ Sizes Weights Paper Handling – Total Cap	64 to 300 gsm Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Pre-cut Tabs Custom acity Feeder (HCF) 2000 sheets A4/210 x 297 mm LEF 64 to 220 gsm acity S,260 sheets	

Output Option – Professional Finisher (with Booklet Maker)		
Capacity ¹	Top Tray: 500 sheets Stacker Tray: 1,500 sheets A4/210 x 297 mm	
Sizes	101.6 x 152.4 mm SEF to 330 x 450 mm SEF	
Weights	64 to 300 gsm	
Stapling ¹	50 sheets of 90 gsm Single, dual, front, SEF and 4-stitch	
Hole Punch (Standard)	2-4 Hole Punch Swedish 4-Hole Punch (Optional)	
Booklet Maker	Bi-folded booklets (5 sheets maximum) Saddle-stitched and Centre folded booklets (15 sheet maximum)	
Output Option – Advanced	Office Finisher	
Capacity ¹	Top Tray: 500 sheets Stacker Tray: 3,000 sheets	
Sizes	A5/148 x 210 mm to 330 x 450 mm	
Weights	64 to 300 gsm	
Stapling ¹	50 sheets Single, dual, front, SEF and 4-stitch	
Hole Punch (Standard)	2-4-Hole Punch Swedish 4-hole Punch (Optional)	
Output Option – Light Proc	Output Option – Light Production Finisher	
Capacity ¹	Top Tray: 500 sheets Stacker Tray: 2,000 sheets 75 gsm, A4/210 x 297 mm	
Sizes	101.6 x 152.4 mm SEF to 330 x 450 mm SEF	
Weights	64 to 300 gsm	
Stapling ¹	Up to 100 sheets 75 gsm Single, dual, front, SEF and 4-stitch	
Hole Punch (Optional)	2-4 Hole Punch Swedish 4-Hole Punch (Optional)	
Booklet Maker Capacity¹	Bi-folded booklets (5 sheets maximum) Saddle-stitched and Center folded booklets (15 sheet maximum)	
Tri-folding (Optional)	Single Sheet C- and Z-folding on 60 to 90 gsm, A4 / A3-sizes Folding Tray: Up to 40 sheets	
Post Process Interposer	200 sheet capacity	
Output Option – Convenier	nce Stapler	
Capacity ¹	50-sheet stapling 5,000 staples Requires a separate outlet	

Network Printing – SMart	Controller (Simultaneous rip, receive, programme ahead, queue processing and transmit)		
Processor	1.33 GHz Freescale		
Memory	2 GB		
System Disk	80 GB minimum		
Print Languages (PDL)	PCL 6 / PCL 5e emulation Adobe PostScript TIFF (6.0 Old JPEG and New JPEG) TIFF Fax Extended (TIFF - FX) PDF LCDS, SCS, XES and IPDS through 3rd-party transforms		
Network Printing – Resolu	tion (printing via CentreWare® software)		
	PostScript: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey). Output resolution 2400 x 2400 dpi PCL: 600 x 600 dpi Supports PCL and PS switching within job		
Network Printing – Printin	g Features		
	Bi-directional Print Drivers provide device and job status Embedded Web server for remote control/monitor/setup Job monitoring at the device and at desktop Special font Banner Sheet Rotate Image Offset Support PCL and PS switching Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) Support for Print on Tabs / Page Segmentation Linearised PDF Save and restore print job settings		
Network Printing – Print D	Driver Options		
Pαper Output	Job Type • Secure, Sample, Delay Paper Selection by attribute (including transparency separators) Duplex (2-sided) Finishing • Multiple stapling positions • Hole punch • Booklet creation • Fit to new paper size • Saddle stitch with Professional finisher • Output tray selections • Store and recall driver setting		
Special Pages	Exception page programming (covers, inserts/tabs, exception pages)		
Image Options	Light/Dark Toner saver Resolution options (600 x 600 and 1200 x 1200 dpi) Reduction/Enlargement Margins Invert Image (negative/mirror)		
Layout/Watermark	N-up (16) / Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark option		

Print Protocols and Networks

Print Protocols and Netwo	rks		
Physical	1000BaseT (Gigabit Ethernet) Ethernet 10/100BaseT, 10BaseT, 10 Wireless Ethernet (IEEE802.11a/b/g) IPv4 and IPv6 support for printing 802.1x support		adaptor
Operating Systems	Microsoft Windows 2000, XP, Windows Server 2003, Windows Vista, Citrix, Novell NetWare 4.x, 5.x, 6 Mac OS 8.x, 9.x, OS X, 10.3 and higher Solaris 2.8, 2.9, 2.10 HPUX 11.0, 11iv2 AIX 5I v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise Linux 4		
Network Protocols	TCP/IP, LPR/LPD, Raw IP (Port 9100) AppleTalk/EtherTalk, Bonjour	, NetBIOS SMB, IPX/SPX, IPP, NDPS@	D/NEPS
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, DDNS,	SLP v2, HTTP, RARP, DHCP Autonet	
Security Protocols/ Features	Protocols: • HTTPS • IPsec Features: • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • Hide print job name and usernam • Hard drive encryption • Auto On-demand Image Overwrite • Xerox Secure Access option		
Fonts	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (TrueType fonts) PostScript 3: 136 PostScript standard fonts (TrueType fonts/send fonts as/substitution table) Font Management Utility for downloading additional fonts (available for Windows and Mac)		
Print Drivers	Environment	PCL XL/5C	PostScript 3
	Windows 2000/XP, Windows Server 2003, Windows Vista, Windows Walk-up (PS), Microsoft Certified (32 bit and 64 bit)	Bi-directional enhanced (Xerox custom graphical user interface)	Bi-directional enhanced (Xerox custom graphical user interface)
	Macintosh System 8.x - 10.2	N/A	Generic PPD Bi-directional via AppleTalk (9.x)
	Macintosh System 10.3 and higher	N/A	Bi-directional enhanced (Xerox custom graphical user interface)
Xerox Mobile Express Driver (X-MED)	Makes it easy for mobile users to fin Plug into a new network, and X-MED capability information. Save a list of for use on any printer in any networf • Printers are automatically discove • Printer list can be managed based • Gives Bi-directional feedback device	automatically discovers available pr "favourite" printers for each location k, and greatly reduce mobile support red l on location	inters and provides status and a, store application print settings calls to IT.
Xerox Global Print Driver (X-GPD)	A truly universal print driver that lets devices from a single driver. It provic of support calls, and simplifying prin • Printers are automatically discove • Printer list can be managed based • Gives Bi-directional feedback device	les a consistent, easy-to-use interface t services management. red l on location	e for end-users, reducing the number

Print Submission Tools	Environment	PCL	PostScript 3
	Solaris 2.8, 2.9, 2.10 HPUX 11.0 AIX 5I v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise Linux 4	Submission Tool only	Submission Tool with full feature set (Includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows 2000/XP, Windows Server 2003, Windows Vista	Submission Tool for any TIFF or PDF file	N/A
Device Management			
Software Installation and Upgrade	Network Controller Install Wizard Software Upgrade via Network		
Management Support	SNMP Version 1. SNMP Version 2c a MIB access (IETF-MIBII RFC 1213), MIB RFC 2790, Printer MIB RFC v.2		
E-Services	Automated Billing Meter Reads		
Xerox CentreWare® Internet Services	Allows simple remote installation se	tting of configuration options and ma	nagement of the device.
Xerox CentreWare® Web	 management from any workstation Works with any SNMP-managed p Provides help with device discover as well as basic accounting and a 	ry and installation, health checks and t	any other operating system: croubleshooting, and device upgrades,
Novell NDPS/NEPS	Server gateway application: centrali	sed management tool	
Xerox CentreWare® for Unicenter TNG®	Provides added identification to the WorkCentre under a Unicenter TNG	general discovery performed by Unice Business Process View	enter TNG and the ability to see the
Xerox CentreWare for Tivoli® NetView®	Provides for the identification of Xer by Tivoli NetView	rox WorkCentre multifunction systems	in the general discovery performed
Xerox CentreWare for HP° OpenView°	Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView		
Xerox Barcode Pro PS (optional) Information available at www.xerox officesapsolutions.com	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.		
Xerox Device Types for SAP R/3 Environment Information available at www.xeroxofficesap solutions.com	 Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): One- to two-sided printing Finishing provides single or dual stapling Tray pull location from any tray Number of copies – provide the ability to print multiple copies Paper Type and colour – provide ability to select different paper types and paper colours, such as transparency, red, etc. Print security via PIN ID capability Job Based Accounting (JBA) – Provides capability to enable/disable printer banner sheets Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net 		

Xerox SAP R/3 Intelligent Barcode Utility (optional) Information available at www.xerox officesapsolutions.com	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.		
CentreWare Internet Service	es – Integrated Web Pages Provided by the Device		
Device Status	Web server embedded in SMart Controller: • Tray status/contents • Consumables status • Alerts		
Job Submission	Print ready files: PS, PCL, TIFF, PDF Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Scan Template Management	Support 250 scan templates Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning		
Browsers (minimum versions)	Netscape 7.x, 9.x Internet Explorer 6.x Safari 3.0 Mozilla Firefox 2.x Opera 9.x Chrome 1.0		
Support	Online support available via web page		
Scanning			
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs.		
Input Speed	Scan at up to 50 ipm colour scanning, up to 80 ipm black and white – A4/210 x 297 mm LEF at all resolutions		
Resolutions (DPI options)	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi		
Scan Presets	Archival Record (Normal Quality - Smallest file size) For Sharing and Printing (Normal Quality - Small file size) For High Quality Printing (High Quality - Large file size) For OCR (High Quality - Large file size) Simple Scan (Normal Quality - Small file size)		
Quality/File Size	Normal Quality (Small file size) Higher Quality (Large file size) Maximum Quality (Largest file size)		
Maximum Scan Area	A3/297 x 420 mm		
Authentication	Secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX/Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x / 5.x / 6.x) PIN-based guest login		
File Formats	TIFF 6.0 with G3 MH, G4 MMR, or JPEG compression (single page or multiple pages) PDF (image only and searchable PDFs with G3 MH, G4 MMR, MRC, JPEG or JBIG2 compression) JIFF with JPEG compression Microsoft XML Paper Spec (XPS)		

File Compression	G3 (photo and half tone photo originals), G4 (text and mixed originals), MRC, JPEG, JBIG2	
Scan Features	 Mixed sized Original Support for Scan Export New scan to export compression formats: MRC (multi-layer) JBIG2 Simplify the scanning workflow User Interface (IQ, file size, Templates) Enhanced IQ Support for Barcode Readers and OCR Scan in Novell IP Build job for Scan to File Auto Detect Colour or Black and White Image data Auto Contrast support for Scan Export – Enable better colour and greyscale scanned Image Quality by correcting for different levels of black within a scanned image Scan to Searchable PDF, PDF/A and XPS Scan to Mailbox Store and reprint print jobs 	
Scan to Email – Optional		
Capability	Scan to email (manual address entry), directory (Exchange/Notes/LDAP) address searching, internal address book or Public address book (up to 128 recipients)	
Network Protocol	SMTP MIME encoded	
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options	
Network Scanning		
Capability	Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services: • Scan to file • Scan to network server / directory • Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver • Scan to email • Scan to Microsoft Exchange public folders • Scan to PC Desktop	
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS	
Document Management Fields (Metadata)	 Features only available in Network Scan to File Templates: 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata Field consists of field name, display at the LUI or not, default value and other configurations Customised fields viewed on user interface Variable data entered using virtual keyboard at device 	
Scan Template Management	Share scan templates among WorkCentre via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option	
Scan Features	Build job (for scan to file only) (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge	

Network Scanning – Software Solutions

Network Scanning – Softwo		
Supported Scan Destinations - scan template creation (varies by scanning software options purchased)	Scan to application (workflow, Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web folders Scan to web URL Scan to remote printer Scan to PC Desktop (SE and Professional editions) Scan to mailbox	
Xerox Scan to PC Desktop Professional (optional)	 A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: Nuance PaperPort Professional image viewing and file management software: Complete PDF functionality Secure PDF workflow of all scanning applications Nuance OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes email inbox polling capability 	
Xerox SMARTsend® (optional)	 Server based document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per server): Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary) Scan to File Destinations: email, Novell Netware folder, network folder, SMB folder, FTP, Microsoft Exchange 2000 Web folders, Web URL, remote printers Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint Workflow initiation via device scanning user interface (template selection at device UI) 	
Xerox SMARTsend Professional (optional)	Everything in Xerox SMARTsend, plus: • Workflow initiation via Paperware (Scan cover sheets) • Server-based Optical Character Recognition (OCR) • Adding Metadata • Scan to Internet fax file destination	
Fax Specifications		
Fax Options – Internet Fax		
Capability	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients	
Maximum Scan Area	A3/297 x 420 mm	
Authentication	Optional secure device login with network user name and password Supports: Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP / IPX (Netware 4.x / 5.x / 6.x) Optional PIN-based guest login	
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book	
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF	
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 100 x 100 dpi 72 x 72 dpi	

Network Protocols	SMTP POP3 (RFC 1939)	
Compliance	ITU-T T.37 compliant 508 Compliant	
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation: • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body	
Fax Features – Network I	Fax Server Enablement	
Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration.	
Maximum Scan Size	A3/297 x 420 mm	
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP / IPX (Netware 4.x / 5.x / 6.x) Optional PIN-based guest login	
Network Protocols	Novell (NCP via IPX/SPX) or IP FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP	
Fax Send Features	One- or two-sided scanning (up to A3/297 x 420 mm) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, five levels of contrast, five levels of sharpness)	
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)	
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Programme. For details visit www.xerox.com .	
Fax Options – Walk Up C	option (one or two line options)	
Compatibility	ITU (CCITT) Group 3	
Memory	32 MB (One line) 256 MB (Two line)	
Speed/Modems	1 or 2 V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time.	
Compression/Speed	MH / MR / MMR / G3 / Super G3	

Fax Send Features	Quality/Resolution • Original type: photo, photo/text, text only • Fax – off platen, mixed sizes or bound/book Auto Send (Up to 5) Audio line monitor Transmission options (Report/Header) Reduce / Split large documents Cover letter Delayed send Build Job (up to 1,000 images) Polling	
Fax Receive Features	One- or two-sided printing Stapled or unstapled, hole punch Receive print mode – Manual (size, margin, stock, header) / Auto Auto answer delay Secure receive Junk fax prevention	
Fax Reports	Activity Dial directory Group directory Options Pending jobs	
Fax Mailboxes	Up to 200 password-protected Poll Remote mailboxes (up to 255) password-protected	
Auto Dialing Features	Speed Dials: • 200 (one-line option) • 1,000 (two-line option) Group Dials: • Up to 100 groups with up to 200 recipients per group (one-line option) • Up to 200 groups with up to 400 recipients per group (two-line option) Auto Redial: • Up to 14 attempts • 1 to 25 minute intervals • Batch send (up to memory capacity)	
Resolutions	Send: 200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 600 x 600 dpi (Superfine) Receive: 200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi (Superfine) 400 x 400 dpi (Superfine) 600 x 600 dpi (Superfine) 600 x 600 dpi (Superfine)	
LAN Fax	Send fax directly from print drivers	
Accounting Options – Xer	ox Standard Accounting	
Tracking	Copy, Print, Fax and Scan usage	
Accounting	Up to 2,500 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)	
Features	Enable/disable via the Web UI or the device GUI in tools, admin can manage the feature remotely via the Web UI, Data can be exported via a CSV file, supports entering XSA ID into the print driver when submitting a print job.	

Accounting Options – Job Based Accounting – Third Party Enablement				
	Enhanced network accounting with up to the minute data on how the WorkCentre system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options are available through Xerox Alliance Partner solutions. For details visit www.xerox.com . Security enhancements with the addition of HTTPS protocol support. WorkCentre requests account authentication from 3rd-party server enabling larger databases of users and accounts.			
Machine Specifications				
Monthly Duty Cycle				
	WorkCentre 7755: up to 200,000 pages/month WorkCentre 7765: up to 250,000 pages/month WorkCentre 7775: up to 300,000 pages/month			
Accessories				
	High Capacity Finisher Simple Catch Tray Offset Catch Tray Advanced Finisher with 50 sheet Stapling Light Production Finisher with 100 sheet Stapling Light Production Finisher with Folder and 100 sheet Stapling Tri Folder C/Z Folder (Light Production Finisher) Swedish 4 Hole Punch (Professional/Advanced/Light Production Finishers) Mobility Plate Foreign Device Interface Kit Convenience Stapler Xerox Copier Assistant Kit Unicode Printing Kit SMARTsend Work Surface Fiery Server Network FreeFlow Add License Tool (5/15/50 Licenses) Scan to PC Desktop (Professional or SE edition) Secure Access Network Scanning and Email iFax and Server Fax Kit Network Accounting Kit			
Electrical Requirements				
	Voltage : 220-240 VAC +/- 10% (198-264 VAC) Frequency: 50/60 Hz +/- 3%, 10 A (220/240 V) Power Consumption: 1.096 KVA maximum printing continuously			
Power Consumption (Base I	Power Consumption (Base IOT)			
Running (Average)	< 1131 watts/hour			
Standby Mode	< 285 watts/hour			
Low Power Mode	< 218 watts/hour (Default time to Low Power = 15 minutes)			
Auto Off / Sleep mode	< 23.7 watts/hour (Default time to Sleep mode = 45 minutes)			
Warm-up Ready to Copy	< 28 seconds (Recovery from Sleep)			
Warm-up Ready to Print	< 130 seconds (Recovery from Sleep)			
Low Power Recovery	< 20 seconds			

Environmental Considerations					
Required Temperature Range	10° to 28° C				
Required Relative Humidity	15% to 85%				
Dimensions and Weight	Width	Depth	Height	Weight	
Configuration with OCT	1,574 mm	787 mm	1,460 mm	277.7 kg	
With Advanced Office Finisher	2,096 mm	787 mm	1,460 mm	351.7 kg	
With Professional Finisher (with Booklet Maker)	2,096 mm	787 mm	1,460 mm	379.4 kg	
With Light Production Finisher (without Folding option)	2,286 mm	787 mm	1,460 mm	398.2 kg	
With Light Production Finisher (with Folding option)	2,489 mm	787 mm	1,460 mm	455.9 kg	

Certifications

FCC Class A Compliant (US), DOC Class A Compliant (Canada) 89/336/EEC (Europe) UL Listed (UL 1950, Third Edition) CB Certified (IEC 60950/EN 60950) 73/23/EEC (Europe) 95/5/EEC (Europe) ENERGY STAR® GOST

Device Specifications

Xerox Extensible Interface Platform[®] (EIP)

	Xerox EIP is a software platform inside the WorkCentre 7755/7765/7775 that enables personalised solutions you can access right from the device touch screen. These applications can leverage your existing databases and meet your specific business challenges.		
Supplies	Description	Order Number	
Toner Cartridges	Black	006R01449	
	Yellow	006R01450	
	Magenta	006R01451	
	Cyan	006R01452	
Waste Toner Bottle	Supplied with each toner cartridge box	008R12990	
Staple Cartridge	For Light Production Finisher	008R13029	
Staple Cartridge	For Booklet maker saddle-stitch stapling	008R12925	
Staple Cartridge	For Convenience Stapler/Advanced Office Finisher/Professional Finisher • Complete Cartridge • Refill Cartridge	008R12964 008R12941	
SMart Kit		Order Number	
Fuser Module		008R12989	





© 2010 Xerox Corporation. All rights reserved. XEROX[®], XEROX and Design[®], CentreWare[®], WorkCentre[™], Scan to PC Desktop[®], Walk-Up[®] and SMart Kit[®] are trademarks or registered trademarks of Xerox Corporation in the United States and other countries. Adobe[®] and PostScript[®] 3[™] are trademarks or registered trademarks of Adobe, Inc. XPS[®] is a register trademark of Microsoft Corporation. PCL[®] is a registered trademark of Hewlett-Packard. As an ENERGY STAR[®] partner, Xerox Corporation has determined that these products meet the ENERGY STAR guidelines for energy efficiency. The ENERGY STAR name and logo are registered U.S. trademarks. Terra Choice Evervices, Inc. of Canada has verified that this Xerox product conforms to all applicable Environmental Choice Eco Logo requirements for minimized impact to the environment. The information in this brochure is subject to change without notice. 06/10 W77SS-01EC