

Xerox[®] WorkCentre[™] 7830/7835/ 7845/7855 Colour Multifunction Printer

The WorkCentre 7800 Series Colour Multifunction Printer is built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.connectkey.com**.

	High Cr Tray Op Stapler and Work Surface		Office Finisher with Booklet Maker	Professional Finisher
System Specifications	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Speed Colour / Black and White	Up to 30 / 30 ppm	Up to 35 / 35 ppm	Up to 45 / 45 ppm	Up to 50 / 55 ppm
Monthly Duty Cycle ¹	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages
Recommended Average Monthly Print Volume ²	8,000 to 12,000 pages	10,000 to 15,000 pages	16,000 to 20,000 pages	18,000 to 22,000 pages
Hard Drive / Processor / Memory	Minimum 160 GB / 1.2 GHz Dual-co	re / 2 GB system plus 1 GB page mem	ory	
Connectivity	10/100/1000Base-T Ethernet, High-Sj	peed USB 2.0 Direct Print, Optional Wi-	Fi (with Xerox® USB Wireless Adapter)	
Controller Features	Unified Address Book, Remote Cont	rol Panel, Online Support (accessed fi	rom the user interface and print drive	r), Configuration Cloning
Optional Controller	EFI Server			
Copy and Print				
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up	to 1200 x 2400 dpi		1
First-print-out Time Colour / Black and White	As fast as 9 / 7.7 seconds		As fast as 7.5 / 6.4 seconds	As fast as 7.1 / 5.9 seconds
Page Description Languages	Adobe [®] PostScript [®] 3 [™] , PDF, PCL [®] 5c	: / PCL 6, XML Paper Specification (XPS	5®) (Optional)	
Print Features	Print from USB, Earth Smart Driver So Monitoring, Colour By Words	ettings, Job Identification, Booklet Cre	ation, Store and Recall Driver Settings	, Bi-directional Status, Scaling, Job
Mobile Printing	Apple® AirPrint, Xerox® PrintBack, Xer	rox® Mobile Print Solution (Optional), >	Kerox® Mobile Print Cloud (Optional), N	Mopria™ certified
Scan				
Standard Features	Destinations: Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A			
Optional Features	Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, other solutions available through various Xerox Alliance Partners			
Fax				
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement			
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax)			
Security				
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) (undergoing evaluation), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions			
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)			
Accounting				
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement			
Optional Features	Equitrac Express®, Equitrac Office®, Equitrac Partners	quitrac Professional®, YSoft® SafeQ®, o	ther network accounting solutions ava	ilable through various Xerox Alliance

Device Specifications					
Control Panel Languages		ternational French, Italian, German, Ir an, Czech, Polish, Hungarian, Romanic	nternational Spanish, Dutch, Brazilian P an, Catalan	ortuguese, Swedish, Norwegian,	
Accessories					
Optional	High Capacity Feeder (HCF) Envelope Tray (Replaces Tray 1) Integrated Office Finisher (optional with 7830/7835 only) Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Professional Finisher Convenience Stapler (includes Work Surface) Smart Card Enablement Kit Xerox Secure Access Unified ID System® EFI Fiery® Network Controller Walk up Fax (One- or Two-line options, includes LAN Fax) Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit				
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Devic	te, this is an interface to third party ac	ccess control devices, such as coin mac	hines and card readers.	
Electrical Requirements					
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A				
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A				
Power Consumption	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855	
Running (Average)	110V: 641 watts 220V: 643 watts	110V: 673 watts 220V: 691 watts	110V: 750 watts 220V: 764 watts	110V: 828 watts 220V: 862 watts	
Standby Mode	110V and 220V: 62 watts 110V: 98.6 watts 110V: 85.7 watts 220V: 95.9 watts 220V: 121 watts				
Low Power Mode	110V and 220V: 59 watts 110V and 220V: 80.5 watts 110V: 80 watts 220V: 94.6 watts				
Auto Off / Sleep mode	110V: 4.2 watts110V: 4.3 watts220V: 4.8 watts220V: 4.8 watts(Default time to Sleep mode = 2 mins)(Default time to Sleep mode = 2 mins)				
Warm-up (from Off)	Max. 194 seconds (Dependent on number of services registered)				
Low Power Recovery	< 9 seconds				
Operating Environment					
Required Temperature Range	50° to 82° F (10° to 28° C)				
Required Relative Humidity	15% to 85%		1		
Sound Power Levels Operating Standby	6.5 LwAd (B) 3.5 LwAd (B)	6.5 LwAd (B) 3.4 LwAd (B)	6.6 LwAd (B) 3.6 LwAd (B)	6.8 LwAd (B) 3.6 LwAd (B)	
Sound Pressure Levels Operating Standby	54 LpAd (dBA) 16.5 LpAd (dBA)	54.3 LpAd (dBA) 16.5 LpAd (dBA)	55.7 LpAd (dBA) 18.5 LpAd (dBA)	55.8 LpAd (dBA) 18.5 LpAd (dBA)	
Dimensions and Weight	Width	Depth	Height	Weight	
Base Configuration	25.2 in. / 640 mm	27.5 in. / 699 mm	45.2 in. / 1,149.2 mm	334.2 lbs. / 151.9 kg	
With Integrated Office Finisher (7830/7835 only)	44.4 in. / 1,129 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	348 lbs. / 158 kg	
With Office Finisher LX (with Booklet Maker)	65.6 in. / 1,666 mm	27.9 in. / 709 mm	45.2 in. / 1,149 mm	403 lbs. / 183 kg	
With Professional Finisher	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	526 lbs. / 239 kg	
With Professional Finisher and High Capacity Feeder	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	590 lbs. / 268 kg	

Certifications			
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) GS Mark ENERGY STAR® 2.0 EPEAT (United States) GOST NOM Blue Angel Environmental Choice CE Mark Common Criteria (IEEE 2600.2 standard) Citrix® Certified WHQL IPv6 Ready Cerner MEDITECH SAP To view the latest list of certifications, go to www.xerox.com/OfficeCerti	fications.	
Paper Handling	WorkCentre 7830 WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Duplex Automatic Document Feed	er		
Capacity ³	110 sheets	130 sheets (Single-pass DADF)	
Speed	up to 70 image per minute black and white and colour (simplex)	up to 80 images per minute black ar up to 133 images per minute black ar	· · · · · · · · · · · · · · · · · · ·
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 lb. bond to 32 lb. bond / 50 gsm to 128 gsm		
Bypass Tray			
Capacity ³	100 sheets		
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in. / 89 x 98 mm to 320 x 483 mm		
Weights	16 lb. bond to 110 lb. cover / 55 to 300 gsm		
Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Lightweight Card Stock Reloaded Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain Reloaded Preprinted Recycled Transparencies		
3 Tray Module (Total 2,180 sheets)	(Optional with WorkCentre 7830/7835 only)		
Capacity ³	Trays 1-4: 520 sheets each		
Sizes	Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 18 Trays 2-4: Custom Sizes from 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 139.7 x		
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm		

Speed Model Calibacity Social Calibacity Soc			
Link Jack Base Base Base Base Base Base Base Base	Types		
Content Content			
scienceOriginal Statistics Related Hexposite Car Statistics Related Related Related Related R			
Interpreter interpr			
Insproved to Sock Sock Sock Sock Sock Sock Sock Soc			
Inspace Inspace Inspace <			
skip skip skip <td></td> <td></td>			
Indek Indek Indek <td></td> <td></td>			
skipweight out Stock Netoded Stock Netoded Stock Netoded Netoded Stock Netoded Netoded Stock Netoded Netoded Stock Netoded Netoded Stock Netoded Netoded Netoded Stock Netoded Netoded Netoded Netoded Netoded Netoded Netoded Netoded Netode Netoded N			
Independent of Sock Metadad Interest of Class Can Stack EngineerSock Sock Metadad EngineerSock Sock Metadadad EngineerSock Sock Metadadad EngineerSock Sock Metadadad EngineerSock Sock Metadadadad EngineerSock Sock Metadadadadadadadadadadadadadadadadadadad			
lightweight dissor dat Stock heloaded lightweight dissor data Stock heloaded lightweight dissor da			
injstueging Glosp, God Stock Reloaded Bon Bon Bon Bon Bon Bon Bon Bon Bon Bon Bon Bon Bon Bon Bon BonFightad Bon			
Initial ConstructionBine Accord Server			
Indef Research Payment Respirate <b< td=""><td></td><td></td></b<>			
Reside Figure Sector			
InterpretationInterpretationHardcoity Toolem Notified StatesThe Second State Sta			
High Capacity Tondem Tray (Total S-Velocits Tray : 8:03 yeles : 8:03 yeles : 8:03 yeles : 8:03 yeles : 9:03 yeles : 9:			
Capacity Tmy 1: 200 sheets Tmy 2: 100 sheets Tmy 2: 100 sheets Tmy 2: 100 sheets Tmy 2: 200 sheets The 2: 200 sheets	High Capacity Tandem Tray (Total		
Inv 2.5 00 sheets Try 3.60 sheets Try 3.60 sheets Try 3.60 sheetsSizesInv 1. Castom Sizes from 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 140 x 182 mm to 290 x 438 mm Try 3.4 Sandrad Sizes 8.5 x 11 in. LF / AU, 185 k. Disculut (7.25 x 10.5 m)Weights61 k. bond 10 400 k. Index / 60 to 256 gmTypsCasd Suck Castom Suck Such Sizes from 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 140 x 182 mm to 290 x 438 mm Try 3.4 Sandrad Sizes 8.5 x 11 in. LF / AU, 185 k. Disculut (7.25 x 10.5 m)TypsBond Card Suck Ladde Sizes 8.5 x 11 in. LF / AU, 185 k. Disculut (7.25 x 10.5 m)Use of the partned Castom Castom Suck Help partnedExtended Sizes 8.5 x 11 in. J AU (1.5 m)Use of the partned Ladde Sizes 8.5 x 11 in. J AU (1.5 m)Extended Sizes 8.5 x 11 in. J AU (1.5 m)Use of the partned Dispred PriorSandrad Sizes 8.5 x 11 in. J AU (1.5 m)Use of the partned Dispred Prior Dispred Prior Di			
ImpIm	cupucity		
Size Toy 1: Custom Sizes from 5.5 x 7.2 in SEF to 1.1 x 17 in, SEF / 140 x 182 mm to 297 x 432 mm tryg 5.2 Custom Sizes from 5.5 x 7.2 in SEF to 12 x 18 in, SEF / 140 x 182 mm to 200 x 438 mm tryg 5.4 St downd Sizes 8.3 x 111 in, LEF A4, J1855, Executive (7.25 x 10.5 in) Weights 16b. hond to 140 lb. index / 60 to 256 gm Types Band Card Stock Custom Closey Card Stock Hole purched Lobels Lettended Lightweight Card Stock Hole purched Lobels Lettended Lightweight Card Stock Hole purched Lobels High Capacity Feeder (HCF) Cord Stock Hole purched Lobels 2000 entes Capacity 2000 entes Stare 3000 fort Stare 300 fort Stare		Tray 3: 867 sheets	
Independent of the second se		Tray 4: 1,133 sheets	
Instant Search 2000 Search	Sizes		
Weights16 Is. bond to 140 Ib. index / 60 to 256 gsmTypesBond Card Stock Cardstock Cardstock Cardstock Cardstock Cardstock Cardstock Cardstock Cardstock Cardstock Cardstock Cardstock Cardstock Liddes <b< td=""><td></td><td></td></b<>			
Types Bond Card Stock Custom Glossy Card Stock Hole punched Labels High Capacity Feeder (HCF) (opt	Weights		
Image: Stand Stock Custom Custom Song Card Stock Hole punched Labels Labels Labels Labels Lightweight Gloss Card Stock Hole punched Lightweight Gloss Card Stock Poin Peninted Hole Scock Lightweight Gloss Card Stock 			
InstrumeGesor Card Stock Hale punched Labe punched Lab	Types		
IndependenceNote Provide Stock Stoc			
ibeis ibeis ibeis ibeis ibeis ibeis ibeis ibeis ibeis ibeis ibeis ibeis i			
IphicipationIphicipationFigure 201EventedFigure 201Source 201Figure 201Source 201SeaSource 201S			
Ightweight Glossy Card Stock Bain Perinted Jiph Capacity Feeder (HCF) (U) Fight Capacity Feeder (HCF) (O) Gapacity 000 sheets Stace Standard Stees 8.5 x11 in. / A4 LEF Veldy Tag 16.1 bond to Alb. Index / S5 to 256 gsm Enversormer Veldy State 8.5 x11 in. / A4 LEF Capacity State 8.5 x11 in. / A4 LEF Veldy Tag 16.1 bond to Alb. Index / S5 to 256 gsm Enversormer Veldy State 8.5 x11 in. / A4 LEF Capacity Bio Bond to Alb. Index / S5 to 256 gsm Enversormer Veldy State 8.5 x11 in. / A4 LEF Capacity D folds over Alb. State 8.5 x11 in. / A4 LEF Capacity D folds over Alb. State 8.5 x11 in. / A4 LEF Capacity D folds over Alb. State 8.5 x11 in. / A4 LEF Capacity D folds over Alb. State 8.5 x11 in. / A4 LEF Capacity D folds over Alb. State 8.5 x11 in. / A4 LEF Capacity D folds over Alb. State 8.5 x11 in. / A4 LEF Capacity D folds folds over Alb. State 8.5 x11 in. / A4 LEF Capacity D folds folds folds over Alb. State 8.5 x11 in. / A4 LEF Capacity D folds folds folds folds folds folds folds folds f			
Pain Province Proprinted Proprinted High Capacity Feeder (HCF) (better) Coooches Capacity 2 Stondard Sizes 8.5 x 11 in. / A4 LEF Weights 16 b. bond to 140 b. index / 55 to 26 g.sm Envelope Tray (Optional-Repoter) Vol 60 envelopes Capacity 3 Up to 60 envelopes Sizes 10 Commercial (9.25 x.4 125 in.), Monarch, DL, C5, K x 9 in. Castor sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm) Sizes 10 Commercial (9.25 x.4 125 in.), Monarch, DL, C5, K x 9 in. Castor sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm) Sizes 10 Commercial (9.25 x.4 125 in.), Monarch, DL, C5, K x 9 in. Castor sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm) Sizes 10 Commercial (9.25 x.4 125 in.), Monarch, DL, C5, K x 9 in. Castor sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm) Sizes 10 Lob to a 10 & 10 Monarch, DL, C5, K x 9 in. Castor sizes: 3.9 x 5.8 in. to 6.1 x 9.5 in. x 9.5 x			
High Capacity Feeder (HCF) (Option Capacity3 2000 sheets Sizes Standard Sizes; 8.5 x 11 in. / A4 LEF Weights 16 lb. bond to 140 lb. index / S5 to 256 gsm Envelope Tray (Optional–Replaces) V Capacity3 Up to 60 envelopes Sizes % 10 commercial (9.25 x 4.125 in.) Monarch, DL, C5, 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm) Veights 20 lb. bond to 24 lb. bond / 75 to 90 gsm Total Capacity 2 lb. bond to 24 lb. bond / 75 to 90 gsm Total Capacity 5.10 sheets Porice Total Capacity 5.10 sheets Firshing E Custom Sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./ 9.8 x 148 mm to 162 x 241 mm) Sizes Sud Offset Catch Tray - up to 250 sheets each lact in the state stat			
Capacity's2000 sheetsSizesStandard Sizes: 8.5 x 11 in. / A4 LEFWeights16 lb. bond to 140 lb. index / 55 to 256 gsmEnvelope Tray (Optional-Replaces>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>		Preprinted	
SizesStandard Sizes: 8.5 x 11 in. / A4 LEFWeights16 b. bond to 140 lb. index / 55 to 256 gsmEnvelope Tray (Optional-Replace>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	High Capacity Feeder (HCF) (Optio	nal)	
Weights16 lb. bond to 140 lb. index / 55 to 256 gsmEnvelope Tray (Optional-ReplacesCapacityUp to 60 envelopesSizesUp to 60 envelopesVieghts20 lb. ondt 02.25 x 4.125 in.), Monarch, DL, C, S 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)Weights20 lb. bondt 02.4 lb. bond / 75 to 90 gsmDevice Total Capacity20 lb. bondt 02.4 lb. bond / 75 to 90 gsmDevice Total Capacity1.40 sheetsDevice Total Capacity1.40 sheetsDevice Total Capacity1.40 sheetsDevice Total Capacity0.01 Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheetsDevice Total CapacityDuol Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheetsDevice Total Capacity0.01 Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheetsStacking Tray0.01 offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheetsDevice Total Capacity0.01 offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheetsStacking Tray0.01 offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheetsDevice Total Capacity0.01 offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheetsStacking Tray0.00 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in / A9 X 20 mmStacking Tray0.50 sheets of 20 lb. bond / 60 to 256 gsmWeights1.50 shoet to 20 lb. 20 sheets of 20 lb. 20 sheets<	Capacity ³	2000 sheets	
Envelope Tray (Optional–Replaces Envelope Tray (Optional–Replaces Capacity ³ Up to 60 envelopes Sizes #10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm) Weights 20 lb. bond to 24 lb. bond / 75 to 90 gsm Total Capacity 5,140 sheets Prinshing 5,140 sheets Output Trays (Standard) Dual Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheets Integrated Office Finisher (Optionet) So sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3 Sizes 3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm Weights 16 lb. bond to 80 lb. cover / 60 to 256 gsm Stapling Single	Sizes	Standard Sizes: 8.5 x 11 in. / A4 LEF	
Capacity³Up to 60 envelopesSizesUp to 60 envelopesSizes#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)WeightsJob bond to 24 lb. bond / 75 to 90 gsmTotal CapacityJob bond to 24 lb. bond / 75 to 90 gsmTotal Capacity, 140 sheetsDevice Total Capacity35, 140 sheetsFinishingUl Offset Catch Tray – up to 750 sheets each Left-side Face up Tray – up to 100 sheetsDevice Total Capacity3Unal Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheetsIntegrated Office Finisher (Obtive - VF 330/R33)Ousless of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3SizesSizesSizes 10.0 sheetsWeightsI6. bond to 80 lb. cover / 60 to 256 gsmStaplingSingle	Weights	16 lb. bond to 140 lb. index / 55 to 256 gsm	
Sizes#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)Weights20 lb. bond to 24 lb. bond / 75 to 90 gsmTotal Capacity20 lb. do to 24 lb. bond / 75 to 90 gsmDevice Total Capacity35,140 sheetsGutput Trays (Standard)Stacking Trays3Dual Offset Catch Tray - up to 250 sheets each eft-side Face up Tray - up to 100 sheetsIntegrated Office Finisher (Opticum - Unit of 20 lb. bond / 80 gsm - 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm - 11 x 17 in. / A3Sizes3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mmWeights16. lb. bond to 80 lb. cover / 60 to 256 gsmStaplingSingle	Envelope Tray (Optional–Replaces	Tray 1)	
I cutom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)Weights20.b cond to 2.4 lb. cond / 75 to 90 gsmTotal Capacity3.4 0 setesDevice Total Capacity3.4 0 setesI staffingCutom staffing StandardCutom staffing StandardStacking Trays ¹ Dul Offset Catch Tray - up to 250 sheets each staffing Staffi	Capacity ³	Up to 60 envelopes	
Weights 20 lb. bond to 24 lb. bond / 75 to 90 gsm 20 lb. dond to 24 lb. bond / 75 to 90 gsm 5,140 sheets 5,140 sheets 5,140 sheets 6,140 sheets 5,140 sheets <td cols<="" td=""><td>Sizes</td><td>#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in.</td></td>	<td>Sizes</td> <td>#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in.</td>	Sizes	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in.
Total Capacity Site of the second		Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)	
Device Total Capacity³ 5,140 sheets Finishing 5,140 sheets Output Trays (Standard) 5,140 sheets of tray - up to 250 sheets each Left-side Face up Tray - up to 100 sheets Stacking Trays³ Dual Offset Catch Tray - up to 250 sheets each Left-side Face up Tray - up to 100 sheets Integrated Office Finisher (Optionary - up to 200 sheets each Left-side Face up Tray - up to 100 sheets 500 sheets of 201 b. bond / 80 gsm - 8.5 x 11 in. / A4 or 250 sheets of 201 b. bond / 80 gsm - 11 x 17 in. / A3 Stacking Tray 500 sheets of 201 b. bond / 80 gsm - 8.5 x 11 in. / A4 or 250 sheets of 201 b. bond / 80 gsm - 11 x 17 in. / A3 Stacking Tray 500 sheets of 201 b. bond / 80 gsm - 8.5 x 11 in. / A4 or 250 sheets of 201 b. bond / 80 gsm - 11 x 17 in. / A3 Stape 161 b. bond to 80 b. cover / 60 to 256 gsm Stapling Single	Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm	
Finishing Output Trays (Standard) Stacking Trays ³ Dual Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheets Integrated Office Finisher (Optionary – up to 100 sheets) Edit-side Face up Tray – up to 100 sheets Stacking Tray 500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3 Sizes 3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm Weights 16 lb. bond to 80 lb. cover / 60 to 256 gsm Stapling Single	Total Capacity		
Output Trays (Standard) Stacking Trays ³ Dual Offset Catch Tray - up to 250 sheets each Left-side Face up Tray - up to 100 sheets Integrated Office Finisher (Option=Vith 7830/7835) Stacking Tray 500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3 Sizes 3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm Weights 16 lb. bond to 80 lb. cover / 60 to 256 gsm Stapling Single	Device Total Capacity ³	5,140 sheets	
Stacking Trays³Dual Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheetsIntegrated Office Finisher (Optionational Stacking TrayStacking Tray500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3Sizes3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mmWeights16 lb. bond to 80 lb. cover / 60 to 256 gsmStaplingSingle	Finishing		
Integrated Office Finisher (Optional Finisher (Optionat Finisher (Optional Finisher (Optional Finisher (Output Trays (Standard)		
Integrated Office Finisher (Option Integrated Office Finisher (Option ith 7830/7835) Stacking Tray 500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3 Sizes 3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm Weights 16 lb. bond to 80 lb. cover / 60 to 256 gsm Stapling Single	Stacking Trays ³		
Stacking Tray 500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3 Sizes 3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm Weights 16 lb. bond to 80 lb. cover / 60 to 256 gsm Stapling Single	Integrated Office Finisher (Option		
Sizes 3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm Weights 16 lb. bond to 80 lb. cover / 60 to 256 gsm Stapling Single			
Weights 16 lb. bond to 80 lb. cover / 60 to 256 gsm Stapling Single			
Stapling Single			
	-		
30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)	Stapling	Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers)	

res 7.2 x eights 16 lb ultiposition Stapling 50 sh oble Punch (Optional) 2-3 H orth America: 2-3 H rope: 2-4 H oklet Maker for Office Finisher LX (Scongpacity3) 40 bc tes Letter Ledged Letter Ledged Letter	8.3 in. to 11.7 x 17 in. / 182 x 2 bond to 80 lb cover / 60 to 256 neets of 24 lb. bond / 90 gsm dole Punch dole Punch re/Crease, Saddle-stitch Staple pooklets (2-15 sheets per booklet er = 8.5 x 11 in. / A4 SEF L = 8.5 x 14 in. / B4 SEF	10 mm to 297 x 432 mm gsm e) (Optional)) sheets dual stapled (8.5 x 11 in. / A4			
res 7.2 x eights 16 lb ultiposition Stapling 50 sh oble Punch (Optional) 2-3 H orth America: 2-3 H rope: 2-4 H oklet Maker for Office Finisher LX (Scongacity3) 40 bc tes Letter Legal Letter Ledgal Letter	8.3 in. to 11.7 x 17 in. / 182 x 2 bond to 80 lb cover / 60 to 256 neets of 24 lb. bond / 90 gsm dole Punch dole Punch re/Crease, Saddle-stitch Staple pooklets (2-15 sheets per booklet er = 8.5 x 11 in. / A4 SEF L = 8.5 x 14 in. / B4 SEF	10 mm to 297 x 432 mm gsm e) (Optional)				
eights 16 lb ultiposition Stapling 50 sh ole Punch (Optional) orth America: 2-3 H 2-4 H rope: 2-4 H roklet Maker for Office Finisher LX (Scor upacity ³ 40 bc res Letter Legal	o bond to 80 lb cover / 60 to 256 neets of 24 lb. bond / 90 gsm Hole Punch Hole Punch re/Crease, Saddle-stitch Staple ooklets (2-15 sheets per booklet er – 8.5 x 11 in. / A4 SEF I – 8.5 x 14 in. / B4 SEF	gsm e) (Optional)				
ultiposition Stapling 50 sh ole Punch (Optional) orth America: 2-3 H 2-4 H rope: 2-4 H roklet Maker for Office Finisher LX (Scor pacity ³ 40 bc tes Letter Legal	heets of 24 lb. bond / 90 gsm Hole Punch Hole Punch re/Crease, Saddle-stitch Staple ooklets (2-15 sheets per booklet Pr – 8.5 x 11 in. / A4 SEF L – 8.5 x 14 in. / B4 SEF	e) (Optional)				
ble Punch (Optional) 2-3 H porth America: 2-4 H rope: 2-4 H boklet Maker for Office Finisher LX (Scongacity3) 40 bc tes Letter Ledgal Ledgal	Hole Punch Hole Punch re/Crease, Saddle-stitch Staple pooklets (2-15 sheets per booklet er – 8.5 x 11 in. / A4 SEF L – 8.5 x 14 in. / B4 SEF	· · · ·				
pacity ³ 40 bc res Letter Legal Ledge	ooklets (2-15 sheets per booklet r – 8.5 x 11 in. / A4 SEF l – 8.5 x 14 in. / B4 SEF	· · · ·				
res Letter Legal Ledge	er – 8.5 x 11 in. / A4 SEF l – 8.5 x 14 in. / B4 SEF	– 20 lb. / 80 gsm or less)				
Legal Ledge	l – 8.5 x 14 in. / B4 SEF					
ddle-stitch Stapling 2-15	er – TTX T7 IN. 7 A3 SEF		Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF			
	sheets / 8-60 page booklet b. bond to 24 lb. bond / 60 to 90	gsm				
ore / Crease 1-15	sheets / unstapled					
ofessional Finisher (Optional)						
500 s Stack 1,500 200 s	Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 or 100 stapled sets of 11 x 17 in. / A3 / SRA3					
	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling					
eights 16 lb.	16 lb. bond to 80 lb. cover / 60 to 220 gsm					
Auto	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported					
orth America: 2-4 H	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)					
Bi-fol	Saddle-stitch 2 to 15 sheets (14 sheets of 90 gsm or less plus 1 sheet of 169 gsm) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, SRA3 supported					
nvenience Stapler (Optional–Includes \	Work Surface)					
5,000	50-sheet stapling 5,000 staples Requires a separate outlet					
ipy Work	WorkCentre 7830 WorkCentre 7835 WorkCentre 7845 WorkCentre 7855					
2.	ist as 8.4 seconds / ist as 6.7 seconds	As fast as 8.2 seconds / As fast as 6.8 seconds	As fast as 7.5 seconds / As fast as 6.2 seconds	As fast as 7.1 seconds / As fast as 5.5 seconds		
des (input:output) 1-1, 1	1-1, 1-2, 2-2, 2-1					
	1 to 9,999					
-	Up to 600 x 600 dpi					
· · · ·	Variable zoom from 25% to 400% in 1% increments					
	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)					

Copy Features	Annotation and Bates [™] stamping (with colour capability and font size ac Authentication for Services (i.e. Colour Copy) Auto Paper Select Auto Reduction & Enlargement to fit selected paper size	djustment)		
	Auto Tray Switching Automatic 2-sided/Duplex Rocklet Creation			
Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built)				
	Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed)			
	Dividers (blank) Edge Erase			
	Features Help (Intuitive text and graphic descriptions)			
	ID Card Copy Image Quality Adjustments			
	Image Shift (with Auto Centre option)			
	Invert Image (negative or mirror image) Large Job Interrupt			
	Multi-up (up to 15 columns by 15 rows)			
	Sample Set			
	Save Job Settings Single Colour			
	Stapling			
	Transparencies			
Xerox® Copier Assistant®	Xerox® Copier Assistant® Software provides a PC-based alternative to the PC attached via the USB port, this software supports text-to-speech, scree features. Section 508 compliant. For more information or to download X	een magnification and easy PC k	eyboard access to basic and advanced copy	
Print	WorkCentre 7830 WorkCentre 7835	WorkCentre 7845	WorkCentre 7855	
Print Resolution	Up to 1200 x 2400 dpi			
Print Features	Application Defaults			
	Banner Sheet Enable / Disable Bi-directional Status			
	Custom Colour Options (Colour By Words)			
	Cover Selection			
	Delay Print (specific time) User Permissions			
	Image Options (Toner Saver, Resolution (Standard, Enhanced, High)			
	Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size)			
	Overlays			
	Paper Selection by Attribute LAN Fax (requires optional Fax Kit)			
	LAN Fax (requires optional Fax Kit) Sample Set			
	Saved Job (colour jobs can be printed as monochrome)			
	Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception p	ogges)		
	Store and Recall Driver Settings			
	Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off B	Banner and Print ID, Smart Sample	Set, Hold All Jobs)	
Print from USB	Allows walk-up printing from Type A USB port on front panel			
	Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS ⁴ , PCL			
	Colour jobs can be printed as monochrome			
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit)			
	Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit)			
	Windows Server 2012 and R2			
	Windows Vista SP2 (32- and 64-bit)			
	Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit)			
	Windows 8.1 (32- and 64-bit)			
	Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86			
	Ubuntu® 13.10 x64			
	openSUSE® 13.1 x64			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Prin	-)	
	NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk®)		
	Microsoft Windows Networking over IP			
	-			
	Bonjour® IPv6			
	Bonjour® IPv6 Secure FTP			

Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, 1	NTP. DNS. SSDP		
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts			
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.			
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade an consistent, easy-to-use interface for end-users, reducing the number of su	d manage Xerox® and non-Xerox devices from a single driver. It provides a pport calls, and simplifying print services management.		
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.			
Print Solutions				
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobil without burdening staff, budget or infrastructure. Getting started takes or brand of printer. Accurate printing with true Microsoft® Office® rendering	nly a few minutes via the cloud. Print from any mobile device to nearly any		
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have addition Mobile Print Solution allows users to print from most mobile devices to ne Simply enter a release code (PIN) at the device and get accurate printing for private, onsite deployment.	arly any brand of printer or MFP without drivers or added complexity.		
Unified Address Book for Fax, Inte	ernet Fax, Email and Scan to			
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.			
Scan	WorkCentre 7830 WorkCentre 7835	WorkCentre 7845 WorkCentre 7855		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan t concurrent jobs)	o network or fax jobs (priority is for return of scanned originals and printing		
Input Speed	Scan at up to 70 ipm colour scanning, up to 70 ipm black and white – $8.5x$ 11 in. / A4 LEF	Scan at up to 133 ipm colour scanning, up to 133 ipm black and white – $8.5 \ x$ 11 in. / A4 LEF		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)			
Maximum Scan Area	11 x 17 in. / A3			
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device clonin Confirmation sheet options	ig to other MFPs		
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS			
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression–single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Linearised PDF / PDF/A			
Document Management Fields (Meta Data)	 Features only available in Network Scan to File Templates: 1 to 6 user programmable metadata fields per network scan to file tem field name, default value and other configurations Customised fields viewed on user interface for variable data input 	plates and unlimited fields within the template – Metadata field consists of		
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)			
Scan to Email (Standard)				
Scan Features	 Email signatures (6 lines each of 128 character max), email message be Scan to Email S/MIME Encryption Email Signing (requires Smart Card option) Auto send to self 	ody (user configurable), email CentreWare IS confirmation sheet options		
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domi Downloaded address list (comma-separated file format) Utilises the Unified Address Book	no)		

Scan to (Standard)		
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)	
Network Scanning – Software Solu	tions	
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: • PaperPort Professional image viewing and file management software – Complete PDF functionality – Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability	
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.	
Xerox® ConnectKey® Share to Cloud (Optional)	ConnectKey Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs™, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.	
Xerox® ConnectKey® for DocuShare® (optional)	Xerox [®] ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).	
Security		
Features	 Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP Xerox Secure Access Unified ID System[®] Local Authentication (internal database) Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) /.NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted Password Protected PDF (when using Email and Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorisation SA access based on network credentials Authorisation per user per service User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPs, 802.1X, Cisco[®] TrustSec Identity Services Engine (ISE) integration, Device Security McAfee[®] Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 	
Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction printers with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions	
Fax		
Network Server Fax Features		
Compatibility	ITU (CCITT) group 3 Various Xerox Business Innovation Partner Solutions	
Maximum Scan Area	11 x 17 in. / A3	
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)	
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print	
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi	
Internet Fax Features		
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients	
Directory Access	Utilises the Unified Address Book	
Send / Receive	Multi-page TIFF, Image only PDF	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)	
Network Protocols	SMTP (send), POP3 (receive)	
Compliance	ITU-T T.37 compliant	

Walk-up Fax Features (Optional (C	ustomer-installable) – 1 and 2 lines)
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilising T38 (optional)
Compression / Speed	MH/G3, MMR/SG3
Resolution	Walkup Send:Standard: 200 x 100 dpiFine: 200 x 200 dpiSuperfine: 600 x 600 dpiReceive:Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report
Directory Access	Utilises the Unified Address Book Group fax available
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals
Auto Resend	Up to 5 attempts
Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. CentreWare Integration available for Tivoli® NetView[®], Unicentre TNG[®], Microsoft Management Console (MMC), HP[®] OpenView[®]
Novell NDPS/NEPS	Server gateway application: centralised management tool.
Xerox® Device Manager	 Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: Device monitoring and troubleshooting Extensive reporting and discovery of new devices Usage collection, chargeback and billing capabilities
Xerox [®] Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions

CentreWare Internet Services – Int	egrated Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS [«] , TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese
Remote Print Services	
Automatic Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time- consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replacement (ASR)	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries).
Accounting	
Xerox® Standard Accounting (Stand	dard)
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file
Accounting Options – Network Acc	ounting – Third Party Enablement
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface
EFI Fiery Network Controller (Optic	
Processor	2.9 GHz, Intel® Pentium® G850 Dual-Core
Memory (ESS) System Disk	1 GB 500 GB HDD
Print Languages (PDL)	PostScript v 3019
Features	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties PANTONE® Colour Tables Expert Colour Settings: Profile, Rendering and Simulation FreeForm – Variable Data capabilities Booklet Maker 4.0 – booklet wizard to create booklets Print from USB flash drive Paper Catalog Secure Erase EFI PrintMe
Connectivity	Fiery® VUE
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet
Optional	Mini-bundle (Spot On, Auto Trapping, Hot folders, Virtual Print) Network Switch to connect both printer and Fiery Controller to Network

Supplies				
Toner Cartridges (Sold)⁵	Black	26,000 pages	006R01517	
	Cyan	15,000 pages	006R01520	
	Magenta	15,000 pages	006R01519	
	Yellow	15,000 pages	006R01518	
Transfer Belt Cleaner	1 Assembly	160,000 pages	001R00613	
Second Bias Transfer Roll	1 Assembly	200,000 pages	008R13064	
Staple Cartridges	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964	
	for Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897	
	for Professional Finisher Booklet Maker (4 cartridges per carton)	5,000 each cartridge	008R12925	
Staple Refills	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941	
Xerox® Smart Kit®				
Drum Cartridge ⁶	1 Cartridge per Colour	125,000	013R00662	
Waste Toner Container ⁷	1 Cartridge	43,000	008R13061	

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ XPS option is required to print XPS files.

⁵ Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality setpoints.

 6 Average drum yield is based on a run length of 5 pages of 8.5 x 11 in. / A4 LEF pages, with split of 30% colour / 70% black and white pages.

⁷ Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office

xerox 🔊

©2014 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey®, Copier Assistant®, DocuShare®, Global Print Driver®, MeterAssistant®, Mobile Express Driver®, Scan to PC Desktop®, SmartKit®, SuppliesAssistant®, WorkCentre and Xerox Secure Access Unified ID System® are trademarks of Xerox Corporation in the United States and/or other countries. Mopria is a trademark of the Mopria Alliance. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR quidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. Updated 10/14 BR9497 W78SS-011H