

# Xerox® WorkCentre® 7800 Series Color Multifunction Printer

WorkCentre 7800 series multifunction systems are powered by the Xerox® ConnectKey™ Controller. These simple-to-implement systems give you real, practical solutions that easily streamline how you communicate, process and share important information, simplify complex paper-driven tasks, and drive down costs while keeping your data secure.



System Specifications	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855	
Speed					
Color / Black-and-white	Up to 30 / 30 ppm	Up to 35 / 35 ppm	Up to 45 / 45 ppm	Up to 50 / 55 ppm	
Monthly Duty Cycle <sup>1</sup>	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages	
Recommended Average Monthly Print Volume <sup>2</sup>	8,000 to 12,000 pages	10,000 to 15,000 pages	16,000 to 20,000 pages	18,000 to 22,000 pages	
Hard Drive / Processor / Memory	160 GB / 1.2 GHz Dual-core /	2 GB system plus 1 GB page m	nemory		
Connectivity	10/100/1000Base-T Ethernet,	High-Speed USB 2.0 direct print	r, Optional Wi-Fi (with Xerox® US	B Wireless Adapter)	
Controller Features	Unified Address Book, Remote	e Control Panel, Online Support	, Configuration Cloning		
Optional Controller	EFI Server				
Copy and Print					
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Pr	int: Up to 1200 x 2400 dpi			
First-print-out Time Color / Black-and-white	As fast as 9 / 7.7 seconds		As fast as 7.5 / 6.4 seconds	As fast as 7.1 / 5.9 seconds	
Page Description Languages	Adobe® PostScript® 3™, PDF, P	PCL® 5c / PCL 6, XML Paper Spe	cification (XPS®) (Optional)		
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring, Color By Words, Xerox® PrintBack				
Mobile Printing	Apple® AirPrint™, Xerox® Mobile Print® (Optional), Xerox® Mobile Print Cloud® (Optional)				
Scan					
Standard Features	Scan to Network, Scan to Email, Scan to Folder, Scan to SMB or FTP, Text Searchable PDF, PDF/A, XPS, Linearized PDF, JPEG, TIFF, Scan to USB Memory Device, Single Touch Scanning, TWAIN Support				
Optional Features	ConnectKey for SharePoint®, ConnectKey Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, numerous solutions available through various Xerox® Business Innovation Partners				
Fax					
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement (solutions available through various Xerox® Business Innovation Partners)				
Optional Features	Fax Forward to Email or SMB,	Walk-up Fax (one-line and two	-line options, includes LAN Fax)	)	
Security	Security				
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions				
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System® with Follow-You Printing®, Smart Card Enablement Kit (CAC/PIV/.NET)				
Accounting					
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email)				
Optional Features	Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox® Business Innovation Partners				

Device Specifications				
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan			
Accessories				
Optional	High Capacity Feeder (HCF) Envelope Tray (Replaces Tray 1) Integrated Office Finisher (optional with 7830/7835 only) Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Professional Finisher Convenience Stapler (includes Work Surface) Smart Card Enablement Kit Xerox Secure Access Unified ID System® (with USB Card Reader) with Follow-You Print™ EFI Fiery® Network Controller Walk up Fax (One- or Two-line options, includes LAN Fax) ScanFlowStore® Xerox® USB Wireless Adapter McAfee Integrity Control Enablement Kit XPS Print Option Kit			
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Acces and card readers.	ss Device, this is an interface	to third party access control de	vices, such as coin machines
Electrical Requirements				
North America		Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A		
Europe	Voltage: 220-240 VAC +/- 10 Frequency: 50/60 Hz +/- 3%,			
Power Consumption	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Running (Average)	643 watts	690 watts	763 watts	862 watts
Standby Mode	62 watts		112 watts	
Low Power Mode	59 watts		80 watts	
Auto Off / Sleep mode	4.2 watts (Default time to Sle	ep mode = 2 minutes)	4.8 watts (Default time to S	leep mode = 2 minutes)
Warm-up	194 seconds			
Low Power Recovery	< 9 seconds			
Operating Environment				
Required Temperature Range	50° to 82° F (10° to 28° C)			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating 6.8 B(A), Standby:	3.6 B(A)	,	
Sound Pressure Levels	Operating: 56 dB(A), Standby	r: 18 dB(A)	,	
Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration	41.9 in. / 1,064 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	321 lbs. / 146 kg
With Integrated Office Finisher (7830/7835 only)	44.4 in. / 1,129 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	348 lbs. / 158 kg
With Office Finisher LX (with Booklet Maker)	65.6 in. / 1,666 mm	27.9 in. / 709 mm	45.2 in. / 1,149 mm	403 lbs. / 183 kg
With Professional Finisher	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	526 lbs. / 239 kg
With Professional Finisher and High Capacity Feeder	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	590 lbs. / 268 kg

Certifications				
	CSA Listed (UL 60950-1, Se CB Certified (IEC 60950-1, Se ENERGY STAR® GOST NOM Environmental Choice CE Marked Common Criteria (IEEE 260 EPEAT GS Mark Citrix® Certified WHQL IPv6 Cerner MEDITECH SAP	Second Edition)		
Paper Handling	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Duplex Automatic Docume				
Capacity <sup>3</sup>	110 sheets		130 sheets (Single-pass D	
Speed	up to 70 image per minute (simplex)	black-and-white and color		e black-and-white and color (simplex) ute black-and-white and color (duplex)
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. /	A5 to A3		
Weights	16 lb. bond to 32 lb. bond /	50 gsm to 128 gsm		
Bypass Tray	T			
Capacity <sup>3</sup>	100 sheets			
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in. / 89 x 98 mm to 320 x 483 mm			
Weights	16 lb. bond to 110 lb. cover	/ 55 to 300 gsm		
Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Glossy Card Stock Plain Plain Reloaded Preprinted Recycled Transparencies	loaded tock tock Reloaded oaded ock		
3 Tray Module (Total 2,180	-	rkCentre 7830/7835 only)		
Capacity <sup>3</sup>	Trays 1-4: 520 sheets each			
Sizes			i. SEF / 140 x 182 mm to 297 ; n. SEF / 139.7 x 182 mm to SF	
Weights	16 lb. bond to 140 lb. index	: / 60 to 256 gsm		

Tunca	Dood
Types	Bond Card Stock
	Card Stock Reloaded
	Custom
	Glossy Card Stock
	Glossy Card Stock Reloaded
	Heavyweight Card Stock
	Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock
	Heavyweight Glossy Card Stock Reloaded
	Hole punched
	Labels
	Letterhead
	Lightweight Lightweight Card Stock
	Lightweight Card Stock Reloaded
	Lightweight Glossy Card Stock
	Lightweight Glossy Card Stock Reloaded
	Plain Plain Reloaded
	Preprinted
	Recycled
	Transparencies
High Capacity Tandem Tray	y (Total 3,140 sheets) (Available with all configurations)
Capacity <sup>3</sup>	Tray 1: 520 sheets
	Tray 2: 520 sheets
	Tray 3: 867 sheets Tray 4: 1,133 sheets
<u>c.</u>	
Sizes	Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm Tray 2: Custom Sizes from 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 140 x 182 mm to 320 x 458 mm
	Trays 3-4: Standard Sizes: 8.5 x 11 in. LEF / A4, JIS B5, Executive (7.25 x 10.5 in.)
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm
Types	Bond
	Card Stock
	Custom
	Glossy Card Stock Hole punched
	Labels
	Letterhead
	Lightweight Card Stock
	Lightweight Glossy Card Stock
	Piain   Preprinted
High Capacity Feeder (HCF)	
Capacity <sup>3</sup>	2000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. / A4 LEF
Weights	16 lb. bond to 140 lb. index / 55 to 256 gsm
Envelope Tray (Optional - R	eplaces Tray 1)
Capacity <sup>3</sup>	Up to 60 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm
Total Capacity	
Device Total Capacity <sup>3</sup>	5,140 sheets
	<u> </u>

Finishing					
Output Trays (Standard)	<u> </u>				
Stacking Trays <sup>3</sup>	Dual Offset Catch Tray – up to 250 sheets each				
	Left-side Face up Tray – up to 100 sheets				
Integrated Office Finisher					
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3				
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm				
Weights	16 lb. bond to 80 lb. cover / 60 to 256 gsm				
Stapling	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)				
Office Finisher LX (Optiona					
Capacity <sup>3</sup>	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)				
Sizes	7.2 x 8.3 in. to 11.7 x 17 in. / 182 x 210 mm to 297 x 432 mm				
Weights	16 lb bond to 80 lb cover / 60 to 256 gsm				
Multiposition Stapling	50 sheets of 24 lb. bond / 90 gsm				
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch				
Booklet Maker for Office Fi	nisher LX (Score/Crease, Saddle-stitch Staple) (Optional)				
Capacity <sup>3</sup>	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)				
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF				
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm				
Score / Crease	1-15 sheets / unstapled				
Professional Finisher (Optio	onal)				
Capacity <sup>3</sup>	Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled  Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 or 100 stapled sets of 11 x 17 in. / A3 / SRA3				
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling				
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm				
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported				
Hole Punch (Standard) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)				
Booklet Maker	Saddle-stitch 2 to 15 sheets (14 sheets of 90 gsm or less plus 1 sheet of 169 gsm) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, SRA3 supported				
Convenience Stapler (Option	onal)				
Capacity <sup>3</sup>	50-sheet stapling 5,000 staples Requires a separate outlet				

Сору	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
First-copy-out Time				
(Letter/A4-size, from Platen to Center Tray) (Color / Black-and-white)	As fast as 8.4 seconds / As fast as 6.7 seconds	As fast as 8.2 seconds / As fast as 6.8 seconds	As fast as 7.5 seconds / As fast as 6.2 seconds	As fast as 7.1 seconds / As fast as 5.5 seconds
Sides (input:output)	1-1, 1-2, 2-2, 2-1			
Quantity	1 to 9,999			
Resolution (max.)	Up to 600 x 600 dpi			
Reduction / Enlargement	Variable zoom from 25% to 4	400% in 1% increments		
Concurrency	Program-ahead to allow job t	o be initiated while initial job is	s processed (Copy, Print, Fax ar	nd Scan)
Copy Features	Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services (i.e. Color Copy) Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling			
Xerox® Copier Assistant®	conjunction with a customer- magnification and easy PC ke	<ul> <li>software provides a PC-base supplied PC attached via the U yboard access to basic and aderox® Copier Assistant for free,</li> </ul>	SB port, this software supports vanced copy features. Section	text-to-speech, screen
Print	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Print Resolution	Up to 1200 x 2400 dpi			
Print Features	Application Defaults Banner Sheet Enable / Disable Bi-directional Status Custom Color Options (Color By Words) Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute LAN Fax (requires optional Fax Kit) Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs TWAIN Print Driver			

Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT			
Operating Systems	Microsoft® Windows® XP (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS 10.5, 10.6, 10.7, 10.8 Solaris® 9, 10 HP-UX® 11v2 IBM® AIX® 5 Redhat® Fedora® Core 15-17 Redhat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix®			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled			
Administrative Protocols	DHCP, BOOTP, SNMP, WINS,	SLP® v2, HTTP, HTTPS, DHCP	Autonet, SSL, NTP, DNS, SSDI	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts			
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup> (X-MED)	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.			
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.			
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.			
Print Solutions				
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.			
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.			
Scan	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Concurrency	Scan while the system is prin scanned originals and printir		nsferring scan to network or fo	ax jobs (priority is for return of
Input Speed	Scan at up to 70 ipm color scanning, up to 70 ipm black- and-white – 8.5 x 11 in. / A4 LEF  Scan at up to 133 ipm color scanning, up to 133 ipm black-and-white – 8.5 x 11 in. / A4 LEF			
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)			
Maximum Scan Area	11 x 17 in. / A3			

Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options		
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS		
File Formats	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) JPEG XPS Encrypted / Password Protected PDF (Network Scan Templates only) Linearized PDF		
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates:  • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template  – Metadata field consists of field name, default value and other configurations  • Customized fields viewed on user interface for variable data input		
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Driver Bound Originals Edge Erase Reduction/Enlargement		
Supported Scan Destinations (Standard)	Scan to USB Drive Scan to Email Scan to PC / Server Client (SMB or FTP) Scan to Mailbox Scan to Secure FTP and HTTPS Scan to Home Scan to Application		
Supported Scan Destinations (Optional)	Xerox® Scan to PC Desktop® (Professional and SE) ScanFlowStore® Xerox® ConnectKey™ for SharePoint® Xerox® ConnectKey Share to Cloud Various Xerox® Business Innovation Partner Solutions		
Authentication	Supports Kerberos (UNIX / Windows Server) SMB (Windows Server) NDS LDAP Xerox® Secure Access Unified ID System® Locally on device (internal database) Convenience Authentication via Magstripe, Proximity and Smart Card (CAC / PIV and .NET) readers		
Scan to Email (Standard)			
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino)  Downloaded address list (comma-separated file format)		
Scan Features	<ul> <li>Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options</li> <li>Scan to Email S/MIME Encryption</li> <li>Email Signing (requires Smart Card option)</li> <li>Auto send to self</li> </ul>		
Network Scanning – Softwo	are Solutions		
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools:  • PaperPort Professional image viewing and file management software  - Complete PDF functionality  - Secure PDF workflow of all scanning applications  • OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion  • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability		

Xerox® ConnectKey™ for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.		
Xerox® ConnectKey Share to Cloud (Optional)	ConnectKey Share to Cloud provides organizations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs™, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.		
Security			
Features	<ul> <li>Expanded Authentication</li> <li>Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008), NDS, LDAP</li> <li>Xerox Secure Access Unified ID System®</li> <li>Local Authentication (internal database)</li> <li>Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET</li> <li>Secure Data</li> <li>Digitally signed PDF (when using Smart Card authentication)</li> <li>Encrypted Scan to Email</li> <li>Encrypted Password Protected PDF (when using Network Scan Templates only)</li> <li>Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>Immediate Image Overwrite</li> <li>On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>FIPS 140-2 256 bit Hard Disk Encryption</li> <li>Expanded Authorization</li> <li>SA access based on network credentials</li> <li>Authorization per user per service</li> <li>User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver</li> <li>Secure Network Access</li> <li>IP Filter, IPsec, IPv6, SSL, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec integration (optional), Device Security</li> <li>McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control (optional)</li> <li>Common Criteria Certification ISO 15408</li> </ul>		
Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System® integrates your Xerox® multifunction systems with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralized print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to <a href="https://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>		
Fax			
Network Server Fax Featur	es		
Compatibility	ITU (CCITT) group 3 Various Xerox® Business Innovation Partner Solutions		
Maximum Scan Area	11 x 17 in. / A3		
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Speed Dial, Delay Send (specific time) Original Type (photo, text or photo and text)		
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print		
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi		
Internet Fax Features			
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients		
Address Directory Access	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)		
Network Protocols	SMTP (send), POP3 (receive)		
Compliance	ITU-T T.37 compliant		

Walk-up Fax Features (Opt	ional (Customer-installable) – 1 and 2 lines)	
Compatibility	ITU (CCITT) Group 3	
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilizing T38 (optional)	
Compression / Speed	MH/G3, MMR/SG3	
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes	
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets Pstn Fax Device Address Book (up to 1,000 contacts)	
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Junk Fax Prevention Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay	
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only	
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report	
Auto Dialing	Speed Dials: 5,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts (per country requirements)  • 1 to 25 minute intervals  • Batch send (up to memory capacity)	
Device Management		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2	
Xerox® CentreWare® Web	Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®	
Novell NDPS/NEPS	Server gateway application: centralized management tool.	
Xerox® Device Mαnαger	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:  • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities	
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions	

Xerox® SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at <a href="https://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>	
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at <a href="https://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>	
CentreWare Internet Service	es – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller:  • Tray status/contents  • Consumables status  • Alerts	
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12	
Support	Install print / scan drivers and online support available via web page	
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese	
Remote Services		
MeterAssistant <sup>®</sup>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox of time.	
SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	
Accounting		
Xerox® Standard Accountin	g (Standard)	
Tracking	Copy, Print, Fax, Scan and Email usage	
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)	
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>	
Accounting Options – Netw	ork Accounting – Third Party Enablement	
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox® Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>WorkCentre requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>	
EFI Fiery Network Controlle	er (Optional)	
Processor	2.60 GHz, Intel® Pentium® Dual-core E5300	
Memory (ESS)	1 GB	
System Disk	160 GB	
Print Languages (PDL)	PostScript v 3019	

Features	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties PANTONE® Color Tables Expert Color Settings: Profile, Rendering and Simulation FreeForm – Variable Data capabilities Booklet Maker 4.0 – booklet wizard to create booklets Print from USB flash drive Paper Catalog Secure Erase EFI PrintMe Fiery® VUE				
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet				
Optional	Mini-bundle (Spot On, Auto Trapping, Hot folders, Virtu Network Switch	al Print)			
Supplies					
Toner Cartridges (Sold) <sup>4</sup>	Black	26,000 pages	006R01517		
	Cyan	15,000 pages	006R01520		
	Magenta	15,000 pages	006R01519		
	Yellow	15,000 pages	006R01518		
Transfer Belt Cleaner	1 Assembly	160,000 pages	001R00613		
Second Bias Transfer Roll	1 Assembly	200,000 pages	008R13064		
Staple Cartridges	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964		
	for Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897		
	for Professional Finisher Booklet Maker (4 cartridges per carton)	5,000 each cartridge	008R12925		
Staple Refills	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)  5,000 each refill 008R12941				
Smart Kits®					
Drum Cartridge	1 Cartridge per Color 125,000 <sup>4</sup> 013R00662				
Waste Toner Container	1 Cartridge	43,0004	008R13061		

 $<sup>^{\</sup>scriptsize 1}$  Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Our products allow use of papers certified by the FSC, PEFC and SFI, and those made with post consumer recycled content. For more information regarding our entire line of paper and specialty media, contact your Xerox® representative or visit us at www.xerox.com/supplies.

Return spent imaging supplies through the Xerox® Green World Alliance collection/reuse/recycling program. For more information, visit <a href="https://www.xerox.com/about-xerox/recycling">www.xerox.com/about-xerox/recycling</a>.

For more information, call **1-800-ASK-XEROX** or visit us at www.xerox.com/office



<sup>&</sup>lt;sup>2</sup> Expected regular monthly throughput

<sup>&</sup>lt;sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>&</sup>lt;sup>4</sup> Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% Black and white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.