

# Xerox<sup>®</sup> WorkCentre<sup>™</sup> 7525/7530/7535/7545/7556 **Multifunction System**



WorkCentre 7500 series shown with 1 Tray Option and Work Surface



WorkCentre 7500 series shown with 3 Tray Option



WorkCentre 7500 series shown with High Capacity Tandem Tray Option, Work Surface and Integrated Office Finisher<sup>1</sup>



WorkCentre 7500 series shown with High Capacity Tandem Tray Option, Work Surface and Office Finisher LX with **Booklet Maker Option** 



shown with High Capacity Tandem Tray Option, Work Surface and Professional Finisher

| System Specifications                  |   |                 |                 |                 |                 |
|--|---|-----------------|-----------------|-----------------|-----------------|
| Output Speed<br>(Printing and Copying) | WorkCentre 7525   | WorkCentre 7530 | WorkCentre 7535 | WorkCentre 7545 | WorkCentre 7556 |
| Colour                                 | Up to 25 ppm  | Up to 30 ppm    | Up to 35 ppm    | Up to 45 ppm    | Up to 50 ppm    |
| Black and White                        | Up to 25 ppm  | Up to 30 ppm    | Up to 35 ppm    | Up to 45 ppm    | Up to 55 ppm    |
| Functions                              |   |                 |                 |                 |                 |
| Standard                               | Copy, Print (Adobe® PostScript® 3™, PCL, XML Paper Specifications (XPS), PDF, Print from USB) Network Scanning (Scan to USB, Email, Mailbox, Network Folder, Home), Fax (Server Fax integration, Internet Fax), Data Security (Hard Disk encryption, Disk Overwrite), Network Accounting, EIP |                 |                 |                 |                 |
| Optional                               | Walk-up Fax (One- or Two-line), ScanFlowStore®, SMARTsend®, Xerox Secure Access Unified ID System®, Foreign Device Interface, Unicode Font Kit, Xerox Copier Assistant®, Scan to PC Desktop®, Work Surface, Integrated Finisher <sup>1</sup> , Convenience Stapler, EFI Fiery Network Server  |                 |                 |                 |                 |
| Specifications                         |   |                 |                 |                 |                 |
| Processor                              | 1.5 GHz   |                 |                 |                 |                 |
| Memory                                 | 2 GB system plus 1 GB page memory   |                 |                 |                 |                 |
| Hard Drive                             | 160 GB  |                 |                 |                 |                 |
| Connectivity                           | 10/100/1000 BaseT Ethernet<br>High-Speed USB 2.0<br>Wireless Ethernet 802.11b (via third-party adapters)  |                 |                 |                 |                 |
| USB Port                               | PC Interface for Xerox Copier Assistant via USB Type B port<br>Software upgrade via USB Type A port<br>USB Print and Scan   |                 |                 |                 |                 |
| Control Panel Languages                | Languages: (Select from 18 languages for user interface – International English, International French, Italian,<br>German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish,<br>Greek, Russian, Czech, Polish, Hungarian or Romanian)         |                 |                 |                 |                 |

| Сору  |  |                            |                            |                           |                           |
|---|--|----------------------------|----------------------------|---------------------------|---------------------------|
| <b>First-Copy-Out Time</b><br>(A4, from Platen to Centre<br>Tray) | WorkCentre 7525  | WorkCentre 7530            | WorkCentre 7535            | WorkCentre 7545           | WorkCentre 7556           |
| Colour  | As fast as<br>13.2 seconds   | As fast as<br>10.9 seconds | As fast as<br>11.0 seconds | As fast as<br>7.8 seconds | As fast as<br>7.2 seconds |
| Black and White   | As fast as<br>11.1 seconds   | As fast as<br>8.7 seconds  | As fast as<br>8.6 seconds  | As fast as<br>6.6 seconds | As fast as<br>5.8 seconds |
| Copy Specifications   |  |                            |                            |                           |                           |
| Sides (input:output)  | 1-1, 1-2, 2-2, 2-1   |                            |                            |                           |                           |
| Quantity  | 1 to 9,999   |                            |                            |                           |                           |
| Resolution (max)  | Scan at 600 x 600 dp   | i, output at 1200 x 240    | 0 dpi                      |                           |                           |
| Reduction/Enlargement   | Variable Zoom from 25  | 5% - 400% in 1% incre      | ments                      |                           |                           |
| Concurrency   | Programme-ahead to   | allow job to be initiate   | d while initial job is pro | cessed (Copy, Print, Fax  | and Scan)                 |
| Basic Copy Features<br>& Options                                  | Collation<br>Automatic 2-sided<br>Auto Reduction & Enlargement to fit selected paper size<br>Hole Punching<br>Booklet Creation<br>Stapling<br>Large Job Interrupt<br>Auto Paper Select<br>Authentication for Services (i.e. Colour Copy)<br>Auto Tray Switching<br>Features Help (Intuitive text and graphic descriptions)   |                            |                            |                           |                           |
| Imaging Copy Features   | <ul> <li>Image Quality:</li> <li>Original Type Selection: Photo &amp; Text, Photo, Text, Newspaper/Magazine, Inkjet Original, Maps.</li> <li>Image Options: Lighten/Darken, Sharpness, Saturation.</li> <li>Image Enhancement: Auto Background Suppression, Auto and Manual Contrast.</li> <li>Colour Effects: Off, Single Colour, Lively, Bright, Warm, Cool.</li> <li>Colour Balance: Normal, Basic Colour Balance, Advanced Colour Balance</li> <li>Book Copying/Bound Copying</li> <li>Edge Erase</li> <li>Single Colour</li> <li>Repeat Image</li> <li>Mixed Size Original</li> <li>Image Shift (with Auto Centre option)</li> <li>Image Shift Preset: Support for 3 Preset Options</li> <li>Annotation and Bates<sup>™</sup> stamping (with colour capability and font size adjustment)</li> </ul> |                            |                            |                           |                           |
| Output Copy Features  | Covers (Front only, front and back, back only, printed inside and out: Blank or Printed)<br>Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the<br>job is built)<br>Transparencies<br>Dividers (blank)<br>Multi-up (up to 15 columns by 15 rows)<br>Invert Image (negative or mirror image)<br>Sample Set<br>Job Settings<br>Save Job Settings   |                            |                            |                           |                           |
| Paper Handling  |  |                            |                            |                           |                           |
| Duplex Automatic Docume   | ent Feeder   |                            |                            |                           |                           |
| Capacity <sup>2</sup>   | 110 sheets   |                            |                            |                           |                           |
| Speed   | up to 70 images per n  | ninute black and white     | and colour                 |                           |                           |

| Paper Sizes Sensed         | A5 to A3   |  |
|----------------------------|--|--|
| Weights                    | 50 gsm to 128 gsm  |  |
| Bypass Tray                |  |  |
| Capacity <sup>2</sup>      | 100 sheets   |  |
| Sizes                      | Custom sizes up to 320 x 483 mm  |  |
| Weights                    | 55 to 300 gsm  |  |
| Types                      | Plain<br>Bond<br>Lightweight<br>Heavyweight<br>Extra Heavyweight<br>Extra Heavyweight Plus<br>Gloss<br>Heavyweight Gloss<br>Extra Heavyweight Gloss<br>Extra Heavyweight Gloss<br>Itabels<br>Transparencies<br>Custom<br>Envelopes |  |
| 1 Tray Option (Includes Tr | ay 1 and Tray 2)   |  |
| Capacity <sup>2</sup>      | Tray 1: 520 sheets<br>Tray 2: 520 sheets   |  |
| Sizes                      | Tray 1: Custom Sizes from 140 x 182 mm to 297 x 432 mm SEF<br>Tray 2: Custom Sizes from 140 x 182 mm to 320 x 457 mm SEF   |  |
| Weights                    | 60 to 256 gsm  |  |
| Types                      | Plain<br>Bond<br>Heavyweight<br>Extra Heavyweight<br>Gloss<br>Heavyweight Gloss<br>Labels<br>Transparencies<br>Custom  |  |
| 3 Tray Option (Includes Tr | ays 1-4)   |  |
| Capacity <sup>2</sup>      | Trays 1-4: 520 sheets each tray  |  |
| Sizes                      | Tray 1: Custom Sizes from 140 x 182 mm to 297 x 432 mm SEF<br>Trays 2-4: Custom Sizes from 140 x 182 mm to 320 x 457 mm SEF  |  |
| Weights                    | 60 to 256 gsm  |  |
| Types                      | Plain<br>Bond<br>Heavyweight<br>Extra Heavyweight<br>Gloss<br>Heavyweight Gloss<br>Labels<br>Transparencies<br>Custom  |  |

| High Capacity Tandem Tray   | y Option   |  |
|-----------------------------|--|--|
| Capacity <sup>2</sup>       | Tray 1: 520 sheets<br>Tray 2: 520 sheets<br>Tray 3: 867 sheets<br>Tray 4: 1,133 sheets   |  |
| Sizes                       | Tray 1: Custom Sizes from 140 x 182 mm to 297 x 432 mm SEF<br>Tray 2: Custom Sizes from 140 x 182 mm to 320 x 457 mm SEF<br>Trays 3-4: Standard Sizes: A4 LEF  |  |
| Weights                     | 60 to 256 gsm  |  |
| Types                       | Plain<br>Bond<br>Heavyweight<br>Extra Heavyweight<br>Gloss<br>Heavyweight Gloss<br>Labels<br>Transparencies<br>Custom  |  |
| High Capacity Feeder (HCF   | ) (Optional with 3 Tray Option or High Capacity Tandem Tray Option)  |  |
| Capacity <sup>2</sup>       | 2000 sheets  |  |
| Sizes                       | Standard Sizes: A4 LEF   |  |
| Weights                     | 55 to 256 gsm  |  |
| Envelope Tray (Optional - R | Replaces Tray 1)   |  |
| Capacity <sup>2</sup>       | Up to 60 envelopes   |  |
| Sizes                       | DL, C5, Custom sizes: 99 x 147 mm to 163 x 241 mm  |  |
| Weights                     | 75 to 90 gsm   |  |
| Total Capacity              |  |  |
| Device Total Capacity       | 5,140 sheets   |  |
| Paper Output / Finishing    |  |  |
| Output Trays (Standard)     |  |  |
| Stacking Trays <sup>2</sup> | Dual Offset Catch Tray – up to 250 sheets each<br>Left-side Face up Tray – up to 100 sheets  |  |
| Output- Integrated Office   | Finisher (Optional with 7525/7530/7535)  |  |
| Stacking Tray               | 500 sheets of 80 gsm A4 or 250 sheets of 80 gsm A3   |  |
| Sizes                       | 89 x 98 mm to A3   |  |
| Weights                     | 60 to 220 gsm  |  |
| Stapling                    | Single<br>Auto stapling:<br>50 sheets maximum: A4/B5-size sheets (less than 90 gsm or 2 sheets of 220 gsm covers)<br>30 sheets maximum: A3/B4-size sheets (less than 90 gsm or 2 sheets of 220 gsm covers) |  |
| Office Finisher LX (Optiona |  |  |
| Capacity <sup>2</sup>       | Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (A4)   |  |
| Sizes                       | 182 x 210 mm to A3   |  |

| Weights   | 60 to 220 gsm  |  |  |
|---|--|--|--|
| Multi Position Stapling                           | 50 sheets of 90 gsm  |  |  |
| Hole Punch (Optional)                             | 2-4 Hole Punch   |  |  |
| Booklet Maker for Office I                        | Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional)  |  |  |
| Capacity  | 40 booklets (2-15 sheets per booklet – 80 gsm or less)   |  |  |
| Sizes   | A4 SEF<br>216 x 356 mm SEF<br>A3 SEF   |  |  |
| Saddle-stitch Stapling                            | 2-15 sheets / 8 – 60 page booklet<br>60 to 90 gsm  |  |  |
| Score/Crease                                      | 1-15 sheets / unstapled  |  |  |
| Professional Finisher (Opt                        | ional)   |  |  |
| Capacity <sup>2</sup>                             | Top Tray: 500 sheets of A4 unstapled<br>Stacking Stapling Tray: 1,500 sheets of A4/A3/SRA3 unstapled or 200 stapled sets of A4/100 stapled sets<br>of A3/SRA3  |  |  |
| Sizes   | B5 to SRA3   |  |  |
| Weights   | 60 to 220 gsm  |  |  |
| Stapling  | Single<br>Auto stapling (50 sheets maximum) – 90 gsm<br>A3, A4, B4 and B5 sizes supported  |  |  |
| Hole Punch  | 2-4 Hole Punch (Standard)<br>Swedish 4-Hole Punch (Optional)   |  |  |
| Booklet Maker                                     | Saddle-stitch up to 15 sheets (One 169 gsm cover plus fourteen 90 gsm sheets)<br>V-fold up to 5 sheets<br>A3, A4, SRA3 supported   |  |  |
| Convenience Stapler (Opt                          | ional)   |  |  |
| Capacity <sup>2</sup>                             | 50-sheet stapling<br>5,000 staples<br>Requires a separate outlet   |  |  |
| Print   |  |  |  |
| Print Controller                                  |  |  |  |
| Page Description<br>Languages (PDL)<br>(Standard) | PCL <sup>®</sup> 6<br>PCL <sup>®</sup> 5c<br>Adobe <sup>®</sup> PostScript <sup>®</sup> 3 <sup>™</sup><br>PDF<br>XPS <sup>®</sup><br>HP-GL2 <sup>™</sup><br>TIFF   |  |  |
| Print resolution                                  | <ul> <li>Print Engine: up to 1200 x 2400 dpi</li> <li>Toner Saver - 600 x 600 dots per inch, with limits on maximum saturation.</li> <li>Standard - 600 x 600 dots per inch with 256 halftone levels.</li> <li>Enhanced - Raster image processing at 600 x 600 dots per inch with eight bits per pixel. Halftone creation with resolution enhancement and LED marking at 1200 x 2400 dots per inch with 256 halftone levels.</li> <li>High Resolution - 1200 x 1200 dots per inch with 256 halftone levels.</li> </ul> |  |  |

| Print Feαtures            | Application defaults<br>Banner Sheet enable/disable<br>Bi-directional status<br>Colour Options<br>• Automatic Colour<br>• Vivid Colour<br>• Black and White<br>• Custom Colour Options<br>• Colour By Words<br>• Colour Correction (allows for different RGB, CMYK,<br>Spot and other specifications)<br>• Colour Adjustments (Lightness, Contrast,<br>Saturation, Colour cast)<br>Cover selection<br>Delay Print (specific time)<br>Duplex (2-sided)<br>Enhanced Gloss at normal speed<br>User Permissions required to access Print and Print<br>Features (e.g. colour access, or time restrictions)<br>reflects in the print driver<br>Finishing<br>• Multiple stapling positions<br>• Hole punch<br>• Booklet creation<br>• Fit to new paper size<br>• Saddle stitch with Professional Finisher<br>• Output tray selections<br>• Store and recall driver setting Inserts and exception<br>pages<br>Image Options<br>• Toner Saver<br>• Resolution options (Standard, High resolution,<br>Enhanced, Toner Saver)<br>• Reduction/Enlargement<br>• Rotate 180 degrees<br>• Margins | Job identification (Print ID or Banner, Print ID in<br>margins on first page only or all pages)<br>Job Type<br>• Secure, Sample, Delay, Save<br>Layout/Watermark (N-up (16) / Multi-up, Booklet<br>Layout / Finishing, Fit to new paper size)<br>Margins<br>Mirror image<br>N-up<br>Overlays<br>Paper selection by attribute<br>Print calibration<br>Print to Fax (requires optional Fax kit)<br>Sample Set<br>Scaling<br>Secure Print<br>Special Pages (exception page programming<br>(covers, inserts, exception pages)<br>Store and Recall driver settings<br>Store file in folder<br>Sustainablity features<br>• Xerox Earth Smart settings<br>• Duplex<br>• N-up<br>• Turn-off banner and print ID on document<br>• Smart Sample set<br>• Hold All Jobs<br>Transparency separators |
|---------------------------|--|---|
|                           | Mirrored output  |   |
| Print from USB            | Allows walk-up printing from Type A USB port on front p<br>Supports direct printing from computer via Type B USB   |   |
| Print Protocols and Netwo | 'ks  |   |
| Operating Systems         | Microsoft Windows XP (32- and 64-bit), Windows Server<br>Windows Vista (32- and 64-bit), Windows 7 (32- and 64<br>Mac OS 10.4 (PPD only)<br>Mac OS 10.5-10.6 (PostScript only)<br>Solaris 9, 10<br>HP UX 11, 11i<br>AIX 5<br>Linux RedHat Fedora Core 1-7<br>Linux RedHat Enterprise Linux 4<br>SUSE 10.X  |   |
| Network Protocols         | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPI<br>NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with<br>AppleTalk® EtherTalk®<br>Microsoft Windows Networking over IP<br>(Most protocols not in use can be disabled)<br>Bonjour IPv6<br>Secure FTP  |   |
| Administrative Protocols  | DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RAR  | P, DHCP Autonet, SSL, NTP   |
| Fonts                     | PCL: 94 scalable fonts, line printer and bitmap font (including Cyrillic font support)<br>PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts  |   |

| Xerox Mobile Express<br>Driver <sup>®</sup> (X-MED) | Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location.<br>Plug into a new network, and X-MED automatically discovers available printers and provides status and<br>capability information. Save a list of "favourite" printers for each location, store application print settings for use<br>on any printer in any network, and greatly reduce mobile support calls to IT.<br>• Printers are automatically discovered<br>• Printer list can be managed based on location<br>• Gives bi-directional feedback device status, supplies, queue management   |  |
|---|---|--|
| Xerox Global Print Driver®<br>(X-GPD)               | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox<br>devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of<br>support calls, and simplifying print services management.<br>• Lets IT managers qualify, deploy and manage all print devices on the network using a single driver<br>• Fast and easy installation of new devices improves IT efficiency<br>• Truly universal print driver supports Xerox and non-Xerox printers, PCL and PostScript<br>• Gives bi-directional feedback device status, supplies, queue management |  |
| Scan  |   |  |
| Concurrency   | Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)  |  |
| Input Speed   | Scan at up to 70 ipm colour scanning, up to 70 ipm black and white – A4 LEF   |  |
| Resolution  | 600 x 600 dpi<br>400 x 400 dpi<br>300 x 300 dpi<br>200 x 200 dpi<br>150 x 150 dpi<br>100 x 100 dpi<br>72 x 72 dpi<br>Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)   |  |
| Maximum Scan Area                                   | A3  |  |
| Scan Template<br>Management                         | Support 250 scan templates<br>Create device specific CentreWare scan templates<br>Select confirmation sheet options<br>Share scan templates via device cloning  |  |
| Network Protocol                                    | FTP via TCP/IP<br>Microsoft SMB via TCP/IP<br>Netware, HTTP and HTTPS   |  |
| File Formats  | Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW)<br>Black and White TIFF (G3MH, G4 MMR compression - single or multiple pages)<br>PDF or PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for B/W<br>and within MRC))<br>JPEG<br>XPS<br>Searchable PDF, PDF/A, XPS<br>Encrypted / Password Protected PDF (for Workflow Scanning)<br>Linearised PDF   |  |
| Document Management<br>Fields (Metadata)            | <ul> <li>Features only available in Network Scan to File Templates:</li> <li>1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata Field consists of field name, display at the LUI or not, default value and other configurations</li> <li>Customised fields viewed on user interface</li> <li>Variable data entered using virtual keyboard at device</li> </ul>  |  |
| Scan Features                                       | Mixed size originals<br>Bound originals<br>Edge erase<br>Reduction/enlargement<br>Scan Build Job<br>Compression Quality/File Size Control<br>Original type (photo and text, photo, text, map, newspaper/magazine)<br>Auto Background and Shadow Suppression<br>Size for size (for mixed size originals)   |  |

|   | 1  |  |
|---|--|--|
| Supported Scan<br>Destinations (Standard)           | Scan to network server<br>Scan to USB Drive<br>Scan to Email<br>Scan to client (SMB or FTP)<br>Scan to Mailbox<br>Scan to Secure FTP<br>Scan to Home   |  |
| Supported Scan<br>Destinations<br>(Optional)        | Scan to application<br>Scan to Microsoft Exchange 2000 Web Folders<br>Scan to PC Desktop (Professional and SE)<br>SMARTsend<br>ScanFlowStore<br>ScanSoft PaperPort<br>ScanSoft OmniPage<br>Various Xerox Alliance Partner Solutions  |  |
| Scan to USB   | Supports walk-up scan to USB via Type A USB port   |  |
| Authentication                                      | Authentication mechanism<br>• Network ID<br>- Supports Kerberos (UNIX / Windows Server 2003 / Windows Server 2008)<br>- SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008)<br>- NDS<br>- LDAP<br>• Xerox Secure Access Unified ID System <sup>®</sup><br>• Locally on device (internal dababase)   |  |
| Scan to Email (Standard)                            |  |  |
| Directory Access                                    | Address list via LDAP (Exchange/Notes/Domino)<br>Downloaded address list (comma-separated file format)   |  |
| Scan Features                                       | Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options<br>Auto send to self   |  |
| Network Scanning – Softw                            | are Solutions  |  |
| Xerox Scan to PC Desktop<br>Professional (optional) | <ul> <li>A desktop offering that provides advanced document imaging, archiving, editing and organisation tools:</li> <li>Nuance PaperPort Professional image viewing and file management software: <ul> <li>Complete PDF functionality</li> <li>Secure PDF workflow of all scanning applications</li> </ul> </li> <li>Nuance OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion</li> <li>Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes email inbox polling capability</li> </ul>   |  |
| Xerox SMARTsend®<br>(optional)                      | <ul> <li>Server based document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per server):</li> <li>Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery</li> <li>Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary)</li> <li>Scan to File Destinations: email, Novell NetWare folder, network folder, SMB folder, FTP, Microsoft Exchange 2000 Web folders, Web URL, remote printers</li> <li>Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint</li> <li>Workflow initiation via device scanning user interface (template selection at device user interface)</li> </ul> |  |
| Xerox SMARTsend<br>Professional (optional)          | Everything in Xerox SMARTsend, plus:<br>• Workflow initiation via Paperware (Scan cover sheets)<br>• Server-based Optical Character Recognition (OCR)<br>• Adding Metadata<br>• Scan to Internet fax file destination  |  |

| Security  |   |   |
|---|---|---|
| Feαtures  | <ul> <li>Expanded Authentication <ul> <li>Network authentication to access device and/or device services via: <ul> <li>Kerberos (UNIX / Windows Server 2003 / Windows Server 2008)</li> <li>SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008)</li> <li>NDS</li> <li>LDAP</li> </ul> </li> <li>Xerox Secure Access</li> <li>Local Authentication (internal database)</li> <li>Secure Data</li> <li>Password Protected PDF (via Workflow scanning; not Scan to Email)</li> <li>Secure Print (up to 10 digits PIN)</li> <li>Immediate Image Overwrite</li> <li>On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>256 bit Hard Disk Encryption</li> </ul></li></ul> | <ul> <li>Expanded Authorisation <ul> <li>SA access based on network credentials</li> <li>Authorisation per user per service</li> <li>User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver</li> </ul> </li> <li>Secure Network Access <ul> <li>IP Filter</li> <li>IPSec</li> <li>IPv6 Ready</li> <li>Secure print-channel encryption with IPSec</li> <li>Secure Web Page via SSL</li> <li>Secure Web Page via SSL</li> <li>Secure web interface via HTTPs</li> <li>802.1X</li> </ul> </li> <li>Device Security <ul> <li>Port disablement including USB ports</li> <li>FIPS 140-2 Compliant Encryption</li> <li>Audit Log</li> <li>Hide Print Job Names</li> <li>Secure Print Separate Queue</li> <li>My Jobs view</li> <li>Common Criteria EAL3 certification (pending)</li> </ul> </li> </ul> |
| Xerox Secure Access<br>Unified ID System®<br>(Optional) | The Xerox Secure Access Unified ID System USB card re<br>Authentication Device (also known as the flat box cont<br>device controller eliminating the need for a second IP of<br>device functionality. The plug-ins are available at the X<br>WorkCentre 7500 series download pages on <b>www.xero</b><br>Secure Access is compatible with Scan to Home.   | croller). The USB card reader connects directly to the address. Device plug-ins must be installed to enable the<br>ferox Secure Access Unified ID System and  |
| Fax   |   |   |
| Network Server Fax Featur                               | es  |   |
| Compatibility   | ITY (CCITT) group 3<br>Various Xerox Alliance Partner Solutions   |   |
| Maximum Scan Area                                       | A3  |   |
| Fax Send Features                                       | One- or two-sided scanning (up to A3)<br>Phone number entry<br>Add to send list (50 numbers maximum)<br>Delay send (specific time)<br>Original type (photo, text or photo and text)<br>Build Job<br>Speed Dial  |   |
| Fax Print Features                                      | One- or two-sided printing<br>Staple on/off<br>Secure print on/off  |   |
| Transmission Resolution                                 | Superfine - 400 x 200 dpi (Scan at 600 x 600 dpi)<br>Fine - 200 x 200 dpi<br>Standard - 200 x 100 dpi   |   |
| Fax Options – Internet Fax                              | (Standard)  |   |
| Capability  | Direct print-ready document transmission to remote In<br>Reception and automatic printout of documents sent v<br>clients  |   |
| Address Directory Access                                | Send: Multi-page TIFF, PDF, PDF/A<br>Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JF   | PEG   |

| Resolution                | 600 x 600 dpi<br>400 x 400 dpi<br>300 x 300 dpi<br>200 x 200 dpi<br>200 x 100 dpi<br>150 x 150 dpi<br>100 x 100 dpi<br>72 x 72 dpi<br>Bit Dept: 1-bit (black and white)   |
|---------------------------|---|
| Network Protocols         | SMTP (send)<br>POP3 (receive)   |
| Compliance                | ITU-T T.37 compliant  |
| Fax Options – Walk-up Opt | tion - One or Two line (Optional; Customer installable)   |
| Compatibility             | ITY (CCITT) Group 3   |
| Speed/Modems              | One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time<br>ISDN via third-party adapter  |
| Compression/Speed         | MH/G3, MMR/G4   |
| Fax Send Features         | LAN Fax (fax from print driver)<br>Auto fax transmission reduction<br>Page-by-page job status at the machine<br>Delay start<br>Automatic memory resend<br>Automatic cover sheets<br>Broadcast<br>Booklet Scan<br>PSTN Fax<br>Build Job<br>Speed Dial<br>Searchable Dial Directory                   |
| Fax Receive Features      | One- or two-sided printing<br>Stapled or unstapled, hole punch<br>Receive print mode – Manual (size, margin, stock, header) / Auto<br>Output tray selection<br>Junk Fax prevention<br>Up to 200 password protected mailboxes  |
| Fax Forward               | Forward to Email or SMB Location<br>Fax forward on receive only   |
| Fax Reports               | Activity<br>Dial directory<br>Group directory<br>Transmission confirmation<br>Pending fax<br>Options report<br>On demand overwrite report   |
| Auto Dialing              | Speed Dials:         1,000 total (one- or two-line options)         Group Dials:         Up to 200 groups with up to 400 recipients per group (one- or two-line options)         Auto Redial:         Up to 14 attempts         1 to 25 minute intervals         Batch send (up to memory capacity) |

| Device Management   |  |
|---|--|
| Management Support  | SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP<br>MIB access (IETF-MIBII RFC 1213), Host Resources<br>MIB RFC 2790, Printer MIB RFC 1759 v.2   |
| Xerox CentreWare® Web   | <ul> <li>A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:</li> <li>Works with any SNMP-managed printer from any manufacturer.</li> <li>Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>Requires Windows XP, 2000 (Professional or Advanced Server) or Windows 2003 and Internet Explorer 6.0 and higher</li> </ul>   |
| Xerox CentreWare<br>for Tivoli® NetView®  | Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by Tivoli NetView   |
| Novell NDPS/NEPS  | Server gateway application: centralised management tool  |
| Xerox CentreWare®<br>for Unicenter TNG®   | Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View  |
| Xerox CentreWare®<br>for Microsoft<br>Management Console<br>(MMC)   | CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.  |
| Xerox CentreWare<br>for HP° OpenView°   | Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed<br>by HP Openview<br>Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare<br>Internet Services for device management directly from OpenView   |
| Xerox Device Manager  | <ul> <li>Xerox Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox Device Manager provides:         <ul> <li>Device monitoring and troubleshooting</li> <li>Extensive reporting and discovery of new devices</li> <li>Usage collection, chargeback and billing capabilities</li> </ul> </li> </ul>   |
| Xerox Device Types for<br>SAP R/3 Environment<br>Information<br>available at www.<br>xeroxofficesapsolutions.<br>com              | <ul> <li>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):</li> <li>One- to two-sided printing</li> <li>Finishing provides single or dual stapling</li> <li>Tray pull location from any tray</li> <li>Number of copies – provide the ability to print multiple copies</li> <li>Paper Type and Colour – provide ability to select different paper types and paper colours, such as transparency, red, etc.</li> <li>Print security via PIN ID capability</li> <li>Network Accounting – Provides capability to add Network Accounting User IDs to SAP print jobs</li> <li>Printer banner sheet – Provide the ability to enable/disable printer banner sheets</li> <li>Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net.</li> <li>Unicode Font Kit</li> </ul> |
| Xerox SAP R/3<br>Intelligent Barcode<br>Utility (optional)<br>Information<br>available at www.<br>xeroxofficesapsolutions.<br>com | Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured<br>PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only.<br>Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Centre Barcode<br>Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data<br>string and data compression.  |

| Xerox Barcode Pro PS<br>(optional)                                  | Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and   |  |  |
|---|--|--|--|
| Information<br>available at www.<br>xeroxofficesapsolutions.<br>com | middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode throug 90 or 270 degrees.  |  |  |
| CentreWare Internet Servi   | ices – Integrated Web Pages Provided by the Device   |  |  |
| Device Status   | Web server embedded in Network Controller:<br>• Tray status/contents<br>• Consumables status<br>• Alerts   |  |  |
| Job Submission  | Print ready files: PS, PCL, TIFF, PDF, JPG, XPS <sup>®</sup><br>Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output<br>destination)<br>Delivery options (Immediate, sample set, delay and secure, Save job or reprint)   |  |  |
| Device Administration   | Allows simple, remote installation setting of configuration options and management of the device   |  |  |
| Browsers  | Netscape 7.x, 9.x<br>Internet Explorer 6.x, 7.x, 8.x<br>Safari 3.0-3.2, 4.0.3<br>Mozilla Firefox 2.x, 3.5, 3.6.3<br>Opera 9.x, 10<br>Chrome 1.0, 4.1, 5.x  |  |  |
| Support   | Install print/scan drivers and online support available via web page   |  |  |
| Languages Supported   | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian   |  |  |
| Smart eSolutions  |  |  |  |
| MeterAssistant <sup>®</sup>   | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage.<br>Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to<br>Xerox on time.<br>Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.   |  |  |
| Online Support Assistant  | Xerox Online Support keeps you up and running by providing instant access to searchable online help right<br>at the WorkCentre 7500 series multifunction system's front panel. You get the same information our Product<br>Support Specialists use when resolving printer problems, assisting with error codes, print quality, media jams,<br>software installation and more.  |  |  |
| EFI Fiery Network Server  | vith System Software 9e (Optional)   |  |  |
| Processor   | 2.66 GHz, Intel Core 2 Duo E5300   |  |  |
| Memory (ESS)  | 1 GB   |  |  |
| System Disk   | 160 GB   |  |  |
| Print Languages (PDL)   | PostScript v 3019  |  |  |
| Features  | Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management<br>Job Preview<br>Job Merge<br>Change Job Properties<br>Pantone Colour Tables<br>Expert Colour Settings: Profile, Rendering and Simulation<br>ColorWise Pro Tools – calibration support, colour editor, profile manager<br>FreeForm – Variable Data capabilities<br>Booklet Maker 4.0 – booklet wizard to create booklets<br>Print from USB flash drive<br>Secure Erase |  |  |
| Connectivity  | 10 Base-T/100 Base-TX/1000 Base-T Ethernet   |  |  |

| Optional                                     | SeeQuence Suite (Impose & Compose)<br>Mini-bundle (Spot On, Auto Trapping, Hot folders, Virtual Print)<br>A la Carte Spot On, Auto Trapping, Hot folder/Virtual Printers)  |  |  |  |
|--|--|--|--|--|
| Accounting                                   |  |  |  |  |
| Accounting – Xerox Stand                     | ard Accounting (Standard)  |  |  |  |
| Tracking                                     | Copy, Print, Fax and Scan usage  |  |  |  |
| Accounting                                   | Up to 2,500 User accounts (User ID)<br>Up to 500 General accounts (Client)<br>Up to 500 Group accounts (Department)  |  |  |  |
| Features                                     | Enable/disable via the Web User Interface or the device control panel in tools<br>Administrator can manage the feature remotely via the Web User Interface<br>Data can be exported via a CSV file<br>Supports entering Xerox Standard Accounting ID into the print driver when submitting a print job  |  |  |  |
| Accounting Options – Net                     | work Accounting – Third Party Enablement   |  |  |  |
|  | <ul> <li>Enhanced network accounting with up to the minute data on how the WorkCentre system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scar and server fax</li> <li>Various options are available through Xerox Alliance Partner solutions. For details visit www.xerox.com</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>WorkCentre requests account authentication from 3rd-party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to 3rd party Networking Account</li> <li>Interface with 3rd party accounting terminal for accounting user interface</li> </ul> |  |  |  |
| Device Specifications                        |  |  |  |  |
| Monthly Duty Cycle                           |  |  |  |  |
|  | WorkCentre 7525: up to 75,000 pages/month<br>WorkCentre 7530: up to 90,000 pages/month<br>WorkCentre 7535: up to 110,000 pages/month<br>WorkCentre 7545: up to 200,000 pages/month<br>WorkCentre 7556: up to 300,000 pages/month   |  |  |  |
| Accessories                                  |  |  |  |  |
| Optional                                     | One tray Module<br>Three Tray Module<br>High Capacity Tandem Tray<br>High Capacity Feeder<br>Envelope Tray (Replaces Tray 1)<br>Integrated Office Finisher (optional with 7525/7530/7535 only)<br>Office Finisher LX<br>Booklet Maker for Office Finisher LX<br>Hole Punch for Office Finisher LX<br>Hole Punch for Office Finisher LX<br>Professional Finisher<br>Convenience Stapler<br>Work Surface<br>Secure Access Unified ID System® (with USB Card Reader)<br>EFI Fiery Network Server<br>Foreign Device Interface<br>Xerox Copier Assistant®<br>Walk up Fax (One- or Two-line options, includes LAN Fax)<br>Xerox Scan to PC Desktop®<br>ScanFlowStore®<br>Xerox Unicode International Print Kit<br>Mobility Plate<br>SMARTsend                          |  |  |  |
| Foreign Device Interface<br>(FDI) (Optional) | Interface to third party access control devices, coin machines, card readers<br>Support a variety of vending stations available through the Xerox Alliance Partner Solutions   |  |  |  |

| Accessibility Option                                   | Xerox Copier Assistant <sup>®</sup> (XCA) Software provides a PC-based alternative to the user interface touch screen. Used<br>in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech,<br>screen magnification and easy PC keyboard access to basic and advanced copy features.<br>Section 508 compliant. For more information, visit <b>www.xerox.com</b> . |        |          |        |  |
|--|---|--------|----------|--------|--|
| Electrical Requirements                                | 1   |        |          |        |  |
| Europe   | Voltage : 220-240 VAC +/- 10 %<br>Frequency: 50/60 Hz +/- 3 % , 10 A<br>Power Consumption: 1.203 KVA maximum printing continuously (240V), 1.760 KVA maximum printing<br>continuously (220V)  |        |          |        |  |
| Power Consumption (Base                                | IOT)  |        |          |        |  |
| Running (Average)                                      | 984 watts/hour  |        |          |        |  |
| Standby Mode   | 130 watts/hour  |        |          |        |  |
| Low Power Mode   | 82 watts/hour   |        |          |        |  |
| Auto Off / Sleep mode                                  | 9.1 watts/hour (Default time to Sleep mode = 2 minutes)   |        |          |        |  |
| Low Power Recovery                                     | < 9 seconds   |        |          |        |  |
| Operating Environment                                  |   |        |          |        |  |
| Required Temperature<br>Range                          | 10° to 28° C  |        |          |        |  |
| Required Relative<br>Humidity                          | 15% to 85%  |        |          |        |  |
| Sound Power Levels                                     | Operating 7.5 B(A), Standby: 3.6 B(A)   |        |          |        |  |
| Sound Pressure Levels                                  | Operating: 58 dB(A), Standby: 18 dB(A)  |        |          |        |  |
| Dimensions and Weight                                  | Width   | Depth  | Height   | Weight |  |
| Base Configuration                                     | 1,064 mm  | 685 mm | 1,127 mm | 140 kg |  |
| With Integrated Office<br>Finisher                     | 1,129 mm  | 685 mm | 1,127 mm | 152 kg |  |
| With Office Finisher LX<br>(with Booklet Maker)        | 1,666 mm  | 695 mm | 1,127 mm | 177 kg |  |
| With Professional Finisher                             | 1,922 mm  | 685 mm | 1,127 mm | 228 kg |  |
| With Professional Finisher<br>and High Capacity Feeder | 1,922 mm  | 685 mm | 1,127 mm | 256 kg |  |
| Certifications   |   |        |          |        |  |
|  | FCC Class A Compliant (US), ICES Class A Compliant (Canada)<br>TUV Listed (UL 60950-1, Second Edition)<br>CB Certified (IEC 60950-1, Second Edition)<br>2006/95/EC (Europe)   |        |          |        |  |

2006/95/EC (Europe) 2005/32/EC (Europe) 2004/108/EC (Europe) 199/5/EC (Europe) ENERGY STAR® GOST NOM Blue Angel Environmental Choice CE Certification Common Criteria certified (EAL3)<sup>3</sup>

| Supplies                      | Description   | Yield                | Order Number |
|-------------------------------|---|----------------------|--------------|
| Toner Cartridges<br>(Metered) | Black   | 26,0004              | 006R01509    |
|                               | Cyan  | 15,0004              | 006R01512    |
|                               | Magenta   | 15,0004              | 006R01511    |
|                               | Yellow  | 15,0004              | 006R01510    |
| Toner Cartridges (Sold)       | Black   | 26,0004              | 006R01513    |
|                               | Cyan  | 15,0004              | 006R01516    |
|                               | Magenta   | 15,000⁴              | 006R01515    |
|                               | Yellow  | 15,000⁴              | 006R01514    |
| Transfer Belt Cleaner         | 1 Assembly  | 160,0004             | 001R00613    |
| Second Bias Transfer Roll     | 1 Assembly  | 200,0004             | 008R13064    |
| Staple Cartridge              | for Integrated Office Finisher,<br>Office Finisher LX, Professional<br>Finisher and Convenience Stapler<br>(1 cartridge per carton) | 5,000 each cartridge | 008R12964    |
| Staple Cartridge              | for Office Finisher LX Booklet Maker<br>(8 cartridge per carton)  | 2,000 each cartridge | 008R12897    |
| Staple Cartridge              | for Professional Finisher Booklet<br>Maker<br>(1 cartridge per carton)  | 5,000 each cartridge | 008R12925    |
| Staple Refills                | for Integrated Office Finisher,<br>Office Finisher LX, Professional<br>Finisher and Convenience Stapler<br>(3 refills per carton)   | 5,000 each refill    | 008R12941    |
| SMart Kits                    | Description   | Yield                | Order Number |
| Drum Cartridge                | 1 Cartridge   | 125,0004             | 013R00662    |
| Waste Toner Container         | 1 Cartridge   | 43,0004              | 008R13061    |

<sup>4</sup> Approximate pages. Declared Yield based on 5 page job size, 30% colour and 70% black and white ratio, using A4-size media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.





© 2011 Xerox Corporation. All rights reserved. XEROX®, XEROX and Design®, CentreWare®, WorkCentre, Scan to PC Desktop®, Walk-Up® and SMart Kit® are trademarks or registered trademarks of Xerox Corporation in the United States and other countries. Adobe® and PostScript® 3™ are trademarks or registered trademarks of Adobe, Inc. XPS® is a register trademark of Microsoft Corporation. PCL® is a registered trademark of Hewlett-Pockard. As an ENERGY STAR® partner, Xerox Corporation has determined that these products meet the ENERGY STAR guidelines for energy efficiency. The ENERGY STAR memory of a registered U.S. trademarks. Terra Choice Environmental Services, Inc., of Canada has verified that these products conform to all applicable Environmental Choice Ecologo requirements for minimized impact to the environment. The information in this brochure is subject to change without notice. 03/11 W785S-01EC